

# Advanced techniques

## Lecture 5

Changho Suh

January 23, 2024

# **Weight initialization & techniques for training stability**

# Outline

---

## 1. Weight initialization

Xavier's initialization

He's initialization


## 2. Techniques for training stability

Adam optimizer


Learning rate decaying

Batch normalization


# Xavier's initialization: Motivation




# Xavier's initialization: Motivation



# Xavier's initialization: Motivation



**Turns out:** With  $w_{ij}^{[\ell]} \sim \mathcal{N}(0, 1)$ ,  
signals blow up as the network gets deeper.



# Xavier's initialization: Motivation

To see this “exploding problem”, consider:

$$z_1^{[\ell]} = \sum_{j=1}^{n^{[\ell-1]}} w_{1j}^{[\ell]} a_j^{[\ell-1]}$$


Signal dynamics can be quantified via:

$$\text{var} \left( z_1^{[\ell]} \right) = \text{var} \left( \sum_{j=1}^{n^{[\ell-1]}} w_{1j}^{[\ell]} a_j^{[\ell-1]} \right)$$

# Variance computation

$$\text{var} \left( z_1^{[\ell]} \right) = \text{var} \left( \sum_{j=1}^{n^{[\ell-1]}} w_{1j}^{[\ell]} a_j^{[\ell-1]} \right)$$

$$= \sum_{j=1}^{n^{[\ell-1]}} \text{var} \left( w_{1j}^{[\ell]} a_j^{[\ell-1]} \right)$$

$$= \sum_{j=1}^{n^{[\ell-1]}} \mathbb{E} \left[ (w_{1j}^{[\ell]})^2 (a_j^{[\ell-1]})^2 \right] - \sum_{j=1}^{n^{[\ell-1]}} \left( \mathbb{E} \left[ w_{1j}^{[\ell]} a_j^{[\ell-1]} \right] \right)^2$$


## Assumption:

- (i) weights independent
- (ii) input independent
- (iii) weights/input ind.
- (iv) zero mean



# Variance computation

$$\begin{aligned}
 \text{var} \left( z_1^{[\ell]} \right) &= \sum_{j=1}^{n^{[\ell-1]}} \mathbb{E} \left[ (w_{1j}^{[\ell]})^2 (a_j^{[\ell-1]})^2 \right] \\
 &= \sum_{j=1}^{n^{[\ell-1]}} \mathbb{E} \left[ (w_{1j}^{[\ell]})^2 \right] \mathbb{E} \left[ (a_j^{[\ell-1]})^2 \right] \\
 &= \sum_{j=1}^{n^{[\ell-1]}} \text{var} \left( w_{1j}^{[\ell]} \right) \text{var} \left( a_j^{[\ell-1]} \right)
 \end{aligned}$$

## Assumption:

- (i) weights independent
- (ii) input independent
- (iii) weights/input ind.
- (iv) zero mean

# Exploding problem

$$\text{var} \left( z_1^{[\ell]} \right) = \sum_{j=1}^{n^{[\ell-1]}} \text{var} \left( w_{1j}^{[\ell]} \right) \text{var} \left( a_j^{[\ell-1]} \right)$$

**Suppose:**  $\text{var} \left( a_j^{[\ell-1]} \right) = 1, \text{var} \left( w_{1j}^{[\ell]} \right) = 1$

**Then:**  $\text{var} \left( z_1^{[\ell]} \right) = n^{[\ell-1]}$

As the network gets deeper, explode!

# Xavier's initialization

$$\text{var} \left( z_1^{[\ell]} \right) = \sum_{j=1}^{n^{[\ell-1]}} \text{var} \left( w_{1j}^{[\ell]} \right) \text{var} \left( a_j^{[\ell-1]} \right)$$

Suppose:  $\text{var} \left( a_j^{[\ell-1]} \right) = 1$

**Idea:** Set  $\text{var} \left( w_{1j}^{[\ell]} \right) = \frac{1}{n^{[\ell-1]}}$

$$w_{ij}^{[\ell]} \text{ i.i.d. } \sim \mathcal{N} \left( 0, \frac{1}{n^{[\ell-1]}} \right)$$

# He's initialization: Motivation

$$\begin{aligned} a_1^{[\ell]} &= \text{ReLU}(z_1^{[\ell]}) \\ &= \max(0, z_1^{[\ell]}) \end{aligned}$$

$$\text{var} \left( a_1^{[\ell]} \right) = \frac{1}{2} \text{var} \left( z_1^{[\ell]} \right)$$

Xavier's initialization  $w_{ij}^{[\ell]} \sim \mathcal{N} \left( 0, \frac{1}{n^{[\ell-1]}} \right)$

$$\longrightarrow \text{var} \left( a_1^{[\ell]} \right) = \frac{1}{2} \text{var} \left( a_j^{[\ell-1]} \right)$$

# He's initialization

$$w_{ij}^{[\ell]} \sim \mathcal{N} \left( 0, \frac{2}{n^{[\ell-1]}} \right)$$

# Techniques for training stability:

Adam optimizer

Learning rate decaying


Batch normalization

# Learning rate decaying

Three popular choices:

1.  $\alpha^{(t)} = \gamma^t \quad 0 < \gamma < 1$

2.  $\alpha^{(t)} = \frac{1}{\sqrt{t}}$



# Batch normalization: Motivation

---

**Turns out:** Different signal scalings across distinct layers incur training instability.

One prominent way to address this:

**Batch normalization**



# Batch


**Recall the cost function** used for gradient descent:

$$J(w^{(t)}) := \frac{1}{m} \sum_{i=1}^m -y^{(i)} \log \hat{y}^{(i)} - (1 - y^{(i)}) \log(1 - \hat{y}^{(i)})$$

**Issue:** Computationally heavy for a **large  $m$** .

**Hence:** In practice, use a chunk of examples, called a *batch*.


batch1	batch2	batch3	...	
--------	--------	--------	-----	--

  $m_B$  examples

# Batch normalization

A hidden layer

BN



## 1. Normalization

$$z_{\text{norm}} = \frac{z - \mu_{\mathcal{B}}}{\sigma_{\mathcal{B}}}$$

$$\mu_{\mathcal{B}} = \frac{1}{m_{\mathcal{B}}} \sum_{i \in \mathcal{B}} z^{(i)} \quad \sigma_{\mathcal{B}}^2 = \frac{1}{m_{\mathcal{B}}} \sum_{i \in \mathcal{B}} (z^{(i)} - \mu_{\mathcal{B}})^2$$

## 2. Customized scaling

$$\tilde{z} = \gamma z_{\text{norm}} + \beta$$

learnable parameters



# Look ahead

---

Will study:

hyperparameter search

cross validation