MSDS & Chemical Safety Technical Specification

Chemical and Enterprise Identification

Chemical Name: PRE-TREAMENT PRIMER

Supplier: Guangzhou ZealMay Biotechnology Co., Ltd.

Address: Room 307,Jingfeng Business Center, No.53-55 Airport Road, Baiyun District, Guangzhou, Guangdong Province, China.

Business Emergency Telephone: 13512796895

Effective date: 5 August 2024

Part IIFire Emergency Response Telephone :119

Information

Pure ☐ mixtures☑

Ingredients:	Content (%)	CAS No.
1 glycerol	25	56-81-5
2 butanediol	20	107-88-0
3 water	30	7732-18-5
4 dextran	15	9004-54-0
5 sophorae flavescentis radix	10	519-02-8

Part III Overview of hazards

Route of invasion: eating by mistake can harm your health.

Environmental hazards: the substance is mild to the environment, but pay attention to water pollution.

Explosion hazard: non-flammable

Part IV First aid measures

Inhaled solvent vapor: transfer the patient to fresh air and keep warm and quiet. In severe cases, medical treatment should be sought immediately.

Contact skin: use special cleaning cloth and wash with soapy water. Do not use solvents. Contaminated clothing can only be used after cleaning. If there are adverse symptoms, should seek medical treatment.

Splash into the eyes: wash with plenty of water, if the pain is more than, should immediately seek medical treatment.

Careless entrance: do not induce vomiting, use clear water to clean the mouth, and immediately seek medical treatment.

Part V Fire protection measures

Fire extinguishers: foam, carbon dioxide, dry powder and other fire extinguishers can be used, except cooling sealed containers, do not use water.

Special hazards: when the temperature rises to a certain extent or is exposed to fire and Mars, it may cause explosions. The combustion process may produce decomposing substances that are harmful to human health.

Fire protection equipment: it is recommended to use self-contained oxygen breathing device.

Part VI Emergency leak handling

Personnel prevention: remove the source of fire. Ensure air circulation and proper personal protection when transferring released liquids. Avoid skin and eye contact.

Environmental prevention: untreated materials can not be discharged to avoid environmental pollution, such as flowing into sewers or sewers, need to notify the relevant government departments to assist in handling.

Clearance: use sand, soil or other absorbent material to absorb the leak and then pack it into an appropriate container for treatment in accordance with local regulations. Use non-sparking tools for operation.

Part VII Operational disposal and storage

Handling: do not destroy the container during handling. Ensure storage containers and delivery equipment are grounded. Eliminate flames and any sources of fire. Ensure good ventilation on site.

Storage Cover tightly and store in a dry place. At the same time, this product should be placed in places where children are not in contact.

Part VIII Contact control/personal protection

Occupational exposure limit (OEL): permissible air concentration -100 ppm, within 8 hours Maximum in 10 minutes -150 ppm.

Respiratory protection: the normal working environment should have proper air circulation and dissolved steam that can be discharged in time. If the steam concentration exceeds the prescribed limit, use the breathing apparatus to provide appropriate fresh air.

Hand protection: Wear gloves made of PVC, butyl rubber, polyurethane or other suitable materials.

Skin protection: wear appropriate protective clothing and remove contaminated clothing to avoid contact with the skin.

Eye protection: wear goggles or safety glasses with face protection.

Part 9 Physical and chemical properties

Physical state: **Liquidity**

Color: **Colorless**

Proportion: 0.850±0.005@25℃

:: Volatile rate: 0.78(butyl acetate =1)

Water solubility: **Insoluble**

:: Solids: ****

:: Boiling: 110~150℃

:: Spontaneous combustion temperature: **500℃**

Viscosity: 0.76 S/25℃

PART X Stability and reactivity

Stability: stable material properties.

Avoidable environment: exposure to high temperature environment or contact with fire source.

Materials to be avoided: strong oxidation.

Degradable substances harmful to the human body: the burning process will produce carbon dioxide, carbon monoxide and other toxic odors and strong black smoke.

Part XI Toxicity

Inhaled solvent gas: High concentration of solvent vapor can stimulate the eyes and respiratory tract, causing headache, head edema, nausea, dizziness, loss of consciousness and affect the central nervous system.

Accidental entry: During swallowing and vomiting, if a small amount of fluid enters the respiratory tract, it will cause bronchitis and pulmonary edema, leading to mild poisoning.

Skin contact: Regular and prolonged contact can irritate the skin and cause dermatitis.

In the eye: Eye discomfort, inflammation.

Part XII. Ecological information

Liquidity: Fluid.

Stability and degradability: solid resin will not biodegrade, solvent evaporation.

Toxicity in water: solid resin is slightly toxic. Solvent is toxic to aquatic organisms.

Part XIII Waste disposal

Excess liquids or wastes should be labeled and treated in accordance with national and local regulations. Incineration pin is generally required.

Solid waste can be landfill, but the source of waste residue should be found.

Empty containers can be scraped and dried with metal and reused.

Empty containers are at risk of fire and explosion.

Part XIV Transport Information

Packing method: PP plastic bottle, glass bottle;

Transportation precautions: light unloading during handling to prevent damage to packaging and containers. Summer should be transported in the morning and evening to prevent sun exposure.

Part XV Legal Information

Hazard signs: harmful.

Safety terms: flammable, inhaled and exposed to harmful skin, make skin uncomfortable.

Dangerous language: avoid contact with skin, construction site, pay attention to ventilation.

Part 16 Other information

Statement: the chemical information provided in this safety specification is accurate and describes all useful information available to our company at present. However, we are not responsible for any loss, such as special, incidental, accidental or consequential loss, caused or related to the use of this specification. Users should conduct their own surveys to verify that the information provided in this specification meets the legislative requirements of the user country and is applicable to their particular use.