

Listado de SW&HW - Expansión PMS CPF2 LA CALERA

Oferta ABB 18-03-26

Descripción	Cant
SOFTWARE EXPANSIÓN	
F095 - PM891 Red. SW License 800xA 6.1.1	
PM891K02 Redundant Processor Unit	
License only.	2
F255 - CI867 Modbus TCP SW License 800xA 6.1.1	
CI867K01 Modbus TCP Communication Interface	
License only.	6
F260 - CI868 IEC 61850 SW License 800xA 6.1.1	
CI868K01 IEC61850 Communication Interface	
License only.	2
F270 - CI871 PROFINET IO SW License 800xA 6.1.1	
CI871K01 PROFINET IO Communication Interface	
License only.	10
K058 - 10 IEC61850 Devices Redundant 6.1.1	
Allows operation clients to access data and alarm and event values from Intelligent Electronic Devices (IEDs) according to IEC 61850, through Redundant IEC 61850 Connect server. Each IED instance created in System 800xA counts as one.	4
HARDWARE EXPANSIÓN CPF2	
SALA 3	
P160 - PM891K02 Redundant Processor Unit	
450MHZ and 256MB.	
Package including:	
- 2 pcs PM891K01 Processor Unit	
- TK850V007 CEX-bus Extension Cable	
- TK855 RCU Data Link Cable	
- TK856 RCU Control Link Cable	
- No license included	
Please note: The BC810K02 is not included in the PM891K02 Redundant Processor Unit Kit. In order to make hot replacement of PM891 Processor Unit possible, the BC810K02 is required to be ordered separately.	1
P265 - CI867AK01 Modbus TCP Interface	
Package including:	
-CI867A, Communication Interface	
-TP867, Baseplate	
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	3
P285 - CI871AK01 Profinet IO Interface	
Package including:	
- CI871A, Communication Interface	
- TP867, Baseplate	
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	6
P305 - CI868AK01 IEC 61850 Interface	
Package including:	
-CI868A, Communication Interface	
-TP867, Baseplate	
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	1
P460 - BC810K02 CEX-bus Interconnection Unit	
Including:	
- 2 pcs BC810, Interconnection Unit	
- 2 pcs TP857, Baseplate	
- TK851, Interconnection Cable	
- 2 pcs TB850, CEX-Bus Terminator	1
A180 - SD854 Power Supply 20A	
20A Power Supply Module. Input AC 100-240V. Input DC 110-150V. Output DC 24-28V.	
Mounting on horizontal DIN rail. Width 48mm.	
G3 compliant.	4
A195 - SS855 Power Voting Unit 40A	
Input DC 24V. 2x20A in and 1x40A out.	
Mounting on horizontal DIN rail. Width 36mm.	
G3 compliant.	2
B200 - TB826 Optical Media Converter SingleMode	
Short to long distance optical fiber conversion. For modulebus communication up to 5000m, for S800 I/O HI up to 20,000m.	4
B250 - TK811V015 POF Cable, 1.5m, Duplex	
1.5m latching duplex connector Duplex plastic fibre.	4

Descripción	Cant
A500 - DI830 Digital Input 24V SOE 16 ch Isolated in two groups of 8 channels. Use Module Termination Unit TU810, TU812, TU814, TU818, TU830, TU833, TU838, TU850. A585 - DO821 Digital Output Relay 8 ch 24-230V a.c./d.c.. 3A, cos phi>0.4, d.c. 42W, normal closed. Individually galvanic isolated channels. Use Module Termination Unit TU811, TU813, TU831, TU836, TU837, TU851. A810 - TU810V1 Compact MTU, 50V Compact Module Termination Unit 2x8 signal terminals. A815 - TU811V1 Compact MTU, 250V Compact Module Termination Unit 1x8 signal terminals. B205 - TB840A Modulebus Cluster Modem Optical cluster modem for 1+1 redundant operation. B245 - TU849 Termination Unit for 1+1 TB840 MTU with individual power supply. Support for non-redundant I/O. Including: - 1 pcs Power Supply Connector - 1 pcs TB807 Modulebus Terminator B250 - TK811V015 POF Cable, 1.5m, Duplex 1.5m latching duplex connector Duplex plastic fibre.	34 8 34 8 8 8 4 8
Description A180 - SD854 Power Supply 20A 20A Power Supply Module. Input AC 100-240V. Output DC 24-28V. Mounting on horizontal DIN rail. Width 48mm. G3 compliant. A195 - SS855 Power Voting Unit 40A Input DC 24V. 2x20A in and 1x40A out. Mounting on horizontal DIN rail. Width 36mm. G3 compliant.	6 4
SALA 4	
P160 - PM891K02 Redundant Processor Unit 450MHZ and 256MB. Package including: - 2 pcs PM891K01 Processor Unit - TK850V007 CEX-bus Extension Cable - TK855 RCU Data Link Cable - TK856 RCU Control Link Cable - No license included	
Please note: The BC810K02 is not included in the PM891K02 Redundant Processor Unit Kit. In order to make hot replacement of PM891 Processor Unit possible, the BC810K02 is required to be ordered separately. P265 - CI867AK01 Modbus TCP Interface Package including: -CI867A, Communication Interface -TP867, Baseplate Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	1 3
P285 - CI871AK01 Profinet IO Interface Package including: - CI871A, Communication Interface - TP867, Baseplate Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	4
P305 - CI868AK01 IEC 61850 Interface Package including: -CI868A, Communication Interface -TP867, Baseplate Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	1
P460 - BC810K02 CEX-bus Interconnection Unit Including: - 2 pcs BC810, Interconnection Unit - 2 pcs TP857, Baseplate - TK851, Interconnection Cable - 2 pcs TB850, CEX-Bus Terminator	1

Descripción	Cant
A180 - SD854 Power Supply 20A 20A Power Supply Module. Input AC 100-240V. Input DC 110-150V. Output DC 24-28V. Mounting on horizontal DIN rail. Width 48mm. G3 compliant.	4
A195 - SS855 Power Voting Unit 40A Input DC 24V. 2x20A in and 1x40A out. Mounting on horizontal DIN rail. Width 36mm. G3 compliant.	2
A500 - DI830 Digital Input 24V SOE 16 ch Isolated in two groups of 8 channels. Use Module Termination Unit TU810, TU812, TU814, TU818, TU830, TU833, TU838, TU850.	8
A585 - DO821 Digital Output Relay 8 ch 24-230V a.c./d.c.. 3A, cos phi>0.4, d.c. 42W, normal closed. Individually galvanic isolated channels. Use Module Termination Unit TU811, TU813, TU831, TU836, TU837, TU851.	4
A810 - TU810V1 Compact MTU, 50V Compact Module Termination Unit 2x8 signal terminals.	8
A815 - TU811V1 Compact MTU, 250V Compact Module Termination Unit 1x8 signal terminals.	4
B205 - TB840A Modulebus Cluster Modem Optical cluster modem for 1+1 redundant operation.	2
B245 - TU849 Termination Unit for 1+1 TB840 MTU with individual power supply. Support for non-redundant I/O. Including: - 1 pcs Power Supply Connector - 1 pcs TB807 Modulebus Terminator	1
B250 - TK811V015 POF Cable, 1.5m, Duplex 1.5m latching duplex connector Duplex plastic fibre.	2
Señales Generadores	
A310 - AI810 Analog Input 8 ch 0(4)..20mA, 0..10V, 12Bit, single ended. Use Module Termination Unit TU810, TU812, TU814, TU818, TU830, TU833, TU835, TU838, TU850.	1
RED DE CONTROL	
A020 - NE810 Network switch DIN-mounted 10 ports managed switch; 8 10/100Mbit RJ45 ports & 2 Gbit SFP ports. Redundant 24V DC-power input.	4
A420 - PT802 Optical transceiver Singlemode, LC-connector, 20km, 1310nm, 100Mbit/s	14
SALA 3 Gabinete 2200 x 800 x 600	
Gabinete 2200 x 800 x 600	3
Circuitos Aliment+Calefa+Illum	3
Switch IEC 61850 Hirshmann RSP 35 o similar	2
Switch Modbus ABB NE810 o de similar Hirshmann	4
Switch PROFINET ABB NE810 o similar Hirshmann	14
Borneras Marshalling	gl
Material menor (Cable+Canal+terminales+indicadores)	gl
SALA 4 Gabinete 2200 x 800 x 600	
Gabinete 2200 x 800 x 600	1
Circuitos Aliment+Calefa+Illum	1
Switch IEC 61850 Hirshmann RSP 35 o similar	2
Switch Modbus ABB NE810 o de similar Hirshmann	1
Switch PROFINET ABB NE810 o similar Hirshmann	4
Borneras Marshalling	gl
Material menor (Cable+Canal+terminales+indicadores)	gl

Descripción	Cant
Repuestos por dos años de operación	
A130 - SD831 Power Supply, 3A Input a.c. 100-240 V or d.c. 110-300 V. Output d.c. 24 V 3A. If redundant power application is required connect to SS8XX voting unit. DIN rail mounted. G2 compliant.	1
A190 - SS832 Power Voting Unit Input d.c. 24 V. Dual 24 V to single 24 V, 2x10A. DIN rail mounted. G2 compliant.	1
R500 - DI830 Digital Input 24V SOE 16 ch Isolated in two groups of 8 channels. Use Module Termination Unit TU810, TU812, TU814, TU818, TU830, TU833, TU838, TU850.	1
R580 - DO820 Digital Output Relay 8 ch 24-230V a.c./d.c. 3A, cos phi>0.4, d.c. 42W. Individually galvanic isolated channels. Use Module Termination Unit TU811, TU813, TU831, TU836, TU837, TU851.	1
R810 - TU810V1 Compact MTU, 50V Compact Module Termination Unit 2x8 signal terminals.	1
R815 - TU811V1 Compact MTU, 250V Compact Module Termination Unit 1x8 signal terminals.	1
S205 - TB840A Modulebus Cluster Modem Optical cluster modem for 1+1 redundant operation.	1
S235 - TU841 Termination unit for 1+1 TB840 Support for non-redundant I/O. Including:	
- 1 pcs Power Supply Connector - 1 pcs TB807 Modulebus Terminator	1
S250 - TK811V015 POF Cable, 1.5m, Duplex 1.5m latching duplex connector Duplex plastic fibre.	1
P265 - CI867AK01 Modbus TCP Interface Package including: -CI867A, Communication Interface -TP867, Baseplate	1
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	
P285 - CI871AK01 Profinet IO Interface Package including: - CI871A, Communication Interface - TP867, Baseplate	1
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	
P305 - CI868AK01 IEC 61850 Interface Package including: -CI868A, Communication Interface -TP867, Baseplate	1
Only compatible with 800xA 6.0.3.3 and 6.1.1, Compact Control Builder 6.0.0-3 and 6.1.1, and onwards.	
Repuestos por la puesta en marcha	
A130 - SD831 Power Supply, 3A Input a.c. 100-240 V or d.c. 110-300 V. Output d.c. 24 V 3A. If redundant power application is required connect to SS8XX voting unit. DIN rail mounted. G2 compliant.	1
A190 - SS832 Power Voting Unit Input d.c. 24 V. Dual 24 V to single 24 V, 2x10A. DIN rail mounted. G2 compliant.	1
Switches	2