

Lecture 1: Basic Prosody

1B: From Qualitative to Quantitative Analysis

Dafydd Gibbon
Bielefeld University, Germany
2022-04-25

II Brazilian Congress of Prosody
Minicourse 9, 25, 27, 39 April 2022
(09:00-11:30 Brazilian Standard Time)

Adding Quantitative to Qualitative Methods

Quantitative methods

- Qualitative methods in phonetics
 - epistemological basis of phonetics and linguistics
 - phonology
 - transcription and manual annotation
- Quantitative methods in phonetics
 - (semi)**automatic annotation with statistical training**
 - **analysis of annotations**
 - signal processing
 - (un)supervised machine learning

The deductive annotation-based approach


Decide on a set of linguistic categories and inventories

- phonetic
- phonological
- morphological
- grammatical (part of speech, PoS tags)
- semantic
- pragmatic
 - speech acts
 - turn-taking
 - discourse grammar

Analyse relevant speech data

- Search for and record data
- Listen, transcribe, annotate

Event annotation with 'Praat': intervals and labels



What goes in:

1. Recording of speech signal
2. Perception of boundaries
 1. visual, acoustic
 2. waveform, spectrum, F0
3. Perception of event intervals as speech sounds

A speech file (.WAV, etc.)




What comes out:

1. Linguistic (etc.) categories
2. Mapping of event intervals to categories
3. Durations of event intervals and a fortiori of categories

A text file (.TextGrid)

Event annotation with 'Praat': intervals and labels



Download Praat

<https://www.fon.hum.uva.nl/praat/>
<https://www.praat.org>

Data

Pre-recording

- Design systematic filenames
- Design data scenario
- Prepare equipment and participants
- You can record with Praat or Audacity

Recording

- record with proper distance (1 span)
- enough to drink

Post-recording

- save with systematic filename
- archive systematically

Annotate with Praat

Read into Praat

Select "Annotation"

Annotate.

Save with systematic filenameAnalysis

Convert the Praat format to CSV spreadsheet format

This can be done easily with a Python script. Contact me.


Analyse the spreadsheet file

With a spreadsheet.

With TGA (Time Group Analyser) online tool

<http://wwwhomes.uni-bielefeld.de/gibbon/TGA/speaker>

Event annotation with 'Praat': intervals and labels



What goes in:

1. Recording of speech signal
2. Perception of boundaries
 1. visual, acoustic
 2. waveform, spectrum, F0
3. Perception of event intervals as speech sounds

A speech file (.WAV, etc.)



What comes out:

1. Linguistic (etc.) categories
2. Mapping of event intervals to categories
3. Durations of event intervals and a fortiori of categories

A text file (.TextGrid)

Annotation Analysis

Event annotation with 'Praat': intervals and labels

What you get: TextGrid format:

File type = "ooTextFile"
Object class = "TextGrid"

```
xmin = 0
xmax = 10.117499318294643
tiers? <exists>
size = 3
item []:
  item [1]:
    class = "IntervalTier"
    name = "Syllables"
    xmin = 0
    xmax = 10.117499318294643
    intervals: size = 62
    intervals [1]:
      xmin = 0
      xmax = 0.1633600447898783
      text = " "
    intervals [2]:
      xmin = 0.1633600447898783
      xmax = 0.37639112051691453
      text = "one"
    intervals [3]:
      xmin = 0.37639112051691453
      xmax = 0.5809009532148712
      text = "two"
    intervals [4]:
      xmin = 0.5809009532148712
      xmax = 0.8351180369157989
      text = "three"
    intervals [5]:
      xmin = 0.8351180369157989
      xmax = 1.0891320731869965
      text = "four"
    intervals [6]:
      xmin = 1.0891320731869965
      xmax = 1.3092641847716007
      text = "five"
  etc.
```

What can you do with the TextGrid format?

You can read it back into Praat.

But what about cross-platform use?

For example:

Spreadsheet software:

LibreOffice Calc

Excel

Statistical software:

R

MatLab

Stata

General programming:

Python

...

Event annotation with 'Praat': intervals and labels

What you get: TextGrid format:

```
File type = "ooTextFile"
Object class = "TextGrid"

xmin = 0
xmax = 10.117499318294643
tiers? <exists>
size = 3
item []:
  item [1]:
    class = "IntervalTier"
    name = "Syllables"
    xmin = 0
    xmax = 10.117499318294643
    intervals: size = 62
    intervals [1]:
      xmin = 0
      xmax = 0.1633600447898783
      text = " "
    intervals [2]:
      xmin = 0.1633600447898783
      xmax = 0.37639112051691453
      text = "one"
    intervals [3]:
      xmin = 0.37639112051691453
      xmax = 0.5809009532148712
      text = "two"
    intervals [4]:
      xmin = 0.5809009532148712
      xmax = 0.8351180369157989
      text = "three"
    intervals [5]:
      xmin = 0.8351180369157989
      xmax = 1.0891320731869965
      text = "four"
    intervals [6]:
      xmin = 1.0891320731869965
      xmax = 1.3092641847716007
      text = "five"
  etc.
```

What you need: CSV format:

Syllables	_	0.000	0.163	0.163	Syllables	twen	5.543	5.716	0.173
Syllables	one	0.163	0.376	0.213	Syllables	ny	5.716	5.780	0.064
Syllables	two	0.376	0.581	0.205	Syllables	one	5.780	5.910	0.130
Syllables	three	0.581	0.835	0.254	Syllables	twen	5.910	6.112	0.202
Syllables	four	0.835	1.089	0.254	Syllables	ty	6.112	6.230	0.118
Syllables	five	1.089	1.309	0.220	Syllables	two	6.230	6.383	0.153
Syllables	six	1.309	1.563	0.254	Syllables	twen	6.383	6.576	0.193
Syllables	se	1.563	1.700	0.137	Syllables	ty	6.576	6.639	0.063
Syllables	ven	1.700	1.828	0.128	Syllables	three	6.639	6.812	0.173
Syllables	eight	1.828	2.008	0.180	Syllables	twen	6.812	7.001	0.189
Syllables	nine	2.008	2.231	0.223	Syllables	ty	7.001	7.087	0.086
Syllables	ten	2.231	2.431	0.200	Syllables	four	7.087	7.241	0.154
Syllables	e	2.431	2.501	0.070	Syllables	twen	7.241	7.421	0.180
Syllables	le	2.501	2.616	0.115	Syllables	ty	7.421	7.473	0.052
Syllables	ven	2.616	2.699	0.083	Syllables	five	7.473	7.683	0.210
Syllables	twelve	2.699	2.976	0.277	Syllables	twen	7.683	7.872	0.189
Syllables	thir	2.976	3.141	0.165	Syllables	ty	7.872	7.919	0.047
Syllables	teen	3.141	3.295	0.154	Syllables	six	7.919	8.157	0.238
Syllables	four	3.295	3.444	0.149	Syllables	twen	8.157	8.354	0.197
Syllables	teen	3.444	3.601	0.157	Syllables	sen	8.354	8.583	0.229
Syllables	fif	3.601	3.736	0.135	Syllables	twen	8.583	8.751	0.168
Syllables	teen	3.736	3.902	0.166	Syllables	ny	8.751	8.854	0.103
Syllables	six	3.902	4.129	0.227	Syllables	eight	8.854	8.982	0.128
Syllables	teen	4.129	4.227	0.098	Syllables	twen	8.982	9.142	0.160
Syllables	se	4.227	4.360	0.133	Syllables	ny	9.142	9.239	0.097
Syllables	ven	4.360	4.428	0.068	Syllables	nine	9.239	9.425	0.186
Syllables	teen	4.428	4.600	0.172	Syllables	thir	9.425	9.676	0.251
Syllables	eigh	4.600	4.705	0.105	Syllables	ty	9.676	9.831	0.155
Syllables	teen	4.705	4.888	0.183	Syllables	_	9.831	10.117	0.286
Syllables	nine	4.888	5.036	0.148					
Syllables	teen	5.036	5.186	0.150					
Syllables	twen	5.186	5.414	0.228					
Syllables	ty	5.414	5.543	0.129					

Event annotation with 'Praat': intervals and labels

What you get: TextGrid format:

File type = "ooTextFile"
Object class = "TextGrid"

```
xmin = 0
xmax = 10.117499318294643
tiers? <exists>
size = 3
item []:
  item [1]:
    class = "IntervalTier"
    name = "Syllables"
    xmin = 0
    xmax = 10.117499318294643
    intervals: size = 62
    intervals [1]:
      xmin = 0
      xmax = 0.1633600447898783
      text = " "
    intervals [2]:
      xmin = 0.1633600447898783
      xmax = 0.37639112051691453
      text = "one"
    intervals [3]:
      xmin = 0.37639112051691453
      xmax = 0.5809009532148712
      text = "two"
    intervals [4]:
      xmin = 0.5809009532148712
      xmax = 0.8351180369157989
      text = "three"
    intervals [5]:
      xmin = 0.8351180369157989
      xmax = 1.0891320731869965
      text = "four"
    intervals [6]:
      xmin = 1.0891320731869965
      xmax = 1.3092641847716007
      text = "five"
  etc.
```

What can you do with the TextGrid format?

You can read it back into Praat.

But what about cross-platform use?

For example:

Spreadsheet software:

LibreOffice Calc

Excel

Statistical software:

R

MatLab

Stata

General programming:

Python

...

How can you get CSV format?

With a Python script...

Python script: `textgridtier2csv.py`

```
#!/usr/bin/python3

# textgrid2csv.py, D. Gibbon, 2015.02.12
# Convert Praat TextGrid to CSV

import os, re, sys
TAB = '\t'; NL = '\n'

# Check input from CLI
if len(sys.argv) < 3:

    print('Usage:', sys.argv[0], '<filename.TextGrid>')
    exit()
textgridfile = sys.argv[1]
if not os.path.isfile(textgridfile):
    print('File', textgridfile, 'does not exist.')
    exit()
csvfile = re.sub('.TextGrid', '.csv', textgridfile)

# Preprocess textgrid format
textgrid = open(textgridfile,
'r').read().split(NL)
nugrid = []
for line in textgrid:
    line = re.sub(' *$', '', line)      # Delete
final spaces
    line = re.sub('^ *', '', line)      # Delete
initial spaces
    line = re.sub('\\"', '', line)      # Delete
quotes
    if line != '':
        nugrid += [line]
```

```
# Initialise CSV text string
csvstring = textgridfile + '\n'
csvstring += TAB.join(
    ['Tier', 'Label', 'xmin', 'xmax', 'xdiff'] ) +
NL

# Initialise row identifier flag
rowflag = False

# Loop through lines in preprocessed textgrid
for line in nugrid:
    if 'name = ' in line:                # Get tier
name
        name = line.split(" ")[-1]
        if 'intervals [' in line:      # Skip
the header
            rowflag = True
        if rowflag and 'xmin' in line:
            xmin = '%.3f'%float(line.split(' ')[-1])
        if rowflag and 'xmax' in line:
            xmax = '%.3f'%float(line.split(' ')[-1])
        if rowflag and "text" in line:
            text = line.split(" ")[-1]
            xdiff = '%.3f'%(float(xmax)-float(xmin))
            row = TAB.join([name, text, xmin, xmax,
xdiff])
            csvstring += row + NL
            rowflag = False

# Output CSV file
open(csvfile, 'w').write(csvstring)
```

What can we do with a CSV annotation file?

Descriptive statistics:

- standard deviation
- normalised Pairwise Variability Index

Other spreadsheet calculations

Duration variability as a function, with visualisation

Event annotation with 'Praat': intervals and labels

What you get: TextGrid format:

```
File type = "ooTextFile"
Object class = "TextGrid"

xmin = 0
xmax = 10.117499318294643
tiers? <exists>
size = 3
item []:
  item [1]:
    class = "IntervalTier"
    name = "Syllables"
    xmin = 0
    xmax = 10.117499318294643
    intervals: size = 62
    intervals [1]:
      xmin = 0
      xmax = 0.1633600447898783
      text = " "
    intervals [2]:
      xmin = 0.1633600447898783
      xmax = 0.37639112051691453
      text = "one"
    intervals [3]:
      xmin = 0.37639112051691453
      xmax = 0.5809009532148712
      text = "two"
    intervals [4]:
      xmin = 0.5809009532148712
      xmax = 0.8351180369157989
      text = "three"
    intervals [5]:
      xmin = 0.8351180369157989
      xmax = 1.0891320731869965
      text = "four"
    intervals [6]:
      xmin = 1.0891320731869965
      xmax = 1.3092641847716007
      text = "five"
  etc.
```

What you need: CSV format:

Syllables	_	0.000	0.163	0.163	Syllables	twen	5.543	5.716	0.173
Syllables	one	0.163	0.376	0.213	Syllables	ny	5.716	5.780	0.064
Syllables	two	0.376	0.581	0.205	Syllables	one	5.780	5.910	0.130
Syllables	three	0.581	0.835	0.254	Syllables	twen	5.910	6.112	0.202
Syllables	four	0.835	1.089	0.254	Syllables	ty	6.112	6.230	0.118
Syllables	five	1.089	1.309	0.220	Syllables	two	6.230	6.383	0.153
Syllables	six	1.309	1.563	0.254	Syllables	twen	6.383	6.576	0.193
Syllables	se	1.563	1.700	0.137	Syllables	ty	6.576	6.639	0.063
Syllables	ven	1.700	1.828	0.128	Syllables	three	6.639	6.812	0.173
Syllables	eight	1.828	2.008	0.180	Syllables	twen	6.812	7.001	0.189
Syllables	nine	2.008	2.231	0.223	Syllables	ty	7.001	7.087	0.086
Syllables	ten	2.231	2.431	0.200	Syllables	four	7.087	7.241	0.154
Syllables	e	2.431	2.501	0.070	Syllables	twen	7.241	7.421	0.180
Syllables	le	2.501	2.616	0.115	Syllables	ty	7.421	7.473	0.052
Syllables	ven	2.616	2.699	0.083	Syllables	five	7.473	7.683	0.210
Syllables	twelve	2.699	2.976	0.277	Syllables	twen	7.683	7.872	0.189
Syllables	thir	2.976	3.141	0.165	Syllables	ty	7.872	7.919	0.047
Syllables	teen	3.141	3.295	0.154	Syllables	six	7.919	8.157	0.238
Syllables	four	3.295	3.444	0.149	Syllables	twen	8.157	8.354	0.197
Syllables	teen	3.444	3.601	0.157	Syllables	sen	8.354	8.583	0.229
Syllables	fif	3.601	3.736	0.135	Syllables	twen	8.583	8.751	0.168
Syllables	teen	3.736	3.902	0.166	Syllables	ny	8.751	8.854	0.103
Syllables	six	3.902	4.129	0.227	Syllables	eight	8.854	8.982	0.128
Syllables	teen	4.129	4.227	0.098	Syllables	twen	8.982	9.142	0.160
Syllables	se	4.227	4.360	0.133	Syllables	ny	9.142	9.239	0.097
Syllables	ven	4.360	4.428	0.068	Syllables	nine	9.239	9.425	0.186
Syllables	teen	4.428	4.600	0.172	Syllables	thir	9.425	9.676	0.251
Syllables	eigh	4.600	4.705	0.105	Syllables	ty	9.676	9.831	0.155
Syllables	teen	4.705	4.888	0.183	Syllables	_	9.831	10.117	0.286
Syllables	nine	4.888	5.036	0.148					
Syllables	teen	5.036	5.186	0.150					
Syllables	twen	5.186	5.414	0.228					
Syllables	ty	5.414	5.543	0.129					

Descriptive statistics: static sets – *nPVI*

Annotation: segmentation and classification (‘labelling’) and the search for isochrony*

a hybrid deductive-inductive method

***isochrony:** equal timing, for example as an idealised phonetic interpretation of rhythm units like syllables or stress groups

Interval analysis and PVI – the search for isochrony

$$rPVI(D) = \sum |d_k - d_{k+1}| / (n - 1)$$

raw Pairwise Variability Index

The measure defines an overall ‘next-door neighbour distance’.

Interval analysis and PVI – the search for isochrony

$$rPVI(D) = \sum |d_k - d_{k+1}| / (n - 1)$$

$$nPVI(D) = 100 \times \sum \left| \frac{d_k - d_{k+1}}{(d_k + d_{k+1})/2} \right| / (n - 1)$$

raw Pairwise Variability Index

normalised Pairwise Variability Index

Interval analysis and PVI – the search for isochrony

$$rPVI(D) = \sum |d_k - d_{k+1}| / (n - 1)$$

raw Pairwise Variability Index

$$nPVI(D) = 100 \times \sum \left| \frac{d_k - d_{k+1}}{(d_k + d_{k+1})/2} \right| / (n - 1)$$

normalised Pairwise Variability Index

Similarity to Manhattan Distance

$$MD(x, y) = \sum_{i=1}^n |x_i - y_i|$$

*Similarity to Canberra Distance
(Normalised Manhattan Distance)*

$$NormMD(x, y) = \sum_{i=1}^n \frac{|x_i - y_i|}{|x_i| + |y_i|}$$



Interval analysis and PVI – the search for isochrony

$$rPVI(D) = \sum |d_k - d_{k+1}| / (n - 1)$$

$$nPVI(D) = 100 \times \sum \left| \frac{d_k - d_{k+1}}{(d_k + d_{k+1})/2} \right| / (n - 1)$$

raw Pairwise Variability Index

normalised Pairwise Variability Index



Interval analysis and PVI – the search for isochrony

$$rPVI(D) = \sum |d_k - d_{k+1}| / (n - 1)$$

Similarity to Manhattan Distance


$$MD(x, y) = \sum_{i=1}^n |x_i - y_i|$$

$$nPVI(D) = 100 \times \sum \left| \frac{d_k - d_{k+1}}{(d_k + d_{k+1})/2} \right| / (n - 1)$$

*Similarity to Canberra Distance
(Normalised Manhattan Distance)*

$$NormMD(x, y) = \sum_{i=1}^n \frac{|x_i - y_i|}{|x_i| + |y_i|}$$

These measures show an overall ‘next-door neighbour distance’:



Assessment of interval duration measures


The interval duration measures can be useful heuristic measures.

They have the following properties:

- the interval duration measures ignore the alternation property of rhythm by using absolute values, and yielding the same values for positive and negative differences;
- they are often called ‘rhythm metrics’, but the interval duration measures calculate irregularity, not rhythmicity;
- the ‘irregularity measures’ do not model rhythm and do not constitute either a model or a theory of rhythm;
- through the annotation procedure the signal is filtered through the perceptual skills of an annotator and the signal is not analysed directly.

Duration variability as a function

Libre Office Calc (Excel, R, MatLab, Python, Stata...)




What does this tell you?

1. Durations are not constant
2. Duration differences are not constant
3. Durations vary through an utterance
4. Morphology is also relevant

So be careful with generalisations which give you a single index, like

1. Standard Deviation
 2. nPVI
- and ignore speech variability in languages

Libre Office Calc (Excel, R, MatLab, Python, Stata...)



What does this tell you?

1. Durations are not constant
2. Duration differences are not constant
3. Durations vary through an utterance
4. Morphology is also relevant


So be careful with generalisations which give you a single index, like

1. Standard Deviation
 2. nPVI
- and ignore speech variability in languages

Libre Office Calc (Excel, R, MatLab, Python, Stata...)


Durations: time → duration

one-to-thirty-2044-04-22



Durations: time → duration

one-to-thirty-2044-04-22




What does this tell you?

1. Durations are not constant
2. Duration differences are not constant
3. Durations vary through an utterance
4. Morphology is also relevant

So be careful with generalisations which give you a single index, like

1. Standard Deviation
 2. nPVI
- and ignore speech variability in languages

Libre Office Calc (Excel, R, MatLab, Python, Stata...)




What does this tell you?

1. Durations are not constant
2. Duration differences are not constant
3. Durations vary through an utterance
4. Morphology is also relevant

So be careful with generalisations which give you a single index, like

1. Standard Deviation
 2. nPVI
- and ignore speech variability in languages

Libre Office Calc (Excel, R, MatLab, Python, Stata...)



What does this tell you?

1. Durations are not constant
2. Duration differences are not constant
3. Durations vary through an utterance
4. Morphology is also relevant

So be careful with generalisations which give you a single index, like

1. Standard Deviation
 2. nPVI
- and ignore speech variability in languages

For Wednesday and Friday

<https://github.com/dafyddg/RFA/>

For Pythonistas:

To get the code: `git clone http://github.com/dafyddg/RFA/`

To use the code:

```
pip install numpy
pip install matplotlib
pip install scipy
pip install graphviz
```

Also:

install GraphViz for your OS: <https://graphviz.org/download/>