Document ID: VIB-PROD-002 Classification: INTERNAL CONFIDENTIAL Effective Date: 2024-04-01 Version: 5.7

Document Owner: VP, Product Engineering

Detailed Solution Datasheets Library: VI Business (India)

1) Executive Purpose and Applicability

The Detailed Solution Datasheets Library strips away marketing narratives to provide the rigorous, exact metric constraints of VI Business (India)'s deployed architectures. It serves as the definitive engineering boundary for solution proposals.

Intended Audience: Pre-Sales Engineers, Network Architects, Bid Technical Writers.
Applicability: For verbatim insertion into RFP "Technical Specification" annexures or "Compliance to Specifications" columns requiring structured limits.

2) Definitions and Assumptions

Definitions:

- **NGFW:** Next-Generation Firewall.
- **Throughput:** The maximum sustainable data transfer rate guaranteed not to degrade CPU operations.

Assumptions:

- **Internal Control:** Committing to throughputs or limits beyond the bounds specified herein fundamentally breaches the underlying hardware OEM capacity matrix and voids our MSA liability constraints.

3) Detailed Core Sections

3.1 Managed SD-WAN (Edge Routing Specifications)

Parameter	Baseline Edge (Branch)	High-Performance Edge (Hub)
Max Validated IPSec Throughput	200 Mbps - 500 Mbps	2 Gbps - 5 Gbps

Parameter	Baseline Edge (Branch)	High-Performance Edge (Hub)
BGP/OSPF Routing Engine	Full Table Support	Full Table + ECMP Optimization
Failover Geometry	Active/Standby < 50ms	Active/Active (Stateful session preservation)
Traffic Steering Engine	Application/Deep Packet Aware	Custom SLA-threshold logic (Latency/Jitter)
High Availability (HA)	Optional (Cold Spare)	Mandatory (Active/Active Chassis Clustering)

3.2 Managed NGFW (Cybersecurity Edge Constraints)

Parameter	Standard Branch NGFW	Tier-1 Data Center NGFW
Max Validated Threat Protection Throughput	300 Mbps	4 Gbps
Intrusion Prevention (IPS) Features	Behavior/Signature based	Core Heuristic + Zero-Day Sandbox routing
URL/Web Filtering limits	60+ pre-defined distinct categories	Unlimited custom granular filtering
Max Concurrent Sessions	50,000	2,000,000+

3.3 Managed SIEM and SOC Log Analytics Specifications

Parameter	Universal SOC Specification
Max Log Ingestion Rate (Scalable)	100 EPS base; scalable to > 10,000 EPS
Standard Hot Log Retention	90 Days (Active searching immediately available)
Cold Storage Archival	12 Months natively
Threat Intelligence Automation	Hourly ingestion of STIX/TAXII threat intel feeds
Data Localization	100% Hosted locally within Pune/Mumbai Tier-III DCs

3.4 Enterprise Cloud Interconnects (ExpressRoute / Direct Connect)

Parameter	ExpressRoute (Azure)	Direct Connect (AWS)
Layer Structure	Layer 3 eBGP Native	Layer 2/3 (Transit Gateway via VIF)
Port Bandwidth Options	1 Gbps to 10 Gbps	1 Gbps to 100 Gbps (DC dependent)

Parameter	ExpressRoute (Azure)	Direct Connect (AWS)
Availability SLA	99.99% (Subject to dual ER circuits)	99.9% base (Dual Ports)
Latency Boundary	`<8ms` (NESCO to Azure Central India)	`<8ms` (NESCO to AWS ap-south-1)

4) Evidence and Proof-Artifact Map

Specification Class	Internal Hardware Verification	Owner
SDN Appliance Metrics	`SharePoint/VIB_Engineering/OEM_Hardware_Limits.xlsx`	Head of Network Platforms
SIEM Scaling Metric	`SharePoint/VIB_Engineering/SOC_Capacity_Plan.pdf`	Lead SOC Architect

5) Governance and Ownership

- **Owner:** VP, Product Engineering
- **Reviewers:** Solutions Directors, Enterprise CISO.
- **Review Frequency:** Bi-Annually, syncing directly with OEM hardware end-of-life (EOL) sequences.

6) Constraints, Exclusions, and Dependencies

- **Constraints:** High-end (10 Gbps+) firewall throughput mandates disabling certain extreme deep-packet sandboxing routines. Solution Architects must design payload profiles correctly to prevent maxing out Edge CPE processors resulting in network degradation.