Document ID: VIB-TECH-COMP-015 Classification: INTERNAL CONFIDENTIAL (External Extracts Permitted)
Effective Date: 2024-04-01 Version: 5.3

Document Owner: National Head of Solution Engineering

Interoperability and Compatibility Matrix: VI Business (India)

1. Executive Purpose and Document Scope

The Interoperability and Compatibility Matrix defines the strict hardware, software, and protocol boundaries within which VI Business (India) managed enterprise services seamlessly integrate with third-party ecosystems.

As Indian enterprises increasingly adopt hybrid-multi-cloud and Bring Your Own Device (BYOD) strategies, this artifact provides Solution Architects and Bid Writers with an audited, definitive compatibility list. It prevents the proposal of unverified integrations that lead to deployment failures and SLA breaches.

2. Definitions, Assumptions, and Applicability

Definitions:

- **SIP:** Session Initiation Protocol (Voice).
- **API:** Application Programming Interface.
- **uCPE:** Universal Customer Premises Equipment.
- **ZTP:** Zero-Touch Provisioning.

Assumptions:

- **"Supported"** means the configuration has been exhaustively tested in the Pune VI Core Lab and carries a formal SLA.
- **"Unsupported/Best Effort"** means the configuration might practically function, but VI Business completely disclaims liability for application performance degradation or outage.

Applicability:

- **Target Audience:** Enterprise Pre-sales, Bid Coordination, Implementation Project Managers.
- **Scope:** Managed SD-WAN edge compatibility, SIP Trunking (Voice), Cloud API integrations, and Enterprise Mobility Management (EMM).

3. Supported Devices and Endpoints

VI Business aggressively curates an OEM-agnostic ecosystem, but we strictly enforce "Gold Standard" hardware tiers to maintain 99.99% core availability.

3.1 Managed SD-WAN (Edge Routing)

- **Tier 1 Supported (Full SLA & ZTP Automation):** Fortinet FortiGate (40F, 80F, 200F Series), Cisco Meraki (MX Series), Palo Alto Networks (Prisma SD-WAN / ION Series).
- **Tier 2 Supported (SLA but Manual Provisioning):** Cisco ISR 4000 Series, Juniper SRX Series.
- **Unsupported (No Managed Services Option):** Consumer-grade routers (e.g., TP-Link, D-Link, Netgear), legacy EoL hardware from any vendor.

3.2 Enterprise IoT / Mobility

- **Supported Endpoints:** Any standard 3GPP-compliant LTE/5G module (e.g., Quectel, Thales) capable of interpreting standard AT commands and supporting absolute Custom APN (cAPN) routing.
- **SIM Compatibility:** Standard 2FF/3FF/4FF physical SIMs and M2M ruggedized eSIMs (eUICC compliant).

4. PBX and Voice Network Compatibility

VI Business is a primary Tier-1 SIP Trunking provider for enterprise Unified Communications (UC) across India.

Third-Party PBX/SBC Vendor	Certified Version Range	Primary Integration Protocol	Certification Lab Status
Microsoft Teams Direct Routing	Current Cloud PBX	SIP via Azure ExpressRoute / Internet	Certified Gold SIP Partner
Cisco Unified Communications Manager (CUCM)	v12.5 and above	SIP (G.711 / G.729a)	Certified
Avaya Aura	v8.1 and above	SIP via Avaya SBCE	Certified
Generic Asterisk/FreePBX	N/A	SIP (Best Effort only)	Untested (Customer Risk)

5. Browser and Mobile App Compatibility

Administrative access to the VI Business Self-Care Portal (Billing, IoT Management, Incident Logging) and specific white-labeled EMM applications follow standard lifecycle support.

- **Desktop Browsers (Full Support):** Google Chrome (Last 2 major versions), Microsoft Edge (Chromium-based), Mozilla Firefox, Apple Safari (macOS only).
- **Unsupported Browsers:** Internet Explorer 11 (Strictly blocked due to TLS vulnerabilities).
- **Mobile Operating Systems (For native VI Apps):**
    - **Android:** Version 11.0 (Red Velvet Cake) and higher.
    - **iOS:** Version 15.0 and higher.

6. Third-Party Interoperability Boundaries

The demilitarized zone (DMZ) between VI Business controls and third-party IT environments relies on standard protocols.

6.1 Cloud Interconnects (ExpressRoute / Direct Connect)

- **BGP Peering:** Border Gateway Protocol (BGP-4) is the exclusive routing mechanism utilized to hand off traffic from the VI MPLS core into AWS or Azure. OSPF or static routing is explicitly denied into public cloud fabrics.
- **Bandwidth Scaling:** Incremental scale (e.g., 50 Mbps increments up to 10 Gbps per port) is fully interoperable with native hyperscaler gateways.

6.2 ITSM and API Interoperability

- **Supported Logic:** Incident synchronization via the VI API Gateway strictly requires the customer ITSM (e.g., ServiceNow, Jira Service Desk) to support outbound OAuth 2.0 (Client Credentials) POST requests.
- **Boundary Policy:** VI Business will *receive* and *acknowledge* standard JSON payloads, but we will not build custom middleware translation scripts on behalf of the customer unless contracted under a separate Professional Services BoM.

7. Testing and Certification Assumptions

- **Custom Environments:** If an RFP demands integration with an unlisted ERP or legacy mainframe system, the Account Manager must request a "Proof of Concept (PoC) Lab Waiver" from Solution Engineering involving a 14-day technical feasibility sprint prior to commercial signature.
- **Firmware Governance:** Interoperability is only guaranteed on OEM firmware versions explicitly approved by the VI Business Change Advisory Board (CAB). Customers forcefully demanding unvetted firmware upgrades instantly void hardware SLA guarantees.

8. Proposal-Use Guidance

- **RFP Use:** Utilize Section 3 and Section 4 to map VI Business capabilities directly against the customer's existing legacy hardware list during the "As-Is" assessment phase of the bid.
- **Limitation of Liability:** Cite Section 7 to defensively reject RFP requirements implying VI Business is responsible for integrating completely bespoke or sunset third-party applications.

9. Governance and Ownership

- **Owner:** National Head of Solution Engineering
- **Reviewers:** Enterprise CISO, Head of Voice Operations.
- **Update Cadence:** Quarterly. Matrix additions mirror the release cycle of the primary OEM partners (Cisco, Microsoft, Fortinet).