apache-camel-spring-boot-1.x (0.0.1)

Maksim Kostromin

Version 0.0.1, 2018-06-14 22:39:30 UTC

Table of Contents

1.	Introduction	2
2	Implementation	3
	2.1. camel spring configuration	3
	2.2. move all files from directory	3
	2.3. move files via jms	3
	2.4. change filename by using camel header.	5
3	BOM	6
4	Links	7

Travis CI status: [Build Status]

Chapter 1. Introduction

Reference documentation

See Travis CI integration tests for details

generated by generator-jvm yeoman generator (java-spring-boot_1.x)

Chapter 2. Implementation

2.1. camel spring configuration

src/main/resources/application.properties

```
camel.springboot.main-run-controller=true
```

2.2. move all files from directory

source directory: /tmp/camel-in/ destination directory: /tmp/camel-out/

src/main/java/daggerok/app/MoveFilesCamelConfig.java

2.3. move files via jms

source directory: /tmp/camel-jms-in/ process queue: files destination directory: /tmp/camel-jms-out/

```
@Slf4j
@Configuration
@RequiredArgsConstructor
public class MoveFilesViaJmsCamelConfig {
  @Bean
  public RouteBuilder moveFilesViaJmsRoute() {
    return new RouteBuilder() {
      @Override
      public void configure() throws Exception {
        from("file:///tmp/camel-jms-in")
            .routeId("in-dir-to-jms")
            .transform()
            .body(GenericFile.class, genericFile -> {
              final File file = File.class.cast(genericFile.getFile());
              try (final FileInputStream inputStream = new FileInputStream(file)) {
                final InputStreamReader streamReader = new InputStreamReader
(inputStream);
                final BufferedReader in = new BufferedReader(streamReader);
                return in.lines().collect(joining());
              } catch (IOException e) {
                log.error(e.getLocalizedMessage());
                throw new RuntimeException(e);
              }
            })
            .to("jms:queue:files")
        from("jms:queue:files")
            .routeId("jms-to-out-dir")
            .to("file:///tmp/camel-jms-out")
      }
    };
 }
}
```

```
@Component
@RequiredArgsConstructor
class ApplicationJmsComponentCustomizer implements ComponentCustomizer<JmsComponent> {
    final ConnectionFactory connectionFactory;
    @Override
    public void customize(JmsComponent component) {
        component.setConnectionFactory(connectionFactory);
    }
}
```

2.4. change filename by using camel header

source directory: /tmp/camel-filename-in/ destination directory: /tmp/camel-filename-out/

setup camel header to change output filename in pattern: uuid-changed.txt

```
@Configuration
@RequiredArgsConstructor
public class ChangeFilenameHeaderCamelConfig {
 @Bean
 public RouteBuilder filenameHeaderRoute() {
    return new RouteBuilder() {
      @Override
      public void configure() throws Exception {
        from("file:///tmp/camel-filename-in")
            .routeId("change-filename-header")
            .setHeader("CamelFileName", () -> format("%s-changed.txt", UUID.
randomUUID().toString()))
            .to("file:///tmp/camel-filename-out");
      }
    };
 }
}
```

Chapter 3. BOM

maven

gradle

```
dependencyManagement {
  imports {
   mavenBom "org.apache.camel:camel-spring-boot-dependencies:$apacheCamelVersion"
```

Chapter 4. Links

GitHub repo GitHub pages