

parcel-examples (0.0.1)

Maksim Kostromin

Version 0.0.1, 2018-06-28 08:54:14 UTC

Table of Contents

1. Introduction	2
2. Implementation	3
2.1. basic example	3
3. Links	5

Travis CI status: [\[Build Status\]](#)

Chapter 1. Introduction

Read [reference documentation](#)

generated by [generator-jvm](#) yeoman generator (java)

Chapter 2. Implementation

2.1. basic example

prepare project

```
mkdir -p basic

echo "node_modules" >> basic/.gitignore
echo "dist" >> basic/.gitignore
echo '{"scripts":{"start":"parcel serve src/","build":"parcel build src/index.html"}}'
> basic/package.json

cd basic/
npm init -y
npm i -D parcel-bundler
```

prepare project files

```
mkdir -p src
touch src/index.html
touch src/styles.css
touch src/main.js
```

main.js

```
(function main() {
  'use strict';
  document.addEventListener('DOMContentLoaded', function onDOMContentLoaded() {
    document.querySelector('#app').textContent = 'hey!';
  }, false);
})();
```

styles.css

```
body {
  padding: 2%;
  margin: 0;
}
```

index.html

```
<!doctype html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width, initial-scale=1.0">
  <meta http-equiv="X-UA-Compatible" content="ie=edge">
  <title>Basic | Parcel</title>
  <link rel="shortcut icon" href="./favicon.ico" type="image/x-icon">
  <link rel="stylesheet" href="./styles.css">
</head>
<body>
  <div id="app"></div>
  <script src="./main.js"></script>
</body>
</html>
```

start development

```
npm start
```

open localhost:1234

build bundle

```
npm run build
```

verify result

```
npm i -g serve
serve dist/
```

Chapter 3. Links

- [GitHub repo](#)
- [GitHub pages](#)