

webpack-examples (0.0.1)

Maksim Kostromin

Version 0.0.1, 2018-06-17 14:45:58 UTC

Table of Contents

1. Introduction	2
2. Quickstart	3
2.1. no config	3
2.2. basic config	3
2.3. add HTML plugin	3
2.4. add webpack-dev-server	4
2.5. add css-loader and style-loader	4
3. Links	6

Travis CI status:

Chapter 1. Introduction

Read [reference documentation](#)

webpack 4 examples:

- [starter without config file](#)
- [basic starter](#)
- [add html-webpack-plugin](#)
- [add webpack-dev-server](#)
- [add css-loader and style-loader](#)

Chapter 2. Quickstart

2.1. no config

using webpack without `webpack.config.js` file

```
mkdir starter-no-config
cd starter-no-config/

mkdir src dist
echo "console.log('hey!');" >> src/index.js
echo "<script src='./main.js'></script>" >> dist/index.html

npm init -y
npm i -g webpack webpack-cli
#npm i -DE webpack webpack-cli

webpack --mode=development
webpack --mode production
```

2.2. basic config

using webpack with basic config file: `config/webpack.dev.js`

```
const { resolve } = require('path');

module.exports = {
  entry: {
    main: './src/index.js'
  },
  mode: 'development',
  output: {
    filename: '[name]-bundle.js',
    path: resolve(__dirname, '../dist'),
  },
};
```

2.3. add HTML plugin

install `html-webpack-plugin`

```
npm i -DE html-webpack-plugin
```

update webpack config

```
const HtmlWebpackPlugin = require('html-webpack-plugin');

module.exports = {
  // ...
  plugins: [
    new HtmlWebpackPlugin({
      template: './src/index.html',
      favicon: './src/favicon.ico',
    }),
  ],
};
```

2.4. add webpack-dev-server

update webpack config

```
const { resolve, join } = require('path');

module.exports = {
  // ...
  devServer: {
    contentBase: join(__dirname, '../dist'),
  },
};
```

install and run webpack-dev-server

```
npm i -DE webpack-dev-server
webpack-dev-server --config config/webpack.dev.js
```

2.5. add css-loader and style-loader

add some css styles

```
body {  
  margin: 0;  
  background-color: #444;  
}  
  
/* lets centred content using flex */  
  
h1 {  
  color: white;  
  height: 100vh;  
  display: flex;  
  align-items: center;  
  justify-content: center;  
  font-size: 3em;  
  font-family: Helvetica, sans-serif, 'DejaVu Sans', Arial;  
}
```



These loaders will apply in reverse order: first, **css-loader**, next: **style-loader**

install css-loader and style-loader

```
npm i -DE css-loader style-loader
```

update webpack config

```
module.exports = {  
  // ...  
  module: {  
    rules: [  
      {  
        test: /\.css$/i,  
        use: [  
          { loader: 'style-loader' },  
          { loader: 'css-loader' },  
        ],  
      },  
    ],  
  },  
};
```

Chapter 3. Links

[AsciiDoctor reference](#)

[GitHub repo: lawwantsin/webpack-course](#)

[GitHub](#)

`link:[Webpack documentation]`

[HTML webpack plugin documentation](#)

[HTML webpack-dev-server documentation](#)