



C++

Goshgar Can Ismayilov



Simple C++ Program

```
1 // Fig. 15.1: fig15_01.cpp
2 // Addition program that displays the sum of two numbers.
3 #include <iostream> // allows program to perform input and output
4
5 int main()
6 {
7     int number1; // first integer to add
8
9     std::cout << "Enter first integer: "; // prompt user for data
10    std::cin >> number1; // read first integer from user into number1
11
12    int number2; // second integer to add
13    int sum; // sum of number1 and number2
14
15    std::cout << "Enter second integer: "; // prompt user for data
16    std::cin >> number2; // read second integer from user into number2
17    sum = number1 + number2; // add the numbers; store result in sum
18    std::cout << "Sum is " << sum << std::endl; // display sum; end line
19 } // end function main
```

```
Enter first integer: 45
Enter second integer: 72
Sum is 117
```

Inline Function

```
1 // Fig. 15.3: fig15_03.cpp
2 // inline function that calculates the volume of a cube.
3 #include <iostream>
4 using std::cout;
5 using std::cin;
6 using std::endl;
7
8 // Definition of inline function cube. Definition of function appears
9 // before function is called, so a function prototype is not required.
10 // First line of function definition acts as the prototype.
11 inline double cube( const double side )
12 {
13     return side * side * side; // calculate the cube of side
14 } // end function cube
15
16 int main()
17 {
18     double sideValue; // stores value entered by user
19
20     for ( int i = 1; i <= 3; i++ )
21     {
22         cout << "\nEnter the side length of your cube: ";
23         cin >> sideValue; // read value from user
24
25         // calculate cube of sideValue and display result
26         cout << "Volume of cube with side "
27             << sideValue << " is " << cube( sideValue ) << endl;
28     }
29 } // end main
```

Enter the side length of your cube: 1.0
Volume of cube with side 1 is 1

Enter the side length of your cube: 2.3
Volume of cube with side 2.3 is 12.167

Enter the side length of your cube: 5.4
Volume of cube with side 5.4 is 157.464



Pass by Value and Reference

```
9  int main()
10 {
11     int x = 2; // value to square using squareByValue
12     int z = 4; // value to square using squareByReference
13
14     // demonstrate squareByValue
15     cout << "x = " << x << " before squareByValue\n";
16     cout << "Value returned by squareByValue: "
17         << squareByValue( x ) << endl;
18     cout << "x = " << x << " after squareByValue\n" << endl;
19
20     // demonstrate squareByReference
21     cout << "z = " << z << " before squareByReference" << endl;
22     squareByReference( z );
23     cout << "z = " << z << " after squareByReference" << endl;
24 } // end main
25
26 // squareByValue multiplies number by itself, stores the
27 // result in number and returns the new value of number
28 int squareByValue( int number )
29 {
30     return number *= number; // caller's argument not modified
31 } // end function squareByValue
32
33 // squareByReference multiplies numberRef by itself and stores the result
34 // in the variable to which numberRef refers in the caller
35 void squareByReference( int &numberRef )
36 {
37     numberRef *= numberRef; // caller's argument modified
38 } // end function squareByReference
```

```
x = 2 before squareByValue
Value returned by squareByValue: 4
x = 2 after squareByValue
```

```
z = 4 before squareByReference
z = 16 after squareByReference
```

Default Function Arguments

```
6 // function prototype that specifies default arguments
7 int boxVolume( int length = 1, int width = 1, int height = 1 );
8
9 int main()
10 {
11     // no arguments--use default values for all dimensions
12     cout << "The default box volume is: " << boxVolume();
13
14     // specify length; default width and height
15     cout << "\n\nThe volume of a box with length 10,\n"
16         << "width 1 and height 1 is: " << boxVolume( 10 );
17
18     // specify length and width; default height
19     cout << "\n\nThe volume of a box with length 10,\n"
20         << "width 5 and height 1 is: " << boxVolume( 10, 5 );
21
22     // specify all arguments
23     cout << "\n\nThe volume of a box with length 10,\n"
24         << "width 5 and height 2 is: " << boxVolume( 10, 5, 2 )
25         << endl;
26 } // end main
27
28 // function boxVolume calculates the volume of a box
29 int boxVolume( int length, int width, int height )
30 {
31     return length * width * height;
32 } // end function boxVolume
```

The default box volume is: 1

The volume of a box with length 10,
width 1 and height 1 is: 10

The volume of a box with length 10,
width 5 and height 1 is: 50

The volume of a box with length 10,
width 5 and height 2 is: 100

Unary Scope Resolution

```
1 // Fig. 15.9: fig15_09.cpp
2 // Using the unary scope resolution operator.
3 #include <iostream>
4 using namespace std;
5
6 int number = 7; // global variable named number
7
8 int main()
9 {
10    double number = 10.5; // local variable named number
11
12   // display values of local and global variables
13   cout << "Local double value of number = " << number
14   << "\nGlobal int value of number = " << ::number << endl;
15 }
```

Local double value of number = 10.5
Global int value of number = 7

Function Overloading

```
6 // function square for int values
7 int square( int x )
8 {
9     cout << "square of integer " << x << " is ";
10    return x * x;
11 } // end function square with int argument
12
13 // function square for double values
14 double square( double y )
15 {
16     cout << "square of double " << y << " is ";
17     return y * y;
18 } // end function square with double argument
19
20 int main()
21 {
22     cout << square( 7 ); // calls int version
23     cout << endl;
24     cout << square( 7.5 ); // calls double version
25     cout << endl;
26 } // end main
```

```
square of integer 7 is 49
square of double 7.5 is 56.25
```

C++ Vectors

```
1 // Fig. 15.14: fig15_14.cpp
2 // Demonstrating C++ Standard Library class template vector.
3 #include <iostream>
4 #include <iomanip>
5 #include <vector>
6 using namespace std;
7
8 void outputVector( const vector< int > & ); // display the vector
9 void inputVector( vector< int > & ); // input values into the vector
10
11 int main()
12 {
13     vector< int > integers1( 7 ); // 7-element vector< int >
14     vector< int > integers2( 10 ); // 10-element vector< int >
15
16     // print integers1 size and contents
17     cout << "Size of vector integers1 is " << integers1.size()
18         << "\nvector after initialization:" << endl;
19     outputVector( integers1 );
20
21     // print integers2 size and contents
22     cout << "\nSize of vector integers2 is " << integers2.size()
23         << "\nvector after initialization:" << endl;
24     outputVector( integers2 );
```

Size of vector integers1 is 7
vector after initialization:

0	0	0	0
0	0	0	

Size of vector integers2 is 10
vector after initialization:

0	0	0	0
0	0	0	0
0	0		

```
87 // output vector contents
88 void outputVector( const vector< int > &array )
89 {
90     size_t i; // declare control variable
91
92     for ( i = 0; i < array.size(); ++i )
93     {
94         cout << setw( 12 ) << array[ i ];
95
96         if ( ( i + 1 ) % 4 == 0 ) // 4 numbers per row of output
97             cout << endl;
98     }
99
100    if ( i % 4 != 0 )
101        cout << endl;
102 }
103
104 // input vector contents
105 void inputVector( vector< int > &array )
106 {
107     for ( size_t i = 0; i < array.size(); ++i )
108         cin >> array[ i ];
109 }
```

C++ Vectors

```
26 // input and print integers1 and integers2
27 cout << "\nEnter 17 integers:" << endl;
28 inputVector( integers1 );
29 inputVector( integers2 );
30
31 cout << "\nAfter input, the vectors contain:\n"
32     << "integers1:" << endl;
33 outputVector( integers1 );
34 cout << "integers2:" << endl;
35 outputVector( integers2 );
36
37 // use inequality (!=) operator with vector objects
38 cout << "\nEvaluating: integers1 != integers2" << endl;
39
40 if ( integers1 != integers2 )
41     cout << "integers1 and integers2 are not equal" << endl;
42
43 // create vector integers3 using integers1 as an
44 // initializer; print size and contents
45 vector< int > integers3( integers1 ); // copy constructor
46
47 cout << "\nSize of vector integers3 is " << integers3.size()
48     << "\nvector after initialization:" << endl;
49 outputVector( integers3 );
50
51 // use overloaded assignment (=) operator
52 cout << "\nAssigning integers2 to integers1:" << endl;
53 integers1 = integers2; // assign integers2 to integers1
54
55 cout << "integers1:" << endl;
56 outputVector( integers1 );
57 cout << "integers2:" << endl;
58 outputVector( integers2 );
59
60 // use equality (==) operator with vector objects
61 cout << "\nEvaluating: integers1 == integers2" << endl;
62
63 if ( integers1 == integers2 )
64     cout << "integers1 and integers2 are equal" << endl;
65
66 // use square brackets to create rvalue
67 cout << "\nintegers1[5] is " << integers1[ 5 ];
```

```
Enter 17 integers:
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17

After input, the vectors contain:
integers1:
    1      2      3      4
        5      6      7
integers2:
    8      9      10     11
    12     13     14     15
    16     17

Evaluating: integers1 != integers2
integers1 and integers2 are not equal

Size of vector integers3 is 7
vector after initialization:
    1      2      3      4
        5      6      7

Assigning integers2 to integers1:
integers1:
    8      9      10     11
    12     13     14     15
    16     17
integers2:
    8      9      10     11
    12     13     14     15

Evaluating: integers1 == integers2
integers1 and integers2 are equal

integers1[5] is 13
```

C++ Vectors

```
69 // use square brackets to create lvalue
70 cout << "\n\nAssigning 1000 to integers1[5]" << endl;
71 integers1[ 5 ] = 1000;
72 cout << "integers1:" << endl;
73 outputVector( integers1 );
74
75 // attempt to use out-of-range index
76 try
77 {
78     cout << "\nAttempt to display integers1.at( 15 )" << endl;
79     cout << integers1.at( 15 ) << endl; // ERROR: out of range
80 }
81 catch ( out_of_range &ex )
82 {
83     cout << "An exception occurred: " << ex.what() << endl;
84 }
85 }
```

integers1[5] is 13

Assigning 1000 to integers1[5]
integers1:

8	9	10	11
12	1000	14	15
16	17		

Attempt to display integers1.at(15)
An exception occurred: invalid vector<T> subscript

Simple C++ Class

```
8 // GradeBook class definition
9 class GradeBook
10 {
11 public:
12     // function that displays a welcome message to the GradeBook user
13     void displayMessage( string courseName )
14     {
15         cout << "Welcome to the grade book for\n" << courseName << "!"
16             << endl;
17     } // end function displayMessage
18 }; // end class GradeBook
19
20 // function main begins program execution
21 int main()
22 {
23     string nameOfCourse; // string of characters to store the course name
24     GradeBook myGradeBook; // create a GradeBook object named myGradeBook
25
26     // prompt for and input course name
27     cout << "Please enter the course name:" << endl;
28     getline( cin, nameOfCourse ); // read a course name with blanks
29     cout << endl; // output a blank line
30
31     // call myGradeBook's displayMessage function
32     // and pass nameOfCourse as an argument
33     myGradeBook.displayMessage( nameOfCourse );
34 } // end main
```

Please enter the course name:
CS101 Introduction to C++ Programming

Welcome to the grade book for
CS101 Introduction to C++ Programming!



```
{
    "camelCase": "camelCase",
    "PascalCase": "PascalCase",
    "snake_case": "snake_case",
    "kebab-case": "kebab-case"
}
```

Class - Set/Get Functions

```
9 // GradeBook class definition
10 class GradeBook
11 {
12 public:
13     // function that sets the course name
14     void setCourseName( string name )
15     {
16         courseName = name; // store the course name in the object
17     } // end function setCourseName
18
19     // function that gets the course name
20     string getCourseName()
21     {
22         return courseName; // return the object's courseName
23     } // end function getCourseName
24
25     // function that displays a welcome message
26     void displayMessage()
27     {
28         // this statement calls getCourseName to get the
29         // name of the course this GradeBook represents
30         cout << "Welcome to the grade book for\n" << getCourseName() << "!"
31             << endl;
32     } // end function displayMessage
33 private:
34     string courseName; // course name for this GradeBook
35 } // end class GradeBook
```

Initial course name is:

Please enter the course name:
CS101 Introduction to C++ Programming

Welcome to the grade book for
CS101 Introduction to C++ Programming!

```
37 // function main begins program execution
38 int main()
39 {
40     string nameOfCourse; // string of characters to store the course name
41     GradeBook myGradeBook; // create a GradeBook object named myGradeBook
42
43     // display initial value of courseName
44     cout << "Initial course name is: " << myGradeBook.getCourseName()
45         << endl;
46
47     // prompt for, input and set course name
48     cout << "\nPlease enter the course name:" << endl;
49     getline( cin, nameOfCourse ); // read a course name with blanks
50     myGradeBook.setCourseName( nameOfCourse ); // set the course name
51
52     cout << endl; // outputs a blank line
53     myGradeBook.displayMessage(); // display message with new course name
54 } // end main
```

Class - Constructor

```
9 // GradeBook class definition
10 class GradeBook
11 {
12 public:
13 // constructor initializes courseName with string supplied as argument
14 GradeBook( string name )
15 {
16     setCourseName( name ); // call set function to initialize courseName
17 } // end GradeBook constructor
18
```

```
gradeBook1 created for course: CS101 Introduction to C++ Programming
gradeBook2 created for course: CS102 Data Structures in C++
```

```
42 // function main begins program execution
43 int main()
44 {
45     // create two GradeBook objects
46     GradeBook gradeBook1( "CS101 Introduction to C++ Programming" );
47     GradeBook gradeBook2( "CS102 Data Structures in C++" );
48
49     // display initial value of courseName for each GradeBook
50     cout << "gradeBook1 created for course: " << gradeBook1.getCourseName()
51         << "\ngradeBook2 created for course: " << gradeBook2.getCourseName()
52         << endl;
53 } // end main
```

Header File

gradeBook1 created for course: CS101 Introduction to C++ Programming
gradeBook2 created for course: CS102 Data Structures in C++

```
1 // Fig. 16.10: fig16_10.cpp
2 // Including class GradeBook from file GradeBook.h for use in main.
3 #include <iostream>
4 #include "GradeBook.h" // include definition of class GradeBook
5 using namespace std;
6
7 // function main begins program execution
8 int main()
9 {
10    // create two GradeBook objects
11    GradeBook gradeBook1( "CS101 Introduction to C++ Programming" );
12    GradeBook gradeBook2( "CS102 Data Structures in C++" );
13
14    // display initial value of courseName for each GradeBook
15    cout << "gradeBook1 created for course: " << gradeBook1.getCourseName()
16                  << "\ngradeBook2 created for course: " << gradeBook2.getCourseName()
17                  << endl;
18 } // end main
```


Interface

```
1 // Fig. 16.11: GradeBook.h
2 // GradeBook class definition. This file presents GradeBook's public
3 // interface without revealing the implementations of GradeBook's member
4 // functions, which are defined in GradeBook.cpp.
5 #include <string> // class GradeBook uses C++ standard string class
6 using namespace std;
7
8 // GradeBook class definition
9 class GradeBook
10 {
11 public:
12     GradeBook( string ); // constructor that initializes courseName
13     void setCourseName( string ); // function that sets the course name
14     string getCourseName(); // function that gets the course name
15     void displayMessage(); // function that displays a welcome message
16 private:
17     string courseName; // course name for this GradeBook
18 } // end class GradeBook
```

```
1 // Fig. 16.10: fig16_10.cpp
2 // Including class GradeBook from file GradeBook.h for use in main.
3 #include <iostream>
4 #include "GradeBook.h" // include definition of class GradeBook
5 using namespace std;
6
7 // function main begins program execution
8 int main()
9 {
10     // create two GradeBook objects
11     GradeBook gradeBook1( "CS101 Introduction to C++ Programming" );
12     GradeBook gradeBook2( "CS102 Data Structures in C++" );
13
14     // display initial value of courseName for each GradeBook
15     cout << "gradeBook1 created for course: " << gradeBook1.getCourseName()
16         << "\ngradeBook2 created for course: " << gradeBook2.getCourseName()
17         << endl;
18 } // end main
```

```
1 // Fig. 16.12: GradeBook.cpp
2 // GradeBook member-function definitions. This file contains
3 // implementations of the member functions prototyped in GradeBook.h.
4 #include <iostream>
5 #include "GradeBook.h" // include definition of class GradeBook
6 using namespace std;
7
8 // constructor initializes courseName with string supplied as argument
9 GradeBook::GradeBook( string name )
10 {
11     setCourseName( name ); // call set function to initialize courseName
12 } // end GradeBook constructor
13
14 // function to set the course name
15 void GradeBook::setCourseName( string name )
16 {
17     courseName = name; // store the course name in the object
18 } // end function setCourseName
19
20 // function to get the course name
21 string GradeBook::getCourseName()
22 {
23     return courseName; // return object's courseName
24 } // end function getCourseName
25
26 // display a welcome message to the GradeBook user
27 void GradeBook::displayMessage()
28 {
29     // call getCourseName to get the courseName
30     cout << "Welcome to the grade book for\n" << getCourseName()
31         << "!" << endl;
32 } // end function displayMessage
```

Interface - Compilation and Linkage



Interface - Deconstructor

```
1 // Fig. 17.11: CreateAndDestroy.h
2 // CreateAndDestroy class definition.
3 // Member functions defined in CreateAndDestroy.cpp.
4 #include <string>
5 using namespace std;
6
7 #ifndef CREATE_H
8 #define CREATE_H
9
10 class CreateAndDestroy
11 {
12 public:
13     CreateAndDestroy( int, string ); // constructor
14     ~CreateAndDestroy(); // destructor
15 private:
16     int objectID; // ID number for object
17     string message; // message describing object
18 }; // end class CreateAndDestroy
19
20 #endif
```

```
1 // Fig. 17.12: CreateAndDestroy.cpp
2 // CreateAndDestroy class member-function definitions.
3 #include <iostream>
4 #include "CreateAndDestroy.h" // include CreateAndDestroy class definition
5 using namespace std;
6
7 // constructor
8 CreateAndDestroy::CreateAndDestroy( int ID, string messageString )
9 {
10     objectID = ID; // set object's ID number
11     message = messageString; // set object's descriptive message
12
13     cout << "Object " << objectID << " constructor runs "
14         << message << endl;
15 } // end CreateAndDestroy constructor
16
17 // destructor
18 CreateAndDestroy::~CreateAndDestroy()
19 {
20     // output newline for certain objects; helps readability
21     cout << ( objectID == 1 || objectID == 6 ? "\n" : "" );
22
23     cout << "Object " << objectID << " destructor runs "
24         << message << endl;
25 } // end ~CreateAndDestroy destructor
```

Const Objects and Functions


```
const Time noon( 12, 0, 0 );
```

```
7 class Time
8 {
9 public:
10    Time( int = 0, int = 0, int = 0 ); // default constructor
11
12   // set functions
13   void setTime( int, int, int ); // set time
14   void setHour( int ); // set hour
15   void setMinute( int ); // set minute
16   void setSecond( int ); // set second
17
18   // get functions (normally declared const)
19   int getHour() const; // return hour
20   int getMinute() const; // return minute
21   int getSecond() const; // return second
22
23   // print functions (normally declared const)
24   void printUniversal() const; // print universal time
25   void printStandard(); // print standard time (should be const)
26 private:
27   int hour; // 0 - 23 (24-hour clock format)
28   int minute; // 0 - 59
29   int second; // 0 - 59
30 }; // end class Time
31
32 #endif
```

```
C:\examples\ch18\fig18_01_03\fig18_03.cpp(13) : error C2662:
'Time::setHour' : cannot convert 'this' pointer from 'const Time' to 'Time &
Conversion loses qualifiers
C:\examples\ch18\fig18_01_03\fig18_03.cpp(20) : error C2662:
'Time::printStandard' : cannot convert 'this' pointer from 'const Time' to
'Time &
Conversion loses qualifiers
```

```
1 // Fig. 18.3: fig18_03.cpp
2 // Attempting to access a const object with non-const member functions.
3 #include "Time.h" // include Time class definition
4
5 int main()
6 {
7     Time wakeUp( 6, 45, 0 ); // non-constant object
8     const Time noon( 12, 0, 0 ); // constant object
9
10    // OBJECT MEMBER FUNCTION
11    wakeUp.setHour( 18 ); // non-const non-const
12
13    noon.setHour( 12 ); // const non-const
14
15    wakeUp.getHour(); // non-const const
16
17    noon.getMinute(); // const const
18    noon.printUniversal(); // const const
19
20    noon.printStandard(); // const non-const
21 } // end main
```

Inheritance (Single vs. Multiple)



Inheritance

```
1 // Fig. 20.4: CommissionEmployee.h
2 // CommissionEmployee class header.
3 #ifndef COMMISSION_H
4 #define COMMISSION_H
5
6 #include <string> // C++ standard string class
7 using namespace std;
8
9 class CommissionEmployee
10 {
11 public:
12     CommissionEmployee( const string &, const string &, const string &,
13                         double = 0.0, double = 0.0 );
14
15     void setFirstName( const string & ); // set first name
16     string getFirstName() const; // return first name
17
18     void setLastName( const string & ); // set last name
19     string getLastname() const; // return last name
20
21     void setSocialSecurityNumber( const string & ); // set SSN
22     string getSocialSecurityNumber() const; // return SSN
23
24     void setGrossSales( double ); // set gross sales amount
25     double getGrossSales() const; // return gross sales amount
26
27     void setCommissionRate( double ); // set commission rate (percentage)
28     double getCommissionRate() const; // return commission rate
29
30     double earnings() const; // calculate earnings
31     void print() const; // print CommissionEmployee object
32 private:
33     string firstName;
34     string lastName;
35     string socialSecurityNumber;
36     double grossSales; // gross weekly sales
37     double commissionRate; // commission percentage
38 }; // end class CommissionEmployee
39
40 #endif
```

Inheritance

```
10 class BasePlusCommissionEmployee
11 {
12 public:
13     BasePlusCommissionEmployee( const string &, const string &,
14         const string &, double = 0.0, double = 0.0, double = 0.0 );
15
16     void setFirstName( const string & ); // set first name
17     string getFirstName() const; // return first name
18
19     void setLastName( const string & ); // set last name
20     string getLastName() const; // return last name
21
22     void setSocialSecurityNumber( const string & ); // set SSN
23     string getSocialSecurityNumber() const; // return SSN
24
25     void setGrossSales( double ); // set gross sales amount
26     double getGrossSales() const; // return gross sales amount
27
28     void setCommissionRate( double ); // set commission rate
29     double getCommissionRate() const; // return commission rate
30
31     void setBaseSalary( double ); // set base salary
32     double getBaseSalary() const; // return base salary
33
34     double earnings() const; // calculate earnings
35     void print() const; // print BasePlusCommissionEmployee object
36 private:
37     string firstName;
38     string lastName;
39     string socialSecurityNumber;
40     double grossSales; // gross weekly sales
41     double commissionRate; // commission percentage
42     double baseSalary; // base salary
43 }; // end class BasePlusCommissionEmployee
44
45 #endif
```

```
1 // Fig. 20.10: BasePlusCommissionEmployee.h
2 // BasePlusCommissionEmployee class derived from
3 // class CommissionEmployee.
4 #ifndef BASEPLUS_H
5 #define BASEPLUS_H
6
7 #include <string> // C++ standard string class
8 #include "CommissionEmployee.h" // CommissionEmployee class declaration
9 using namespace std;
10
11 class BasePlusCommissionEmployee : public CommissionEmployee
12 {
13 public:
14     BasePlusCommissionEmployee( const string &, const string &,
15         const string &, double = 0.0, double = 0.0, double = 0.0 );
16
17     void setBaseSalary( double ); // set base salary
18     double getBaseSalary() const; // return base salary
19
20     double earnings() const; // calculate earnings
21     void print() const; // print BasePlusCommissionEmployee object
22 private:
23     double baseSalary; // base salary
24 }; // end class BasePlusCommissionEmployee
25
26 #endif
```

Inheritance Protected Data

```
1 // Fig. 20.12: CommissionEmployee.h
2 // CommissionEmployee class definition with protected data.
3 #ifndef COMMISSION_H
4 #define COMMISSION_H
5
6 #include <string> // C++ standard string class
7 using namespace std;
8
9 class CommissionEmployee
10 {
11 public:
12     CommissionEmployee( const string &, const string &, const string &,
13                         double = 0.0, double = 0.0 );
14
15     void setFirstName( const string & ); // set first name
16     string getFirstName() const; // return first name
17
18     void setLastName( const string & ); // set last name
19     string getLastname() const; // return last name
20
21     void setSocialSecurityNumber( const string & ); // set SSN
22     string getSocialSecurityNumber() const; // return SSN
23
24     void setGrossSales( double ); // set gross sales amount
25     double getGrossSales() const; // return gross sales amount
26
27     void setCommissionRate( double ); // set commission rate
28     double getCommissionRate() const; // return commission rate
29
30     double earnings() const; // calculate earnings
31     void print() const; // print CommissionEmployee object
32 protected:
33     string firstName;
34     string lastName;
35     string socialSecurityNumber;
36     double grossSales; // gross weekly sales
37     double commissionRate; // commission percentage
38 }; // end class CommissionEmployee
39
40 #endif
```

Polymorphism

- Assignment of derived-class address to base-class pointer
- Assignment of base-class address to derived-class pointer
- Invoking derived-class functions with base-class pointer
- Invoking base-class functions with derived-class pointer

Polymorphism (1)

```
10 int main()
11 {
12     // create base-class object
13     CommissionEmployee commissionEmployee(
14         "Sue", "Jones", "222-22-2222", 10000, .06 );
15
16     // create base-class pointer
17     CommissionEmployee *commissionEmployeePtr = 0;
18
19     // create derived-class object
20     BasePlusCommissionEmployee basePlusCommissionEmployee(
21         "Bob", "Lewis", "333-33-3333", 5000, .04, 300 );
22
23     // create derived-class pointer
24     BasePlusCommissionEmployee *basePlusCommissionEmployeePtr = 0;
25
26     // set floating-point output formatting
27     cout << fixed << setprecision( 2 );
28
29     // output objects commissionEmployee and basePlusCommissionEmployee
30     cout << "Print base-class and derived-class objects:\n\n";
31     commissionEmployee.print(); // invokes base-class print
32     cout << "\n\n";
33     basePlusCommissionEmployee.print(); // invokes derived-class print
34
35     // aim base-class pointer at base-class object and print
36     commissionEmployeePtr = &commissionEmployee; // perfectly natural
37     cout << "\n\n\nCalling print with base-class pointer to "
38         << "\nbase-class object invokes base-class print function:\n\n";
39     commissionEmployeePtr->print(); // invokes base-class print
40
41     // aim derived-class pointer at derived-class object and print
42     basePlusCommissionEmployeePtr = &basePlusCommissionEmployee; // natural
43     cout << "\n\n\nCalling print with derived-class pointer to "
44         << "\nderived-class object invokes derived-class "
45         << "print function:\n\n";
46     basePlusCommissionEmployeePtr->print(); // invokes derived-class print
47
48     // aim base-class pointer at derived-class object and print
49     commissionEmployeePtr = &basePlusCommissionEmployee;
50     cout << "\n\n\nCalling print with base-class pointer to "
51         << "derived-class object\ninvokes base-class print "
52         << "function on that derived-class object:\n\n";
53     commissionEmployeePtr->print(); // invokes base-class print
54     cout << endl;
55 } // end main
```

Polymorphism (1)

Print base-class and derived-class objects:

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

```
base-salaried commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04  
base salary: 300.00
```

Calling print with base-class pointer to
base-class object invokes base-class print function:

```
commission employee: Sue Jones  
social security number: 222-22-2222  
gross sales: 10000.00  
commission rate: 0.06
```

Calling print with derived-class pointer to
derived-class object invokes derived-class print function:

```
base-salaried commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04  
base salary: 300.00
```

Calling print with base-class pointer to derived-class object
invokes base-class print function on that derived-class object:

```
commission employee: Bob Lewis  
social security number: 333-33-3333  
gross sales: 5000.00  
commission rate: 0.04
```

Polymorphism (2)

```
1 // Fig. 13.2: fig13_02.cpp
2 // Aiming a derived-class pointer at a base-class object.
3 #include "CommissionEmployee.h"
4 #include "BasePlusCommissionEmployee.h"
5
6 int main()
7 {
8     CommissionEmployee commissionEmployee(
9         "Sue", "Jones", "222-22-2222", 10000, .06 );
10    BasePlusCommissionEmployee *basePlusCommissionEmployeePtr = 0;
11
12    // aim derived-class pointer at base-class object
13    // Error: a CommissionEmployee is not a BasePlusCommissionEmployee
14    basePlusCommissionEmployeePtr = &commissionEmployee;
15 } // end main
```

```
C:\cpphttp8_examples\ch13\Fig13_02\fig13_02.cpp(14) : error C2440: '=' :
cannot convert from 'CommissionEmployee *' to 'BasePlusCommissionEmployee *'
Cast from base to derived requires dynamic_cast or static_cast
```

Polymorphism (3)

```
7 int main()
8 {
9     CommissionEmployee *commissionEmployeePtr = 0; // base class
10    BasePlusCommissionEmployee basePlusCommissionEmployee(
11        "Bob", "Lewis", "333-33-3333", 5000, .04, 300 ); // derived class
12
13    // aim base-class pointer at derived-class object
14    commissionEmployeePtr = &basePlusCommissionEmployee;
15
16    // invoke base-class member functions on derived-class
17    // object through base-class pointer (allowed)
18    string firstName = commissionEmployeePtr->getFirstName();
19    string lastName = commissionEmployeePtr->getLastName();
20    string ssn = commissionEmployeePtr->getSocialSecurityNumber();
21    double grossSales = commissionEmployeePtr->getGrossSales();
22    double commissionRate = commissionEmployeePtr->getCommissionRate();
23
24    // attempt to invoke derived-class-only member functions
25    // on derived-class object through base-class pointer (disallowed)
26    double baseSalary = commissionEmployeePtr->getBaseSalary();
27    commissionEmployeePtr->setBaseSalary( 500 );
28 } // end main
```

```
fig13_03.cpp:26: error: 'getBaseSalary' undeclared (first use this function)
fig13_03.cpp:27: error: 'setBaseSalary' undeclared (first use this function)
```

Exception Handling

```
1 // Fig. 16.1: DivideByZeroException.h
2 // Class DivideByZeroException definition.
3 #include <stdexcept> // stdexcept header contains runtime_error
4 using namespace std;
5
6 // DivideByZeroException objects should be thrown by functions
7 // upon detecting division-by-zero exceptions
8 class DivideByZeroException : public runtime_error
9 {
10 public:
11     // constructor specifies default error message
12     DivideByZeroException()
13         runtime_error( "attempted to divide by zero" )
14 }; // end class DivideByZeroException
```

```
1 // Fig. 16.2: Fig16_02.cpp
2 // A simple exception-handling example that checks for
3 // divide-by-zero exceptions.
4 #include <iostream>
5 #include "DivideByZeroException.h" // DivideByZeroException class
6 using namespace std;
7
8 // perform division and throw DivideByZeroException object if
9 // divide-by-zero exception occurs
10 double quotient( int numerator, int denominator )
11 {
12     // throw DivideByZeroException if trying to divide by zero
13     if ( denominator == 0 )
14         throw DivideByZeroException(); // terminate function
15
16     // return division result
17     return static_cast< double >( numerator ) / denominator;
18 } // end function quotient
19
20 int main()
21 {
22     int number1; // user-specified numerator
23     int number2; // user-specified denominator
24     double result; // result of division
25
26     cout << "Enter two integers (end-of-file to end): ";
27
28     // enable user to enter two integers to divide
29     while ( cin >> number1 >> number2 )
30     {
31         // try block contains code that might throw exception
32         // and code that will not execute if an exception occurs
33         try
34         {
35             result = quotient( number1, number2 );
36             cout << "The quotient is: " << result << endl;
37         } // end try
38         catch ( DivideByZeroException &divideByZeroException )
39         {
40             cout << "Exception occurred: "
41                 << divideByZeroException.what() << endl;
42         } // end catch
43
44         cout << "\nEnter two integers (end-of-file to end): ";
45     } // end while
46
47     cout << endl;
48 } // end main
```

Exception Handling

```
7 // throw, catch and rethrow exception
8 void throwException()
9 {
10    // throw exception and catch it immediately
11    try
12    {
13        cout << " Function throwException throws an exception\n";
14        throw exception(); // generate exception
15    } // end try
16    catch ( exception & ) // handle exception
17    {
18        cout << " Exception handled in function throwException"
19        << "\n Function throwException rethrows exception";
20        throw; // rethrow exception for further processing
21    } // end catch
22
23    cout << "This also should not print\n";
24 } // end function throwException
25
26 int main()
27 {
28    // throw exception
29    try
30    {
31        cout << "\nmain invokes function throwException\n";
32        throwException();
33        cout << "This should not print\n";
34    } // end try
35    catch ( exception & ) // handle exception
36    {
37        cout << "\n\nException handled in main\n";
38    } // end catch
39
40    cout << "Program control continues after catch in main\n";
41 } // end main
```

Exception Handling

