Introduction to Vim, I

Introduction to Programming

EE231002

Sep. 26, 2016

Starting vim

• To start vim: vim file




For new file



Three Modes in vim

- There are three modes in vim.
 - Normal mode: copy, delete, paste
 - Insert mode: insert text
 - · Command line mode: save file, exit, search and replace



Inserting Text

- When vim starts, it enters normal mode
- Press i to enter insert mode
 - Note the -- INSERT -- on the lower-left corner
 - You can type in C program at this time



Insert Mode

- In insert mode, you can type in texts
- To move cursor
 - $\bullet \mid \uparrow \mid, \mid \downarrow \mid$, \longleftarrow , \longmapsto keys move cursor in four directions
 - PgUp and PgDn keys scroll one page of text
 - Home key moves cursor to the beginning of the line
 - End key moves cursor to the end of the line
 - Tab key moves cursor to fixed columns (4x or 8x)
 - In our labs please use Tab key for indentation and each Tab key moves 4 spaces
- Press Esc key to return to normal mode

Quitting vim

- In normal mode, the following commands save file or quit vim program
 - :w: save typed inputs to the file

 - | :q! |: forced quitting from vim program
 - Changes are not updated to the file
 - :wq: save file and then quit vim program
 - ZZ : same as wq but is a normal mode command
 - Note that that the above except ZZ are executed in command line mode

```
int degreeC, degreeF; // store temperatures

printf("Enter temperature in Celsius: "); // prompt
scanf("%d", &degreeC); // read temp
degreeF=degreeC*9.0/5.0+32.0; // conversion
printf("Temperature in Fahrenheit: %d\n", degreeF);
return 0;
}
```

Show Line Numbers in vim

- vim does not show line numbers by default
 - Line numbers are very useful in debugging compiler errors
 - To show line number type in : set nu in normal mode

```
int degreeC, degreeF; // store temperatures
   printf("Enter temperature in Celsius: "); // prompt
   scanf("%d", &degreeC);
                                              // read temp
   degreeF=degreeC*9.0/5.0+32.0;
                                             // conversion
   printf("Temperature in Fahrenheit: %d\n", degreeF);
   return 0;
:set nu
                michang - ssh ee231002@140.114.24.112 - 63×10
       int degreeC, degreeF; // store temperatures
10
       printf("Enter temperature in Celsius: "); // prompt
       scanf("%d", &degreeC);
                                             // read temp
13
       degreeF=degreeC*9.0/5.0+32.0;
                                                 // conversion
14
       printf("Temperature in Fahrenheit: %d\n", degreeF);
15
       return 0:
16 }
                                             15,10-13
                                                           Bot
```

Color Text

- vim takes advantage of the color terminal to make the file more legible
- The text color can be turned off by using :syntax off command
- :syntax on turns on color text

```
int degreeC, degreeF;
                            // store temperatures
   printf("Enter temperature in Celsius: "); // prompt
   scanf("%d", &degreeC);
                                               // read temp
   degreeF=degreeC*9.0/5.0+32.0;
                                               // conversion
   printf("Temperature in Fahrenheit: %d\n", degreeF);
   return 0:
                                              15,10-13
                                                             Bot
. . .
                 michang - ssh ee231002@140.114.24.112 - 63×9
    int degreeC, degreeF;// store temperatures
   printf("Enter temperature in Celsius: ");// prompt
   scanf("%d", &degreeC);// read temp
   degreeF=degreeC*9.0/5.0+32.0;// conversion
   printf("Temperature in Fahrenheit: %d\n", degreeF);
   return 0:
                                               15,10-13
                                                             Bot
```

Color Text, II

 Depending on terminal background, the text color may need to be adjusted

```
:set bg=dark
           8 {
                 int degreeC, degreeF; // store temperatures
           10
                 printf("Enter temperature in Celsius: "); // prompt
                 scanf("%d", &degreeC);
                                                           // read temp
          13
                 degreeF=degreeC\times9.0/5.0+32.0;
                                                           // conversion
          14
                 printf("Temperature in Fahrenheit: %d\n", degreeF);
          15
                 return 0:
          16 }
                                                      15,10-13
                                                                    Bot
:set bg=light
          . . .
                 int degreeC. degreeF: // store temperatures
           10
                 printf("Enter temperature in Celsius: "); // prompt
                 scanf("%d", &degreeC);
                 degreeF=degreeC*9.0/5.0+32.0;
                 printf("Temperature in Fahrenheit: %d\n", degreeF);
```

16 }

return 0;


Auto-indent

- In insert mode, after typing a line of text the cursor moves to the first column – not aligned with the indented text
- This can be changed by set ai, auto-indent, command
- | :set noai | sets no auto-indent

```
int degreeC, degreeF; // store temperatures
       printf("Enter temperature in Celsius: "); // prompt
12
  INSERT --
                                            12.1
                                                          Bot
       int degreeC, degreeF; // store temperatures
10
       printf("Enter temperature in Celsius: "); // prompt
  INSERT --
                                            12.2-5
                                                          Bot
```

.vimrc

- vim program executes the commands in .vimrc every time it is invoked.
- Please copy ~ee231002/. vimrc to your home directory



- This file sets
 - Auto-indent mode
 - Each Tab inserts 4 spaces

vim Tutorial

- vim program provides a tutorial for users to learn the easy commands
- At a linux terminal type in vimtutor as following to enter the tutorial

[ee231002@ws38 lab01]\$ vimtutor

vim Tutorial, II

Most frequently used commands are demonstrated

● ● ● ★ michang — ssh ee231002@140.114.24.112 — 80×24

= Welcome to the VIM Tutor — Version 1.7 =

Vim is a very powerful editor that has many commands, too many to explain in a tutor such as this. This tutor is designed to describe enough of the commands that you will be able to easily use Vim as an all-purpose editor.

The approximate time required to complete the tutor is 25-30 minutes, depending upon how much time is spent with experimentation.

ATTENTION:

The commands in the lessons will modify the text. Make a copy of this file to practise on (if you started "vimtutor" this is already a copy).

It is important to remember that this tutor is set up to teach by use. That means that you need to execute the commands to learn them properly. If you only read the text, you will forget the commands!

Now, make sure that your Shift-Lock key is NOT depressed and press the j key enough times to move the cursor so that Lesson 1.1 completely fills the screen.