

Flag 4 (Login 2)

Analysis & Exploitation Steps:-




Figure 1: Analyzing AndroidManifest.xml and Searched for the String "flag_four" and Found an Activity of Class "b3nac.injuredandroid.FlagFourActivity"




Figure 2: Displays the Decompiled Source for "b3nac.injuredandroid.FlagFourActivity" Class

```

b3nac.injuredandroid.g x
1 package b3nac.injuredandroid;
2
3 import android.util.Base64;
4
5 /* JADX INFO: loaded from: classes.dex */
6 public class g {
7
8     /* JADX INFO: renamed from: a, reason: collision with root package name */
9     private byte[] f1468a = Base64.decode("NF9vdmVyZG9uZV9vbWVsZXRz", 0);
10
11     public byte[] a() {
12         return this.f1468a;
13     }
14 }

```

Figure 3: Displays the Class that Decodes a Hardcoded Base64 String

```

$ echo "NF9vdmVyZG9uZV9vbWVsZXRz" | base64 -d
4_overdone_omelets

```

Figure 4: Displays the Decoding of Base64 String that is used for comparison




Figure 5: Displays Successful Submission of the Flag

Impacts:-

- **Exposes vulnerable application logic, may reveal sensitive functionality & increases the attack surface**

Remediations:-

- **Review imported and inherited classes, restrict sensitive application logic & validate access to sensitive functions**