

---

## Configure Custom DNS-Filtering Profiles



For supported software information, click [here](#).

Domain Name System (DNS) filtering allows you to control access to websites, webpages, and IP addresses, to provide protection from malicious websites, such as known malware and phishing sites.


You can create custom profiles that you can use when configuring internet protection rules. You associate custom DNS filtering profiles with devices that are connected to a Secure Web Gateway (SWG) and that need to send traffic to the internet. DNS filtering processes any traffic that matches an internet protection rule in a DNS-filtering profile. Any logs that are generated are sent to the logging profile associated with the DNS profile.

In a DNS-filtering profile you can configure the following components to use to filter DNS requests:


- Deny lists—Define the URLs and IP addresses of DNS requests for which access is blocked, and define the action to take when a URL or an IP address matches. Deny lists are sometimes referred to as blacklists.
- Allow lists—Define the URLs and IP addresses of DNS requests to which to explicitly allow access. Allow lists are sometimes referred to as whitelists.
- Query-based actions—Define rules for DNS operation codes (opcodes), which are the commands that are sent to DNS servers to have them perform an action.
- Reputation-based actions—Define how to handle DNS requests from newly observed website domains.

To configure custom DNS-filtering profiles:

1. Go to Configure > Real-Time Protection > Profiles.



The following screen displays:



2. Select the DNS Filtering tab.
3. To customize which columns display, click Select Columns and then click the columns to select or deselect the ones you want to display. Click Reset to return to the default column display settings.

Select Columns

☒ Deny List

☒ Allow List

☐ Query Based Actions

☒ Reputations & Profiles

Reset

- Click + Add to create a rule. The Create DNS Filtering screen displays, and the Deny and Allow List step is selected. By default, all fields are configured. To customize DNS-filtering actions, enter information for the following fields. Note that if the traffic matches both a deny list and an allow list, the action in the deny list takes precedence.

Configure > SASE > Real-Time Protection > Profiles > DNS Filtering

Create DNS Filtering Profile

1

2

3

4

DENY & ALLOW LIST

QUERY BASED ACTIONS

REPUTATIONS & PROFILES

REVIEW & SUBMIT

By default, all fields have been configured. Otherwise, you can choose which deny and allow actions to enforce for your DNS filtering.

If traffic is matched in both the deny and allow, then the action in the deny takes precedence.

Deny List

Choose which domains and actions to deny (blacklist).

Action

Alert

Patterns

Type a PCRE RegEx pattern

+

Strings

Type a comma separated list of strings

Allow List

Choose which domains to allow (whitelist).

Patterns

Type a PCRE RegEx pattern

+

Strings

Type a comma separated list of strings

☐ Enable Logging




Cancel




Back

Skip to Review

Next

Field	Description
Deny List (Group of Fields)	Choose the domains and actions to deny (block).
<ul style="list-style-type: none"> <li>Action</li> </ul>	Select the action to take for domain names or IP addresses when denying (blocking) incoming DNS requests:





Field	Description
	<ul style="list-style-type: none"> <li>◦ Alert—Allow the DNS response and generate an entry in the DNS filtering log in Versa Analytics.</li> <li>◦ Allow—Allow the DNS response without generating an entry in the DNS filtering log in Versa Analytics.</li> <li>◦ Drop Packet—The browser waits for a response from the DNS server and then drops the packet. It is not possible to determine whether the packet was dropped because of a delayed response from the DNS server or because a firewall blocked access to the website.</li> <li>◦ Drop Session—The browser waits for a response from the server and drops the session. It is not possible to determine whether the session was dropped because of a delayed response from the DNS server or because a firewall blocked access to the website.</li> <li>◦ Reject—Send an ICMP unreachable message back to the client.</li> <li>◦ Sinkhole—Return a false IP address to the URL, thus blocking a DNS sinkhole. A DNS sinkhole spoofs DNS servers to prevent the resolution of the hostnames associated with URLs. This action can help you identify infected hosts in a network if a firewall is unable to find the original source IP address of DNS request sender. Sinkhole malware DNS queries create responses to the client host queries directed at malicious domains and try to connect to a sinkhole IP address instead of connecting to malicious domains. You can check the traffic logs to identify infected hosts.</li> </ul>
<ul style="list-style-type: none"> <li>◦ Patterns</li> </ul>	<p>Click the  Add icon to add a domain name or an IP address to deny. You can specify a fixed string or a Perl-Compatible Regular Expression (PCRE). Note that if the pattern matches the same domain name or IP address in a deny list and an allow list, the action in the deny list takes precedence. Click the  Add icon again to add more patterns. Click the  Delete icon to delete a pattern.</p>
<ul style="list-style-type: none"> <li>◦ Strings</li> </ul>	<p>Enter a complete string for matching a domain name or IP address to block. Note that if the string matches</p>

Field	Description
	the same domain name or IP address in a deny list and an allow list, the action in the deny list takes precedence.
Allow List (Group of Fields)	Choose the domains and actions that you want to allow.
<ul style="list-style-type: none"> <li>Patterns</li> </ul>	Click the  Add icon to add a domain name or an IP address to allow. You can specify a fixed string or a Perl-Compatible Regular Expression (PCRE). Note that if the pattern matches the same domain name or IP address in a deny list and an allow list, the action in the deny list takes precedence. Click the  Add icon again to add more patterns. Click the  Delete icon to delete a pattern.
<ul style="list-style-type: none"> <li>Strings</li> </ul>	Enter a complete domain name for matching a domain name or IP address to allow. You can add multiple comma-separated strings. Note that if the string matches the same domain name or IP address in a deny list and an allow list, the action in the deny list takes precedence.
<ul style="list-style-type: none"> <li>Enable Logging</li> </ul>	Click to log information about the allowed domain names and IP addresses.




- Click Next to go to the Query-Based Actions screen, to define rules for DNS operation codes (opcodes), which are commands that are sent to the DNS server to have it perform an action.

Configure > SASE > Real-Time Protection > Profiles > DNS Filtering

Create DNS Filtering Profile


1  DENY & ALLOW LIST 2  QUERY BASED ACTIONS 3  REPUTATIONS & PROFILES 4  REVIEW & SUBMIT


By default, all fields have been configured. Otherwise, you can choose which queries to enforce for your DNS filtering.

 Add  Delete Select Columns 

NAME	ACTION	REQUEST TYPE	DETAILS
No Data			

Cancel Back Skip to Review **Next**

- Click the  Add icon, and in the Add Query-Based Actions popup window, enter information for the following fields.

Add Query Based Actions

Choose which action and configurations to apply for your query.

Name\*

Action

Allow

Request Type

-- Select --

Cancel

Add

Field	Description
Name (Required)	Enter a name for the query-based action.
Action	<p>Select the action to take on the DNS request:</p> <ul style="list-style-type: none"> <li>◦ Alert—Allow the DNS response and generate an entry in the DNS filtering log in Versa Analytics.</li> <li>◦ Allow—Allow the DNS response without generating an entry in the DNS filtering log in Versa Analytics.</li> <li>◦ Drop Packet—The browser waits for a response from the DNS server and then drops the packet. It is not possible to determine whether the packet was dropped because of a delayed response from the DNS server or because a firewall blocked access to the website.</li> <li>◦ Drop Session—The browser waits for a response from the server and drops the session. It is not possible to determine whether the session was dropped because of a delayed response from the DNS server or because a firewall blocked access to the website.</li> <li>◦ Reject—Send an ICMP unreachable message back to the client.</li> <li>◦ Sinkhole—Return a false IP address to the URL, thus blocking a DNS sinkhole. A DNS sinkhole spoofs DNS servers to prevent the resolution of the hostnames associated with URLs. This action can help you identify infected hosts in a network if a firewall is unable to find the original source IP address of DNS request sender. Sinkhole malware DNS queries create responses to the client host queries directed at malicious domains and try to connect to a sinkhole IP address instead of connecting to malicious domains. You can check the traffic logs to identify infected hosts.</li> </ul>
Request Type	<p>Select the type of DNS opcode to which the rule applies:</p> <ul style="list-style-type: none"> <li>◦ IQuery—Send a request for an inverse DNS query command.</li> <li>◦ Notify—Send a request for a DNS notify command.</li> </ul>



	<ul style="list-style-type: none"> <li>◦ Query—Send a request for a DNS query command.</li> <li>◦ Status—Send a request for a DNS status command.</li> <li>◦ Update—Send a request for a DNS update command.</li> </ul> <p>For each request type, you must enter additional information, as described in the following steps.</p>
--	---

7. For the IQuery request type, enter information for the following fields.

Add Query Based Actions

IQuery

Address Group ⓘ

Select 1 or more Address Groups

IPv4/IPv6 Subnet ⓘ

Enter a list of IP Subnet values

IP Range ⓘ

Enter a list of IP Range values


IP WildCard ⓘ


Enter a list of wildcard values

Cancel

Add

Field	Description
Address Group	Select one or more address groups.
IPv4/IPv6 Subnet	Enter a list of IPv4 or IPv6 subnet values.
IP Range	Enter a list of IP address ranges.
IP Wildcard	Enter a list of IP address wildcard values.

8. For the Notify or Status request type, click the  Add icon to add zone names.



The dialog box titled "Add Query Based Actions" features a close button (X) in the top right corner. It contains a large empty text input field at the top. Below it, the "Action" section has a dropdown menu currently set to "Alert". The "Request Type" section has a dropdown menu currently set to "Notify". The "Zones" section includes a large empty text input field and a blue circular button with a white plus sign (+) to its right. At the bottom, there are two buttons: "Cancel" and "Add". A vertical scrollbar is visible on the right side of the dialog.

9. For the Query request type, enter information for the following fields.

Add Query Based Actions

Query

Number of additional records

-- Select --

Number of questions

-- Select --

Query Type


CERT

Domain Names

Cancel

Add

Field	Description
Number of Additional Records	Enter the number of additional records and select one of the following operators: <ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>
Number of Questions	Enter the number of questions and select one of the following operators: <ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>

Query Type	Select the query type.
Domain Names	Enter the domain name. Click the  Add icon to add more domain names.

10. For the Update request type, enter information for the following fields.

×

Add Query Based Actions

Number of zone records

-- Select --

Number of prerequisite records

-- Select --

Number of additional records

-- Select --

Number of update records


-- Select --

Domain Names

Cancel

Add

Field	Description
Number of Zone Records	Enter the number of zone records and select one of the following operators: <ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>
Number of Prerequisite Records	Enter the number of prerequisite records and select one of the following operators:

	<ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>
Number of Additional Records	Enter the number of additional records and select one of the following operators: <ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>
Number of Update Records	Enter the number of update records and select one of the following operators: <ul style="list-style-type: none"> <li>◦ equal-to</li> <li>◦ greater-than</li> <li>◦ less-than</li> <li>◦ not-equal-to</li> </ul>
Domain Name	Click the  Add icon to add domain names.

11. Click Next to go to the Reputations and Profiles screen, to define how to handle DNS requests from newly observed website domains. Enter information for the following fields.

Configure > SASE > Real-Time Protection > Profiles > DNS Filtering

### Create DNS Filtering Profile

1 DENY & ALLOW LIST
 2 QUERY BASED ACTIONS
 3 REPUTATIONS & PROFILES
 4 REVIEW & SUBMIT

By default, all fields have been configured. Otherwise, you can choose which reputation based actions to enforce for your DNS filtering.

**Newly Observed Domains**  
Configure how to handle requests from newly observed domains.

Action:

Duration to wait before taking action:   
Enter a range between 1 - 168

**IP Filtering and URL Filtering Profiles**  
Choose which profiles to apply to the session.

IP Filtering Profile:

URL Filtering Profile:

Cancel
Back
Skip to Review
Next

Field	Description
Newly Observed Domains (Group of Fields)	Configure how to handle requests from newly observed domains.
<ul style="list-style-type: none"> <li>Duration</li> </ul>	<p>How long to wait, in hours, before taking the configured action on a newly observed domain.</p> <p><b>Range:</b> 1 through 168 hours</p>
<ul style="list-style-type: none"> <li>Action</li> </ul>	<p>Action to take on the newly observed domain:</p> <ul style="list-style-type: none"> <li>Alert—Allow the DNS response and generate an entry in the DNS filtering log.</li> <li>Allow—Allow the DNS response and do not add an entry in the DNS filtering log.</li> <li>Drop Packet—Have the browser wait for a response from the DNS server. If a response is not possible to determine whether the packet was dropped because of a firewall blocked access to the website.</li> <li>Drop Session—Have the browser wait for a response from the server. If a response is not possible to determine whether the session was dropped because of a firewall blocked access to the website.</li> <li>Reject—Send an ICMP unreachable message back to the client.</li> </ul>

	<ul style="list-style-type: none"> <li>◦ Sinkhole—Return a false IP address to the URL, thus blocking a DNS sinkhole. DNS servers to prevent the resolution of the hostnames associated with the domain. This helps identify infected hosts in a network if a firewall is unable to find the original IP address of the request sender. Sinkhole malware DNS queries create responses to the queries for the malicious domains and try to connect to a sinkhole IP address instead of the original domains. You can check the traffic logs to identify infected hosts.</li> </ul>
IP-Filtering and URL-Filtering Profiles (Group of Fields)	Choose the profiles to apply to the session.
<ul style="list-style-type: none"> <li>◦ IP-Filtering Profile</li> </ul>	Select an IP-filtering profile to use to evaluate the resolved IP addresses and associated with the domain. The action taken based on the IP-filtering profile is to select predefined and custom IP-filtering profiles. For more information, see <a href="#">Configuring IP-Filtering Profiles</a> .
<ul style="list-style-type: none"> <li>◦ URL-Filtering Profile</li> </ul>	Select the URL-filtering profile to use to evaluate domain names and common response messages. The action taken based on the URL-filtering profile applies to select predefined and custom URL-filtering profiles. For more information, see <a href="#">Configuring URL-Filtering Profiles</a> .

12. Click Next to go to the Review and Submit screen.

13. In the General section, enter a name for the DNS-filtering profile and, optionally, a description and tags.

14. For all other sections, review the information. If you need to make changes, click the Edit icon.

15. Click Save.

To delete a file DNS profile, select the profile in the DNS Filtering tab and click the  Delete icon.

---

## Supported Software Information

Releases 11.2.1 and later support all content described in this article.

---

## Additional Information

[Configure Custom URL-Filtering Profiles](#)

[Configure SASE Internet Protection Rules](#)