

## Factory Default Settings for Branch Devices



For supported software information, click here.

Each physical or virtual Versa Operating System<sup>TM</sup> (VOS<sup>TM</sup>) device has default factory settings. The default factory settings are stored in the following files:

- /opt/versa/etc/bootcfg/default-device-versa-csg7xx-specific.cfg—For CSG700 series appliances
- /opt/versa/etc/bootcfg/default-device-versa-csg1xxx-specific.cfg—For CSG1000 series appliances
- /opt/versa/etc/bootcfg/default-device.cfg—For all other appliances

The default factory settings are stored in files in the /opt/versa/etc/bootcfg directory on the VOS device. For example:

```
[admin@CSG355: bootcfg] $ pwd
/opt/versa/etc/bootcfg
[admin@CSG355: bootcfg] $ Is -al
total 56
drwxrwxr-x 2 versa versa 4096 Nov 24 20:50 .
drwxrwxr-x 17 versa versa 4096 Nov 24 20:59 ..
-rw-rw-r- 1 versa versa 13962 Oct 2 07:01 default-device.cfg
-rw-rw-r-- 1 versa versa 16156 Oct 2 07:01 default-device-versa-csg1xxx-specific.cfg
-rw-rw-r-- 1 versa versa 14458 Oct 2 07:01 default-device-versa-csg7xx-specific.cfg
```

To return to the factory default configuration, issue the following command on the VOS device:

admin@CSG355-cli> request system load-default

## For example:

```
admin@CSG355-cli> request system load-default?

Description: Reset the appliance to default device configuration

Possible completions:

create-snapshot - Create FACTORY-DEFAULT snapshot (on load default completion)

admin@ODI-TEST-CSG355-JAB20023804-cli> request system load-default
```

## Supported Software Information

Releases 20.2 and later support all content described in this article.

https://docs.versa-networks.com/Secure\_SD-WAN/01\_Configuration\_from\_Director/SD-WAN\_Configuration/Basic\_SD-WAN\_...
Updated: Wed, 23 Oct 2024 08:12:58 GMT
Copyright © 2024, Versa Networks, Inc.

## **Additional Information**

<u>Configure Basic Features</u>
<u>View Branch Device Configuration</u>