
Configure SaaS Tenant Control Profiles

 For supported software information, click [here](#).


You use SaaS tenant control profiles to block users from directly accessing select services, such as web-based Office365, without going through a Versa gateway. When you configure a SaaS tenant control profile, the tenant control profile inserts fields and values in the HTTP header when traffic goes through the gateway. The headers come from the SaaS application vendors, such as YouTube or Office365. The profile is automatically inserted into all a tenant's TLS decryption profiles.

For a SaaS tenant control configuration to take effect, you must configure a TLS decryption profile that refers to the SaaS tenant control profile, and you must configure policy rules. For more information, see [Configure SASE TLS Decryption](#).


You can configure only one SaaS tenant control profile for each tenant.

To configure SaaS a tenant control profile:

1. Go to Configure > Secure Services Edge > Real-Time Protection > Profiles.



The following screen displays.



2. Select the Secure Web Gateway (SWG) tab, and then select the SaaS Tenant Control tab.
3. To customize which columns display, click Select Columns, and then click the columns to select or deselect the one you want to display. Click Reset to return to the default column display settings.


Select Columns

☒ Rules

☒ Application

☒ Action Request

Reset

4. Click the  Add icon to create a profile. The Create HTTP Header Profile screen displays.

Configure > SASE > Real-Time Protection > Profiles > Http Header


Create Http Header Profile

1
Application Rules

2
Review & Submit

Add Application Rules for your Tenant Control

Search


 Add

Delete

Refresh

Select Columns

Name	Application	Type	Action Request	Values
No Data				

5. In Step 1, Application Rules, click the  Add icon. In the Add Application Rule screen, enter information for the following fields.

Add Application Rule

Choose your configurations to enforce your rule

Name *

Enter a Rule Name

Action Type

Choose which action to use for your application

☒ Insert
☐ Delete

Application

Select an Application Type

Cancel

Add

Field	Description				
Name	Enter a name for the application rule.				
Action Type	Click to choose the action to use for the application: <ul style="list-style-type: none"> ◦ Delete ◦ Insert 				
Application	<p>Select an application. For applications that have predefined headers, the following fields display. Enter information for the following fields.</p> <div> <div> <p>Action Type</p> <p>Choose which action to use for your application</p> <p><input checked="" type="radio"/> Insert <input type="radio"/> Delete</p> </div> <div> <p>Application</p> <p>Google-Apps-Access-Control</p> </div> </div> <p>Select one or more headers for your rule</p> <table> <tr> <th>Header</th><th>Value</th></tr> <tr> <td><input type="text"/></td><td><input type="text"/></td></tr> </table> <p> <ul style="list-style-type: none"> ◦ Header—Select a header for the application. ◦ Value—Enter a value. You can enter multiple values, each one separated by a comma. <p>To delete the header, click Delete Existing.</p> </p>	Header	Value	<input type="text"/>	<input type="text"/>
Header	Value				
<input type="text"/>	<input type="text"/>				

6. Click Add.

Supported Software Information

Releases 11.4.1 and later support all content described in this article.

Additional Information

[Configure SASE TLS Decryption](#)