
Versa SSE Quick Start Guide

This guide describes the minimum configuration requirements to set up an SSE Client through Concerto. You can find more advanced SSE configurations on the Versa Documentation Portal.

The following links provide more basic Concerto information:

- [Quick video on Concerto configuration](#)
- [Concerto Home Screen Overview](#)

For more information on the required configuration steps outlined in this guide, see the following articles on the Versa Documentation Portal:

- [Configure Site-to-Site Tunnels](#)
- [User and Device Authentication](#)
- [Versa SASE Client Install](#)
- [Configure TLS Decryption](#)
- [Configure SASE Secure Client Access Profiles](#)
- [Configure SASE Secure Client Access Rules](#)
- [Configure SASE Internet Protection Rules](#)
- [Configure SASE Private Application Protection Rules](#)
- [Publish SASE Gateways](#)

This Quick Start Guide covers the following steps to set up an SSE Client through Concerto:

[Step 1: Log in to Concerto](#)

[Step 2: Configure Site-to-Site Tunnel or SD-WAN](#)

[Step 3: Configure User Authentication](#)

[Step 4: Set the Versa Directory User Password and Install SASE Client](#)

[Step 5: Configure Decryption Profiles](#)

[Step 6: Configure a TLS Decryption Policy Rule](#)

[Step 7: Configure a Secure Client Access Profile](#)

[Step 8: Configure a Secure Client Access Policy Rule](#)

[Step 9: Create an Internet Protection Policy](#)


[Step 10: Create a Private Protection Policy \(Optional\)](#)

[Step 11: Publish Policies to Gateways](#)

[Step 12: Connect to the Gateways Using the Configured Client Policy](#)

Step 1: Log in to Concerto

Log in to Concerto Orchestrator using the credentials and URL provided to you. You may be asked to change your password if you are logging into the portal for the first time.

The image shows the login page for Versa Networks Concerto. At the top center is the Versa Networks logo, which consists of a stylized 'V' made of two overlapping shapes (one green, one blue) followed by the text 'VERSA NETWORKS'. Below the logo is a white rectangular box containing the text 'Non-Production Use Only' in blue. Inside this box are two input fields: 'Username' and 'Password'. The 'Password' field has a small eye icon to its right. Below the input fields is a blue button labeled 'Login'. To the right of the 'Password' field, outside the white box, is a link that says 'Forgot Password'. Below the white box, centered, is a link that says 'Login with SSO'.

Step 2: Configure Site-to-Site Tunnel or SD-WAN

For more information, see [Configure Site-to-Site Tunnels](#).

Select Configure > Settings > Site-To-Site Tunnels. (If you do not have an IPsec tunnel endpoint to use [existing branch router or datacenter edge router], you can skip Step 2).

Note that this step is needed if you are interconnecting your private enterprise network into the Versa SSE infrastructure – whether for connectivity to your IDP or your internal private networks. If you have purchased Versa SD-WAN, you can use SD-WAN instead of IPsec/GRE for connectivity into the gateways from your enterprise network. (You must confirm your purchase with Versa account team).

View

Configure

Deploy

Monitor

Analytics

Inventory

Users

Settings

Security Service Edge

Secure SD-WAN

Search...

> Real-Time Protection

> Secure Client Access

> TLS Decryption

> User and Device Authentication

Settings

BGP Peer Policies

Captive Portal

Certificates

Endpoint Information Profile

Files And Folders

Mobile Device Manager

> Partner Integration

SIEM Integration

SiteToSite Tunnels

Click + Add.

Below are all the Site-to-Site Tunnels

Search

+ Add

Delete

Refresh

Select Columns

	Name	Gateway	Type	Description	Tags	Last Modified	Enabled	Settings
No Data								

You need to configure the following parameters according to your tunnel requirements:

- Type
- IPsec Information
- Address and Routing/Policy Configurations
- Name, Description, and Tags.

1 Enter TYPE

Type

☒ IPsec
 ☐ GRE

☒ Enabled

Tunnel Type

Route Based ▼

Gateway Link

Versa Gateway

Select ▼

↔

Remote Public IP Address or FQDN

Enter IP Address or FQDN

The IPsec tunnel is configured on the Gateway as Responder-only. This means that the IKE session has to be initiated by the peer.

Cancel
Next

2 Enter IPSEC INFORMATION

3 Enter ADDRESS & ROUTING / POLICY CONFIGURATIONS


4 Enter NAME, DESCRIPTION & TAGS

Step 3: Configure User Authentication


For more information, see [User and Device Authentication](#).

For authorized access, you must be authenticated by Versa Secure Client.

Select Configure > User and Device Authentication > Profiles.



In the User and Device Authentication Profile page, click + Add.



There are many ways you can integrate an IDP to utilize authentication methods such as SAML, RADIUS, or LDAP. The simplest way is to use a Versa Directory, which is an IDP hosted by Versa Networks for customers who do not have an IDP. The following output focuses on using Versa Directory. Refer to the documentation if selecting SAML, LDAP, or RADIUS for descriptions of the fields required for input and relevant instructions.

Add User and Device Authentication Profile

Select which user / device authentication profile you would like to configure.

LDAP

LDAP is a client-server protocol that enables a network device to access an LDAP server, which provides directory services that store descriptive attribute-based information.

Note: LDAP authentication profile can be combined with SAML, User Certificate Based and Device Certificate Based authentication profiles.

SAML

SAML is a common standard for authenticating users so that they can access multiple services and applications. SAML is most commonly used for web browser-based single sign-on (SSO)

Note: SAML authentication profile can be combined with LDAP, User Certificate Based and Device Certificate Based authentication profiles.

RADIUS

RADIUS server provides an external database that you can use to authenticate users before allowing them to access a network, a device, or related services.

Note: RADIUS authentication profile can not be combined with other authentication profiles.

Versa Directory

With Versa directory authentication, you upload lists of users and groups for authentication purposes, as well as add individual users and user groups.

Note: Versa Directory authentication profile can not be combined with other authentication profiles.

User Certificate Based

Note: User certificate based authentication profile can be combined with LDAP, SAML and device certificate based authentication profiles.

Device Certificate Based

Note: Device certificate based authentication profile can be combined with LDAP, SAML and user certificate based authentication profiles.

Cancel

Get Started

You can use the default settings or add more concurrent logins for testing.

Add Versa Directory Authentication Profile

1

2

3

SettingsUsers And User GroupsReview & Submit

Cache Expiry Time (mins)

10

Concurrent Logins

1

Cancel

Skip to Review

Next

Click + Add to create users.

Add Versa Directory Authentication Profile

2

3

Settings
Users And User Groups
Review & Submit

User List

Group List

Upload user list in the following formats: csv

Browse

Note: CSV file should be in the following format: User Name(Email)*, First Name, Last Name, Phone, Description, and Group Name.

Users (0)

+Add

Delete

	User Name	First Name	Last Name	Phone Number	Description	Group Name
	No Data					

Cancel

Back

Skip to Review

Next

Add the user email which will be the user's login name, First Name, and Last Name, and then click + Add New to create a group for the user.

Note: A valid email address capable of receiving messages is required.


Add User

User Name(Email)*
guycamero@googlemail.com

First Name*
Alex

Last Name*
Cameron

Phone Number



Description

Group Name*

+ Add New

Cancel

Add

Enter the name for the user group.

Add User Group

Name*

VersaGroup

Description


Group for Versa Users

Cancel

Add

Click Add.

Add User



User Name(Email)*

guycamero@googlemail.com


First Name*

Alex

Last Name*

Cameron

Phone Number

▼

Description

Group Name* [+ Add New](#)

VersaGroup▼

Cancel

Add

Click Next to continue.

[https://docs.versa-networks.com/Security_Service_Edge_\(SSE\)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...](https://docs.versa-networks.com/Security_Service_Edge_(SSE)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...)

Updated: Wed, 23 Oct 2024 08:41:00 GMT

Copyright © 2024, Versa Networks, Inc.

11

Add Versa Directory Authentication Profile

2

3

Settings
Users And User Groups
Review & Submit

User List

Group List

Upload user list in the following formats: csv

Browse

Note: CSV file should be in the following format: User Name(Email)*, First Name, Last Name, Phone, Description, and Group Name.

Users (1)

+Add

Delete

	User Name	First Name	Last Name	Phone Number	Description	Group Name
<input type="checkbox"/>	guycamero@googlemail.com	Alex	Cameron			VersaGroup

Showing 1-1 of 1 results
10
Rows per Page
Go to page 1
Previous
1
Next

Cancel

Back

Skip to Review

Next

Enter a name for the new directory authentication profile and select Save.

Add Versa Directory Authentication Profile

3

Settings
Users And User Groups
Review & Submit

Review your configurations. Before submitting, review and edit any steps of your configuration below..

General

Name

VersaDirectory

Description

Tags

Settings
Edit

Cache Expiry Time (mins)
10

Concurrent Logins
1

Users & User Groups
Edit

Users(1)

guycamero@gmail.com

User Groups(1)

VersaGroup

Cancel

Back

Save

The new profile is saved to Concerto. You can click Refresh Now to check that the status is successful. Close the window when it is finished.

Tasks

All

Search

Auto Refresh every 15 secs

Refresh now

User	Name	Description	Start Time	End Time	Progress
adminAlex	IAM Server user(s) sync	Create SASE user(s) in IAM Server f...	10/3/2024 3:41:34 PM	10/3/2024 3:41:36 PM	<div> <div> </div> </div>
<div> Task ID: e80638b2-1970-4a33-9182-237d8fa3ad40 </div> <div> Messages: <ul style="list-style-type: none"> Fetching users from IAM server Constructing IAM server user payload Creating users [guycamero@gmail.com] on IAM server IAM task UUID 2e7de5d1-f67e-4085-abba-076f91d7f4fc IAM task 2e7de5d1-f67e-4085-abba-076f91d7f4fc status completed Success Users [guycamero@gmail.com] Successfully synced SASE local users to IAM Server </div>					

Step 4: Set the Versa Directory User Password and Install SASE Client

Log in to the email account that was referenced in the Versa Directory. Your email should have a message from Versa Networks letting you know a new account was created. Click SET PASSWORD to create a new password.



Versa Identity and Access Management (IAM) Notification



Hi Alex,

Welcome to Versa Secure Access! Your administrator has created an account for you.

The username to access this account is guycamero@googlemail.com

Versa Secure Access is the most simplified cloud managed remote access solution. We are committed to facilitate a secure, seamless, and robust connectivity to your corporate network, cloud resources and internet.

TO GET STARTED, PLEASE SET YOUR PASSWORD

SET PASSWORD

You can start working remotely with our secure, seamless, and robust remote access service after you set your password. Please download and install the Versa Secure Access app for your operating system.

[IOS](#)

[MAC OS](#)

[Windows](#)

[Android/Chrome OS](#)

After installation, launch the app and register using the below details:

1. Portal FQDN or IP: ConcertoExample.poc.versa-now.net
2. Enterprise Name: ConcertoExample
3. User ID: guycamero@googlemail.com

Note that if you are an enterprise user that will be leveraging Versa Directory, all users (email addresses) will receive the welcome message to set their password. If you are an administrator and your enterprise is using a different IDP, such as Okta, Azure AD, or Entrata, you will have to generate an email to your organization with the download link and

[https://docs.versa-networks.com/Security_Service_Edge_\(SSE\)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...](https://docs.versa-networks.com/Security_Service_Edge_(SSE)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...)

Updated: Wed, 23 Oct 2024 08:41:00 GMT

Copyright © 2024, Versa Networks, Inc.

instructions (or automate this process using your IT automation tools).

To access this information, navigate to Configure > Secure Client Access > Policy Rules. In the upper right corner, next to Publish, click the Client Download link.

Configure > SASE > Secure Client Access > Policy Rules

Secure Client Access Policy Rule List

Publish (0)

Client Download

Download your Versa Secure Client


Below is your link to download and validate connection..


Portal FQDN


hawaii.poc.versaflow.net


Enterprise Names

Hawaii

 Client installation instructions

 Windows

 Mac OS

 Ubuntu

From the device on which you want to install the Versa Client, open the email from Versa, and then select to install the correct software for your device.

Windows is used as an example in this guide.



Versa Identity and Access Management (IAM) Notification



Hi Alex,

Welcome to Versa Secure Access! Your administrator has created an account for you.

The username to access this account is guycamero@googlemail.com

Versa Secure Access is the most simplified cloud managed remote access solution. We are committed to facilitate a secure, seamless, and robust connectivity to your corporate network, cloud resources and internet.

TO GET STARTED, PLEASE SET YOUR PASSWORD

SET PASSWORD

You can start working remotely with our secure, seamless, and robust remote access service after you set your password. Please download and install the Versa Secure Access app for your operating system.

[IOS](#)

[MAC OS](#)


[Windows](#)

[Android/Chrome OS](#)


After installation, launch the app and register using the below details:

1. Portal FQDN or IP: ConcertoExample.poc.versa-now.net
2. Enterprise Name: ConcertoExample
3. User ID: guycamero@googlemail.com


Follow the steps to download the Versa SASE Client.




Install the Versa SASE Client executable.




Click Next to continue.




Create a desktop shortcut, if you prefer, and then click Next.



Select Install to install Versa SASE Client with the set configuration.



Select Finish when completed. The Versa SASE Client screen displays after finalizing configurations in Concerto.




Step 5: Configure Decryption Profiles


For more information, see [Configure TLS Decryption](#).

The TLS decryption configuration is optional, however it provides additional capabilities and is required when using advanced security protection functions such as CASB and DLP. You can upload your own certificate chain or leverage the auto-generated certificate provided and signed by Versa Networks, and is installed on your client machines when the Versa SASE client application is installed.

In the Concerto Orchestrator, click Configure > TLS Decryption > Profiles.



Click +Add to create a TLS decryption profile.




Depending on your requirements, you can decrypt traffic or inspect traffic. Select Decryption Profile, and then click Next.

12345

Profile TypeCertificate SetupInspection OptionsDecryption OptionsReview & Validate


Create a TLS Decryption Profile

Decryption enforces security policies on encrypted traffic to help prevent malicious content from entering the network and to protect sensitive data disguised as encrypted traffic from leaving the network. You can configure a decryption profile with SSL inspection and policy enforcement information. This section will guide you through the process of configuring the decryption profiles.



Decryption Profile

This profile applies both decryption and inspection protocols that you can associate with your decryption rules.



Inspection Profile

This profile applies only inspection protocols that you can associate with your decryption rules.

Cancel

Back

Skip to Review

Next

Versa Networks automatically creates a CA Certificate for you. You can upload your own certificate, but for this example, the Versa-generated certificate is used.

Under Inspection Options, configure how to handle unsupported or expired certificates.

✓

Profile Type

✓

Certificate Setup

3

Inspection Options

4

Decryption Options

5

Review & Validate

Based on the most common secure enterprise settings, we've chosen the inspection options, below.

If you prefer, you can customize which inspection options you'd like to enable for your decryption.

TLS Inspection is the process of intercepting and reviewing SSL or TLS encrypted internet communication between the client and the server. The inspection of SSL or TLS encrypted traffic has become critically important because the vast majority of internet traffic is SSL or TLS encrypted, including malicious traffic.

[More Information](#)

Certificate Validation

This is the Internet protocol used by web browsers to determine the revocation status of SSL/TLS certificates supplied by HTTPS websites.

Verify with OCSP

Enable server certificate verification using the Online Certificate Status Protocol (OCSP).

Block Unknown Certificates

Block SSL sessions whose certificate status is unknown.

Response timeout(seconds) for an OCSP request

5

Server Certificate Actions

Choose what actions should occur for the following server certificate checks.

When the certificate expires, do the following:

Block

When the certificate is received from an untrusted issuer, do the following:

Block

Choose whether to restrict the certificate key usage extensions to either digital signature or key encipherment.

☐ Restrict Certificate Extension

SSL or TLS Protocol Checks

Choose what actions should occur for the following SSL or TLS protocol checks.

When the negotiated SSL or TLS protocol between the Client and Server uses an unsupported key length, do the following:

Block

Minimum Supported RSA Key Length

1024 bits

Enter a value of 512 bits or higher

When the negotiated SSL or TLS protocol between the Client and Server uses an unsupported cipher, do the following:

Block

When the negotiated SSL or TLS protocol between the Client and Server uses an unsupported protocol version, do the following:

Block

Cancel

Back

Skip to Review

Next

Select the decryption options you would like to support. This example uses the following settings.

[https://docs.versa-networks.com/Security_Service_Edge_\(SSE\)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start...](https://docs.versa-networks.com/Security_Service_Edge_(SSE)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start...)

Updated: Wed, 23 Oct 2024 08:41:00 GMT

Copyright © 2024, Versa Networks, Inc.

Transport Layer Security (TLS) Version Support

Select the minimum and maximum version of TLS that is supported. When you select a version that is not TLS 1.3, select one or more key exchange algorithms for the SSL connection.

TLS 1.0

TLS 1.1

TLS 1.2

TLS 1.3

Key Exchange Algorithms

☒ ECDHE—Elliptic-Curve Diffie-Hellman Key Exchange

☒ RSA—Rivest-Shamir-Adleman algorithm

Advanced

Algorithms

Select which encryption and authentication algorithms to use.

Encryption Algorithms	Authentication Algorithms
<input checked="" type="checkbox"/> AES-128-CBC	<input checked="" type="checkbox"/> SHA
<input checked="" type="checkbox"/> AES-128-GCM	<input checked="" type="checkbox"/> SHA256
<input checked="" type="checkbox"/> AES-256-CBC	<input checked="" type="checkbox"/> SHA384
<input checked="" type="checkbox"/> AES-256-GCM	
<input checked="" type="checkbox"/> CAMELLIA-256-CBC	
<input checked="" type="checkbox"/> CHACHA20-POLY1305	
<input checked="" type="checkbox"/> SEED-CBC	

TLS Cipher Suites

The following TLS cipher suites are automatically selected based on your algorithms above.

<input type="checkbox"/> TLS-AES-128-GCM-SHA256	<input type="checkbox"/> TLS-AES-256-GCM-SHA384
<input type="checkbox"/> TLS-CHACHA20-POLY1305-SHA256	<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA
<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-128-CBC-SHA256	<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-128-GCM-SHA256
<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA	<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-256-CBC-SHA384
<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-AES-256-GCM-SHA384	<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA
<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-128-CBC-SHA256	<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-128-GCM-SHA256
<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA	<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-256-CBC-SHA384
<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-AES-256-GCM-SHA384	<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-128-CBC-SHA
<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-128-CBC-SHA256	<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-128-GCM-SHA256
<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-256-CBC-SHA	<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-256-CBC-SHA256
<input checked="" type="checkbox"/> TLS-RSA-WITH-AES-256-GCM-SHA384	<input checked="" type="checkbox"/> TLS-ECDHE-ECDSA-WITH-CHACHA20-POLY1305-SHA256
<input checked="" type="checkbox"/> TLS-ECDHE-RSA-WITH-CHACHA20-POLY1305-SHA256	<input checked="" type="checkbox"/> TLS-RSA-WITH-CAMELLIA-256-CBC-SHA
<input checked="" type="checkbox"/> TLS-RSA-WITH-SEED-CBC-SHA	

Cancel

Back

Skip to Review

Next

Enter the decryption profile name and select Save.

Profile Type Certificate Setup Inspection Options Decryption Options Review & Validate

Review and name your profile

Below are the configurations of your profile. Review and edit any step of your configuration before validating.

General

Name* Description

Tags

Certificate Setup [Edit](#)


Certificate Authority ConcertoExample

Issued For VOS Certificate


Step 6: Configure a TLS Decryption Policy Rule

For more information, see [Configure TLS Decryption](#).

Select Configure > TLS Decryption > Policy Rules.



In the TLS Decryption Rules List window, scroll down and click Let's Go.



Select a decrypt and inspect profile to use in the Decrypt and Inspect the Traffic pane. Note that you can also create Do Not Decrypt rules for traffic that you do not want to decrypt. For example, you can choose not to decrypt personal user information such as financial information.

1

2

3

4

5

Decryption Enforcement

Users & Groups

Endpoint Information Profile (EIP)

Network

Review & Validate

What type of rule would you like to create?

You can customize either configuration you'd like to enforce

Decrypt and Inspect the Traffic

Normally, encrypted traffic is not blocked. Decryption enforces security policies on encrypted traffic to help prevent malicious content from entering the network and to protect sensitive data disguised as encrypted traffic from leaving the network.

Use the following decryption profile

+ Add New

decryption-profile

x

URL Filtering Action Override(optional)

Select a URL Profile

Do Not Decrypt

This option does not decrypt and enforce security rules on traffic because the traffic remains encrypted. This option should be used on sites, applications or services you need for your organization.

Do not decrypt but do inspect the traffic

Encryption does not necessarily mean that content is safe. Gain visibility into the hidden traffic within your network and identify, classify, and inspect the packets for threats. Know what is being intentionally or accidentally sent outside of your organization.

Select Profile

Do not decrypt and do not inspect the traffic

Allow traffic from certain trusted sites to go un-inspected. Keep in mind, this can be risky because webpages are not static.

Cancel

Back

Skip to Review

Next

For Users & Groups, you can retain the default option All Users, or you can select specific users or groups.

Action

2

3

4

5

Decryption Enforcement

Users & Groups


Endpoint Information Profile (EIP)

Network

Review & Validate

By default we have chosen all users and groups to apply your security enforcements

If you prefer, you can select the specific users or groups for the security posture.



Users & Groups

✓ All Users

Customize

Cancel

Back

Skip to Review

Next

Endpoint Information Profiles (EIP) allow you to validate additional details about the posture of a user's device before taking actions. We do not use EIP profiles in this example. For more information about about EIP, see [Configure Endpoint Information Profiles](#).

Action

Match Criteria

1

2

3

4

5

Decryption Enforcement

Users & Groups

Endpoint Information Profile (EIP)

Network

Review & Validate

User Defined

Predefined

+ Add Existing EIP Profile

Delete

+ Create New EIP Profile

Select Columns

<input type="checkbox"/>	Name	Description	Rules
No User Defined EIP Profiles Added			

Cancel

Back

Skip to Review

Next

The Network step provides additional ways to identify and control policies. In this example, we use the default settings. Click Next.

Action

Match Criteria

✓

✓

✓

4

5

Decryption Enforcement

Users & Groups

Endpoint Information Profile (EIP)

Network

Review & Validate

All traffic is selected, and it will receive the previously selected security enforcements

If you prefer, you can customize which traffic to include or exclude from the layered traffic, below

Services

✓

All layer 4 services

Customize

Source & Destination (Layer 3)

✓

Destination Zone

Internet

Customize

Schedule

✓

None Selected

Customize

URL Categories & Reputations

Customize

Cancel

Back

Skip to Review

Next

Enter a Name, and then click Save to finalize and save the decryption rule.

Action

Match Criteria

✓

✓

✓

✓

5

Decryption Enforcement

Users & Groups

Endpoint Information Profile (EIP)

Network

Review & Validate

Review your TLS Decryption Rule configurations below

Below are the configurations of your rule. Review and edit any step of your configuration before deploying.

General

Name *

deryption-profile

Description

Tags

✓

Rule is Enabled

Decryption Enforcement

Rule Type

Decrypt and Inspect the Traffic

Bypass Decryption for URL profiles

None Selected

Profile

deryption-profile

Users & Groups

Cancel


Back

Save


Step 7: Configure a Secure Client Access Profile

For more information, see [Configure SASE Secure Client Access Profiles](#).

Select Configure > Secure Client Access > Profiles.



Select Client-Based Profile and click Get Started.



Add some routes to reach your site-to-site tunnel or your private network with SD-WAN through Versa Gateways. Note that if you did not configure a site-to-site tunnel in Step 2, and you are using only the Versa Secure Internet Access (VSIA) solution, you can skip adding the routes, but you must configure a DNS resolver.

1


2

3

Routes & DNS ResolversApplication MonitorReview & Deploy

Add which routes and DNS resolvers to use.


If you prefer, you can customize which routes and DNS resolvers to use for the client profile.



Routes ⓘ

No Routes have been added

Add Routes



DNS Resolvers ⓘ

No DNS Resolvers have been added

Add DNS Resolvers

Cancel

Back

Skip to Review

Next

Click +Add to add routes.

123

Routes & DNS ResolversApplication MonitorReview & Deploy

Add which routes and DNS resolvers to use.
If you prefer, you can customize which routes and DNS resolvers to use for the client profile.

← Back

Routes

+ Add

Delete

Select Columns

Name	Prefix	Metric	Encrypted
No Data			

Cancel

Back

Skip to Review

Next

In the Add Route window, enter a name and prefix, and then click Add.

https://docs.versa-networks.com/Security_Service_Edge_(SSE)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...

Updated: Wed, 23 Oct 2024 08:41:00 GMT

Copyright © 2024, Versa Networks, Inc.

38

Add Route

Name*

SiteServers

Description

Prefix* ⓘ

10.1.100.0/24

Metric

Encryption is enabled

Cancel

Add

To configure a DNS Resolver, click Back after adding routes, and click + Add in the DNS Resolvers pane.

1 — 2 — 3
 Routes & DNS Resolvers Application Monitor Review & Deploy

Add which routes and DNS resolvers to use.

If you prefer, you can customize which routes and DNS resolvers to use for the client profile.

← Back
DNS Resolvers

+ Add
Delete
Select Columns ▼

Name	Description	DNS Server IP Address	Domain
No Data			

In the Add DNS Resolver window, enter Name and DNS Server IP Address, and then click Add.

Add DNS Resolver

✕

Name*

Google

Description

Domain

DNS server IP Address*

8.8.8.8|

+

Cancel

Add

After configuring a DNS Resolver, click Next.

1

2

3

Routes & DNS ResolversApplication MonitorReview & Deploy

Add which routes and DNS resolvers to use.
If you prefer, you can customize which routes and DNS resolvers to use for the client profile.

Back

DNS Resolvers

+ Add

Delete

Select Columns

	Name	Description	DNS Server IP Address	Domain
<input type="checkbox"/>	Google	-	8.8.8.8	-

Showing 1-1 of 1 results10Rows per PageGo to page 1Previous1Next


Cancel

Back

Skip to Review

Next

During this step, click Add Application Monitor to enable DEM application monitoring.



In the Application Monitor Configuration screen, select Device Monitoring, Internet Monitoring, and Local Network Monitoring.

Set the Interval as 60 seconds, check Select All applications, and then click Next.

✓
Routes & DNS Resolvers

2
Application Monitor

3
Review & Deploy

Add applications you want to include for monitoring at selected network segments.

If you prefer, you can customize which application to include for monitoring for the client profile.

← Back
Application Monitor

Network Segments

☒ Device Monitoring
 ☒ Internet Monitoring
 ☒ Local Network Monitoring

Interval (seconds)

Bitcasa ✕

Druva ✕

Rally Software ✕

Citrix Workspace ✕

Rescue Remote Support ✕

Microsoft Intune Company Portal ✕

Apple App Store ✕

DocuSign ✕

Microsoft Skype For Business ✕

Amazon Kindle ✕

Planview Projectplace ✕

PingOne For Enterprise ✕

Google Play Store ✕

Facebook ✕

SpiderOak ✕

Webex ✕

Carbonite ✕

Egnyte ✕

GoToMeeting ✕

Mozy ✕

Dailymotion ✕

Salesforce.com ✕

Google Hangouts ✕

YouTube ✕

Google Workspace ✕

Eventbrite ✕

Swizznet ✕

Foursquare ✕

Diligent Boards ✕

JungleDisk ✕

TeamViewer ✕

RingCentral ✕

GitHub ✕

LivePerson ✕

ElephantDrive ✕

Toggl Track ✕

Twitter ✕

CrowdStrike Falcon ✕

iCloud Drive ✕

Google Drive ✕

Tresorit ✕

Amazon WorkSpaces ✕

Zoom ✕

Dropbox ✕

Filemail ✕

OpenDrive ✕

Amazon Drive ✕

Backblaze B2 Cloud Storage ✕

Workday ✕

Skype ✕

Google Drive Backup And Sync ✕

Microsoft Office 365 Outlook.com ✕

Adobe Creative Cloud ✕

SugarSync ✕

Search for Application

☒ Select All

Clear All

Cancel

Back

Skip to Review

Next

Enter a policy name in the Name field, and then click Save.

✓

Routes & DNS Resolvers

✓

Application Monitor

3

Review & Deploy

Review and Configure

Below are the configurations of your profile. Review and edit any step of your configuration before validating.

General

Name* ⓘ
client_access_profile

Description

Tags

Routes & DNS Resolvers ⓘ [Edit](#)

Routes 1 Added

Name	IP Address
------	------------

Cancel


Back

Save


Step 8: Configure a Secure Client Access Policy Rule

For more information, see [Configure SASE Secure Client Access Rules](#).

Select Configure > Secure Client Access > Policy Rules.



In the Secure Client Access Policy Rule List window, scroll down and click Let's Go.



Select the operating system to use. For this example policy, we use Windows.

1 2 3 4 5 6 7 8 9

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address Traffic Action Gateways Client Configuration Agent Profile From EIP Review & Configure

Match Criteria Action

Choose the operating system for this rule below.

If you prefer, you can customize which operating system options you would like to enable for the rule.

Windows

☒ All Window Operating Systems

- ☒ Windows 11
- ☒ Windows 10
- ☒ Windows 10 Mobile
- ☒ Windows 7
- ☒ Windows 8
- ☒ Windows 8.1
- ☒ Windows Server 2012
- ☒ Windows Server 2012 R2
- ☒ Windows Server 2016
- ☒ Windows Server 2019
- ☒ Windows Vista
- ☒ Windows XP
- ☒ Windows Server 2022

Apple

☐ All Apple Operating Systems

- ☐ Mac OS
- ☐ Mac OS X Server
- ☐ OSX

☐ All Apple Mobile

- ☐ iOS
- ☐ iPadOS

Android

☐ All Android

- ☐ Android

Linux

☐ All Linux Operating Systems

- ☐ Fedora
- ☐ Red Hat Enterprise Linux
- ☐ Ubuntu

Cancel Back Skip to Review Next

This policy uses the option for Known Users, but you can select a specific user or group of users that match or utilize this profile rule.

1 2 3 4 5 6 7 8 9

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address Traffic Action Gateways Client Configuration Agent Profile From EIP Review & Configure

Match Criteria Action

By default we have chosen all users and groups to apply your security enforcements

If you prefer, you can select the specific users or groups for the security posture.

Users & Groups ⓘ

✓ Known Users

[Customize](#)

Cancel Back Skip to Review Next

Endpoint Information Profile (EIP) and compliance check with MDM can identify additional potential risks on a device. To keep this policy simple, click Next without configuration changes.

✓

✓

3

4

5

6

7

8

9

Operating System

Users/User Groups

Device Risk Info

Source Geo Location & Source IP Address

Traffic Action

Gateways

Client Configuration

Agent Profile From EIP

Review & Configure

Match Criteria

Action

Choose Your Device Risk Information

Use Endpoint Information Profile (EIP) and Device Compliance Status options to select devices exhibiting specific attributes that determine the risk status of the device

Endpoint Information Profile (EIP)

Select an existing profile or create a new profile with the values for the different EIP attributes collected by the Versa Client. This can be used by the Versa Cloud Gateways for granular policy enforcement based on the end user's device risk.

User Defined

Predefined

+ Create New EIP Profile

+ Add Existing EIP Profile

Delete

Select Columns

<input type="checkbox"/>	Name	Description	Rules
No User Defined EIP Profiles Added			

Device Compliant Status

If 3rd party MDM is used, select one or more device compliance status below

Cancel

Back

Skip to Review

Next

You can manage user access based on Source geographic location and source IP address. In this simple policy example, we use the default.

Match Criteria

1 Operating System 2 Users/User Groups 3 Device Risk Info 4 Source Geo Location & Source IP Address 5 Traffic Action 6 Gateways 7 Client Configuration 8 Agent Profile From EIP 9 Review & Configure

Action

By default we've chosen all source geo locations and source IP addresses.
These are location selections for allowing or denying access to the Versa Client. If you prefer, you can select specific geo locations.

Source Geo Location ⓘ

✓ All Geo locations are selected

[Customize](#)

Source IP Address ⓘ

[Customize](#)

[Cancel](#) [Back](#) [Skip to Review](#) [Next](#)

Based on previously configured constraints, you can now define how you want to control applications. In this policy, we allow traffic that matches the rule to pass.

We select the option Breakout to Internet to configure all traffic to go directly to the internet rather than through the gateway. You can specify which applications are sent through the gateway. In the following example, we select YouTube and Facebook.

Note that the field "Select Subscription type for users matching this rule" aligns to the license type you purchase. The options are:

- VSPA (Versa Secure Private Access)—focused on ZTNA for private network control and access.
- VSIA (Versa Secure Internet Access)—focused on ZTNA for public application control (Internet).
- VSPA + VSIA—focused on both.

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address **5 Traffic Action** Gateways Client Configuration Agent Profile From EIP Review & Configure

Based on the most common secure enterprise settings, we've chosen the traffic steering below.
If you prefer, you can customize which traffic steering option you would like to enable for the rule.

Select subscription type for users matching this rule.
Versa Secure Private Access (VSPA) & Versa Secure Internet Access (VSIA)

☐ **Deny**
Drop all traffic that matches the rule
Display Message after Connection is Blocked
You are not allowed to connect to the enterprise VPN, please contact administrator

☒ **Allow**
Allow all traffic that matches the rule to pass

☐ Send Apps to Versa Cloud Gateway ☒ Breakout To Internet

With this option, the default behavior is to send all private traffic over the tunnel to the Versa Cloud Gateway and all Internet bound traffic from the user device to the Internet directly (Split Tunnel / Direct Internet Access). Select applications below to send traffic for those applications over the tunnel to the Versa Cloud Gateway.

Display Message after Successful Connection
Welcome to ConcertoExample

☒ YouTube ☒ Facebook Search for Applications + Add New Clear All

Predefined Applications (Selected: 2 of 54)

Bitcasa	Druva	Rally Software	Citrix Worksp...	Rescue Remot...	Microsoft Intu...	Apple App Store
Outlook	Slack	LinkedIn	Google	Dropbox	OneDrive	Facebook

Cancel Back Skip to Review **Next**

The following screen varies based on the Concerto headend and Versa Cloud Gateways that are provisioned for you. If your deployment does not match, select the gateways in your environment you want to use to quickly validate this policy.

In this example, there is one gateway group for the two Versa Cloud Gateways in this SASE headend. This allows for configurations such as Best Gateway Selection, which is auto-configured and provided based on the group name and grouping of the attached gateways.

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address Traffic Action **Gateways** Client Configuration Agent Profile From EIP Review & Configure

By default all gateway groups have been selected.
If you prefer, you can select a specific gateway to allow access.

Gateway Groups

- ☒ All Selected | 1
- ☒ NAM

Gateways

Select VPN
ConcertoExample-Enterprise

Gateway	Gateway Group	Client Address Pool Name
<input checked="" type="checkbox"/> VCG-EAST-01-PHE	NAM	10.1.10.0/24-Pool-1
<input checked="" type="checkbox"/> VCG-WEST-01-PHE	NAM	10.120.1.0/24-Pool-1

Cancel Back Skip to Review **Next**

In the Client Configuration screen, select the Secure Client Access Profile that you created in Step 7.

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address Traffic Action Gateways **Client Configuration** Agent Profile From EIP Review & Configure

Based on the most common secure enterprise settings, we have defined your client configuration.
If you prefer, you can customize the client configuration setting for the rule.

Secure Client Access Profile

Use the following Secure Client Access profile for this rule.
client_access_profile

Profile Details

+ Routes And DNS Resolvers

MFA
MFA is switched off

VPN Type
☒ IPsec ☐ SSL

Client Controls
☒ Always On
☒ Remember Credentials
☒ Allow Client Customization
[Customize](#)

Cancel Back Skip to Review **Next**

Enter a name for your policy in the Name field, and then click Save.

Operating System Users/User Groups Device Risk Info Source Geo Location & Source IP Address Traffic Action Gateways Client Configuration Agent Profile From EIP Review & Configure

Review your Client Access Rule Configurations below

Below are the configurations for your rule. Review and edit any step of your configuration before deploying.

General

Name Description

Tags

☒ Rule is Enabled


Operating Systems [Edit](#)

Operating System Versions Custom Selection

Step 9: Create an Internet Protection Policy

For more information, see [Configure SASE Internet Protection Rules](#).

Select Configure > Real-Time Protection > Internet Protection.




Scroll down and click Let's Go.


[https://docs.versa-networks.com/Security_Service_Edge_\(SSE\)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...](https://docs.versa-networks.com/Security_Service_Edge_(SSE)/Configuration_from_Concerto/02_Versa_SSE_Quick_Start_...)

Updated: Wed, 23 Oct 2024 08:41:00 GMT

Copyright © 2024, Versa Networks, Inc.



In the Applications and URLs screen, select the Applications tab, then select Facebook and YouTube as the applications for this policy.



Click Next to use the default settings for EIP, GEO Locations, and Network Layer 3-4, until you reach Security Enforcement.

The Security Enforcement screen displays options to control the selected applications as you want. You can allow, deny or reject applications, as well as use security profiles to utilize security enforcements for better data security. Note that the enforcement options vary based on your license.

Applications & URLs Users & Groups Endpoint Information Profile (EIP) GEO Locations Network Layer 3-4 Security Enforcement Review & Deploy (7)

Review your Internet Protection Policy configurations below.
Below are the configurations of your rule. Review and edit any step of your configuration before deploying.

General

Name * ⓘ Application_Rule_1 Description

Tags

☒ Rule is Enabled

Applications & URLs [Edit](#)

Applications Custom Selection


Cancel Back Save

Step 10: Create a Private Protection Policy (Optional)


For more information, see Configure [SASE Private Application Protection Rules](#).

In this step, we configure rules to protect private applications. (You can skip Step 10 if you did not create a site-to-site tunnel in Step 2).

Select Configure > Real-Time Protection > Private App Protection.



In the Private App Protection Rules List window, scroll down and click Let's Go.



For this policy, we protect all applications that users are allowed to access. Leaving the list blank uses Any as the selector. Click Next.

1 Applications 2 Users & Groups 3 Endpoint Information Profile (EIP) 4 GEO Locations 5 Network Layer 3-4 6 Security Enforcement 7 Review & Deploy

Match Criteria Action

By default, we've included all applications to match.
If you prefer, you can customize which traffic to include or exclude from applications below.

Applications

Application Group Applications

Search for Application Group + Add New

Cancel Back Skip to Review Next

Click Next to progress through the screens for Users & Groups, Endpoint Information Profiles, GEO Locations, and Network Layer 3-4, until you reach the Security Enforcement screen. Note that the enforcement options that are available depend on your license.

In the Security Enforcement screen, under Profiles, select the required protection policies, and then click Next.

✓

Applications

✓

Users & Groups

✓

Endpoint Information Profile (EIP)

✓

GEO Locations

✓

Network Layer 3-4

✓

Security Enforcement

7

Review & Deploy

Review your Private App Protection Policy configurations below.

Below are the configurations of your rule. Review and edit any step of your configuration before deploying.

General

Name* ⓘ

SiteProtectionRule

Description

Tags

Rule is Enabled

Cancel

Back

Save

Step 11: Publish Policies to Gateways

For more information, see [Publish SASE Gateways](#).

After you configure the required policies, you can push them to the Gateways. To do this, click Publish on the top right side of the page.

Configure > SASE > Real-Time Protection > Private App Protection

Publish (2)

Private App Protection Rules List

Below are all the rules for your Private App Protection Policy.

Search by keyword or name

Filter

+ Add

Clone

Reorder

Delete

Refresh

Select Columns

	Rule Name	Applications	Users	EIP	Network Layer 3-4		Geo Locations
					Source & Destination	Services	Source
<input type="checkbox"/>	SiteProtectionRule	All Applications	All Users		<div> <div>Source Zone</div> <div>SD-WAN Zone</div> <div>Versa Client</div> </div> <div> <div>Destination Zone</div> <div>SD-WAN Zone</div> </div>	All Layer 4 Services	All Source Geo Locations sele

Showing 1-1 of 1 results

10 Rows per Page

Go to page 1

Previous 1 Next

Verify that the required gateways are selected, and then click Publish.

Gateway Publish Status

Name	Status	Last Published	Unpublished Configs	Published Configs
<input type="checkbox"/> Advanced Security Cloud				
<input checked="" type="checkbox"/> East				
<input checked="" type="checkbox"/> VCG-EAST-01-PHE	Need Publication	10/2/2024, 3:31:43 AM alexconcerto		
<input checked="" type="checkbox"/> West				
<input checked="" type="checkbox"/> VCG-WEST-01-PHE	Need Publication	10/2/2024, 3:31:43 AM alexconcerto		

Close

Publish

Wait for the status indicators to change to Completed, and then click Close.

Configure > SASE > Publish

Publish Status

Gateway Publish Status

Name	Status	Last Published	Unpublished Configs	Published Configs
<input type="checkbox"/> Advanced Security Cloud				
<input checked="" type="checkbox"/> East				
<input checked="" type="checkbox"/> VCG-EAST-01-PHE	Completed	10/3/2024, 5:03:46 PM adminAlex		
<input checked="" type="checkbox"/> West				
<input checked="" type="checkbox"/> VCG-WEST-01-PHE	Completed	10/3/2024, 5:03:46 PM adminAlex		


Close

Publish


Step 12: Connect to Gateways Using the Configured Client Policy

After you configure the required policies, connect to the gateways from a Windows device using the following procedure.


Open the Versa SASE client, and then click Register.




The email that you receive in the email account configured in Step 3 contains details about how to register the account. Copy the details for Portal FQDN or IP, Enterprise Name, and User ID from the email.





When prompted, enter the the configured password, and then click Submit.





After a few moments the SASE client connects to a gateway.



Next, you can validate the traffic sent through the gateway. For example, open YouTube to verify if the decryption policy is active. To do this, click the  Site Information icon next to the YouTube URL, and then click Connection is secure.



Click the  icon next to Certificate is valid.



You can view the VOS certificate in use.

Certificate Viewer: *.google.com

General

Details

Issued To

Common Name (CN)

Organization (O)

Organizational Unit (OU)

*.google.com

<Not Part Of Certificate>

<Not Part Of Certificate>

Issued By

Common Name (CN)

Organization (O)

Organizational Unit (OU)

VOS Certificate

ConcertoExample

Versa Titan

Validity Period

Issued On

Expires On

Wednesday, October 2, 2024 at 5:26:27 PM

Friday, October 3, 2025 at 5:26:27 PM

SHA-256 Fingerprints


Certificate

Public Key

bb27550ef41d4be5af8c1b58374297200ab00eac90acca6a591067705962280d

38f36e8ce15bc74712987399b42e06c01c58011adc1948b0ef4fc87e786f062b

Next, go to Analytics > Logs > Firewall.



After a few minutes, you can view logs for the applications that are sent through the gateways.

Firewall > Logs >
America/Los_Angeles

ConcertoExample
all
Last day

297

0

Total Allowed

Total Denied

Logs
Charts
Maps

Firewall logs

☐ Show Domain Names

Set filters here...
Apply | Clear | Copy Filter
Show 10 entries

	Receive Time	Appliance	Source Address	Destination Address	Source Port	Destination Port	Application	User	URL Category
	Oct 3rd 2024, 5:34:35 PM PDT	VCG-WEST-01-PHE	10.120.1.7	74.125.166.169	50623	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:34 PM PDT	VCG-WEST-01-PHE	10.120.1.7	31.13.65.36	50620	443	facebook	guycamero@googlemail.com	social_network
	Oct 3rd 2024, 5:34:34 PM PDT	VCG-WEST-01-PHE	10.120.1.7	31.13.65.36	50622	443	facebook	guycamero@googlemail.com	social_network
	Oct 3rd 2024, 5:34:34 PM PDT	VCG-WEST-01-PHE	10.120.1.7	74.125.166.169	50614	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:17 PM PDT	VCG-WEST-01-PHE	10.120.1.7	142.250.191.46	50556	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:17 PM PDT	VCG-WEST-01-PHE	10.120.1.7	142.251.46.206	50579	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:17 PM PDT	VCG-WEST-01-PHE	10.120.1.7	74.125.166.169	50590	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:17 PM PDT	VCG-WEST-01-PHE	10.120.1.7	142.250.191.46	50599	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:01 PM PDT	VCG-WEST-01-PHE	10.120.1.7	74.125.166.169	50548	443	youtube	guycamero@googlemail.com	streaming_medi
	Oct 3rd 2024, 5:34:01 PM PDT	VCG-WEST-01-PHE	10.120.1.7	142.251.46.206	50547	443	youtube	guycamero@googlemail.com	streaming_medi

Showing 1 to 10 of 297 entries

Previous
1
2
3
4
5
...
30
Next

You can also test connectivity through your site-to-site tunnel using Ping.