

Contents

| | |
|--|--|
| 1 Basic | |
| 1.1 .vimrc | |
| 1.2 Default Code | |
| 1.3 Common Sense | |
| 1.4 Useful STL | |
| 1.5 Bi/Ternary Search | |
| 1.6 TroubleShoot | |
| 2 flow | |
| 2.1 MinCostFlow * | |
| 2.2 Dinic | |
| 2.3 Kuhn Munkres 最大完美二分匹配 | |
| 2.4 Directed MST * | |
| 2.5 SW min-cut (不限 S-T 的 min-cut) * | |
| 2.6 Bounded Max Flow | |
| 2.7 Flow Method * | |
| 3 Math | |
| 3.1 Fast Pow & Inverse & Combination | |
| 3.2 Ext GCD | |
| 3.3 Sieve 質數篩 | |
| 3.4 FFT * | |
| 3.5 NTT * | |
| 3.6 Linear Recurrence * | |
| 3.7 Miller Rabin | |
| 3.8 Faulhaber ($\sum_{i=1}^n i^p$) * | |
| 3.9 Chinese Remainder * | |
| 3.10 Pollard Rho * | |
| 3.11 Josephus Problem * | |
| 3.12 Gaussian Elimination * | |
| 3.13 Result * | |
| 4 Geometry | |
| 4.1 definition * | |
| 4.2 halfPlaneIntersection * | |
| 4.3 Convex Hull * | |
| 4.4 Convex Hull trick * | |
| 4.5 掃描的線 | |
| 4.6 Polar sort | |
| 4.7 Li Chao Segment Tree * | |
| 4.8 KD Tree * | |
| 5 Tree | |
| 5.1 LCA | |
| 6 Graph | |
| 6.1 HeavyLightDecomposition * | |
| 6.2 Centroid Decomposition * | |
| 6.3 DominatorTree * | |
| 6.4 MaximumClique 最大團 * | |
| 6.5 MaximalClique 極大團 * | |
| 6.6 Minimum Steiner Tree | |
| 6.7 BCC based on vertex * | |
| 6.8 Strongly Connected Component * | |
| 6.9 差分約束 * | |
| 7 String | |
| 7.1 PalTree * | |
| 7.2 SuffixArray * | |
| 7.3 MinRoation * | |
| 7.4 RollingHash | |
| 7.5 KMP | |
| 7.6 LCS & LIS | |
| 7.7 Aho-Corasick * | |
| 7.8 Z Value * | |
| 7.9 manacher * | |
| 8 Data Structure | |
| 8.1 Treap | |
| 8.2 BIT | |
| 8.3 二維偏序 * | |
| 8.4 持久化 * | |
| 8.5 2D 線段樹 | |
| 8.6 Black Magic | |
| 9 Others | |
| 9.1 SOS dp * | |
| 9.2 MO's Algorithm * | |

1 Basic

1.1 .vimrc

```

linenumber, relative-linenumber, mouse, cindent, expandtab,
shiftwidth, softtabstop, nowrap, ignorecase(when search), noVi-
compatible, backspace
nornu when enter insert mode

```

```

1 se nu rnu mouse=a cin et sw=2 sts=2 nowrap ic nocp bs=2
2 syn on

```

1.2 Default Code

所有模板的 define 都在這

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 #ifdef LOCAL // ===== Local ===== g++ -DLOCAL ...
5 void dbg() { cerr << '\n'; }
6 template<class T, class ...U> void dbg(T a, U ...b) {
7     cerr << a << ' ', dbg(b...); }
8 template<class T> void org(T l, T r) {
9     while (l != r) cerr << *l++ << ' '; cerr << '\n'; }
10 #define DEBUG(args...) \
11     (dbg("#> (" + string(#args) + ") = (" + args, ")"))
12 #define ORANGE(args...) \
13     (cerr << "#> [" + string(#args) + "] = " + org(args))
14 #else // ===== OnlineJudge =====
15 #define DEBUG(...) ((void)0)
16 #define ORANGE(...) ((void)0)
17 #endif
18
19 #define ll long long
20 #define ld long double
21 #define INF 0x3f3f3f3f
22 #define LLINF 0x3f3f3f3f3f3f3f3f
23 #define NINF 0xc1c1c1c1
24 #define NLLINF 0xc1c1c1c1c1c1c1c1
25 #define X first
26 #define Y second
27 #define PB emplace_back
28 #define pll pair<ll, ll>
29 #define MEM(a,n) memset(a, n, sizeof(a))
30 #define ios ios::sync_with_stdio(0); cin.tie(0); cout.
31     tie(0);
32 const int MXN = + 5;
33
34 void sol(){}
35 int main(){
36     io int t=1;
37     cin >> t; // !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
38     while(t--){ sol(); } }
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

```

1.3 Common Sense

陣列過大時本機的指令：

```

windows: g++ -Wl,-stack,40000000 a.cpp
linux: ulimit -s unlimited
1e7 的 int 陣列 = 4e7 byte = 40 mb
STL 式模板函式名稱定義：
.init(n, ...) => 初始化並重置全部變數，0-base
.addEdge(u, v, ...) => 加入一條邊，有向圖為 u -> v，無向圖為 u <-> v
.run() => 執行並回傳答案
.build() => 查詢前處理
.query(...) => 查詢並回傳答案
memset 設 -0x3f 的值是 -0x3e3e3e3f / 0xc1c1c1c1

```

1.4 Useful STL

```

131 // unique
132 sort(a.begin(), a.end());
133 a.resize(unique(a.begin(), a.end()) - a.begin());
134 // O(n) a[k] = kth small, a[i] < a[k] if i < k
135 nth_element(a.begin(), a.begin()+k, a.end());
136 // stable_sort(a.begin(), a.end())
137 // lower_bound: first element >= val
138 // upper_bound: first element > val
139 // set_union, set_intersection, set_difference,
140 // set_symmetric_difference
141 set_union(a.begin(), a.end(), b.begin(), b.end(),
142     inserter(c, c.begin()));
143 //next_permutation prev_permutation(sort/reverse first)
144 do{ for(auto i : a) cout << i << ' ';
145 } while(next_permutation(a.begin(), a.end()));
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200

```

1.5 Bi/Ternary Search

```

1 while(l < r){ // first l of check(l) == true
2     ll m = (l + r) >> 1;
3     if(!check(m)) l = m + 1; else r = m; }
4 while(l < r){ // last l of check(l) == false
5     ll m = (l + r + 1) >> 1;
6     if(!check(m)) l = m; else r = m - 1; }
7 while(l < r){
8     ll ml = l + (r - l) / 3, mr = r - (r - l) / 3;
9     if(check(ml)>check(mr)) l = ml + 1; else r = mr - 1;}

```

1.6 Troubleshoot

提交前：

如果樣本不夠，寫幾個簡單的測資。
複雜度會不會爛？生成最大的測資試試。
記憶體使用是否正常？

會 overflow 嗎？
確定提交正確的檔案。

WA：

記得輸出你的答案！也輸出 debug 看看。
測資之間是否重置了所有變數？
演算法可以處理整個輸入範圍嗎？
再讀一次題目。

您是否正確處理所有邊緣測資？

您是否正確理解了題目？

任何未初始化的變數？

有 overflow 嗎？

混淆 n, m, i, j 等等？

確定演算法有效嗎？

哪些特殊情況沒有想到？

確定 STL 函數按你的想法執行嗎？

寫一些 assert 看看是否有些東西不如預期？

寫一些測資來跑你的演算法。

產生一些簡單的測資跑演算法看看。

再次瀏覽此列表。

向隊友解釋你的演算法。

請隊友查看您的代碼。

去散步，例如去廁所。

你的輸出格式正確嗎？(包括空格)

重寫，或者讓隊友來做。

RE：

您是否在本機測試了所有極端情況？

任何未初始化的變數？

您是否在任何向量範圍之外閱讀或寫作？

任何可能失敗的 assert？

任何的除以 0？(例如 mod 0)

任何的無限遞迴？

無效的 pointer 或 iterator？

你是否使用了太多的記憶體？

TLE：

有無限迴圈嗎？

複雜度是多少？

是否正在複製大量不必要的數據？(改用參考)

有沒有開 io？

避免 vector/map。(使用 array/unordered_map)

你的隊友對你的演算法有什麼看法？

MLE：

您的演算法應該需要的最大記憶體是多少？

測資之間是否重置了所有變數？

2 flow

2.1 MinCostFlow *

```

1 struct zkwflow{
2     static const int MXN = 10000;
3     struct Edge{ int v, f, re; ll w;};
4     int n, s, t, ptr[MXN]; bool vis[MXN]; ll dis[MXN];
5     vector<Edge> E[MXN];
6     void init(int _n, int _s, int _t){
7         n=_n, s=_s, t=_t;
8         for(int i=0; i<n; i++) E[i].clear();
9     }
10    void addEdge(int u, int v, int f, ll w){
11        E[u].emplace_back(v, f, (int)E[v].size(), w);
12        E[v].emplace_back(u, 0, (int)E[u].size()-1, -w);
13    }
14    bool SPFA(){
15        fill_n(dis, n, LLMXN); memset(vis, 0, 4 * n);
16        queue<int> q; q.push(s); dis[s] = 0;
17        while (!q.empty()){
18            int u = q.front(); q.pop(); vis[u] = false;
19            for(auto &it : E[u]){
20                if(it.f > 0 && dis[it.v] > dis[u] + it.w){
21                    dis[it.v] = dis[u] + it.w;
22                    if(!vis[it.v]){
23                        vis[it.v] = 1; q.push(it.v);
24                    } } } }
25        return dis[t] != LLMXN;
26    }
27    int DFS(int u, int nf){
28        if(u == t) return nf;
29        int res = 0; vis[u] = 1;
30        for(int &i = ptr[u]; i < (int)E[u].size(); ++i){
31            auto &it = E[u][i];
32            if(it.f>0&&dis[it.v]==dis[u]+it.w&&!vis[it.v]){
33                int tf = DFS(it.v, min(nf, it.f));
34                res += tf, nf -= tf, it.f -= tf;
35                E[it.v][it.re].f += tf;
36                if(nf == 0){ vis[u] = false; break; }

```

```

37    }
38    }
39    return res;
40 }
41 pair<int, ll> flow(){
42     int flow = 0; ll cost = 0;
43     while (SPFA()){
44         memset(ptr, 0, 4 * n);
45         int f = DFS(s, INF);
46         flow += f; cost += dis[t] * f;
47     }
48     return{ flow, cost };
49 }
50 } flow;

```

2.2 Dinic

求最大流 $O(N^2 E)$ ，求二分最大匹配 $O(E\sqrt{N})$

dinic.init(n, st, en) \Rightarrow 0-base

dinic.addEdge(u, v, f) $\Rightarrow u \rightarrow v$, flow f units

dinic.run() \Rightarrow return max flow from st to en

Dinic 玄學：若 TLE，可以先加“正向邊”且每次都 run()，再全加一次每次都 run()。

範例 code 待補

```

1 const int MXN = 10005;
2 struct Dinic{
3     struct Edge{ ll v, f, re; };
4     int n, s, t, lvl[MXN];
5     vector<Edge> e[MXN];
6     void init(int _n, int _s, int _t){
7         n = _n; s = _s; t = _t;
8         for(int i = 0; i < n; ++i) e[i].clear(); }
9     void addEdge(int u, int v, ll f = 1){
10        e[u].push_back({v, f, e[v].size()});
11        e[v].push_back({u, 0, e[u].size() - 1}); }
12    bool bfs(){
13        memset(lvl, -1, n * 4);
14        queue<int> q;
15        q.push(s);
16        lvl[s] = 0;
17        while(!q.empty()){
18            int u = q.front(); q.pop();
19            for(auto &i : e[u])
20                if(i.f > 0 && lvl[i.v] == -1)
21                    lvl[i.v] = lvl[u] + 1, q.push(i.v); }
22    return lvl[t] != -1; }
23    ll dfs(int u, ll nf){
24        if(u == t) return nf;
25        ll res = 0;
26        for(auto &i : e[u])
27            if(i.f > 0 && lvl[i.v] == lvl[u] + 1){
28                int tmp = dfs(i.v, min(nf, i.f));
29                res += tmp, nf -= tmp, i.f -= tmp;
30                e[i.v][i.re].f += tmp;
31                if(nf == 0) return res; }
32        if(!res) lvl[u] = -1;
33    return res; }
34    ll run(ll res){
35        while(bfs()) res += dfs(s, LLINF);
36    return res; } };

```

2.3 Kuhn Munkres 最大完美二分匹配

二分完全圖最大權完美匹配 $O(n^3)$ (不太會跑滿)

轉換：

最大權匹配 (沒邊就補 0)

最小權完美匹配 (權重取負)

最大權重積 (ll 改 ld, memset 改 fill, w 取自然對數 log(w), 答案為 exp(ans))

二分圖判斷: DFS 建樹記深度 -> 有邊的兩點深度奇偶性相同 -> 奇環 -> 非二分圖

二分圖最小頂點覆蓋 = 最大匹配

| 最大匹配 | + | 最小邊覆蓋 | = |V|

| 最小點覆蓋 | + | 最大獨立集 | = |V|

| 最大匹配 | = | 最小點覆蓋 |

最大團 = 補圖的最大獨立集

```

1 const int MXN = 1005;
2 struct KM{ // 1-base
3     int n, mx[MXN], my[MXN], pa[MXN];
4     ll g[MXN][MXN], lx[MXN], ly[MXN], sy[MXN];
5     bool vx[MXN], vy[MXN];
6     void init(int _n){
7         n = _n;
8         MEM(g, 0); }
9     void addEdge(int x, int y, ll w){ g[x][y] = w; }
10    void augment(int y){

```

```

11 for(int x, z; y; y = z)
12     x = pa[y], z = mx[x], my[y] = x, mx[x] = y; }
13 void bfs(int st){
14     for(int i = 1; i <= n; ++i)
15         sy[i] = LLINF, vx[i] = vy[i] = 0;
16     queue<int> q; q.push(st);
17     for(;;){
18         while(!q.empty()){
19             int x = q.front(); q.pop();
20             vx[x] = 1;
21             for(int y = 1; y <= n; ++y)
22                 if(!vy[y]){
23                     ll t = lx[x] + ly[y] - g[x][y];
24                     if(t == 0){
25                         pa[y] = x;
26                         if(!my[y]){ augment(y); return; }
27                         vy[y] = 1, q.push(my[y]); }
28                     else if(sy[y] > t) pa[y] = x, sy[y] = t; } }
29             ll cut = LLINF;
30             for(int y = 1; y <= n; ++y)
31                 if(!vy[y] && cut > sy[y]) cut = sy[y];
32             for(int j = 1; j <= n; ++j){
33                 if(vx[j]) lx[j] -= cut;
34                 if(vy[j]) ly[j] += cut;
35                 else sy[j] -= cut; }
36             for(int y = 1; y <= n; ++y)
37                 if(!vy[y] && sy[y] == 0){
38                     if(!my[y]){ augment(y); return; }
39                     vy[y] = 1, q.push(my[y]); } } }
40     ll run(){
41         MEM(mx, 0), MEM(my, 0), MEM(ly, 0), MEM(lx, -0x3f);
42         for(int x=1; x <= n; ++x) for(int y=1; y <= n; ++y)
43             lx[x] = max(lx[x], g[x][y]);
44         for(int x = 1; x <= n; ++x) bfs(x);
45         ll ret = 0;
46         for(int y = 1; y <= n; ++y) ret += g[my[y]][y];
47         return ret; } };
```

2.4 Directed MST *

```

1 struct DMST {
2     struct Edge{ int u, v, c;
3         Edge(int u, int v, int c):u(u),v(v),c(c){} };
4     int v, e, root;
5     Edge edges[MXN];
6     int newV(){ return ++v; }
7     void addEdge(int u, int v, int c)
8         { edges[++e] = Edge(u, v, c); }
9     bool con[MXN];
10    int mnInW[MXN], prv[MXN], cyc[MXN], vis[MXN];
11    int run(){
12        memset(con, 0, 4*(V+1));
13        int r1 = 0, r2 = 0;
14        while(1){
15            fill(mnInW, mnInW+V+1, INF);
16            fill(prv, prv+V+1, -1);
17            for(int i = 1; i <= e; ++i){
18                int u=edges[i].u, v=edges[i].v, c=edges[i].c;
19                if(u != v && v != root && c < mnInW[v])
20                    mnInW[v] = c, prv[v] = u; }
21            fill(vis, vis+V+1, -1);
22            fill(cyc, cyc+V+1, -1);
23            r1 = 0;
24            bool jf = 0;
25            for(int i = 1; i <= v; ++i){
26                if(con[i]) continue;
27                if(prv[i] == -1 && i != root) return -1;
28                if(prv[i] > 0) r1 += mnInW[i];
29                int s;
30                for(s = i; s != -1 && vis[s] == -1; s = prv[s])
31                    vis[s] = i;
32                if(s > 0 && vis[s] == i){
33                    jf = 1; int v = s;
34                    do{ cyc[v] = s, con[v] = 1;
35                        r2 += mnInW[v]; v = prv[v];
36                    }while(v != s);
37                    con[s] = 0;
38                } }
39            if(!jf) break;
40            for(int i = 1; i <= e; ++i){
41                int &u = edges[i].u;
42                int &v = edges[i].v;
```

```

43         if(cyc[v] > 0) edges[i].c -= mnInW[edges[i].v];
44         if(cyc[u] > 0) edges[i].u = cyc[edges[i].u];
45         if(cyc[v] > 0) edges[i].v = cyc[edges[i].v];
46         if(u == v) edges[i--] = edges[E--];
47     } }
48     return r1+r2;}};
```

2.5 SW min-cut (不限 S-T 的 min-cut) *

```

1 struct SW{ // O(V^3)
2     int n,vst[MXN],del[MXN];
3     int edge[MXN][MXN],wei[MXN];
4     void init(int _n){
5         n = _n; memset(del, 0, sizeof(del));
6         memset(edge, 0, sizeof(edge));
7     }
8     void addEdge(int u, int v, int w){
9         edge[u][v] += w; edge[v][u] += w;
10    }
11    void search(int &s, int &t){
12        memset(vst, 0, sizeof(vst)); memset(wei, 0, sizeof(
13            wei));
14        s = t = -1;
15        while (true){
16            int mx=-1, cur=0;
17            for (int i=0; i<n; i++)
18                if (!del[i] && !vst[i] && mx<wei[i])
19                    cur = i, mx = wei[i];
20            if (mx == -1) break;
21            vst[cur] = 1;
22            s = t; t = cur;
23            for (int i=0; i<n; i++)
24                if (!vst[i] && !del[i]) wei[i] += edge[cur][i];
25        }
26    }
27    int solve(){
28        int res = 2147483647;
29        for (int i=0,x,y; i<n-1; i++){
30            search(x,y);
31            res = min(res,wei[y]);
32            del[y] = 1;
33            for (int j=0; j<n; j++)
34                edge[x][j] = (edge[j][x] += edge[y][j]);
35        }
36        return res;
37    } }graph;
```

2.6 Bounded Max Flow

```

1 // flow use ISAP
2 // Max flow with lower/upper bound on edges
3 // source = 1 , sink = n
4 int in[ N ] , out[ N ];
5 int l[ M ] , r[ M ] , a[ M ] , b[ M ]; //0-base, a下界, b
6 // 上界
7 int solve(){
8     flow.init( n ); //n為點的數量, m為邊的數量, 點是1-
9     base
10    for( int i = 0 ; i < m ; i ++ ){
11        in[ r[ i ] ] += a[ i ];
12        out[ l[ i ] ] += a[ i ];
13        flow.addEdge( l[ i ] , r[ i ] , b[ i ] - a[ i ] );
14        // flow from l[i] to r[i] must in [a[i], b[i]]
15    }
16    int nd = 0;
17    for( int i = 1 ; i <= n ; i ++ ){
18        if( in[ i ] < out[ i ] ){
19            flow.addEdge( i , flow.t , out[ i ] - in[ i ] );
20            nd += out[ i ] - in[ i ];
21        }
22        if( out[ i ] < in[ i ] )
23            flow.addEdge( flow.s , i , in[ i ] - out[ i ] );
24    }
25    // original sink to source
26    flow.addEdge( n , 1 , INF );
27    if( flow.maxflow() != nd )
28        return -1; // no solution
29    int ans = flow.G[ 1 ].back().c; // source to sink
30    flow.G[ 1 ].back().c = flow.G[ n ].back().c = 0;
31    // take out super source and super sink
32    for( size_t i = 0 ; i < flow.G[ flow.s ].size() ; i
33        ++ )
```

```

31 flow.G[ flow.s ][ i ].c = 0;
32 Edge &e = flow.G[ flow.s ][ i ];
33 flow.G[ e.v ][ e.r ].c = 0;
34 }
35 for( size_t i = 0 ; i < flow.G[ flow.t ].size() ; i
    ++ ){
36 flow.G[ flow.t ][ i ].c = 0;
37 Edge &e = flow.G[ flow.t ][ i ];
38 flow.G[ e.v ][ e.r ].c = 0;
39 }
40 flow.addEdge( flow.s , 1 , INF );
41 flow.addEdge( n , flow.t , INF );
42 flow.reset();
43 return ans + flow.maxflow();
44 }

```

2.7 Flow Method *

Maximize $c^T x$ subject to $Ax \leq b, x \geq 0$;
 with the corresponding symmetric dual problem,
 Minimize $b^T y$ subject to $A^T y \geq c, y \geq 0$.
 Maximize $c^T x$ subject to $Ax \leq b$;
 with the corresponding asymmetric dual problem,
 Minimize $b^T y$ subject to $A^T y = c, y \geq 0$.
 Minimum vertex cover on bipartite graph =
 Maximum matching on bipartite graph
 Minimum edge cover on bipartite graph =
 vertex number - Minimum vertex cover(Maximum matching)
 Independent set on bipartite graph =
 vertex number - Minimum vertex cover(Maximum matching)
 找出最小點覆蓋，做完 dinic 之後，從源點 dfs 只走還有流量的
 邊，紀錄每個點有沒有被走到，左邊沒被走到的點跟右邊被走
 到的點就是答案
 Maximum density subgraph $(\sum W_e + \sum W_v)/|V|$
 Binary search on answer:
 For a fixed D, construct a Max flow model as follow:
 Let S be Sum of all weight(or inf)
 1. from source to each node with cap = S
 2. For each (u,v,w) in E, $(u \rightarrow v, \text{cap}=w)$, $(v \rightarrow u, \text{cap}=w)$
 3. For each node v, from v to sink with cap = $S + 2 * D - \deg[v] - 2 * 9$
 (W of v)
 where $\deg[v] = \sum \text{weight of edge associated with } v$
 If maxflow < $S * |V|$, D is an answer.
 Requiring subgraph: all vertex can be reached from source with
 edge whose cap > 0.

• Maximum/Minimum flow with lower bound / Circulation problem

1. Construct super source S and sink T .
2. For each edge (x,y,l,u) , connect $x \rightarrow y$ with capacity $u-l$.
3. For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
4. If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
5. The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.

• Construct minimum vertex cover from maximum matching M on bipartite graph (X,Y)

1. Redirect every edge: $y \rightarrow x$ if $(x,y) \in M$, $x \rightarrow y$ otherwise.
2. DFS from unmatched vertices in X .
3. $x \in X$ is chosen iff x is unvisited.
4. $y \in Y$ is chosen iff y is visited.

• Maximum density induced subgraph

1. Binary search on answer, suppose we're checking answer T
2. Construct a max flow model, let K be the sum of all weights
3. Connect source $s \rightarrow v$, $v \in G$ with capacity K
4. For each edge (u,v,w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
5. For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
6. T is a valid answer if the maximum flow $f < K|V|$

• Minimum weight edge cover

1. For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u,v)$.
2. Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
3. Find the minimum weight perfect matching on G' .

• Project selection problem

1. If $p_v > 0$, create edge (s,v) with capacity p_v ; otherwise, create edge (v,t) with capacity $-p_v$.
2. Create edge (u,v) with capacity w with w being the cost of choosing u without choosing v .
3. The mincut is equivalent to the maximum profit of a subset of projects.

• 0/1 quadratic programming

$$\sum_x c_x x + \sum_y c_y \bar{y} + \sum_{xy} c_{xy} x \bar{y} + \sum_{xyx'y'} c_{xyx'y'} (x \bar{y} + x' \bar{y}')$$

can be minimized by the mincut of the following graph:

1. Create edge (x,t) with capacity c_x and create edge (s,y) with capacity c_y .
2. Create edge (x,y) with capacity c_{xy} .
3. Create edge (x,y) and edge (x',y') with capacity $c_{xyx'y'}$.

3 Math

3.1 Fast Pow & Inverse & Combination

$fpow(a,b,m) = a^b \pmod{m}$
 $fa[i] = i! \pmod{MOD}$
 $fi[i] = i!^{-1} \equiv 1 \pmod{MOD}$
 $c(a,b) = \binom{a}{b} \pmod{MOD}$

```

1 ll fpow(ll a, ll b, ll m){
2 ll ret = 1;
3 a %= m;
4 while(b){
5 if(b&1) ret = ret * a % m;
6 a = a * a % m;
7 b >>= 1; }
8 return ret; }
9
10 ll fa[MXN], fi[MXN];
11 void init(){
12 fa[0] = 1;
13 for(ll i = 1; i < MXN; ++i)
14 fa[i] = fa[i-1] * i % MOD;
15 fi[MXN-1] = fpow(fa[MXN-1], MOD-2, MOD);
16 for(ll i = MXN-1; i > 0; --i)
17 fi[i] = fi[i+1] * i % MOD; }
18
19 ll c(ll a, ll b){
20 return fa[a] * fi[b] % MOD * fi[a-b] % MOD; }

```

3.2 Ext GCD

```

1 //a * p.first + b * p.second = gcd(a, b)
2 pair<ll, ll> extgcd(ll a, ll b) {
3 pair<ll, ll> res;
4 if (a < 0) {
5 res = extgcd(-a, b);
6 res.first *= -1;
7 return res;
8 }
9 if (b < 0) {
10 res = extgcd(a, -b);
11 res.second *= -1;
12 return res;
13 }
14 if (b == 0) return {1, 0};
15 res = extgcd(b, a % b);
16 return {res.second, res.first - res.second * (a / b)};
17 }

```

3.3 Sieve 質數篩

```

1 const int MXN = 2e9 + 5; // 2^27 約0.7s, 2^30 約6~7s
2 bool np[MXN]; // np[i] = 1 -> i is'n a prime
3 vector<int> plist; // prime list
4 void sieveBuild(int n){
5 MEM(np, 0);
6 for(int i = 2, sq = sqrt(n); i <= sq; ++i)
7 if(!np[i])
8 for(int j = i * i; j <= n; j += i) np[j] = 1;
9 for(int i = 2; i <= n; ++i) if(!np[i]) plist.PB(i); }

```


3.4 FFT *

```

1 // const int MAXN = 262144;
2 // (must be 2^k)
3 // before any usage, run pre_fft() first
4 typedef long double ld;
5 typedef complex<ld> cplx; //real() ,imag()
6 const ld PI = acos(-1);
7 const cplx I(0, 1);
8 cplx omega[MAXN+1];
9 void pre_fft(){
10     for(int i=0; i<=MAXN; i++)
11         omega[i] = exp(i * 2 * PI / MAXN * I);
12 }
13 // n must be 2^k
14 void fft(int n, cplx a[], bool inv=false){
15     int basic = MAXN / n;
16     int theta = basic;
17     for (int m = n; m >= 2; m >= 1) {
18         int mh = m >> 1;
19         for (int i = 0; i < mh; i++) {
20             cplx w = omega[inv ? MAXN-(i*theta%MAXN)
21                             : i*theta%MAXN];
22             for (int j = i; j < n; j += m) {
23                 int k = j + mh;
24                 cplx x = a[j] - a[k];
25                 a[j] += a[k];
26                 a[k] = w * x;
27             }
28             theta = (theta * 2) % MAXN;
29         }
30         int i = 0;
31         for (int j = 1; j < n - 1; j++) {
32             for (int k = n >> 1; k > (i ^ k); k >= 1);
33             if (j < i) swap(a[i], a[j]);
34         }
35         if(inv) for (i = 0; i < n; i++) a[i] /= n;
36     }
37 cplx arr[MAXN+1];
38 inline void mul(int _n, ll a[], int _m, ll b[], ll ans[])
39 {
40     int n=1, sum=_n+_m-1;
41     while(n<sum)
42         n<<=1;
43     for(int i=0; i<n; i++)
44     {
45         double x=(i<n?a[i]:0), y=(i<m?b[i]:0);
46         arr[i]=complex<double>(x+y, x-y);
47     }
48     fft(n, arr);
49     for(int i=0; i<n; i++)
50         arr[i]=arr[i]*arr[i];
51     fft(n, arr, true);
52     for(int i=0; i<sum; i++)
53         ans[i]=(long long int)(arr[i].real()/4+0.5);
54 }

```

3.5 NTT *

```

1 // Remember coefficient are mod P
2 /* p=a*2^n+1
3    n      2^n      p      a      root
4    16    65536    65537    1      3
5    20    1048576   7340033   7      3 */
6 // (must be 2^k)
7 template<LL P, LL root, int MAXN>
8 struct NTT{
9     static LL bigmod(LL a, LL b) {
10         LL res = 1;
11         for (LL bs = a; b; b >= 1, bs = (bs * bs) % P)
12             if(b&1) res=(res*bs)%P;
13         return res;
14     }
15     static LL inv(LL a, LL b) {
16         if(a==1) return 1;
17         return (((LL)(a-inv(b%a,a))*b+1)/a)%b;
18     }
19     LL omega[MAXN+1];
20     NTT() {
21         omega[0] = 1;
22         LL r = bigmod(root, (P-1)/MAXN);
23         for (int i=1; i<=MAXN; i++)

```

```

24         omega[i] = (omega[i-1]*r)%P;
25     }
26     // n must be 2^k
27     void tran(int n, LL a[], bool inv_ntt=false){
28         int basic = MAXN / n, theta = basic;
29         for (int m = n; m >= 2; m >= 1) {
30             int mh = m >> 1;
31             for (int i = 0; i < mh; i++) {
32                 LL w = omega[i*theta%MAXN];
33                 for (int j = i; j < n; j += m) {
34                     int k = j + mh;
35                     LL x = a[j] - a[k];
36                     if (x < 0) x += P;
37                     a[j] += a[k];
38                     if (a[j] > P) a[j] -= P;
39                     a[k] = (w * x) % P;
40                 }
41             }
42             theta = (theta * 2) % MAXN;
43         }
44         int i = 0;
45         for (int j = 1; j < n - 1; j++) {
46             for (int k = n >> 1; k > (i ^ k); k >= 1);
47             if (j < i) swap(a[i], a[j]);
48         }
49         if (inv_ntt) {
50             LL ni = inv(n, P);
51             reverse(a+1, a+n);
52             for (i = 0; i < n; i++)
53                 a[i] = (a[i] * ni) % P;
54         }
55     }
56 };
57 const LL P=2013265921, root=31;
58 const int MAXN=4194304;
59 NTT<P, root, MAXN> ntt;

```

3.6 Linear Recurrence *

```

1 // Usage: linearRec({0, 1}, {1, 1}, k) //k'th fib
2 typedef vector<ll> Poly;
3 //S: 前i項的值, tr: 遞迴係數, k: 求第k項
4 ll linearRec(Poly& S, Poly& tr, ll k) {
5     int n = tr.size();
6     auto combine = [&](Poly& a, Poly& b) {
7         Poly res(n * 2 + 1);
8         rep(i, 0, n+1) rep(j, 0, n+1)
9             res[i+j]=(res[i+j] + a[i]*b[j])%mod;
10        for(int i = 2*n; i > n; --i) rep(j, 0, n)
11            res[i-1-j]=(res[i-1-j] + res[i]*tr[j])%mod;
12        res.resize(n + 1);
13        return res;
14    };
15    Poly pol(n + 1), e(pol);
16    pol[0] = e[1] = 1;
17    for (++k; k; k /= 2) {
18        if (k % 2) pol = combine(pol, e);
19        e = combine(e, e);
20    }
21    ll res = 0;
22    rep(i, 0, n) res=(res + pol[i+1]*S[i])%mod;
23    return res;
24 }

```

3.7 Miller Rabin

isprime(n) ⇒ 判斷 n 是否為質數
記得填 magic number

```

1 // magic numbers when n <
2 // 4,759,123,141 : 2, 7, 61
3 // 1,122,004,669,633 : 2, 13, 23, 1662803
4 // 3,474,749,660,383 : 2, 3, 5, 7, 11, 13
5 // 2^64 : 2, 325, 9375, 28178, 450775,
6 // 9780504, 1795265022
7 // Make sure testing integer is in range [2, n-2] if
8 // you want to use magic.
9 vector<ll> magic = {};
10 bool witness(ll a, ll n, ll u, ll t){
11     if(!a) return 0;
12     ll x = fpow(a, u, n);
13     while(t--){
14         ll nx = x * x % n;

```

```

13 if(nx == 1 && x != 1 && x != n - 1) return 1;
14 x = nx; }
15 return x != 1; }
16 bool isprime(ll n) {
17 if(n < 2) return 0;
18 if(~n & 1) return n == 2;
19 ll u = n - 1, t = 0;
20 while(~u & 1) u >>= 1, t++;
21 for(auto i : magic){
22 ll a = i % n;
23 if(witness(a, n, u, t)) return 0; }
24 return 1; }

```

3.8 Faulhaber ($\sum_{i=1}^n i^p$) *

```

1 /* faulhaber' s formula -
2 * cal power sum formula of all p=1~k in O(k^2) */
3 #define MAXK 2500
4 const int mod = 1000000007;
5 int b[MAXK]; // bernoulli number
6 int inv[MAXK+1]; // inverse
7 int cm[MAXK+1][MAXK+1]; // combinactories
8 int co[MAXK][MAXK+2]; // coeeficient of x^j when p=i
9 inline int getinv(int x) {
10 int a=x,b=mod,a0=1,a1=0,b0=0,b1=1;
11 while(b) {
12 int q,t;
13 q=a/b; t=b; b=a-b*q; a=t;
14 t=b0; b0=a0-b0*q; a0=t;
15 t=b1; b1=a1-b1*q; a1=t;
16 }
17 return a0<0?a0+mod:a0;
18 }
19 inline void pre() {
20 /* combinational */
21 for(int i=0;i<=MAXK;i++) {
22 cm[i][0]=cm[i][i]=1;
23 for(int j=1;j<i;j++)
24 cm[i][j]=add(cm[i-1][j-1],cm[i-1][j]);
25 }
26 /* inverse */
27 for(int i=1;i<=MAXK;i++) inv[i]=getinv(i);
28 /* bernoulli */
29 b[0]=1; b[1]=getinv(2); // with b[1] = 1/2
30 for(int i=2;i<MAXK;i++) {
31 if(i&1) { b[i]=0; continue; }
32 b[i]=1;
33 for(int j=0;j<i;j++)
34 b[i]=sub(b[i],
35 mul(cm[i][j],mul(b[j], inv[i-j+1])));
36 }
37 /* faulhaber */
38 // sigma_x=1~n {x^p} =
39 // 1/(p+1) * sigma_j=0~p {C(p+1,j)*Bj*n^(p-j+1)}
40 for(int i=1;i<MAXK;i++) {
41 co[i][0]=0;
42 for(int j=0;j<i;j++)
43 co[i][i-j+1]=mul(inv[i+1], mul(cm[i+1][j], b[j]));
44 }
45 }
46 /* sample usage: return f(n,p) = sigma_x=1~n (x^p) */
47 inline int solve(int n,int p) {
48 int sol=0,m=n;
49 for(int i=1;i<=p+1;i++) {
50 sol=add(sol,mul(co[p][i],m));
51 m = mul(m, n);
52 }
53 return sol;
54 }

```

3.9 Chinese Remainder *

```

1 LL x[N],m[N];
2 LL CRT(LL x1, LL m1, LL x2, LL m2) {
3 LL g = __gcd(m1, m2);
4 if((x2 - x1) % g) return -1; // no sol
5 m1 /= g; m2 /= g;
6 pair<LL,LL> p = gcd(m1, m2);
7 LL lcm = m1 * m2 * g;
8 LL res = p.first * (x2 - x1) * m1 + x1;

```

```

9 return (res % lcm + lcm) % lcm;
10 }
11 LL solve(int n){ // n>=2, be careful with no solution
12 LL res=CRT(x[0],m[0],x[1],m[1]),p=m[0]/__gcd(m[0],m
13 [1])*m[1];
14 for(int i=2;i<n;i++){
15 res=CRT(res,p,x[i],m[i]);
16 p=p/__gcd(p,m[i])*m[i];
17 }
18 return res;

```

3.10 Pollard Rho *

```

1 // does not work when n is prime O(n^(1/4))
2 LL f(LL x, LL mod){ return add(mul(x,x,mod),1,mod); }
3 LL pollard_rho(LL n) {
4 if(!(n&1)) return 2;
5 while(true){
6 LL y=2, x=rand()%(n-1)+1, res=1;
7 for(int sz=2; res==1; sz*=2) {
8 for(int i=0; i<sz && res<=1; i++) {
9 x = f(x, n);
10 res = __gcd(abs(x-y), n);
11 }
12 y = x;
13 }
14 if (res!=0 && res!=n) return res;
15 } }

```

3.11 Josephus Problem *

```

1 int josephus(int n, int m){ //n人 每m次
2 int ans = 0;
3 for (int i=1; i<=n; ++i)
4 ans = (ans + m) % i;
5 return ans;
6 }

```

3.12 Gaussian Elimination *

```

1 const int GAUSS_MOD = 1000000007LL;
2 struct GAUSS{
3 int n;
4 vector<vector<int>> v;
5 int ppow(int a, int k){
6 if(k == 0) return 1;
7 if(k % 2 == 0) return ppow(a * a % GAUSS_MOD,
8 k >> 1);
9 if(k % 2 == 1) return ppow(a * a % GAUSS_MOD,
10 k >> 1) * a % GAUSS_MOD;
11 }
12 vector<int> solve(){
13 vector<int> ans(n);
14 REP(now, 0, n){
15 REP(i, now, n) if(v[now][now] == 0 && v[i
16 ][now] != 0)
17 swap(v[i], v[now]); // det = -det;
18 if(v[now][now] == 0) return ans;
19 int inv = ppow(v[now][now], GAUSS_MOD - 2)
20 ;
21 REP(i, 0, n) if(i != now){
22 int tmp = v[i][now] * inv % GAUSS_MOD;
23 REP(j, now, n + 1) (v[i][j] +=
24 GAUSS_MOD - tmp * v[now][j] %
25 GAUSS_MOD) %= GAUSS_MOD;
26 }
27 REP(i, 0, n) ans[i] = v[i][n + 1] * ppow(v[i
28 ][i], GAUSS_MOD - 2) % GAUSS_MOD;
29 return ans;
30 }
31 }
32 // gs.v.clear(), gs.v.resize(n, vector<int>(n + 1
33 , 0));
34 } gs;

```

3.13 Result *

- Lucas' Theorem :
For $n, m \in \mathbb{Z}^+$ and prime P , $C(m, n) \bmod P = \prod_i (C(m_i, n_i))$ where m_i is the i -th digit of m in base P .
- Stirling approximation :
$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n e^{\frac{1}{12n}}$$

- Stirling Numbers(permutation $|P| = n$ with k cycles):
 $S(n, k) = \text{coefficient of } x^k \text{ in } \prod_{i=0}^{n-1} (x+i)$
- Stirling Numbers(Partition n elements into k non-empty set):
 $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$
- Pick's Theorem : $A = i + b/2 - 1$
 其面積 A 和內部格點數目 i 、邊上格點數目 b 的關係
- Catalan number : $C_n = \binom{2n}{n} / (n+1)$
 $C_n^{n+m} - C_{n+1}^{n+m} = (m+n)! \frac{2-m+1}{n+1}$ for $n \geq m$
 $C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}$
 $C_0 = 1$ and $C_{n+1} = 2 \binom{2n+1}{n+2} C_n$
 $C_0 = 1$ and $C_{n+1} = \sum_{i=0}^n C_i C_{n-i}$ for $n \geq 0$
- Euler Characteristic:
 planar graph: $V - E + F - C = 1$
 convex polyhedron: $V - E + F = 2$
 V, E, F, C : number of vertices, edges, faces(regions), and components
- Kirchhoff's theorem :
 $A_{ii} = \deg(i), A_{ij} = (i, j) \in E ? -1 : 0$, Deleting any one row, on column, and cal the $\det(A)$
- Polya's theorem (c 為方法數, m 為總數):
 $(\sum_{i=1}^m c^{gcd(i,m)})/m$
- Burnside lemma:
 $|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$
- 錯排公式: (n 個人中, 每個人皆不再原來位置的組合數):
 $dp[0] = 1; dp[1] = 0;$
 $dp[i] = (i-1) * (dp[i-1] + dp[i-2]);$
- Bell 數 (有 n 個人, 把他們拆組的方法總數) :
 $B_0 = 1$
 $B_n = \sum_{k=0}^n s(n, k)$ (second - stirling)
 $B_{n+1} = \sum_{k=0}^n \binom{n}{k} B_k$
- Wilson's theorem :
 $(p-1)! \equiv -1 \pmod{p}$
- Fermat's little theorem :
 $a^p \equiv a \pmod{p}$
- Euler's totient function:
 $A^{B^C} \pmod{p} = \text{pow}(A, \text{pow}(B, C, p-1)) \pmod{p}$
- 歐拉函數降冪公式:
 $A^B \pmod{C} = A^{B \pmod{\phi(C)} + \phi(C)} \pmod{C}$
- 6 的倍數:
 $(a-1)^3 + (a+1)^3 + (-a)^3 + (-a)^3 = 6a$

4 Geometry

4.1 definition *

```

1 const ld EPS = 1e-8;
2 const ld PI = acos(-1);
3 int dcmp(ld x){ // float x (<, ==, >) y -> (-1, 0, 1)
4   if(abs(x) < eps) return 0;
5   else return x < 0 ? -1 : 1;
6 }
7 struct Pt{
8   ld x, y;
9   Pt(ld _x = 0, ld _y = 0): x(_x), y(_y){}
10  Pt operator+(const Pt &a) const{
11    return Pt(x + a.x, y + a.y); }
12  Pt operator-(const Pt &a) const{
13    return Pt(x - a.x, y - a.y); }
14  Pt operator*(const ld &a) const{
15    return Pt(x * a, y * a); }
16  Pt operator/(const ld &a) const{
17    return Pt(x / a, y / a); }
18  ld operator*(const Pt &a) const{ // dot product
19    return x * a.x + y * a.y; }
20  ld operator^(const Pt &a) const{ // cross product
21    return x * a.y - y * a.x; }
22  bool operator<(const Pt &a) const{
23    return x < a.x || (x == a.x && y < a.y); }
24  // return dcmp(x-a.x) < 0 ||
25  // (dcmp(x-a.x) == 0 && dcmp(y-a.y) < 0); }
26  bool operator==(const Pt &a) const{
27    return dcmp(x - a.x) == 0 && dcmp(y - a.y) == 0; }

```

```

28 int qua() { // 在哪個象限(軸上點歸類到逆時針的象限)
29   if(x > 0 && y >= 0) return 1;
30   if(x <= 0 && y > 0) return 2;
31   if(x < 0 && y <= 0) return 3;
32   if(x >= 0 && y < 0) return 4;
33 }
34 ld angle() const{ // -pi ~ pi
35   if(dcmp(x) == 0 && dcmp(y) == 0) return 0;
36   return atan2(y, x); }
37 }
38 };
39 ld norm2(const Pt &a){
40   return a * a; }
41 ld norm(const Pt &a){ // norm(a - b) = dis of a, b
42   return sqrt(norm2(a)); }
43 Pt perp(const Pt &a){ // 垂直向量(順時針旋轉90度)
44   return Pt(-a.y, a.x); }
45 Pt rotate(const Pt &a, ld ang){
46   return Pt(a.x * cos(ang) - a.y * sin(ang),
47            a.x * sin(ang) + a.y * cos(ang)); }
48 struct Line{
49   Pt s, e, v; // start, end, end - start
50   ld ang; // angle of v
51   Line(Pt _s = Pt(0, 0), Pt _e = Pt(0, 0)):
52     s(_s), e(_e) { v = e - s; ang = atan2(v.y, v.x); }
53   bool operator<(const Line &L) const{ // sort by angle
54     return ang < L.ang;
55   } };
56 struct Circle{
57   Pt o; ld r;
58   Circle(Pt _o = Pt(0, 0), ld _r = 0): o(_o), r(_r){}
59 };

```

4.2 halfPlaneIntersection *

```

1 #define N 100010
2 #define EPS 1e-8
3 #define SIDE 10000000
4 struct PO{ double x, y; } p[ N ], o;
5 struct LI{
6   PO a, b;
7   double angle;
8   void in( double x1, double y1, double x2, double
9     y2 ){
10     a.x = x1; a.y = y1; b.x = x2; b.y = y2;
11 }
12 }li[ N ], deq[ N ];
13 int n, m, cnt;
14 inline int dc( double x ){
15   if ( x > EPS ) return 1;
16   else if ( x < -EPS ) return -1;
17   return 0;
18 }
19 inline PO operator-( PO a, PO b ){
20   PO c;
21   c.x = a.x - b.x; c.y = a.y - b.y;
22   return c;
23 }
24 inline double cross( PO a, PO b, PO c ){
25   return ( b.x - a.x ) * ( c.y - a.y ) - ( b.y - a.y )
26     * ( c.x - a.x );
27 }
28 inline bool cmp( const LI &a, const LI &b ){
29   if( dc( a.angle - b.angle ) == 0 ) return dc( cross(
30     a.a, a.b, b.a ) ) < 0;
31   return a.angle > b.angle;
32 }
33 inline PO getpoint( LI &a, LI &b ){
34   double k1 = cross( a.a, b.b, b.a );
35   double k2 = cross( a.b, b.a, b.b );
36   PO tmp = a.b - a.a, ans;
37   ans.x = a.a.x + tmp.x * k1 / ( k1 + k2 );
38   ans.y = a.a.y + tmp.y * k1 / ( k1 + k2 );
39   return ans;
40 }
41 inline void getcut(){
42   sort( li + 1, li + 1 + n, cmp ); m = 1;
43   for( int i = 2; i <= n; i++ )
44     if( dc( li[ i ].angle - li[ m ].angle ) != 0 )
45       li[ ++m ] = li[ i ];
46   deq[ 1 ] = li[ 1 ]; deq[ 2 ] = li[ 2 ];
47   int bot = 1, top = 2;

```

```

45 for( int i = 3 ; i <= m ; i ++ ){
46     while( bot < top && dc( cross( li[ i ].a , li[ i ].b ,
        getpoint( deq[ top ] , deq[ top - 1 ] ) ) < 0 ) top -- ;
47     while( bot < top && dc( cross( li[ i ].a , li[ i ].b ,
        getpoint( deq[ bot ] , deq[ bot + 1 ] ) ) < 0 ) bot ++ ;
48     deq[ ++ top ] = li[ i ] ;
49 }
50 while( bot < top && dc( cross( deq[ bot ].a , deq[ bot ].b ,
    getpoint( deq[ top ] , deq[ top - 1 ] ) ) < 0 ) top -- ;
51 while( bot < top && dc( cross( deq[ top ].a , deq[ top ].b ,
    getpoint( deq[ bot ] , deq[ bot + 1 ] ) ) < 0 ) bot ++ ;
52 cnt = 0 ;
53 if( bot == top ) return ;
54 for( int i = bot ; i < top ; i ++ ) p[ ++ cnt ] =
    getpoint( deq[ i ] , deq[ i + 1 ] ) ;
55 if( top - 1 > bot ) p[ ++ cnt ] = getpoint( deq[ bot ] ,
    deq[ top ] ) ;
56 }
57 double px[ N ] , py[ N ] ;
58 void read( int rm ) {
59     for( int i = 1 ; i <= n ; i ++ ) px[ i + n ] = px[ i ] ,
        py[ i + n ] = py[ i ] ;
60     for( int i = 1 ; i <= n ; i ++ ){
61         // half-plane from li[ i ].a -> li[ i ].b
62         li[ i ].a.x = px[ i + rm + 1 ] ; li[ i ].a.y = py[ i +
            rm + 1 ] ;
63         li[ i ].b.x = px[ i ] ; li[ i ].b.y = py[ i ] ;
64         li[ i ].angle = atan2( li[ i ].b.y - li[ i ].a.y ,
            li[ i ].b.x - li[ i ].a.x ) ;
65     }
66 }
67 inline double getarea( int rm ){
68     read( rm ) ; getcut() ;
69     double res = 0.0 ;
70     p[ cnt + 1 ] = p[ 1 ] ;
71     for( int i = 1 ; i <= cnt ; i ++ ) res += cross( o ,
        p[ i ] , p[ i + 1 ] ) ;
72     if( res < 0.0 ) res *= -1.0 ;
73     return res ;
74 }

```

4.3 Convex Hull *

```

1 double cross( Pt o , Pt a , Pt b ){
2     return ( a-o ) ^ ( b-o ) ;
3 }
4 vector<Pt> convex_hull( vector<Pt> pt ){
5     sort( pt.begin() , pt.end() ) ;
6     int top=0 ;
7     vector<Pt> stk( 2*pt.size() ) ;
8     for( int i=0 ; i<(int)pt.size() ; i++){
9         while( top >= 2 && cross( stk[top-2] , stk[top-1] , pt[i] )
            <= 0 )
10             top-- ;
11         stk[top++] = pt[i] ;
12     }
13     for( int i=pt.size()-2 , t=top+1 ; i>=0 ; i-- ){
14         while( top >= t && cross( stk[top-2] , stk[top-1] , pt[i] )
            <= 0 )
15             top-- ;
16         stk[top++] = pt[i] ;
17     }
18     stk.resize( top-1 ) ;
19     return stk ;
20 }

```

4.4 Convex Hull trick *

```

1 /* Given a convexhull, answer queries in O( lg N )
2 CH should not contain identical points, the area should
3 be > 0 , min pair(x, y) should be listed first */
4 double det( const Pt& p1 , const Pt& p2 )
5 { return p1.X * p2.Y - p1.Y * p2.X ; }
6 struct Conv{
7     int n ;
8     vector<Pt> a ;
9     vector<Pt> upper , lower ;
10    Conv( vector<Pt> _a ) : a( _a ){

```

```

        n = a.size() ;
        int ptr = 0 ;
        for( int i=1 ; i<n ; ++i ) if( a[ptr] < a[i] ) ptr = i ;
        for( int i=0 ; i<=ptr ; ++i ) lower.push_back( a[i] ) ;
        for( int i=ptr ; i<n ; ++i ) upper.push_back( a[i] ) ;
        upper.push_back( a[0] ) ;
    }
    int sign( LL x ){ // fixed when changed to double
        return x < 0 ? -1 : x > 0 ; }
    pair<LL, int> get_tang( vector<Pt> &conv , Pt vec ){
        int l = 0 , r = (int)conv.size() - 2 ;
        for( ; l + 1 < r ; ){
            int mid = ( l + r ) / 2 ;
            if( sign( det( conv[mid+1] - conv[mid] , vec ) ) > 0 ) r = mid ;
            else l = mid ;
        }
        return max( make_pair( det( vec , conv[r] ) , r ) ,
            make_pair( det( vec , conv[0] ) , 0 ) ) ;
    }
    void upd_tang( const Pt &p , int id , int &i0 , int &i1 ){
        if( det( a[i0] - p , a[id] - p ) > 0 ) i0 = id ;
        if( det( a[i1] - p , a[id] - p ) < 0 ) i1 = id ;
    }
    void bi_search( int l , int r , Pt p , int &i0 , int &i1 ){
        if( l == r ) return ;
        upd_tang( p , l % n , i0 , i1 ) ;
        int sl = sign( det( a[l % n] - p , a[(l + 1) % n] - p ) ) ;
        for( ; l + 1 < r ; ){
            int mid = ( l + r ) / 2 ;
            int smid = sign( det( a[mid % n] - p , a[(mid + 1) % n] - p ) ) ;
            if( smid == sl ) l = mid ;
            else r = mid ;
        }
        upd_tang( p , r % n , i0 , i1 ) ;
    }
    int bi_search( Pt u , Pt v , int l , int r ) {
        int sl = sign( det( v - u , a[l % n] - u ) ) ;
        for( ; l + 1 < r ; ){
            int mid = ( l + r ) / 2 ;
            int smid = sign( det( v - u , a[mid % n] - u ) ) ;
            if( smid == sl ) l = mid ;
            else r = mid ;
        }
        return l % n ;
    }
    // 1. whether a given point is inside the CH
    bool contain( Pt p ) {
        if( p.X < lower[0].X || p.X > lower.back().X )
            return 0 ;
        int id = lower_bound( lower.begin() , lower.end() , Pt( p.X ,
            -INF ) ) - lower.begin() ;
        if( lower[id].X == p.X ) {
            if( lower[id].Y > p.Y ) return 0 ;
        } else if( det( lower[id-1] - p , lower[id] - p ) < 0 ) return 0 ;
        id = lower_bound( upper.begin() , upper.end() , Pt( p.X ,
            INF ) , greater<Pt>() ) - upper.begin() ;
        if( upper[id].X == p.X ) {
            if( upper[id].Y < p.Y ) return 0 ;
        } else if( det( upper[id-1] - p , upper[id] - p ) < 0 ) return 0 ;
        return 1 ;
    }
    // 2. Find 2 tang pts on CH of a given outside point
    // return true with i0, i1 as index of tangent points
    // return false if inside CH
    bool get_tang( Pt p , int &i0 , int &i1 ) {
        if( contain( p ) ) return false ;
        i0 = i1 = 0 ;
        int id = lower_bound( lower.begin() , lower.end() , p ) -
            lower.begin() ;
        bi_search( 0 , id , p , i0 , i1 ) ;
        bi_search( id , (int)lower.size() , p , i0 , i1 ) ;
        id = lower_bound( upper.begin() , upper.end() , p ,
            greater<Pt>() ) - upper.begin() ;
        bi_search( (int)lower.size() - 1 , (int)lower.size() -
            1 + id , p , i0 , i1 ) ;
        bi_search( (int)lower.size() - 1 + id , (int)lower.size() -
            1 + (int)upper.size() , p , i0 , i1 ) ;
        return true ;
    }
    // 3. Find tangent points of a given vector
    // ret the idx of vertex has max cross value with vec
    int get_tang( Pt vec ){

```



```

86 pair<LL, int> ret = get_tang(upper, vec);
87 ret.second = (ret.second+(int)lower.size()-1)%n;
88 ret = max(ret, get_tang(lower, vec));
89 return ret.second;
90 }
91 // 4. Find intersection point of a given line
92 // return 1 and intersection is on edge (i, next(i))
93 // return 0 if no strictly intersection
94 bool get_intersection(Pt u, Pt v, int &i0, int &i1){
95     int p0 = get_tang(u - v), p1 = get_tang(v - u);
96     if(sign(det(v-u,a[p0]-u))*sign(det(v-u,a[p1]-u))<0){
97         if (p0 > p1) swap(p0, p1);
98         i0 = bi_search(u, v, p0, p1);
99         i1 = bi_search(u, v, p1, p0 + n);
100         return 1;
101     }
102     return 0;
103 }

```

4.5 掃描的線

```

1 ScanLine sl;
2 sl.add(兩點座標);
3 sl.run()
4
5 template <typename T>
6 struct SegmentTree{
7     struct Node{
8         T len = 0, tag = 0;
9         int nl, nr;
10        Node *l, *r;
11    } *root;
12    vector<T> vec;
13    int n;
14    SegmentTree(){
15        void init(vector<T> _vec){
16            vec = _vec;
17            n = vec.size() - 1;
18            root = build(0, n - 1);
19        }
20        Node* build(int l, int r){
21            Node *res = new Node();
22            res->nl = l, res->nr = r;
23            if(l == r){
24                res->l = res->r = nullptr;
25                return res;
26            }
27            int mid = (l + r) >> 1;
28            res->l = build(l, mid);
29            res->r = build(mid + 1, r);
30            return res;
31        }
32        void push(Node *cur){
33            int l = cur->nl, r = cur->nr;
34            if(cur->tag) cur->len = vec[r + 1] - vec[l];
35            else cur->len = l == r ? 0 : cur->l->len + cur->r->len;
36        }
37        void update(Node *cur, int ql, int qr, int x){
38            int l = cur->nl, r = cur->nr;
39            if(vec[r + 1] <= ql || qr <= vec[l]) return;
40            if(ql <= vec[l] && vec[r + 1] <= qr){
41                cur->tag += x;
42                push(cur);
43                return;
44            }
45            update(cur->l, ql, qr, x);
46            update(cur->r, ql, qr, x);
47            push(cur);
48        }
49        void update(int l, int r, int x){
50            update(root, l, r, x);
51        }
52    };
53 template <typename T>
54 struct ScanLine{
55     struct Line{
56         T l, r, h, flag;
57         bool operator<(const Line &rhs){
58             return h < rhs.h;
59         }
60     };

```

```

61 vector<T> vec; vector<Line> line; SegmentTree<T> seg;
62 int n, cnt = 0;
63 ScanLine<int> _n: n(_n << 1) {
64     line.resize(n), vec.resize(n);
65 }
66 void add(int x1, int y1, int x2, int y2){
67     line[cnt] = {x1, x2, y1, 1}, line[cnt + 1] = {x1,
68         x2, y2, -1};
69     vec[cnt] = x1, vec[cnt + 1] = x2;
70     cnt += 2;
71 }
72 T run(){
73     T res = 0;
74     sort(line.begin(), line.end());
75     sort(vec.begin(), vec.end());
76     vec.erase(unique(vec.begin(), vec.end()), vec.end());
77     seg.init(vec);
78     for(int i = 0; i < n - 1; ++i){
79         seg.update(line[i].l, line[i].r, line[i].flag);
80         res += seg.root->len * (line[i + 1].h - line[i].h);
81     }
82     return res;
83 }

```

4.6 Polar sort

```

1 sort(pl.begin(), pl.end(), [&](Pt a, Pt b){
2     // a = a - o, b = b - o;
3     if(a.qua() == b.qua()) return (a ^ b) > 0;
4     return a.qua() < b.qua();
5 }); // degree 0 to 359
6 sort(pl.begin(), pl.end(), [&](Pt a, Pt b){
7     return (a - pt[i]).angle() < (b - pt[i]).angle();
8 }); // degree -180 to 180, slower

```

4.7 Li Chao Segment Tree *

```

1 struct LiChao_min{
2     struct line{
3         ll m, c;
4         line(ll _m=0, ll _c=0){ m=_m; c=_c; }
5         ll eval(ll x){ return m*x+c; } // overflow
6     };
7     struct node{
8         node *l, *r; line f;
9         node(line v){ f=v; l=r=NULL; }
10    };
11    typedef node* pnode;
12    pnode root; ll sz, ql, qr;
13    #define mid ((l+r)>>1)
14    void insert(line v, ll l, ll r, pnode &nd){
15        /* if(!(ql<=l&&r<=qr)){
16            if(!nd) nd=new node(line(0,INF));
17            if(ql<=mid) insert(v,l,mid,nd->l);
18            if(qr>mid) insert(v,mid+1,r,nd->r);
19            return;
20        } used for adding segment */
21        if(!nd){ nd=new node(v); return; }
22        ll trl=nd->f.eval(l), trr=nd->f.eval(r);
23        ll vl=v.eval(l), vr=v.eval(r);
24        if(trl<=vl&&trr<=vr) return;
25        if(trl>vl&&trr>vr) { nd->f=v; return; }
26        if(trl>vl) swap(nd->f,v);
27        if(nd->f.eval(mid)<v.eval(mid))
28            insert(v,mid+1,r,nd->r);
29        else swap(nd->f,v), insert(v,l,mid,nd->l);
30    }
31    ll query(ll x, ll l, ll r, pnode &nd){
32        if(!nd) return INF;
33        if(l==r) return nd->f.eval(x);
34        if(mid>=x)
35            return min(nd->f.eval(x), query(x,l,mid,nd->l));
36        return min(nd->f.eval(x), query(x,mid+1,r,nd->r));
37    }
38    /* -sz<=ll query_x<=sz */
39    void init(ll _sz){ sz=_sz+1; root=NULL; }
40    void add_line(ll m, ll c, ll l=-INF, ll r=INF){
41        line v(m,c); ql=l; qr=r; insert(v,-sz,sz,root);
42    }

```

```
43 ll query(ll x) { return query(x, -sz, sz, root); }
44 };
```

4.8 KD Tree *

```
1 struct KDTree{ // O(sqrtN + K)
2     struct Nd{
3         LL x[MXK], mn[MXK], mx[MXK];
4         int id, f;
5         Nd *l, *r;
6     } tree[MXN], *root;
7     int n, k;
8     LL dis(LL a, LL b){ return (a-b)*(a-b); }
9     LL dis(LL a[MXK], LL b[MXK]){
10         LL ret=0;
11         for(int i=0; i<k; i++) ret+=dis(a[i], b[i]);
12         return ret;
13     }
14     void init(vector<vector<LL>> &ip, int _n, int _k){
15         n=_n, k=_k;
16         for(int i=0; i<n; i++){
17             tree[i].id=i;
18             copy(ip[i].begin(), ip[i].end(), tree[i].x);
19         }
20         root=build(0, n-1, 0);
21     }
22     Nd* build(int l, int r, int d){
23         if(l>r) return NULL;
24         if(d==k) d=0;
25         int m=(l+r)>>1;
26         nth_element(tree+l, tree+m, tree+r+1, [&](const Nd &a,
27             const Nd &b){ return a.x[d]<b.x[d]; });
28         tree[m].f=d;
29         copy(tree[m].x, tree[m].x+k, tree[m].mn);
30         copy(tree[m].x, tree[m].x+k, tree[m].mx);
31         tree[m].l=build(l, m-1, d+1);
32         tree[m].r=build(m+1, r, d+1);
33         for(int i=0; i<k; i++){
34             tree[m].mn[i]=min(tree[m].mn[i], tree[m].l->mn[i]);
35             tree[m].mx[i]=max(tree[m].mx[i], tree[m].r->mx[i]);
36         }
37         tree[m].r=build(m+1, r, d+1);
38         if(tree[m].r){
39             for(int i=0; i<k; i++){
40                 tree[m].mn[i]=min(tree[m].mn[i], tree[m].r->mn[i]);
41                 tree[m].mx[i]=max(tree[m].mx[i], tree[m].r->mx[i]);
42             }
43         }
44         return tree+m;
45     }
46     LL pt[MXK], md;
47     int mID;
48     bool touch(Nd *r){
49         LL d=0;
50         for(int i=0; i<k; i++){
51             if(pt[i]<=r->mn[i]) d+=dis(pt[i], r->mn[i]);
52             else if(pt[i]>=r->mx[i]) d+=dis(pt[i], r->mx[i]);
53         }
54         return d<md;
55     }
56     void nearest(Nd *r){
57         if(!r || !touch(r)) return;
58         LL td=dis(r->x, pt);
59         if(td<md) md=td, mID=r->id;
60         nearest(pt[r->f]<r->x[r->f]?r->l:r->r);
61         nearest(pt[r->f]>r->x[r->f]?r->r:r->l);
62     }
63     pair<LL, int> query(vector<LL> &_pt, LL _md=1LL<<57){
64         mID=-1, md=_md;
65         copy(_pt.begin(), _pt.end(), pt);
66         nearest(root);
67         return {md, mID};
68     }
69 };
```

5 Tree

5.1 LCA

求樹上兩點的最低共同祖先

lca.init(n) \Rightarrow 0-base
 lca.addEdge(u, v) $\Rightarrow u \leftrightarrow v$
 lca.build(root, root) $\Rightarrow O(n \lg n)$
 lca.qlca(u, v) $\Rightarrow O(\lg n)$ u, v 的 LCA
 lca.qdis(u, v) $\Rightarrow O(\lg n)$ u, v 的距離 (可用倍增法帶權)
 lca.anc[u][i] \Rightarrow u 的第 2^i 個祖先

```
1 const int MXN = 5e5+5;
2 struct LCA{
3     int n, lgn, ti = 0;
4     int anc[MXN][24], in[MXN], out[MXN];
5     vector<int> g[MXN];
6     void init(int _n){
7         n = _n, lgn = __lg(n) + 5;
8         for(int i = 0; i < n; ++i) g[i].clear();
9     }
10    void addEdge(int u, int v){ g[u].PB(v), g[v].PB(u); }
11    void build(int u, int f){
12        in[u] = ti++;
13        int cur = f;
14        for(int i = 0; i < lgn; ++i)
15            anc[u][i] = cur, cur = anc[cur][i];
16        out[u] = ti++;
17        for(auto i : g[u]) if(i != f) build(i, u);
18    }
19    bool isanc(int a, int u){
20        return in[a] <= in[u] && out[a] >= out[u];
21    }
22    int qlca(int u, int v){
23        if(isanc(u, v)) return u;
24        if(isanc(v, u)) return v;
25        for(int i = lgn-1; i >= 0; --i)
26            if(!isanc(anc[u][i], v)) u = anc[u][i];
27        return anc[u][0];
28    }
29    int qdis(int u, int v){
30        int dis = !isanc(u, v) + !isanc(v, u);
31        for(int i = lgn-1; i >= 0; --i){
32            if(!isanc(anc[u][i], v)) u = anc[u][i], dis += 1<<i;
33            if(!isanc(anc[v][i], u)) v = anc[v][i], dis += 1<<i;
34        }
35        return dis;
36    }
37 };
```

6 Graph

6.1 HeavyLightDecomposition *

```
1 const int MXN = 200005;
2 template <typename T>
3 struct HeavyDecompose{ // 1-base, Need "ulimit -s unlimited"
4     SegmentTree<T> st;
5     vector<T> vec, tmp; // If tree point has weight
6     vector<int> e[MXN];
7     int sz[MXN], dep[MXN], fa[MXN], h[MXN];
8     int cnt = 0, r = 0, n = 0;
9     int root[MXN], id[MXN];
10    void addEdge(int a, int b){
11        e[a].emplace_back(b);
12        e[b].emplace_back(a);
13    }
14    HeavyDecompose(int n, int r): n(n), r(r){
15        vec.resize(n+1); tmp.resize(n+1);
16    }
17    void build(){
18        dfs1(r, 0, 0);
19        dfs2(r, r);
20        st.init(tmp); // SegmentTree Need Add Method
21    }
22    void dfs1(int x, int f, int d){
23        dep[x] = d, fa[x] = f, sz[x] = 1, h[x] = 0;
24        for(int i : e[x]){
25            if(i == f) continue;
26            dfs1(i, x, d+1);
27            sz[x] += sz[i];
28            if(sz[i] > sz[h[x]]) h[x] = i;
29        }
30    }
31    void dfs2(int x, int f){
32        id[x] = cnt++, root[x] = f, tmp[id[x]] = vec[x];
33        if(!h[x]) return;
34        dfs2(h[x], f);
35        for(int i : e[x]){
36            if(i == fa[x] || i == h[x]) continue;
37            dfs2(i, i);
38        }
39    }
40 };
```

```

39 }
40 void update(int x, int y, T v){
41     while(root[x] != root[y]){
42         if(dep[root[x]] < dep[root[y]]) swap(x, y);
43         st.update(id[root[x]], id[x], v);
44         x = fa[root[x]];
45     }
46     if(dep[x] > dep[y]) swap(x, y);
47     st.update(id[x], id[y], v);
48 }
49 T query(int x, int y){
50     T res = 0;
51     while(root[x] != root[y]){
52         if(dep[root[x]] < dep[root[y]]) swap(x, y);
53         res = (st.query(id[root[x]], id[x]) + res) % MOD;
54         x = fa[root[x]];
55     }
56     if(dep[x] > dep[y]) swap(x, y);
57     res = (st.query(id[x], id[y]) + res) % MOD;
58     return res;
59 }
60 void update(int x, T v){
61     st.update(id[x], id[x] + sz[x] - 1, v);
62 }
63 T query(int x){
64     return st.query(id[x], id[x] + sz[x] - 1);
65 }
66 int getLca(int x, int y){
67     while(root[x] != root[y]){
68         if(dep[root[x]] > dep[root[y]]) x = fa[root[x]];
69         else y = fa[root[y]];
70     }
71     return dep[x] > dep[y] ? y : x;
72 }
73 };

```

6.2 Centroid Decomposition *

```

1 struct CentroidDecomposition {
2     int n;
3     vector<vector<int>> G, out;
4     vector<int> sz, v;
5     CentroidDecomposition(int _n) : n(_n), G(_n), out(
6         _n), sz(_n), v(_n) {}
7     int dfs(int x, int par){
8         sz[x] = 1;
9         for (auto &i : G[x]) {
10             if(i == par || v[i]) continue;
11             sz[x] += dfs(i, x);
12         }
13         return sz[x];
14     }
15     int search_centroid(int x, int p, const int mid){
16         for (auto &i : G[x]) {
17             if(i == p || v[i]) continue;
18             if(sz[i] > mid) return search_centroid(i,
19                 x, mid);
20         }
21         return x;
22     }
23     void add_edge(int l, int r){
24         G[l].PB(r); G[r].PB(l);
25     }
26     int get(int x){
27         int centroid = search_centroid(x, -1, dfs(x,
28             -1)/2);
29         v[centroid] = true;
30         for (auto &i : G[centroid]) {
31             if(!v[i]) out[centroid].PB(get(i));
32         }
33         v[centroid] = false;
34         return centroid;
35     }
36 };

```

6.3 DominatorTree *

```

1 struct DominatorTree{ // O(N)
2     #define REP(i,s,e) for(int i=(s);i<=(e);i++)
3     #define REPD(i,s,e) for(int i=(s);i>=(e);i--)
4     int n, m, s;
5     vector<int> g[ MAXN ], pred[ MAXN ];
6     vector<int> cov[ MAXN ];

```

```

7     int dfn[ MAXN ], nfd[ MAXN ], ts;
8     int par[ MAXN ]; //idom[u] s到u的最後一個必經點
9     int sdom[ MAXN ], idom[ MAXN ];
10    int mom[ MAXN ], mn[ MAXN ];
11    inline bool cmp( int u, int v )
12    { return dfn[ u ] < dfn[ v ]; }
13    int eval( int u ){
14        if( mom[ u ] == u ) return u;
15        int res = eval( mom[ u ] );
16        if(cmp( sdom[ mn[ mom[ u ] ] ], sdom[ mn[ u ] ] ))
17            mn[ u ] = mn[ mom[ u ] ];
18        return mom[ u ] = res;
19    }
20    void init( int _n, int _m, int _s ){
21        ts = 0; n = _n; m = _m; s = _s;
22        REP( i, 1, n ) g[ i ].clear(), pred[ i ].clear();
23    }
24    void addEdge( int u, int v ){
25        g[ u ].push_back( v );
26        pred[ v ].push_back( u );
27    }
28    void dfs( int u ){
29        ts++;
30        dfn[ u ] = ts;
31        nfd[ ts ] = u;
32        for( int v : g[ u ] ) if( dfn[ v ] == 0 ){
33            par[ v ] = u;
34            dfs( v );
35        }
36    }
37    void build(){
38        REP( i, 1, n ){
39            dfn[ i ] = nfd[ i ] = 0;
40            cov[ i ].clear();
41            mom[ i ] = mn[ i ] = sdom[ i ] = i;
42        }
43        dfs( s );
44        REPD( i, n, 2 ){
45            int u = nfd[ i ];
46            if( u == 0 ) continue;
47            for( int v : pred[ u ] ) if( dfn[ v ] ){
48                eval( v );
49                if( cmp( sdom[ mn[ v ] ], sdom[ u ] ) )
50                    sdom[ u ] = sdom[ mn[ v ] ];
51            }
52            cov[ sdom[ u ] ].push_back( u );
53            mom[ u ] = par[ u ];
54            for( int w : cov[ par[ u ] ] ){
55                eval( w );
56                if( cmp( sdom[ mn[ w ] ], par[ u ] ) )
57                    idom[ w ] = mn[ w ];
58                else idom[ w ] = par[ u ];
59            }
60            cov[ par[ u ] ].clear();
61        }
62        REP( i, 2, n ){
63            int u = nfd[ i ];
64            if( u == 0 ) continue;
65            if( idom[ u ] != sdom[ u ] )
66                idom[ u ] = idom[ idom[ u ] ];
67        }
68    }
69 };

```

6.4 MaximumClique 最大團 *

```

1 #define N 111
2 struct MaxClique{ // 0-base
3     typedef bitset<N> Int;
4     Int linkto[N], v[N];
5     int n;
6     void init(int _n){
7         n = _n;
8         for(int i = 0 ; i < n ; i++){
9             linkto[i].reset(); v[i].reset();
10        }
11    }
12    void addEdge(int a, int b)
13    { v[a][b] = v[b][a] = 1; }
14    int popcount(const Int& val)
15    { return val.count(); }
16    int lowbit(const Int& val)
17    { return val._Find_first(); }
18    int ans, stk[N];
19    int id[N], di[N], deg[N];
20    Int cans;

```

```

20 void maxclique(int elem_num, Int candi){
21     if(elem_num > ans){
22         ans = elem_num; cans.reset();
23         for(int i = 0 ; i < elem_num ; i ++){
24             cans[id[stk[i]]] = 1;
25         }
26         int potential = elem_num + popcount(candi);
27         if(potential <= ans) return;
28         int pivot = lowbit(candi);
29         Int smaller_candi = candi & (~linkto[pivot]);
30         while(smaller_candi.count() && potential > ans){
31             int next = lowbit(smaller_candi);
32             candi[next] = !candi[next];
33             smaller_candi[next] = !smaller_candi[next];
34             potential --;
35             if(next == pivot || (smaller_candi & linkto[next
36                 ]).count()){
37                 stk[elem_num] = next;
38                 maxclique(elem_num + 1, candi & linkto[next]);
39             } }
40         int solve(){
41             for(int i = 0 ; i < n ; i ++){
42                 id[i] = i; deg[i] = v[i].count();
43             }
44             sort(id , id + n , [&](int id1, int id2){
45                 return deg[id1] > deg[id2]; });
46             for(int i = 0 ; i < n ; i ++){ di[id[i]] = i;
47             for(int i = 0 ; i < n ; i ++){
48                 for(int j = 0 ; j < n ; j ++){
49                     if(v[i][j]) linkto[di[i]][di[j]] = 1;
50                 }
51                 Int cand; cand.reset();
52                 for(int i = 0 ; i < n ; i ++){ cand[i] = 1;
53                 ans = 1;
54                 cans.reset(); cans[0] = 1;
55                 maxclique(0, cand);
56                 return ans;
57             } }
58     } }
59 } } solver;

```

6.5 MaximalClique 極大團 *

```

1 #define N 80
2 struct MaxClique{ // 0-base
3     typedef bitset<N> Int;
4     Int lnk[N] , v[N];
5     int n;
6     void init(int _n){
7         n = _n;
8         for(int i = 0 ; i < n ; i ++){
9             lnk[i].reset(); v[i].reset();
10        } }
11     void addEdge(int a , int b)
12     { v[a][b] = v[b][a] = 1; }
13     int ans , stk[N], id[N] , di[N] , deg[N];
14     Int cans;
15     void dfs(int elem_num, Int candi, Int ex){
16         if(candi.none() && ex.none()){
17             cans.reset();
18             for(int i = 0 ; i < elem_num ; i ++){
19                 cans[id[stk[i]]] = 1;
20                 ans = elem_num; // cans is a maximal clique
21                 return;
22             }
23             int pivot = (candilex)._Find_first();
24             Int smaller_candi = candi & (~lnk[pivot]);
25             while(smaller_candi.count()){
26                 int nxt = smaller_candi._Find_first();
27                 candi[nxt] = smaller_candi[nxt] = 0;
28                 ex[nxt] = 1;
29                 stk[elem_num] = nxt;
30                 dfs(elem_num+1, candi & lnk[nxt], ex & lnk[nxt]);
31             } }
32     int solve(){
33         for(int i = 0 ; i < n ; i ++){
34             id[i] = i; deg[i] = v[i].count();
35         }
36         sort(id , id + n , [&](int id1, int id2){
37             return deg[id1] > deg[id2]; });
38         for(int i = 0 ; i < n ; i ++){ di[id[i]] = i;
39         for(int i = 0 ; i < n ; i ++){
40             for(int j = 0 ; j < n ; j ++){
41                 if(v[i][j]) lnk[di[i]][di[j]] = 1;
42             }
43             ans = 1; cans.reset(); cans[0] = 1;

```

```

43     dfs(0, Int(string(n, '1')), 0);
44     return ans;
45 } } solver;

```

6.6 Minimum Steiner Tree

```

1 const int MXNN = 105;
2 const int MXNK = 10 + 1;
3 template<typename T>
4 struct SteinerTree{ // 有重要點的MST權重和, 1-base
5     int n, k;
6     T inf;
7     vector<vector<T>> dp;
8     vector<vector<pair<int, T>>> edge;
9     priority_queue<pair<T, int>, vector<pair<T, int>>,
10         greater<pair<T, int>>> pq;
11     vector<int> vis;
12     void init(int _n, int _k, T _inf){
13         // n points, 1~k 是重要點, type T的INF
14         n = _n, k = _k, inf = _inf;
15         dp.assign(n + 1, vector<T>(1 << k, inf));
16         edge.resize(n + 1); }
17     void addEdge(int u, int v, T w){ // u <-(w)-> v
18         edge[u].emplace_back(v, w);
19         edge[v].emplace_back(u, w); }
20     void dijkstra(int s, int cnt){
21         vis.assign(n + 1, 0);
22         while(!pq.empty()){
23             auto [d, u] = pq.top(); pq.pop();
24             if(vis[u]) continue;
25             vis[u] = 1;
26             for(auto &[v, w] : edge[u]){
27                 // if(cnt > 1 && v <= k) continue;
28                 if(dp[v][s] > dp[u][s] + w){
29                     dp[v][s] = dp[u][s] + w;
30                     pq.push({dp[v][s], v}); } } }
31     T run(){ // return total cost 0(nk*2^k + n^2*2^k)
32         for(int i = 1; i <= k; ++i) dp[i][1 << (i - 1)] = 0;
33         for(int s = 1; s < (1 << k); ++s){
34             int cnt = 0, tmp = s;
35             while(tmp) cnt += (tmp & 1), tmp >>= 1;
36             for(int i = k + 1; i <= n; ++i){
37                 for(int sb = s & (s-1); sb; sb = s & (sb-1))
38                     dp[i][s] =
39                     min(dp[i][s], dp[i][sb] + dp[i][s ^ sb]);
40                 for(int i = (cnt > 1 ? k + 1 : 1); i <= n; ++i){
41                     if(dp[i][s] != inf) pq.push({dp[i][s], i});
42                 }
43                 dijkstra(s, cnt); }
44             T res = inf;
45             for(int i = 1; i <= n; ++i){
46                 res = min(res, dp[i][(1 << k) - 1]);
47             }
48             return res; } }

```

6.7 BCC based on vertex *

```

1 struct BccVertex {
2     int n, nScc, step, dfn[MXN], low[MXN];
3     vector<int> E[MXN], sccv[MXN];
4     int top, stk[MXN];
5     void init(int _n) {
6         n = _n; nScc = step = 0;
7         for (int i=0; i<n; i++) E[i].clear();
8     }
9     void addEdge(int u, int v)
10     { E[u].PB(v); E[v].PB(u); }
11     void DFS(int u, int f) {
12         dfn[u] = low[u] = step++;
13         stk[top++] = u;
14         for (auto v:E[u]) {
15             if (v == f) continue;
16             if (dfn[v] == -1) {
17                 DFS(v, u);
18                 low[u] = min(low[u], low[v]);
19                 if (low[v] >= dfn[u]) {
20                     int z;
21                     sccv[nScc].clear();
22                     do {
23                         z = stk[--top];
24                         sccv[nScc].PB(z);
25                     } while (z != v);
26                     sccv[nScc++].PB(u);
27                 }

```



```

28     }else
29         low[u] = min(low[u],dfn[v]);
30     } }
31     vector<vector<int>> solve() {
32         vector<vector<int>> res;
33         for (int i=0; i<n; i++)
34             dfn[i] = low[i] = -1;
35         for (int i=0; i<n; i++)
36             if (dfn[i] == -1) {
37                 top = 0;
38                 DFS(i,i);
39             }
40         REP(i,nScc) res.PB(sccv[i]);
41         return res;
42     }
43 }graph;

```

6.8 Strongly Connected Component *

```

1 struct Scc{
2     int n, nScc, vst[MXN], bln[MXN];
3     vector<int> E[MXN], rE[MXN], vec;
4     void init(int _n){
5         n = _n;
6         for (int i=0; i<MXN; i++)
7             E[i].clear(), rE[i].clear();
8     }
9     void addEdge(int u, int v){
10         E[u].PB(v); rE[v].PB(u);
11     }
12     void DFS(int u){
13         vst[u]=1;
14         for (auto v : E[u]) if (!vst[v]) DFS(v);
15         vec.PB(u);
16     }
17     void rDFS(int u){
18         vst[u] = 1; bln[u] = nScc;
19         for (auto v : rE[u]) if (!vst[v]) rDFS(v);
20     }
21     void solve(){
22         nScc = 0;
23         vec.clear();
24         FZ(vst);
25         for (int i=0; i<n; i++)
26             if (!vst[i]) DFS(i);
27         reverse(vec.begin(),vec.end());
28         FZ(vst);
29         for (auto v : vec)
30             if (!vst[v]){
31                 rDFS(v); nScc++;
32             }
33     }
34 };

```

6.9 差分約束 *

約束條件 $V_j - V_i \leq W$ 建邊 $V_i \rightarrow V_j$ 權重為 W → bellman-ford or spfa

7 String

7.1 PalTree *

```

1 // len[s]是對應的回文長度
2 // num[s]是有幾個回文後綴
3 // cnt[s]是這個回文字串在整個字串中的出現次數
4 // fail[s]是他長度次長的回文後綴，aba的fail是a
5 const int MXN = 1000010;
6 struct PalT{
7     int nxt[MXN][26], fail[MXN], len[MXN];
8     int tot, lst, n, state[MXN], cnt[MXN], num[MXN];
9     int diff[MXN], sfail[MXN], fac[MXN], dp[MXN];
10    char s[MXN]={'-1'};
11    int newNode(int l, int f){
12        len[tot]=l, fail[tot]=f, cnt[tot]=num[tot]=0;
13        memset(nxt[tot], 0, sizeof(nxt[tot]));
14        diff[tot]=(l>0?l-len[f]:0);
15        sfail[tot]=(l>0&&diff[tot]==diff[f]?sfail[f]:f);
16        return tot++;
17    }
18    int getfail(int x){
19        while(s[n-len[x]-1]!=s[n]) x=fail[x];
20        return x;
21    }

```

```

22    int getmin(int v){
23        dp[v]=fac[n-len[sfail[v]]-diff[v]];
24        if(diff[v]==diff[fail[v]])
25            dp[v]=min(dp[v], dp[fail[v]]);
26        return dp[v]+1;
27    }
28    int push(){
29        int c=s[n]-'a', np=getfail(lst);
30        if(!(lst=nxt[np][c])){
31            lst=newNode(len[np]+2, nxt[getfail(fail[np])][c]);
32            nxt[np][c]=lst; num[lst]=num[fail[lst]]+1;
33        }
34        fac[n]=n;
35        for(int v=lst; len[v]>0; v=sfail[v])
36            fac[n]=min(fac[n], getmin(v));
37        return ++cnt[lst], lst;
38    }
39    void init(const char *_s){
40        tot=lst=n=0;
41        newNode(0,1), newNode(-1,1);
42        for(; _s[n];) s[n+1]=_s[n], ++n, state[n-1]=push();
43        for(int i=tot-1; i>1; i--) cnt[fail[i]]+=cnt[i];
44    }
45 }palt;

```

7.2 SuffixArray *

```

1 const int MAX = 1020304;
2 int ct[MAX], he[MAX], rk[MAX];
3 int sa[MAX], tsa[MAX], tp[MAX][2];
4 void suffix_array(char *ip){
5     int len = strlen(ip);
6     int alp = 256;
7     memset(ct, 0, sizeof(ct));
8     for(int i=0; i<len; i++) ct[ip[i]+1]++;
9     for(int i=1; i<alp; i++) ct[i]+=ct[i-1];
10    for(int i=0; i<len; i++) rk[i]=ct[ip[i]];
11    for(int i=1; i<len; i*=2){
12        for(int j=0; j<len; j++){
13            if(j+i>len) tp[j][1]=0;
14            else tp[j][1]=rk[j+i]+1;
15            tp[j][0]=rk[j];
16        }
17        memset(ct, 0, sizeof(ct));
18        for(int j=0; j<len; j++) ct[tp[j][1]+1]++;
19        for(int j=1; j<len+2; j++) ct[j]+=ct[j-1];
20        for(int j=0; j<len; j++) sa[ct[tp[j][1]]++] = j;
21        memset(ct, 0, sizeof(ct));
22        for(int j=0; j<len; j++) ct[tp[j][0]+1]++;
23        for(int j=1; j<len+1; j++) ct[j]+=ct[j-1];
24        for(int j=0; j<len; j++)
25            sa[ct[tp[tsa[j]][0]]++] = tsa[j];
26        rk[sa[0]]=0;
27        for(int j=1; j<len; j++){
28            if( tp[sa[j]][0] == tp[sa[j-1]][0] &&
29               tp[sa[j]][1] == tp[sa[j-1]][1] )
30                rk[sa[j]] = rk[sa[j-1]];
31            else
32                rk[sa[j]] = j;
33        }
34    }
35    for(int i=0, h=0; i<len; i++){
36        if(rk[i]==0) h=0;
37        else{
38            int j=sa[rk[i]-1];
39            h=max(0, h-1);
40            for(; ip[i+h]==ip[j+h]; h++);
41        }
42        he[rk[i]]=h;
43    }
44 }

```

7.3 MinRoation *

```

1 //rotate(begin(s),begin(s)+minRotation(s),end(s))
2 int minRotation(string s) {
3     int a = 0, N = s.size(); s += s;
4     rep(b,0,N) rep(k,0,N) {
5         if(a+k == b || s[a+k] < s[b+k])
6             {b += max(0, k-1); break;}
7         if(s[a+k] > s[b+k]) {a = b; break;}
8     } return a;

```

9|}

7.4 RollingHash

```

1 struct RollingHash {
2     const int p1 = 44129; // 65537, 40961, 90001, 971651
3     vector<ll> pre;
4     void init(string s) {
5         pre.resize(s.size() + 1); pre[0] = 0;
6         for (int i = 0; i < (int)s.size(); i++)
7             pre[i + 1] = (pre[i] * p1 + s[i]) % MOD;
8     }
9     ll query(int l, int r) {return (pre[r + 1] - pre[l] *
10         fpow(p1, r - l + 1));}

```

7.5 KMP

在 k 結尾的情況下，這個子字串可以由開頭長度為 (k + 1) - (fail[k] + 1) 的部分重複出現來表達
 fail[k] + 1 為次長相同前綴後綴長度
 如果我們不只想求最多，那可能的長度由大到小會是
 fail[k]+1, fail[fail[k]+1], fail[fail[fail[k]]]+1...
 直到有值為 -1 為止

```

1 const int MXN = 2e7 + 5;
2 int fail[MXN]; vector<int> mi;
3 void kmp(string &t, string &p){ // O(n), 0-base
4     // pattern match in target, idx store in mi
5     mi.clear();
6     if (p.size() > t.size()) return;
7     for (int i = 1, j = fail[0] = -1; i < p.size(); ++i){
8         while (j >= 0 && p[j + 1] != p[i]) j = fail[j];
9         if (p[j + 1] == p[i]) j++;
10        fail[i] = j; }
11    for (int i = 0, j = -1; i < t.size(); ++i){
12        while (j >= 0 && p[j + 1] != t[i]) j = fail[j];
13        if (p[j + 1] == t[i]) j++;
14        if (j == p.size() - 1)
15            j = fail[j], mi.pb(i - p.size() + 1); } }

```

7.6 LCS & LIS

LIS: 最長遞增子序列
 LCS: 最長共同子字串 (利用 LIS), 但常數可能較大

```

1 int lis(vector<ll> &v){ // O(nlgn)
2     vector<ll> p;
3     for(int i = 0; i < v.size(); ++i)
4         if(p.empty() || p.back() < v[i]) p.pb(v[i]);
5         else *lower_bound(p.begin(), p.end(), v[i]) = v[i];
6     return p.size(); }
7
8 int lcs(string s, string t){ // O(nlgn)
9     map<char, vector<int>> > mp;
10    for(int i = 0; i < s.size(); ++i) mp[s[i]].pb(i);
11    vector<int> p;
12    for(int i = 0; i < t.size(); ++i){
13        auto &v = mp[t[i]];
14        for(int j = v.size() - 1; j >= 0; --j)
15            if(p.empty() || p.back() < v[j]) p.pb(v[j]);
16            else *lower_bound(p.begin(), p.end(), v[j])=v[j];}
17    return p.size(); }

```

7.7 Aho-Corasick *

```

1 struct ACautomata{
2     struct Node{
3         int cnt,i;
4         Node *go[26], *fail, *dic;
5         Node (){
6             cnt = 0; fail = 0; dic = 0; i = 0;
7             memset(go,0,sizeof(go));
8         }
9     }pool[1048576],*root;
10    int nMem,n_pattern;
11    Node* new_Node(){
12        pool[nMem] = Node();
13        return &pool[nMem++];
14    }
15    void init() {
16        nMem=0;root=new_Node();n_pattern=0;
17        add("");
18    }
19    void add(const string &str) { insert(root,str,0); }

```

```

20 void insert(Node *cur, const string &str, int pos){
21     for(int i=pos;i<str.size();i++){
22         if(!cur->go[str[i]-'a'])
23             cur->go[str[i]-'a'] = new_Node();
24         cur=cur->go[str[i]-'a'];
25     }
26     cur->cnt++; cur->i=n_pattern++;
27 }
28 void make_fail(){
29     queue<Node*> que;
30     que.push(root);
31     while (!que.empty()){
32         Node* fr=que.front(); que.pop();
33         for (int i=0; i<26; i++){
34             if (fr->go[i]){
35                 Node *ptr = fr->fail;
36                 while (ptr && !ptr->go[i]) ptr = ptr->fail;
37                 fr->go[i]->fail=ptr=(ptr?ptr->go[i]:root);
38                 fr->go[i]->dic=(ptr->cnt?ptr:ptr->dic);
39                 que.push(fr->go[i]);
40             } } } }
41 void query(string s){
42     Node *cur=root;
43     for(int i=0;i<(int)s.size();i++){
44         while(cur&&!cur->go[s[i]-'a']) cur=cur->fail;
45         cur=(cur?cur->go[s[i]-'a']:root);
46         if(cur->i>=0) ans[cur->i]++;
47         for(Node *tmp=cur->dic;tmp;tmp=tmp->dic)
48             ans[tmp->i]++;
49     } // ans[i] : number of occurrence of pattern i
50 }AC;

```

7.8 Z Value *

```

1 int z[MAXN];
2 void Z_value(const string& s) { //z[i] = lcp(s[1...],s[
3     i...])
4     int i, j, left, right, len = s.size();
5     left=right=0; z[0]=len;
6     for(i=1;i<len;i++) {
7         j=max(min(z[i-left],right-i),0);
8         for(;i+j<len&&s[i+j]==s[j];j++);
9         z[i]=j;
10        if(i+z[i]>right) {
11            right=i+z[i];
12        } } }

```

7.9 manacher *

```

1 struct Manacher {
2     char str[MAXN]; int p[MAXN], len = 0;
3     void init(string s) {
4         MEM(p, 0);
5         str[len++] = '$', str[len++] = '#';
6         int sz = s.size();
7         for(int i = 0; i < sz; ++i)
8             str[len++] = s[i], str[len++] = '#';
9         str[len] = '*';
10        int mx = 0, id = 0;
11        for(int i = 1; i < len; ++i) {
12            p[i] = mx > i ? min(p[id<1] - i, mx - i) : 1;
13            while(str[i + p[i]] == str[i - p[i]]) p[i]++;
14            if(i + p[i] > mx) {
15                mx = i + p[i];
16                id = i;}}
17    int query(int l, int r) {
18        int ans = 0;
19        l = 2 * l + 2, r = 2 * r + 2;
20        for(int i = l; i < r; i++)
21            ans = max(ans, p[i]);
22        return ans - 1;};

```

8 Data Structure

8.1 Treap

Treap *th = 0
 th = merge(th, new Treap(val)) ⇒ 新增元素到 th
 th = merge(merge(tl, tm), tr) ⇒ 合併 tl,tm,tr 到 th
 split(th, k, tl, tr) ⇒ 分割 th, tl 的元素 ≤ k (失去 BST 性質後不能用)
 kth(th, k, tl, tr) ⇒ 分割 th, gsz(tl) ≤ k (< when gsz(th) < k)
 gsz ⇒ get size | gsum ⇒ get sum | th->rev ^= 1 ⇒ 反轉 th

帶懶標版本，並示範 sum/rev 如何 pull/push
注意 Treap 複雜度好但常數大，動作能用其他方法就用，並做 io 等優化

```

1 struct Treap{
2     Treap *l, *r;
3     int pri, sz, rev;
4     ll val, sum;
5     Treap(int _val): l(0), r(0),
6         pri(rand()), sz(1), rev(0),
7         val(_val), sum(_val){} };
8
9 ll gsz(Treap *x){ return x ? x->sz : 0; }
10 ll gsum(Treap *x){ return x ? x->sum : 0; }
11
12 Treap* pull(Treap *x){
13     x->sz = gsz(x->l) + gsz(x->r) + 1;
14     x->sum = x->val + gsum(x->l) + gsum(x->r);
15     return x; }
16 void push(Treap *x){
17     if(x->rev){
18         swap(x->l, x->r);
19         if(x->l) x->l->rev ^= 1;
20         if(x->r) x->r->rev ^= 1;
21         x->rev = 0; } }
22
23 Treap* merge(Treap* a, Treap* b){
24     if(!a || !b) return a ? a : b;
25     push(a), push(b);
26     if(a->pri > b->pri){
27         a->r = merge(a->r, b);
28         return pull(a); }
29     else{
30         b->l = merge(a, b->l);
31         return pull(b); } }
32
33 void split(Treap *x, int k, Treap *&a, Treap *&b){
34     if(!x) a = b = 0;
35     else{
36         push(x);
37         if(x->val <= k) a = x, split(x->r, k, a->r, b);
38         else b = x, split(x->l, k, a, b->l);
39         pull(x); } }
40
41 void kth(Treap *x, int k, Treap *&a, Treap *&b){
42     if(!x) a = b = 0;
43     else{
44         push(x);
45         if(gsz(x->l) < k)
46             a = x, kth(x->r, k - gsz(x->l) - 1, a->r, b);
47         else b = x, kth(x->l, k, a, b->l);
48         pull(x); } }

```

8.2 BIT

bit.init(n) \Rightarrow 1-base
bit.add(i, x) \Rightarrow add a[i] by x
bit.sum(i) \Rightarrow get sum of [1, i]
bit.kth(k) \Rightarrow get kth small number (by using bit.add(num, 1))
維護差分可以變成區間加值，單點求值

```

1 const int MXN = 1e6+5;
2 struct BIT{
3     ll n, a[MXN];
4     void init(int _n){ n = _n; MEM(a, 0); }
5     void add(int i, int x){
6         for(; i <= n; i += i & -i) a[i] += x; }
7     int sum(int i){
8         int ret = 0;
9         for(; i > 0; i -= i & -i) ret += a[i];
10        return ret; }
11    int kth(int k){
12        int res = 0;
13        for(int i = 1 << __lg(n); i > 0; i >>= 1)
14            if(res + i <= n && a[res+i] < k) k -= a[res+i];
15        return res; } }

```

8.3 二維偏序 *

```

1 struct Node {
2     int x, y, id;
3     bool operator < (const Node &b) const {
4         if(x == b.x) return y < b.y;
5         return x < b.x; } }
6 struct TDPO {

```

```

7     vector<Node> p; vector<ll> ans;
8     void init(vector<Node> _p) {
9         p = _p; bit.init(MXN);
10        ans.resize(p.size());
11        sort(p.begin(), p.end());
12    void bulid() {
13        int sz = p.size();
14        for(int i = 0; i < sz; ++i) {
15            ans[p[i].id] = bit.sum(p[i].y - 1);
16            bit.add(p[i].y, 1); } } }

```

8.4 持久化 *

```

1 struct Seg {
2     // Persistent Segment Tree, single point modify,
3     // range query sum
4     // 0-indexed, [l, r)
5     static Seg mem[M], *pt;
6     int l, r, m, val;
7     Seg* ch[2];
8     Seg() = default;
9     Seg(int _l, int _r) : l(_l), r(_r), m(l + r >> 1),
10        val(0) {
11         if(r - l > 1) {
12             ch[0] = new (pt++) Seg(l, m);
13             ch[1] = new (pt++) Seg(m, r);
14         }
15     }
16     void pull() { val = ch[0]->val + ch[1]->val; }
17     Seg* modify(int p, int v) {
18         Seg *now = new (pt++) Seg(*this);
19         if(r - l == 1) {
20             now->val = v;
21         } else {
22             now->ch[p >= m] = ch[p >= m]->modify(p, v);
23             now->pull();
24         }
25         return now;
26     }
27     int query(int a, int b) {
28         if(a <= l && r <= b) return val;
29         int ans = 0;
30         if(a < m) ans += ch[0]->query(a, b);
31         if(m < b) ans += ch[1]->query(a, b);
32         return ans;
33     }
34     Seg::mem[M], *Seg::pt = mem;
35     // Init Tree
36     Seg *root = new (Seg::pt++) Seg(0, n);

```

8.5 2D 線段樹

```

1 // 2D range add, range sum in log^2
2 struct seg {
3     int l, r;
4     ll sum, lz;
5     seg *ch[2];
6     seg(int _l, int _r) : l(_l), r(_r), sum(0), lz(0) {}
7     void push() {
8         if(lz) ch[0]->add(l, r, lz), ch[1]->modify(l, r,
9             lz), lz = 0;
10    }
11    void pull() { sum = ch[0]->sum + ch[1]->sum; }
12    void add(int _l, int _r, ll d) {
13        if(_l <= l && r <= _r) {
14            sum += d * (r - l);
15            lz += d;
16            return;
17        }
18        if(!ch[0]) ch[0] = new seg(l, l + r >> 1), ch[1] =
19            new seg(l + r >> 1, r);
20        push();
21        if(_l < l + r >> 1) ch[0]->add(_l, _r, d);
22        if(l + r >> 1 < _r) ch[1]->add(_l, _r, d);
23        pull();
24    }
25    ll qsum(int _l, int _r) {
26        if(_l <= l && r <= _r) return sum;
27        if(!ch[0]) return lz * (min(r, _r) - max(l, _l));
28        push();
29        ll res = 0;
30        if(_l < l + r >> 1) res += ch[0]->qsum(_l, _r);

```

```

29     if (l + r >> 1 < _r) res += ch[1]->qsum(_l, _r);
30     return res;
31 }
32 };
33 struct seg2 {
34     int l, r;
35     seg v, lz;
36     seg2 *ch[2]{};
37     seg2(int _l, int _r) : l(_l), r(_r), v(0, N), lz(0, N)
38     {
39         if (l < r - 1) ch[0] = new seg2(l, l + r >> 1), ch
40             [1] = new seg2(l + r >> 1, r);
41     }
42     void add(int _l, int _r, int _l2, int _r2, ll d) {
43         v.add(_l2, _r2, d * (min(r, _r) - max(l, _l)));
44         if (_l <= l && r <= _r) {
45             lz.add(_l2, _r2, d);
46             return;
47         }
48         if (_l < l + r >> 1) ch[0]->add(_l, _r, _l2, _r2, d
49             );
50         if (l + r >> 1 < _r) ch[1]->add(_l, _r, _l2, _r2, d
51             );
52     }
53     ll qsum(int _l, int _r, int _l2, int _r2) {
54         ll res = v.qsum(_l2, _r2);
55         if (_l <= l && r <= _r) return res;
56         res += lz.qsum(_l2, _r2) * (min(r, _r) - max(l, _l)
57             );
58         if (_l < l + r >> 1) res += ch[0]->query(_l, _r,
59             _l2, _r2);
60         if (l + r >> 1 < _r) res += ch[1]->query(_l, _r,
61             _l2, _r2);
62         return res;
63     }
64 };

```

8.6 Black Magic

```

1 #include <bits/extc++.h>
2 using namespace __gnu_pbds;
3 typedef tree<int, null_type, less<int>, rb_tree_tag,
4     tree_order_statistics_node_update> set_t;
5 #include <ext/pb_ds/assoc_container.hpp>
6 typedef cc_hash_table<int, int> umap_t;
7 typedef priority_queue<int> heap;
8 #include <ext/rope>
9 using namespace __gnu_cxx;
10 int main() {
11     // Insert some entries into s.
12     set_t s; s.insert(12); s.insert(505);
13     // The order of the keys should be: 12, 505.
14     assert(*s.find_by_order(0) == 12);
15     assert(*s.find_by_order(3) == 505);
16     // The order of the keys should be: 12, 505.
17     assert(s.order_of_key(12) == 0);
18     assert(s.order_of_key(505) == 1);
19     // Erase an entry.
20     s.erase(12);
21     // The order of the keys should be: 505.
22     assert(*s.find_by_order(0) == 505);
23     // The order of the keys should be: 505.
24     assert(s.order_of_key(505) == 0);
25     heap h1, h2; h1.join(h2);
26     rope<char> r[2];
27     r[1] = r[0]; // persistenet
28     string t = "abc";
29     r[1].insert(0, t.c_str());
30     r[1].erase(1, 1);
31     cout << r[1].substr(0, 2);
32 }

```

9 Others

9.1 SOS dp *

```

1 for(int i = 0; i < (1<<N); ++i)
2     F[i] = A[i];
3 for(int i = 0; i < N; ++i) for(int mask = 0; mask < (1<<
4     N); ++mask){

```

```

4     if(mask & (1<<i))
5         F[mask] += F[mask^(1<<i)];
6 }

```

9.2 MO's Algorithm *

```

1 struct MoSolver {
2     struct query {
3         int l, r, id;
4         bool operator < (const query &o) {
5             if (l / C == o.l / C) return (l / C) & 1 ? r > o.
6                 r : r < o.r;
7             return l / C < o.l / C;
8         }
9     };
10     int cur_ans;
11     vector<int> ans;
12     void add(int x) {
13         // do something
14     }
15     void sub(int x) {
16         // do something
17     }
18     vector<query> Q;
19     void add_query(int l, int r, int id) {
20         // [l, r)
21         Q.push_back({l, r, id});
22         ans.push_back(0);
23     }
24     void run() {
25         sort(Q.begin(), Q.end());
26         int pl = 0, pr = 0;
27         cur_ans = 0;
28         for (query &i : Q) {
29             while (pl > i.l)
30                 add(a[--pl]);
31             while (pr < i.r)
32                 add(a[pr++]);
33             while (pl < i.l)
34                 sub(a[pl++]);
35             while (pr > i.r)
36                 sub(a[--pr]);
37             ans[i.id] = cur;
38         }
39     };

```




