NAME

tr – translate or delete characters

SYNOPSIS

tr [OPTION]... SET1 [SET2]

DESCRIPTION

Translate, squeeze, and/or delete characters from standard input, writing to standard output.

-c, -C, --complement

use the complement of SET1

-d, --delete

delete characters in SET1, do not translate

-s, --squeeze-repeats

replace each sequence of a repeated character that is listed in the last specified SET, with a single occurrence of that character

-t, --truncate-set1

first truncate SET1 to length of SET2

--help display this help and exit

--version

output version information and exit

SETs are specified as strings of characters. Most represent themselves. Interpreted sequences are:

NNN character with octal value NNN (1 to 3 octal digits)

\\ backslash

\a audible BEL

\b backspace

\f form feed

\n new line

\r return

\t horizontal tab

\v vertical tab

CHAR1-CHAR2

all characters from CHAR1 to CHAR2 in ascending order

[CHAR*]

in SET2, copies of CHAR until length of SET1

[CHAR*REPEAT]

REPEAT copies of CHAR, REPEAT octal if starting with 0

[:alnum:]

all letters and digits

[:alpha:]

all letters

[:blank:]

all horizontal whitespace

[:cntrl:] all control characters

[:digit:] all digits

```
[:graph:]
         all printable characters, not including space
[:lower:]
         all lower case letters
[:print:]
         all printable characters, including space
[:punct:]
         all punctuation characters
[:space:]
         all horizontal or vertical whitespace
[:upper:]
         all upper case letters
[:xdigit:]
         all hexadecimal digits
[=CHAR=]
         all characters which are equivalent to CHAR
```

Translation occurs if **-d** is not given and both SET1 and SET2 appear. **-t** may be used only when translating. SET2 is extended to length of SET1 by repeating its last character as necessary. Excess characters of SET2 are ignored. Only [:lower:] and [:upper:] are guaranteed to expand in ascending order; used in SET2 while translating, they may only be used in pairs to specify case conversion. **-s** uses the last specified SET, and occurs after translation or deletion.

AUTHOR

Written by Jim Meyering.

REPORTING BUGS

GNU coreutils online help: http://www.gnu.org/software/coreutils/> Report tr translation bugs to http://translationproject.org/team/>

COPYRIGHT

Copyright © 2017 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later http://gnu.org/licenses/gpl.html.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: http://www.gnu.org/software/coreutils/tr or available locally via: info '(coreutils) tr invocation'