

### RA Document

RA Details	
RA Technical End Date/Time	23-07-2020 13:00:00
RA Opening Date/Time	23-07-2020 13:30:00
RA Life Cycle (From Publish Date)	90 (Days)
RA Offer Validity (From End Date)	45 (Days)
Ministry/State Name	Ministry Of Defence
Department Name	Department Of Defence
Organisation Name	Indian Army
Office Name	*****
Total Quantity	30
Item Category	Plastic Moulded Chair
MSE Exemption for Years of Experience and Turnover	No
Startup Exemption for Years of Experience and Turnover	No
Inspection Required	No

### EMD Detail

Required	No
----------	----

### ePBG Detail

Required	No
----------	----

### Splitting

RA splitting not applied.

### Plastic Moulded Chair ( 30 pieces )

#### Technical Specifications

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
---------------	--------------------	--------	----------------------------------

GENERIC	<b>TYPE OF CHAIR</b>	PLASTIC MOULDED SEAT CUM BACK WITH SUPPORT STRUCTURE	PLASTIC MOULDED SEAT CUM BACK WITH SUPPORT STRUCTURE
	<b>Seat cushion</b>	With	With
	<b>Back Cushion</b>	With	With
	Conformity to Indian Standard IS 13713-Latest	Yes	*
	<b>Plastic Material</b>	POLYPROPELENE	POLYPROPELENE
	<b>ARMS</b>	With arms	With arms
DIMENSION & WEIGHT	<b>Seat Width in mm (+/- 5 mm)</b>	425	425
	<b>Seat Depth in mm (+/- 5 mm)</b>	380	380
	<b>Chair Height in mm (+/- 10 mm)</b>	870	870
	Chair Dimensions	Conforming To IS 3663 (Latest)	*
	Weight of Chair (IN Grams)	6000	*
	<b>Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)</b>	50	50
	<b>Density of PU Foam in KG per CuM</b>	50	50
PERFORMANCE	<b>Thickness of Polyurethane Foam Used in Backrest in mm (+/- 2 mm)</b>	50	50
	Stability of the Chair	Conforming To IS 5416 (Part 2)	*
	Strength of the Chair	Conforming To IS 5416 (Part 1)	*
	Maximum Ash Content is Not more than 1% in Conformity test as per Annex D of IS: 14887 (Latest)	Complied that Ash content is less than 1%	*
Support / Under Structure	UV Resistance Test - % of Tensile strength retention after 192 hours exposure as per ASTM D2562 -99 Table 1- Cycle Number 2 is more than 50 %	Complied Minimum 50% tensile strength retained after exposure as per test	*
	<b>Support / Under Structure</b>	Sigle Moulded Piece No Support Structure	Sigle Moulded Piece No Support Structure

	<b>Support Structure Finishing</b>	Single Moulded Piece No Support Structure	Single Moulded Piece No Support Structure
CERTIFICATION	Test reports to be furnished to buyer on demand	YES	*
MISC	Colour	Black	*
WARANTEE PERIOD	<b>WARANTEE PERIOD IN NUMBER OF YEARS</b>	1	1

\* Specifications highlighted in bold are the Golden Parameters.

\* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.

### Additional Specification Documents

#### Consignee/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days	
1	*****	*****BARDHAMAN	30	15	

### Bid Specific Additional Terms and Conditions

1. IMPORTED PRODUCTS: In case of imported products, OEM or Authorized Seller of OEM should have a registered office in India to provide after sales service support in India. The certificate to this effect should be submitted.
2. Scope of supply (Bid price to include all cost components) : Supply Installation Testing Commissioning of Goods and Training of operators and providing Statutory Clearances required (if any)

[This RA is also governed by the General Terms and Conditions](#)

**---Thank You---**