

Bid Number: GEM/2020/B/713234

Dated: 16-07-2020

### **Bid Document**

Dia Document					
Bid Details					
Bid End Date/Time	27-07-2020 15:00:00				
Bid Opening Date/Time	27-07-2020 15:30:00				
Bid Life Cycle (From Publish Date)	90 (Days)				
Bid Offer Validity (From End Date)	30 (Days)				
Ministry/State Name	Uttar Pradesh				
Department Name	Urban Development Department Uttar Pradesh				
Organisation Name	N/a				
Office Name	Nagar Palika Parisad Ujhani				
Total Quantity	300				
Item Category	Anti Wear Hydraulic Oil				
Experience Criteria	1 Year (s)				
MSE Exemption for Years of Experience and Turnover	No				
Startup Exemption for Years of Experience and Turnover	No				
Document required from seller	Experience Criteria, Bidder Turnover *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer				
Bid to RA enabled	No				
Inspection Required	No				

#### **EMD Detail**

l I Required	I No.
Nequired	110

### ePBG Detail

Required	No

### Splitting

Bid splitting not applied.

1. Experience Criteria: In respect of the filter applied for experience criteria, the Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / Public Listed Company for number of years as indicated in the bid document before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity during each of the year. In case of bunch bids, the category of primary product having highest value should meet this criterion.

# Anti Wear Hydraulic Oil ( 300 liter )

## **Technical Specifications**

## \* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
Grade	Grade of Anti Wire Hydraulic Oil	VG-68	VG-68
REQUIREMENTS FOR ANTI WIRE HYDRAULIC OIL	Kinematic viscosity at 40°C, cSt	(61.2-74.8) for VG 68 grade	(61.2-74.8) for VG 68 grade
	Viscosity index, Min	90 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Pour point,°C, Max	0 (for VG 68, VG 100, VG 150 grade)	*
	Flash point( COC ),°C, Min	210 (for VG 68, VG 100 grade)	*
	Neutralization number, mg KOH/g of oil, Max	To be reported (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Rust preventing characteristics	Shall pass the test B after 24 h	*
	Copper strip corrosion for 3 hours at 100°C	Not worse than 1	*
	Foam stability after 10 minutes setting time, foam; At 24°C,ml,Max	Nil	*
	Foam stability after 10 minutes setting time, foam; At 93°C,ml,Max	Nil	*
	Foam stability after 10 minutes setting time, foam; At 24°C after cooling down from 93°C, ml Max	Nil	*
	Emulsion characteristics, Max	40-37-3 (30) for VG 68 grade	*
	Air release value, minutes to 0 point 2 percent volume air content at 50°C, Max	15 for VG 68 grade	*
	Oxidation test for 1000 hours: Neutralization number of oil, mg KOH/g, Max	2 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Oxidation test for 1000 hours: Total sludge in oil and water layer plus those adhering to the catalyst coils or test tube mg,Max	100 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Oxidation test for 1000 hours: Metal in combined oil, water and sludge Copper, mg, Max	50 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Oxidation test for 1000 hours: Metal in combined	50 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*

	oil, water and sludge: Iron, mg, Max		
	Hydrolvtic stability : Copper specimen mass loss, mg/cm	0.5 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Hydrolytic stability : Acidity of water layer, mg KOH,Max	6 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Four ball wear test at 20 kg load;Wear scar diameter, mm,Max	0.35 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Pump wear test ( Vickers 104C, 250 hours test );Total mass loss to rings and vanes; mg,Max	50 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	FZG-Niemann EP test, pass load stage, Min	10th (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Thermal stability test at 135°C for 168 hours: Viscosity increase, percent, Max	5 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Thermal stability test at 135°C for 168 hours: Sludge mg/100 ml, Max	25 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Thermal stability test at 135°C for 168 hours: Copper rod mass, loss, mg/200 m, Max	10 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Thermal stability test at 135°C for 168 hours: Copper rod rating, Max	2 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Filtration time seconds: Without water,Max	600 (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Filtration time seconds: With 2 percent water, Max	Twice the time without water (for VG 32, VG 46, VG 68, VG 100, VG 150 grade)	*
	Seal compatibility test: Volume change,percent, Max	±4	*
	Seal compatibility test: Change in shore hardness, Max	(1 to +4)	*
Packing , Marking and Labelling	The material shall be packed in metal containers or in any other suitable containers as agreed to between the purchaser and the supplier	MS Barrels	*
	Packing size (Liters)	210	*
Certification	Conformity to specification	IS : 11656 (Latest)	*
	Whether ISI Marked	NO	*
	CM/L Number(Must declare if ISI Marked)	-	*
	RDSO Approval	NA	*
	RDSO approval certificate to be submitted to the buyer on demand	NA	*

Test Report Details	Availability of Test Report from Central Govt/ State Govt/NABL/ILAC accredited lab (hint: Must be declared)	YES	*
	Test Report to be furnished to the Buyer on demand (Must be declared, write NA if Test Report is not available)	YES	*

<sup>\*</sup> Specifications highlighted in bold are the Golden Parameters.

### **Additional Specification Documents**

### **Consignees/Reporting Officer and Quantity**

	Consignee/Reporting Officer	Address	Quantity	Delivery Days
1	Nafees Ahamad Saifi	243639,railway road nagar palika ujhani	300	15

# **Bid Specific Additional Terms and Conditions**

1.Scope of supply (Bid price to include all cost components) : Only supply of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---

<sup>\*</sup> Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.