

Bid Number: GEM/2020/B/704741

Dated: 09-07-2020

## **Bid Document**

Bid Document		
Bid Details		
Bid End Date/Time	20-07-2020 12:00:00	
Bid Opening Date/Time	20-07-2020 12:30:00	
Bid Life Cycle (From Publish Date)	90 (Days)	
Bid Offer Validity (From End Date)	45 (Days)	
Ministry/State Name	Ministry Of Coal	
Department Name	Materials Management	
Organisation Name	NIC	
Office Name	Materials Management	
Total Quantity	2	
Item Category	true rms clamp meter	
MSE Exemption for Years of Experience and Turnover	No	
Startup Exemption for Years of Experience and Turnover	No	
Bid to RA enabled	No	
Inspection Required	No	

#### **EMD Detail**

Required	No

## ePBG Detail

Required	No
----------	----

## Splitting

Bid splitting not applied.

## True Rms Clamp Meter ( 2 pieces )

## **Technical Specifications**

## \* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
GENERAL FEATURES	Туре	Hand Held	Hand Held
	Display	3.5 digit Backlit LCD	3.5 digit Backlit LCD
	Measurement Type	True RMS	True RMS
	count	3000	3000
MEASUREMENT FEATURES	Resistance Measurement Range	4	4.0
	Resistance Measurement Accuracy (+/-)	0.5	0.5
	Frequency Measurement Range	0.5	0.5
	Frequency Measurement Accuracy (+/-)	0.1	0.1
	AC Current Measurement Range	10	10.0
	AC Current Measurement Accuracy (+/-)	1	1.0
	AC Voltage Measurement Range	400	400.0
	AC Voltage Measurement Accuracy (+/-)	1.5	1.5
	DC Current Measurement Range	100	100.0
	DC Current Measurement Accuracy (+/-)	1	1.0
	DC Voltage Measurement Range	40	40.0
	DC Voltage Measurement Accuracy (+/-)	1	1.0
	Other features,if applicable	-	*
GENERIC	Jaw Size (Dia in Closed State)	32	*
	Dimensions (H x W x L) (mm x mm x mm)	-	*
	Weight	260	*
POWER REQUIREMENT	S Power Requirements	Battery Operated	*

	Type of Battery	Non- Rechargeable (Alkaline)	*
	if rechargeable , then chemistry of the battery	lithium ion	*
	if Non-rechargeable , then size of the battery / cell	AA	*
	Number of non- rechargeable the battery / cell	2	*
	Voltage of rechargeable Battery milliamphere hour	1.5	*
	Suitable charger/adaptor provided	NA	*
OPERATING CONDITION	Minimum Operating Temperature	0	*
	Maximum Operating Temperature	50	*
	Operating Humidity (RH)	90	*
SAFETY	Safety Certification	UL	*
	Safety Rating	CAT III 600 V of IEC 61010 -2-D31	CAT III 600 V of IEC 61010 -2-D31
ACCESSORIES	Details of the Standard Accessories Supplied with the Equipment	-	*
SERVICE	Warranty	3	3.0
TEST REPORT DETAILS & TESTS	The equipment supplied with calibration certificate	yes	*
	conformity to Dry Heat for 16 hrs at a specified maximum temp	Yes	*
	conformity to Cold Test for 4 hrs at a specified minimum temp in accordance with IS:900 0/part-2/section-4/1977 latest	Yes	*
	conformity to Damp Heat (Cyclic)Test for 2 Cycles of 24 h each at a temp of 40 degree C & 95% RH	Yes	*
	Availability of Test	Yes	*

Reports from Central Govt/NABL/ILAC approved accredited lab to prove conform to the specification	
Test Report Number and date for the specification test	- *
Name and address of the Lab for the specification test	

<sup>\*</sup> Specifications highlighted in bold are the Golden Parameters.

#### **Additional Specification Documents**

### **Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	Kulothungan Kasinathan	607807,PERMANENT CENTRAL STORES, NLC INDIA LIMITED, NEYVELI 607807	2	60

# **Bid Specific Additional Terms and Conditions**

1. Scope of supply (Bid price to include all cost components): Only supply of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---

<sup>\*</sup> Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.