

Dated: 13-07-2020



Bid Document

| Bid Document | | | |
|--|--|--|--|
| Bid Details | | | |
| Bid End Date/Time | 24-07-2020 11:00:00 | | |
| Bid Opening Date/Time | 24-07-2020 11:30:00 | | |
| Bid Life Cycle (From Publish Date) | 90 (Days) | | |
| Bid Offer Validity (From End Date) | 30 (Days) | | |
| Ministry/State Name | Uttar Pradesh | | |
| Department Name | Urban Development Department Uttar Pradesh | | |
| Organisation Name | N/a | | |
| Office Name | Nagar Palika Parishad Bahjoi Sambhal | | |
| Total Quantity | 100 | | |
| Item Category | LED Luminaire (For Road and Street Lights) | | |
| OEM Average Turnover (Last 3 Years) | 35 Lakh (s) | | |
| Experience Criteria | 2 Year (s) | | |
| MSE Exemption for Years of Experience and Turnover | No | | |
| Startup Exemption for Years of Experience and Turnover | No | | |
| Document required from seller | Experience Criteria, Past Performance, Certificate (Requested in ATC), OEM Authorization Certificate, OEM Annual Turnover *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer | | |
| Past Performance | 80 % | | |
| Bid to RA enabled | No | | |
| Inspection Required | No | | |
| · | | | |

EMD Detail

| Advisory Bank | State Bank of India |
|-------------------|---------------------|
| EMD Percentage(%) | 5.00 |
| EMD Amount | 49560 |

ePBG Detail

| Advisory Bank | State Bank of India |
|-------------------------------------|---------------------|
| ePBG Percentage(%) | 5.00 |
| Duration of ePBG required (Months). | 12 |

- (a). EMD EXEMPTION: The bidder seeking EMD exemption, must submit the valid supporting document for the relevant category as per GeM GTC with the bid. Under MSE category, only manufacturers for goods and Service Providers for Services are eligible for exemption from EMD. Traders are excluded from the purview of this Policy.
- (b). EMD & Performance security should be in favour of Beneficiary, wherever it is applicable.

Beneficiary:

EXECUTIVE OFFICER

NAGAR PALIKA PARISHAD BAHJOI SAMBHAL, UP NOTE : WITHOUT EMD TECHNICALLY NOT ACCEPTED. (Executive Officer)

Splitting

Bid splitting not applied.

- 1. Experience Criteria: In respect of the filter applied for experience criteria, the Bidder or its OEM {themselves or through reseller(s)} should have regularly, manufactured and supplied same or similar Category Products to any Central / State Govt Organization / PSU / Public Listed Company for number of years as indicated in the bid document before the bid opening date. Copies of relevant contracts to be submitted along with bid in support of having supplied some quantity during each of the year. In case of bunch bids, the category of primary product having highest value should meet this criterion.
- 2. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.
- 3. Past Performance: The Bidder or its OEM {themselves or through re-seller(s)} should have supplied same or similar Category Products for 80% of bid quantity, in at least one of the last three years before the bid opening date to any Central / State Govt Organization / PSU / Public Listed Company. Copies of relevant contracts (proving supply of cumulative order quantity in any one year) to be submitted along with bid in support of quantity supplied in the relevant year. In case of bunch bids, the category related to primary product having highest bid value should meet this criterion.

LED Luminaire (For Road And Street Lights) (100 pieces)

Technical Specifications

* As per GeM Category Specification

| Specification | Specification Name | Values | Bid Requirement (Allowed Values) |
|--------------------------|---|---------------------------------|-------------------------------------|
| STANDARDS | LED Luminaire conformity to IS:10322/Part 5/Section 3/2012 latest and IS: 16107 (Part 2/Sec 1):2012 latest | Yes | * |
| | Photo biological safety of LEDs used shall be as per IS:16108/2012 (exempt group) | Yes | * |
| | Types of LED Luminaire as per the IS: 16107(Part-2/Sec1)/2012 | Type B | * |
| | Types of LED Modules as per the IS:IS: 16103(Part-2)/2012 | Type 3 | * |
| | LED Rating (in Watts)/System Wattage/Rated Power | 90W | 90W |
| | Luminaire System Efficacy (Lumen/watt) | >/= 100 Lm/Watt | * |
| | Ingress Protection (IP Rating) as per IS:10322 (Part 1):1982 latest | IP66 | * |
| | Warranty for free replacement (in years) | 5 | 5 |
| ELECTRICAL EFFICIENCY | Input operating Voltage range and frequency | 90 to 300 Volts AC at 50 Hz+/-2 | * |
| | Automatic Higher Cut off voltage above 300 volt | Yes | * |
| | Rated voltage | 230 V AC 50 Hz | * |
| | AC Power Factor at full load | ≥ 0.95 | * |
| | Driver Efficiency (in %age) Upto 100W: ≥85%, Above 100W: >/=90% | Yes | * |
| | Total Harmonics Distortion | ≤ 10 | * |
| | "The total circuit power shall not be more than | Yes | * |

| | 110 percent of the value declared by the manufacturer (as per Cl. 8 of IS:16104:2012 lates)" | | |
|-----------------------|--|------------------------|---|
| OPTICAL | LED chip Efficacy | ≥130 Lm/Watt | * |
| | Colour temperature | 6000+/-500K | * |
| | Working life for LED (Minimum 50,000 burning hours as per LM-80 and LM 21 reports) | Yes | * |
| | Colour Rendering Index(CRI) | ≥70 | * |
| | LED Beam Angle | ≥120 | * |
| | Optic lense materal (UV stabilised) | Poly carbonate lense | * |
| THERMAL MANAGEMENT | Heat sink should be die- cast aluminium along with sufficient heat sink fins to dissipate heat effectively | Yes | * |
| | Junctiojn / Soldering point temperature shall not exceed 85 deg.c as per LM 80 report | Yes | * |
| | Capacitor shall be rated for a temperature of 105 deg. celsius or better | Yes | * |
| | Operating temperature range | -10 deg C to +50 deg C | -20 deg. C to +50 deg. C, -10 deg C to +50 deg C, -10 deg C to +55 deg C |
| | Operating Humidity Range | 10 % to 95% RH | * |
| PROTECTION | Short circuit Protection | Yes | * |
| | Over load protecton | Yes | * |
| | Over Voltage protection | Yes | * |
| | Reverse polarity | Yes | * |
| | High voltage test (1.5 KV for one minute between supply terminals and body of the unit) | Yes | * |
| | Insulation resistance between earth and current carrying part | >100 M Ohm | * |

| | The luminaire shall be protected against surges and transients (Internal) The luminaire shall be protected against surges and transients | >/=4KV Yes | * |
|----------------|--|---------------|-------|
| CONSTRUCTIONAL | of >/=10KV (External) The Luminaires casing/housing (single piece housing) shall be pressure die casted aluminium alloy with higher thermal conductivity | Yes | * |
| | The luminaire body must be corrosion resistant powder coated | Yes | * |
| | All fastners must be of stainless steel | Yes | * |
| | Protection of the entire housing (both LED section and driver section) as per IS:10322 (Part 1):1982 latest | IP66 | * |
| | Extruded silicon loop gasket shall be provided in the lantern body to ensure a weather proof seal between the UV Glass cover and the metal housing to exclude the entry of the dust, water, insects etc., | Yes | * |
| | Luminaries light transparency should be of Toughened glass | Yes | * |
| | Toughned transparent glass cover thickness | >/=4 mm | * |
| | Toughned Glass shall not get discoloured shall not suffer degration due to heat and ageing within warranty period | Yes | * |
| | Number of electronic control gear (power supplies) | 1 No. | 1 No. |

| | Light Source | SMD LED Chip as per LM 80/IS16106 | * |
|-------------|---|--------------------------------------|---------------|
| | Driver components shall be industrial grade or above | Yes | * |
| | PCB shall be FR4 grade minimum 0.8 to 1.0 mm thick or more | Yes | * |
| | The Luminaires works on single phase three wires system (Phase, Neutral and Earth) | Yes | * |
| | Suitable connector shall be provided for LED connection between driver output and LED | Yes | * |
| | Length of ISI marked three core wire (shall be provided along with supply of material) | 50 cm | 50 cm, 100 cm |
| MARKING | "Manufactures Name and and brand on the aluminium die cast body " | Engraved/Embossed | * |
| | Manufacturer's name, model number, serial number | Yes | * |
| | Date of manufacture (month-year), and lot number as identification mark inside each unit and the outside of each packaging box | Yes | * |
| | The operation characteristics voltage and power be marked inside of each LED luminaire unit | Yes | * |
| | Diameter of pole Luminiare suitable for: (upto 45W Pole OD: shall be 40mm), (>45W<120W Pole OD: Shall be 50 mm), (above 120W: OD shall be 60 mm for which luminiare is suitable | Yes | * |
| REPORTS AND | LED Make | OSRAM / NICHIA / CREE | * |

| CERTIFICATIONS | | / SAMSUNG / SEOUL / LUMILEDS / PHILIPS / SYSKA / LUMENMAX / EVERLIGHT / EDISON / BRIDGELUX / NATIONSTAR / REFOND | |
|----------------|---|---|---|
| | System must have EMI/EMC compliance as applicable (Test reports shall be furnish to the buyer / consignee on demand) | Yes | * |
| | LM 79 (Photometry) (Ref.IS:16106:2012) report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-79 report shall have total lumen output, power, PF, Current in Amps, CRI & CCT etc.,) | Yes | * |
| | LM 80 & TM 21 (Ref. IS:16105:2012) Report and Photo biological report for LED report from Central Government Lab /NABL/ILAC accrediated lab. Reports shall be furnish to the buyer / consignee on demand (LM-80 report shall have the Pohoto Biological report of the LED Chip being used in the luminaire) | Yes | * |
| | Availability of test Report from Central Government Lab /NABL/ILAC accrediated lab to Indian Standrad IS:10322/part 5/sec-3/2012 and IS 16107 (Part 2/Sec 1): 2012 | Yes | * |
| | Seller shall furnish the Type test reports to the buyer / consignee on demand | Yes | * |
| | DC or AC supplied | Yes | * |

| electronic control gear for LED Module shall comlpy as per IS:15885 (Part 2/Sec.13) | | |
|--|-----|---|
| LED Luminaire for road and street lighting shall comply with Complusory Registration(CRS) of BIS for safety as per IS 10322 (Part 5/Section 3): 2012 as applicable on date | Yes | * |

^{*} Specifications highlighted in bold are the Golden Parameters.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

| S.No. | Consignee/Reporti ng Officer | Address | Quantity | Delivery Days |
|-------|---------------------------------|--|----------|---------------|
| 1 | Navdeep Kumar | 244302,NAGAR PALIKA PARISHAD BAHJOI SAMBHAL UP | 100 | 30 |

Bid Specific Additional Terms and Conditions

- 1. Scope of supply (Bid price to include all cost components) : Supply Installation Testing and Commissioning of Goods
- 2. Bidder's offer is liable to be rejected if they don't upload any of the certificates / documents sought in the Bid document, ATC and Corrigendum if any.
- 3. ISO 9001: The bidder must have ISO 9001 certification.
- 4. Material Test Certificate Should Be Sent Along with The Supply. The Material Will Be Checked by Buyer's Lab & the Results of the Lab will be the Sole Criteria for Acceptance of the Item.
- 5. The bidder is required to upload, along with the bid, all relevant certificates such as BIS licence, type test certificate, approval certificates and other certificates as prescribed in the Product Specification given in the bid document.
- 6. To be eligible for award of contract, Bidder / OEM must possess following Certificates / Test Reports on the date of bid opening (to be uploaded with bid): MUST UPLOAD UP PWD "AAA" CATEGORY CERTIFICATE.
- 7. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria. In case of bunch bids, the OEM of CATEGORY RELATED TO primary product having highest bid value should meet this criterion.
- 8. Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the

^{*} Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement (allowed Values) by the Buyer.

State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.

- 9. Dedicated /toll Free Telephone No. for Service Support: BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.
- 10. Escalation Matrix For Service Support : Bidder/OEM must provide Escalation Matrix of Telephone Numbers for Service Support.
- 11. Timely Servicing / rectification of defects during warranty period: After having been notified of the defects / service requirement during warranty period, Seller has to complete the required Service / Rectification within 7 days time limit. If the Seller fails to complete service / rectification with defined time limit, a penalty of 0.5% of Unit Price of the product shall be charged as penalty for each week of delay from the seller. Seller can deposit the penalty with the Buyer directly else the Buyer shall have a right to recover all such penalty amount from the Performance Security (PBG).Cumulative Penalty cannot exceed more than 10% of the total contract value after which the Buyer shall have the right to get the service / rectification done from alternate sources at the risk and cost of the Seller besides forfeiture of PBG. Seller shall be liable to re-imberse the cost of such service / rectification to the Buyer.
- 12. **Bidder financial standing:** The bidder should not be under liquidation, court receivership or similar proceedings, should not be bankrupt. Bidder to upload undertaking to this effect with bid.
- 13. **Upload Manufacturer authorization:** Wherever Authorised Distributors are submitting the bid, Manufacturers Authorisation Form (MAF)/Certificate with OEM details such as name, designation, address, e-mail Id and Phone No. required to be furnished along with the bid.
- 14. OPTION CLAUSE: The Purchaser reserves the right to increase or decrease the quantity to be ordered up to 25 percent at the time of placement of contract. The purchaser also reserves the right to increase the ordered quantity by up to 25% of the contracted quantity during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly.
- 15. Successful Bidder can submit the Performance Security in the form of Fixed Deposit Receipt also (besides PBG which is allowed as per GeM GTC). FDR should be made out or pledged in the name of EXECUTIVE OFFICER, NAGAR PALIKA PARISHAD BAHJOI SAMBHAL,UP A/C (Name of the Seller). The bank should certify on it that the deposit can be withdrawn only on the demand or with the sanction of the pledgee. For release of Security Deposit, the FDR will be released in favour of bidder by the Buyer after making endorsement on the back of the FDR duly signed and stamped along with covering letter. Successful Bidder has to upload scanned copy of the FDR document in place of PBG and has to ensure delivery of hard copy of Original FDR to the Buyer within 15 days of award of contract.
- 16. Bidders can also submit the EMD with Fixed Deposit Receipt made out or pledged in the name of EXECUTIVE OFFICER, NAGAR PALIKA PARISHAD BAHJOI SAMBHAL, UP A/C (Name of the Seller). The bank should certify on it that the deposit can be withdrawn only on the demand or with the sanction of the pledgee. For release of EMD, the FDR will be released in favour of bidder by the Buyer after making endorsement on the back of the FDR duly signed and stamped along with covering letter.
 - Bidder has to upload scanned copy / proof of the FDR along with bid and has to ensure delivery of hardcopy to the Buyer within 5 days of Bid End date / Bid Opening date.
- 17. For fulfilling the experience criteria any one of the following documents may be considered as valid proof for meeting the experience criteria:
 - a. Purchase Order copy along with Invoice(s) with self-certification by the bidder that supplies against the invoices have been executed.
 - b. Execution certificate by client with order value.
 - c. Any other document in support of order execution like Third Party Inspection release note, etc.
- 18. The Bidder / OEM {themselves or through reseller(s)}, should have executed project for supply and installation / commissioning of same or similar Category Products during

preceding 3 financial years (i.e. current year and three previous financial years) as on opening of bid, as per following criteria:

- (i) Single order of at least 35% of estimated bid value; or
- (ii) Two orders of at least 20% each of estimated bid value; or
- (iii) Three orders of at least 15% each of estimated bid value.

Satisfactory Performance certificate issued by respective Buyer Organization for the above Orders should be uploaded with bid. In case of bunch bids, the Category related to primary product having highest bid value should meet this criterion

This Bid is also governed by the General Terms and Conditions

---Thank You---