



Bid Document

Bid Document				
Bid Details				
Bid End Date/Time	27-07-2020 16:00:00			
Bid Opening Date/Time	27-07-2020 16:30:00			
Bid Life Cycle (From Publish Date)	90 (Days)			
Bid Offer Validity (From End Date)	15 (Days)			
Ministry/State Name	Ministry Of Labour And Employment			
Department Name	Na			
Organisation Name	Employees Provident Fund Organisation (epfo)			
Office Name	Ro Shivamogga			
Total Quantity	1			
Item Category	Online UPS			
MSE Exemption for Years of Experience and Turnover	No			
Startup Exemption for Years of Experience and Turnover	No			
Bid to RA enabled	No			
Inspection Required	No			

EMD Detail

Required	No

ePBG Detail

Required No	
---------------	--

Splitting

Bid splitting not applied.

Online UPS (1 pieces)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
Generic	Rating in KVA (KVA)	2.0 KVA	2.0 KVA
	Technology	IGBT-PWM with inbuilt isolation transformer	IGBT-PWM with inbuilt isolation transformer

	Input Power	single phase 160V - 260V sinewave,50Hz	single phase 160V - 260V sinewave,50Hz	
		Single phase 230V +/-1% sinewave 50 Hz	Single phase 230V +/-1% sinewave 50 Hz	
		30		
	Minimum VAH (VAH)	1872	1872	
	Warranty for UPS (Years) 5 Movable trolly for Batteries ra		5	
			Without trollery but with rack	
	Warranty for battery	2	2	
	Degree of Protection	IP20	IP20	
	Cabling 5 meters for input and out put	Without	Without	
	Paralleling kit for synchronising	Without	Without	
	Installation and Commissioning	Yes	*	
Constructional	Minimum thickness of M.S.Sheet Enclosure duly painted (mm)	1.0	*	
	Type of Battery	SMF-VRLA conforming to JISC:8702(Pt.I,II&III)	SMF-VRLA conforming to JISC:8702(Pt.I,II&III)	
Functional	Maximum overshoot and Under shoot of output rated voltage	4	*	
	Voltage Regulation from no load to full load (%)	< / = 3%	*	
	20% Overload limit for minimum 10 minutes	No, only for 5 Minutes	No, only for 5 Minutes	
	Overall Efficiency (%)	>/=90%	>/=90%	
	Total Harmonic Distortion(THD) (%)	Maximum 3%	*	
	50% Overload limit for minimum 1 minutes	No, only for 3 seconds	No, only for 3 seconds	
Protection	Protection for under voltage at battery terminal at 10.5V per 12 V battery	Yes	*	
	Protection of Over voltage,Short Circuit & over load at UPS output terminal	Yes	*	
Metering And Indications	Digital Metering in UPS for AC Input Voltage,Output AC Voltage,Current,Frequency, Battery Voltage and Current	Yes	*	
	Indicators for mains presence,Battery charging and discharging,Output Over Load, Low Battery Voltage	Yes	*	
Reports And Certification	Damp Heat : in accordance with IS:9000(part 5/sec.2)1981 at Temperature of 40 degree C,two cycles of (12+12)	Yes	*	

hours each 2007)		
Dry Heat Test: in accordance with IS:9000 (part 3/sec.5)1977 (reaffirmed 2007) at 55 degree C for 16 hrs	Yes	*
Cold Test: in accordance with IS:9000 (Part 2/Sec.4)1977 (Reaffirmed 2007) at -10 degree C for 4 hrs.	Yes	*
Availability of the Type Test Report from Central Govt. /NABL/ILAC Accredited lab covering all technical requirements.	Yes	*
Type Test Certificate No.	-	*
Type Test Certificate date	-	*
Name of Lab	-	*
Address of Lab	-	*
As per Meity (Government of India) guidelines UPS shall have valid BIS CRS certifications as applicable	Not applicable presently	*

^{*} Specifications highlighted in bold are the Golden Parameters.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days
1	Raju Vasudeo Mogera	577201,EPFO REGIONAL OFFICE KARTHIK PLAZA DURGI GUDI MAIN ROAD SHIMOGA	1	15

Special terms and conditions for category Online UPS

1.Calculation of Minimum VAH based on Back up time Minimum VAH requirements would be calculated on the basis of following: (VAH Calculation: Battery Voltage x Battery Ah x No. of Batteries = VAH)UPS Rating15 Minutes30 Minutes60 Minutes90 Minutes120 Minutes180 Minutes240 Minutes1 KVA400 VAH800 VAH1600 VAH2400 VAH3200 VAH4800 VAH6400 VAH2 KVA800 VAH1600 VAH3200 VAH4800 VAH6400 VAH9600 VAH12800 VAH3 KVA1200 VAH2400 VAH4800 VAH7200VAH9600 VAH14400 VAH19200 VAH5 KVA2000 VAH4000 VAH8000 VAH12000 VAH16000 VAH24000 VAH32000 VAH6 KVA2400 VAH4800 VAH9600 VAH14400 VAH19200 VAH28800 VAH38400 VAH7.5 KVA3000 VAH6000 VAH12000 VAH18000 VAH24000 VAH36000 VAH48000 VAH10 KVA4000 VAH8000 VAH16000 VAH24000 VAH32000 VAH48000 VAH64000 VAH36000 VAH24000 VAH24000 VAH36000 VAH24000 VAH24000 VAH36000 VAH36000 VAH48000 VAH64000 VAH96000 VAH36000 VAH48000 VAH64000 VAH96000 VAH192000 VAH38000 VAH192000 VAH384000 VAH192000 VAH38000 VAH192000 VAH384000 VAH3840000 VAH384000 VAH3840000 VAH3840000 VAH384000 VAH384000 VAH384000 VAH384000 VAH38400

Bid Specific Additional Terms and Conditions

1.Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If

^{*} Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement (allowed Values) by the Buyer.

service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.

This Bid is also governed by the General Terms and Conditions

---Thank You---