



Bid Document

Bid Bocument				
Bid Details				
Bid End Date/Time	27-07-2020 13:00:00			
Bid Opening Date/Time	27-07-2020 13:30:00			
Bid Life Cycle (From Publish Date)	90 (Days)			
Bid Offer Validity (From End Date)	75 (Days)			
Ministry/State Name	Ministry Of Defence			
Department Name	Department Of Defence			
Organisation Name	Border Road Organisation			
Office Name	******			
Total Quantity	4			
Item Category	water baths			
MSE Exemption for Years of Experience and Turnover	No			
Startup Exemption for Years of Experience and Turnover	No			
Bid to RA enabled	No			
Inspection Required	No			

EMD Detail

Required	No

ePBG Detail

Required No	
---------------	--

Splitting

Bid splitting not applied.

Water Baths (4 pieces)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
	Chamber Length of offered product:	-	*
	Chamber Width of offered	-	*

		product:		1
		Chamber Depth of offered product:	-	*
		Water bath Chamber Capacity	>over 14 to 18 litre	2 to 4 litre, > over 4 to 6 litre, > over 8 to 10 litre, > over 10 to 14 litre, > over 14 to 18 litre, > over 18 to 22 litre, > over 22 to 26 litre, > over 26 to 30 litre, over 6 to 8 litre, over 30 to 34 Litre
		Chamber Construction:	Double walled rectangular chamber	single walled rectangular chamber, Double walled rectangular chamber, Double walled rectangular chamber with mineral wool/solid insulation material filling in between
		Material of inner Chamber and lid Construction:	Stainless Steel (SS 304)	*
		Material of Outer Chamber Construction:	Epoxy / Powder coated Stainless Steel SS304	Epoxy coated/Powder coated mild steel, Epoxy / Powder coated Stainless Steel SS304
		Weight (kg)	8	*
		Number of racks provided with Water bath unit	2	0, 2, 4, 6, 8, 10, 12, 14
		Number of 75 mm diameter Holes provided:	0	0, 6, 8, 12, 15, 24
1 1	Heating Arrangement Parameters	Heat source:	Heating shall be done by a immersion heater.	*
		Heating Capacity (>=):	1000	800, 1000, 1500, 2000, 2400, 2500, 3000, 200, 1200
Cor	trol Panel and Display t	Control Panel has:	ON/Off Switch,Power mains Indicator,Temperature controller	ON/Off Switch, Heating & Temprature (Set & Actual) Indicators, Power mains Indicator, Temperature controller, Circulation Controller (if Water bath has circulation facility), Refrigeration Controller (if Water bath has chamber refrigeration facility), Shaking Controller (if Water bath has shaking facility)
		Adjustable shaking frequency in rpm	NA	20-200, NA
		Type of Temperature controller	Thermostat based control	Thermostat based control, Digital controller cum Indicator PID Based control Or higher
		Water bath Display type:	Analog Display	Analog Display, Digital (numerical/application specific) backlit LCD display, LED
		Integrated circulation pump for temperature homogeneity	No	Yes, No Or higher

	Removable bottom plate and shaking inserts	No	Yes, No Or higher
Water bath Temperature	Temperature range of bath chamber:	5°C above ambient to 99.9°C	5°C above ambient to 99.9°C, 5°C above ambient to 90°C, 5°C above ambient to 95°C, 20°C to 99.9°C, 10°C to 100°C
	Temperature control sensitivity:	±0.5°C or better	±0.5°C or better, ±0.2°C or better, ±0.1°C or better Or higher
	Least temperature increment Step available	0.1 degree C	5 degree C, 1 degree C, 0.1 degree C, 0.01 degree C Or higher
	Temperature Accuracy:	±1°C or better	±5°C or better, ±1°C or better, ±0.5°C or better, ±0.2°C or better, ±0.1°C or better Or higher
	Safety Features:	Low fluid Alarm	Low fluid Alarm, High limit Alarm, Over temperature Alarm & cutoff, Redundant safety thermostat
Power Requirement, Certifications and Warranty	Power requirement:	220 V 50 Hz Single Phase AC	220 V 50 Hz Single Phase AC, 440 V 50Hz three phase AC
	Availability of Test Report from Central Govt/NABL/ILAC accredited lab to prove conformity to specification	No	Yes, No
	Manufactured by ISO 9001:2008 or latest certified firm:	YES	*
	Equipment has CE certification	No	Yes, No
	Warranty Period:	3	3, 5 Or higher
Cover	Lid/cover Provided	No	*
	Shape of Cover	Rectangular	*
Timer Unit	Timer Provided	Yes	Yes, No
	Timer Setting (minimum increment step)	5	0 - 300
Miscellaneous Features	Drain plug in Chamber provided	No	Yes, No
	Data Logging facility through (RS 232/USB/HDMI/Bluetooth etc) to computer available:	No	Yes, No
	Steel holder for tubes and Flasks provided:	-	*
	Drain screw for emptying of water bath	No	Yes, No Or higher
	Seamless and waterproof keypad		Yes, No Or higher

^{*} Specifications highlighted in bold are the Golden Parameters.

* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally

be preferred over 'Bid requirement (allowed Values) by the Buyer.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days
1	*****	********JODHPUR	4	30

Bid Specific Additional Terms and Conditions

1.Scope of supply (Bid price to include all cost components) : Only supply of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---