

### Bid Document

Bid Details	
Bid End Date/Time	20-07-2020 14:00:00
Bid Opening Date/Time	20-07-2020 14:30:00
Bid Life Cycle (From Publish Date)	90 (Days)
Bid Offer Validity (From End Date)	30 (Days)
Ministry/State Name	Maharashtra
Department Name	Rural Development And Panchayat Raj Department Maharashtra
Organisation Name	N/a
Office Name	Solapur Municipal Corporation Solapur
Total Quantity	20
Item Category	chairs-office
MSE Exemption for Years of Experience and Turnover	No
Startup Exemption for Years of Experience and Turnover	No
Document required from seller	Experience Criteria,OEM Authorization Certificate *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer
Bid to RA enabled	No
Inspection Required	No

### EMD Detail

Required	No
----------	----

### ePBG Detail

Required	No
----------	----

### Splitting

Bid splitting not applied.

## Chairs-office ( 20 pieces )

### Technical Specifications

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
MATERIAL	<b>Type of material (other than wood) used in Polythene cane Chair</b>	NOT APPLICABLE	solid wood, teak wood, hot pressed board, plastic net, NOT APPLICABLE, Polypropylene Copolymer (PPCP) - Moulded single piece, Teak wood section (45 mm X 22 mm)
	<b>Material of Fabric Back Cover</b>	leather foam	knitted with cane, leather foam, plastic net, leather, leatherite, polyster, N.A
	Thickness of Plywood used in Backrest IN MM ( $\pm 1$ mm)	20 mm	*
	<b>Frame Material</b>	STAINLESS STEEL 202	*
	Density of Polyurethane Foam Used in Seat $\pm 2$ (Kg/Cub M)	32 Kg/Cub.M	*
	<b>Material of Fabric of Seat Cover</b>	leather foam	black leatherite, leather foam, plastic net, knitted with cane, fabric, polyurathane, N.A, Leatherette
	Density of Polyurethane Foam Used in Backrest $\pm 2$ (Kg/Cub M)	32 Kg/Cub.M	*
	<b>Thickness of Plywood used in Seat <math>\pm 1</math>(mm)</b>	20 mm	12 mm, 18 mm, 20 mm, 25 mm, 30 mm, 35 mm, 40 mm, N.A
	<b>GSM/Thickness of Fabric <math>\pm 5</math> (Gram per Sq Meter)</b>	250 Gram per Sq Meter	80 Gram per Sq Meter, 220 Gram per Sq Meter, 250 Gram per Sq Meter, 290 Gram per Sq Meter, N.A
	<b>Arm Material</b>	NA	*
	<b>Thickness of Polyurethane Foam</b>	50 mm	25 mm, 50 mm, 62 mm, 65 mm, 70 mm,

	<b>Used in Backrest IN MM (+/- 3 mm)</b>		N.A, 40 mm
	<b>Thickness of Polyurethane Foam Used in Seat IN MM (+/- 3 mm)</b>	50 mm	*
	Shoe Type	plastic	*
GENERIC	Conformity to Indian Standard IS 3499 (Part-1) Latest	Yes	*
	<b>Chair Type</b>	Without Arms	With Arms, Without Arms
	<b>Type of Seat and Backrest</b>	Padded with Polyurethane Foam	Made of Polythene cane, Padded with Polyurethane Foam, moulded plywood, injection moulded Polypropylene, Seat made of padded with polyurethane foam and Backrest made of Mesh with support of injection moulded polypropylene, Supported by two MS chrome plate strip (30 mm X 10 mm), By Back patti as supporting bracket
	<b>Frame Type</b>	4 Legs	Cantilever, 4 Legs
	<b>Castors</b>	Without	With, Without
DIMENSION	<b>Size of Material (mm)</b>	14 SWG 25 mm round pipe	14 SWG 25 mm round pipe, 16 SWG 30 mm round pipe, 2 mm thick 25 mm tube, 40 mm teak wood, 16 gauge tubular pipe, N.A, armrest supports dia. 25 mm X 1.6 mm thick and frame of dia. 25 mm X 2 mm thick
	<b>Chair Height ±15(mm)</b>	700 mm	*
	<b>Seat Depth ±10(mm)</b>	550 mm	*
	<b>Seat Width ±10 (mm)</b>	380 mm	*
	<b>Seat Height IN MM ±5(mm)</b>	430	400, 430, 460, 480, 500, 380, 450, 254
	<b>Backrest Width ±10(mm)</b>	380 mm	350 mm, 380 mm, 400 mm, 430 mm, 450 mm,

			500 mm, 550 mm, 480 mm, 520 mm, 280 mm
	<b>Backrest Height ±10(mm)</b>	400 mm	*
	<b>Arm Length ±5(mm)</b>	N.A	200 mm, 250 mm, 300 mm, 350 mm, 400 mm, 450 mm, N.A, 470 mm, 490 mm
	<b>Arm Width ±2(mm)</b>	N.A	*
COLOUR & FINISH	Colour of Fabric for Seat and Backrest	black	*
	<b>Paint Type</b>	powder coated on MS	chrome, epoxy polyester, polished, synthetic enamel, powder coated on MS, N.A, Black coated with dry film thickness of 40 to 60 microns
	Colour of Paint	NA	*
CERTIFICATION	Polythene cane conforming to Type-1 of IS 5378 /1994	NO	*
	<b>Test reports to be furnished to buyer on demand</b>	NO	YES, NO
	<b>BIFMA certification</b>	NO	YES, NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	NO	YES, NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	NO	YES, NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	NO	YES, NO
WARRANTY	<b>Warranty period in number of years</b>	1	1, 2, 3, 4, 5

\* Specifications highlighted in bold are the Golden Parameters.

\* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.

#### Additional Specification Documents

#### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days
-------	-----------------------------	---------	----------	---------------

1	Laxman Hanmanta Chalwadi	413001,Solapur Municipal Corporation , Computer Department , Dr.Babasaheb Ambedkar Chowk (Park Chowk) Solapur	20	25
---	--------------------------------	---------------------------------------------------------------------------------------------------------------------------	----	----

### **Bid Specific Additional Terms and Conditions**

1. ISO 9001: The bidder must have ISO 9001 certification.

[This Bid is also governed by the General Terms and Conditions](#)

**---Thank You---**