

Bid Number: GEM/2020/B/715587 Dated: 17-07-2020

Bid Document

Bid Details				
Bid End Date/Time	27-07-2020 19:00:00			
Bid Opening Date/Time	27-07-2020 19:30:00			
Bid Life Cycle (From Publish Date)	90 (Days)			
Bid Offer Validity (From End Date)	80 (Days)			
Ministry/State Name	Ministry Of Coal			
Department Name	Materials Management			
Organisation Name	Bharat Coking Coal Limited			
Office Name	Bccl Dhanbad			
Total Quantity	1680			
Item Category	Anti Wear Hydraulic Oil			
MSE Exemption for Years of Experience and Turnover	No			
Startup Exemption for Years of Experience and Turnover	No			
Document required from seller	OEM Authorization Certificate *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer			
Bid to RA enabled	No			
Inspection Required	No			

EMD Detail

Required	No

ePBG Detail

I I Required	l No
Required	110

Splitting

Bid splitting not applied.

Anti Wear Hydraulic Oil (1680 liter)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
Grade	Grade of Anti Wire Hydraulic Oil	100	100
REQUIREMENTS FOR ANTI WIRE HYDRAULIC OIL	Kinematic viscosity at 40°C, cSt	(101-109) for 100 grade	(101-109) for 100 grade
	Viscosity index, Min	135 for 100 grade	*
	Pour point,°C, Max	Minus 33 for 100 grade	*
	Flash point(COC),°C, Min	220 for 100 grade	*
	Neutralization number, mg KOH/g of oil, Max	1.5 (for TH 46, 100 grade)	*
	Rust preventing characteristics	Shall pass the test B after 24 h	*
	Copper strip corrosion for 3 hours at 100°C	Not worse than 1	*
	Foam stability after 10 minutes setting time, foam; At 24°C,ml,Max	Nil	*
	Foam stability after 10 minutes setting time, foam; At 93°C,ml,Max	Nil	*
	Foam stability after 10 minutes setting time, foam; At 24°C after cooling down from 93°C, ml Max	Nil	*
	Emulsion characteristics, Max	40-37-3 (20) for 100 grade	*
	Air release value, minutes to 0 point 2 percent volume air content at 50°C, Max	7 (for VG 32, TH46, 100 grade)	*
	Oxidation test for 1000 hours: Neutralization number of oil, mg KOH/g, Max	NA (for TH-46, 100 grade)	*
	Oxidation test for 1000 hours: Total sludge in oil and water layer plus those adhering to the catalyst coils or test tube mg,Max	NA (for TH-46, 100 grade)	*
	Oxidation test for 1000 hours: Metal in combined oil, water and sludge Copper, mg, Max	NA (for TH-46, 100 grade)	*
	Oxidation test for 1000 hours: Metal in combined oil, water and sludge: Iron, mg, Max	NA (for TH-46, 100 grade)	*
	Hydrolvtic stability : Copper specimen mass loss, mg/cm	NA (for TH-46, 100 grade)	*
	Hydrolytic stability : Acidity of water layer, mg KOH,Max	NA (for TH-46, 100 grade)	*
	Four ball wear test at 20 kg load;Wear scar diameter, mm,Max	NA (for TH-46, 100 grade)	*
	Pump wear test (Vickers 104C, 250 hours test);Total	NA (for TH-46, 100 grade)	*

	mass loss to rings and vanes; mg,Max		
	FZG-Niemann EP test, pass load stage, Min	8th (for TH-46, 100 grade)	*
	Thermal stability test at 135°C for 168 hours: Viscosity increase, percent, Max	NA (for TH-46, 100 grade)	*
	Thermal stability test at 135°C for 168 hours: Sludge mg/100 ml, Max	NA (for TH-46, 100 grade)	*
	Thermal stability test at 135°C for 168 hours: Copper rod mass, loss, mg/200 m, Max	NA (for TH-46, 100 grade)	*
	Thermal stability test at 135°C for 168 hours: Copper rod rating, Max	NA (for TH-46, 100 grade)	*
	Filtration time seconds: Without water,Max	NA (for TH-46, 100 grade)	*
	Filtration time seconds: With 2 percent water, Max	NA (for TH-46, 100 grade)	*
	Seal compatibility test: Volume change,percent, Max	±4	*
	Seal compatibility test: Change in shore hardness, Max	(1 to +4)	*
Packing , Marking and Labelling	The material shall be packed in metal containers or in any other suitable containers as agreed to between the purchaser and the supplier	MS Barrels	*
	Packing size (Liters)	210	*
Certification	Conformity to specification	Generally conforming to Is : 11656 (latest)	*
	Whether ISI Marked	NO	*
	CM/L Number(Must declare if ISI Marked)	-	*
	RDSO Approval	NA	*
	RDSO approval certificate to be submitted to the buyer on demand	NA	*
Test Report Details	Availability of Test Report from Central Govt/ State Govt/NABL/ILAC accredited lab (hint: Must be declared)	YES	*
	Test Report to be furnished to the Buyer on demand (Must be declared, write NA if Test Report is not available)	YES	*
* Specifications highlighted	in hold are the Golden Paramet	arc	

^{*} Specifications highlighted in bold are the Golden Parameters.

* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement (allowed Values) by the Buyer.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days
1	Anup Dungdung	828101,Office of Depot Officer ,Regional Store Sijua Area , Post Office BANSJORA (SUB OFFICE), DHANBAD, JHARKHAND	1680	30

Bid Specific Additional Terms and Conditions

1.Scope of supply (Bid price to include all cost components) : Only supply of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---