

### Bid Document

Bid Details	
Bid End Date/Time	27-07-2020 18:00:00
Bid Opening Date/Time	27-07-2020 18:30:00
Bid Life Cycle (From Publish Date)	90 (Days)
Bid Offer Validity (From End Date)	15 (Days)
Ministry/State Name	Odisha
Department Name	Housing And Urban Development Department Odisha
Organisation Name	N/a
Office Name	District Urban Development Agency Bargarh
Total Quantity	5
Item Category	Revolving Chair
MSE Exemption for Years of Experience and Turnover	No
Startup Exemption for Years of Experience and Turnover	No
Bid to RA enabled	No
Inspection Required	No

### EMD Detail

Required	No
----------	----

### ePBG Detail

Required	No
----------	----

### Splitting

Bid splitting not applied.

### Revolving Chair ( 5 pieces )

#### Technical Specifications

[\\* As per GeM Category Specification](#)

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
MATERIAL	<b>Pedestal Base</b>	, Nylon Base With Nylon Twin Caster Wheels Minimum Of 50-70 Mm	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm

	Diameter	Size, ABS Plastic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Electro Coated with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Stainless Steel with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast Chrome Finish With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, , Nylon Base With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Aluminium Alloy With Nylon Twin Caster Wheels Minimum Of 50-70 Diameter, Wooden Cladded With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Chrome finish with 5 wheels
<b>Arm Material</b>	Proppylene	*
<b>seat material</b>	pressed and moulded plywood with polypropylene cover	pressed and moulded plywood with polypropylene cover, PU foam covered with mesh fabric, PU Foam covered with Fabric, PU Foam Covered With pure leather, PU Foam Covered With pure leatherite, Pressed and Moulded Plywood with PU Foam covered with Fabric, Pressed and Moulded Plywood with PU Foam covered with Pure Leather, Pressed and Moulded Plywood with PU Foam covered with Leatherite
Density of PU foam used in seat KG per Cu Meter (+/- 3)	50	*
Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	NA	*
<b>Material of Fabric Back Cover / Material for Backrest</b>	mesh fabric	mesh fabric, Innner frame Upholstered with Mesh fabric and mounted on main assembly, pure leather, 100% polyester fabric, nylon with poly olefin elastomer, Leatherite, N.A, Polyester mesh with fibreglass plastic frame
<b>Material of Fabric of Seat Cover</b>	100% polyester fabric	foam laminated mesh fabrics, Mesh Fabrics, pure leather, leatherite, 100% polyester fabric, N.A, Fire retardant fabric

	GSM/Thickness of fabric ±5%(Gram/Square meter)	290 gram	*
GENERAL	<b>Chair Type</b>	central tilt	*
	Tilt Tension Adjustment	Yes	*
	<b>Height Adjustment ± 5(mm)</b>	up to 120 mm	up to 100 mm, up to 120 mm, N.A, up to 90 mm, up to 65 mm
	<b>Arm</b>	With	With, Without
	<b>Type of backrest support</b>	Backrest With Adjustable Lumber Support	backrest with lumber support of polypropylene at multilevel across back, backrest symmetrical lumber support, Backrest With Adjustable Lumber Support, Countered lumber supporting
	<b>Arm Type</b>	Adjustable	Adjustable, Fixed, NA
	Colour of Fabric for Seat and Backrest	black	*
	<b>Ergonomic Seat Design</b>	Yes	Yes, No
	<b>Back type</b>	fixed	push back, fixed, height adjustable
	Backrest is made of two pcs injection moulded frame	Backrest is made of two pcs injection moulded frame	*
	<b>backrest has separate adjustable headrest</b>	No	Yes, No
	<b>Seat type</b>	fixed	fixed, sliding
	Seat is curved	Yes	*
	Locking mechanism	Yes	*
	Type of locking	upright locking	*
	<b>Number of arm movement</b>	2(up & down)	2(up & down), 4(up & down end left & right), 6(Up & Down,Left & Right And Swivel), 8(Up & Down,Left & Right,Swivel And Front & Back), N.A, 6 (UP and down, front and back, swivel), 4 (UP and down, front and back)
	<b>Lumber support</b>	external & adjustable	integrated, external & fixed, external & adjustable, N.A, Cushioned and upholstered Lumbar Support
DIMENSION	<b>Overall Chair Height ±15mm</b>	1180	*
	<b>Backrest Height ±15mm</b>	600	*
	<b>Backrest Width ±10mm</b>	500	*
	<b>Seat Height ±15 mm</b>	450	420, 450, 480, 500, 520
	<b>Seat Width ±10 mm</b>	480	440, 480, 500, 520, 550, 460, 360, 415
	<b>Seat Depth ±10 mm</b>	520	400, 460, 480, 500, 520, 550, 420, 440, 540, 360
	<b>Thickness of MS Plate</b>	0.6	*

	<b>Joining the under structure with Seat</b>		
	<b>Thickness of Plywood used in Seat ±1(mm)</b>	12 mm	12 mm, 15 mm, 18 mm, N.A, 65 mm
	<b>Thickness of Plywood used in Backrest ± 1(mm)</b>	N.A	12 mm, 15 mm, 18 mm, N.A
	Padestal Size (Diameter in mm) +/- 10 mm	650	*
	<b>Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)</b>	35 mm	*
	<b>Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)</b>	N.A	*
WARANTEE	<b>Warrantee period in number of years</b>	1-year	1-year, 2-year, 3-year, 4-year, 5-year
CERTIFICATION	<b>Test reports to be furnished to buyer on demand</b>	YES	YES, NO
	<b>BIFMA Certification</b>	YES	YES, NO
	<b>OEM of offered product is ISO 9001:2015 certified</b>	YES	YES, NO
	<b>OEM of offered product is ISO 14001:2015 certified</b>	YES	YES, NO
	<b>OEM of offered product is ISO 18001:2007 certified</b>	YES	YES, NO
	<b>Green guard certification</b>	YES	YES, NO
	<b>Aiota</b>	-	YES, NO

\* Specifications highlighted in bold are the Golden Parameters.

\* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.

#### Additional Specification Documents

#### Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporting Officer	Address	Quantity	Delivery Days
1	Asit Kumar Sahoo	768028,DRDA OFFICE NEAR PRIVATE BUS STAND, BARGARH PIN-768028 -	5	15

#### Bid Specific Additional Terms and Conditions

- 1.Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.
- 2.Dedicated /toll Free Telephone No. for Service Support : BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.
- 3.Escalation Matrix For Service Support : Bidder/OEM must provide Escalation Matrix of Telephone Numbers for

Service Support.

[This Bid is also governed by the General Terms and Conditions](#)

**---Thank You---**