

Bid Number: GEM/2020/B/701190

Dated: 07-07-2020

Bid Document

Bia Document			
Bid Details			

EMD Detail

Required	No

ePBG Detail

Required	No
----------	----

Splitting

Bid splitting not applied.

Revolving Chair (2 pieces)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
MATERIAL	Pedestal Base	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size
	Arm Material	Steel covered with polypropelene	Steel covered with polypropelene
	seat material	PU Foam covered with Fabric	PU Foam covered with Fabric
	Density of PU foam used in seat KG per Cu Meter (+/- 3)	35	*
	Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	40	*
	Material of Fabric Back Cover / Material for Backrest	100% polyester fabric	100% polyester fabric
	Material of Fabric of Seat Cover	100% polyester fabric	100% polyester fabric
	GSM/Thickness of fabric ±5%(Gram/Square meter)	220 gram	*
GENERAL	Chair Type	push back	push back
	Tilt Tension Adjustment	Yes	*
	Height Adjustment ± 5(mm)	up to 120 mm	up to 120 mm
	Arm	With	With
	Type of backrest support	backrest symmetrical lumber support	backrest symmetrical lumber support
	Arm Type	Fixed	Fixed
	Colour of Fabric for Seat and Backrest	As per Buyer's choice	*
	Ergonomic Seat Design	Yes	Yes
	Back type	push back	push back
	Backrest is made of two pcs injection moulded frame	Backrest is made of two pcs injection moulded frame	*
	backrest has separate adjustable headrest	No	No
	Seat type	fixed	fixed

	Seat is curved	Yes	*
	Locking mechanism	Yes	*
	Type of locking	N.A	*
	Number of arm movement	N.A	N.A
	Lumber support	N.A	N.A
DIMENSION	Overall Chair Height ±15mm	860	860
	Backrest Height ±15mm	410	410.0
	Backrest Width ±10mm	440	440.0
	Seat Height ±15 mm	420	420
	Seat Width ±10 mm	440	440
	Seat Depth ±10 mm	460	460.0
	Thickness of MS Plate Joining the under structure with Seat	2	2.0
	Thickness of Plywood used in Seat ±1(mm)	12 mm	12 mm
	Thickness of Plywood used in Backrest ± 1(mm)	N.A	N.A
	Padestal Size (Diameter in mm) +/- 10 mm	680	*
	Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)	N.A	N.A
	Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)	N.A	N.A
WARANTEE	Warrantee period in number of years	1-year	1-year
CERTIFICATION	Test reports to be furnished to buyer on demand	YES	YES
	BIFMA Certification	NO	NO
	OEM of offered product is ISO 9001:2015 certified	YES	YES
	OEM of offered	NO	NO

product is ISO 14001:2015 certified		
OEM of offered product is ISO 18001:2007 certified	NO	NO
Green guard certification	NO	NO
Aiota	-	NO

^{*} Specifications highlighted in bold are the Golden Parameters.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	Vasundhara Mahadev Morudkar	400085,CENTRAL STORES UNIT, BARC, TROMBAY, MUMBAI	2	30

Bid Specific Additional Terms and Conditions

1. Scope of supply (Bid price to include all cost components) : Supply Installation Testing and Commissioning of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---

^{*} Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement (allowed Values) by the Buyer.