

Bid Number: GEM/2020/B/712120

Dated: 15-07-2020

Bid Document

Bid Document			
Bid Details			
Bid End Date/Time	25-07-2020 18:00:00		
Bid Opening Date/Time	25-07-2020 18:30:00		
Bid Life Cycle (From Publish Date)	90 (Days)		
Bid Offer Validity (From End Date)	75 (Days)		
Ministry/State Name	Gujarat		
Department Name	Health & Family Welfare Department Gujarat		
Organisation Name	N/a		
Office Name	Distric Panchayat Navsari(Health Branch)		
Total Quantity	3		
Item Category	Patient Bed (Fowler and Semi Fowler)		
MSE Exemption for Years of Experience and Turnover	No		
Startup Exemption for Years of Experience and Turnover	No		
Bid to RA enabled	No		
Inspection Required	No		

EMD Detail

Required	No

ePBG Detail

Required	No

Splitting

Bid splitting not applied.

Patient Bed (Fowler And Semi Fowler) (3 pieces)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
Performance Parameters	Type of bed	Fowler	Fowler
	Number of bed platform sections	4 for fowler bed	4 for fowler bed
	Availability of Backrest section	Yes	*
	Backrest section linkage	welded with MS CRCA tube (14 G)	*
	Availability of Leg section	Yes	Yes
	Leg section linkage	welded with MS CRCA tube (16 G)	welded with MS CRCA tube (16 G)
	Mattress platform shall be perforated	Yes	*
	Screw mechanism	welded with ERW MS tube (18 G) in M.S. cover made from (16 G) ERW tube	*
	Manual adjustments	Backrest , knee rest through two screw systems with thrust bearings individually manouvred by two handles for fowler bed	Backrest , knee rest through two screw systems with thrust bearings individually manouvred by two handles for fowler bed
	Back rest - min 45 % of the frame length	Yes	*
	The bottom end of the H legs are provided with PVC shoes	NA in case of bed with castors	NA in case of bed with castors
	The bed has head & foot panels detachable by hand without need of any tool	Yes	*
	Saline rod provision	four locations on the bed platform to hold stainless steel Telescopic Saline rod 12mm dia with 15.87 mm dia x 1.2 mm (18 G) stainless steel	*
	Provision for mounting of syringe pump	outer covering tube with a knob to mount syringe pump	*
	Finishing & workmanship shall be	Yes	*

	of high standard		
	All corners shall be rounded off so that there shall be no sharp corners and holes should be burr free	Yes	*
	Coating for metal parts	M.S. tubular parts, linkages, flats are to be In-house, pretreated / shot blasted and Epoxy powder coated with coating thickness 50 to 100 microns	*
	Material of handle	Plastic	Plastic
	Number of detachable moulded PP with PVC insert head and foot side panels	4	*
	Provision of castors	H' Type Legs with 600 mm Height with 125 mm(5") dia High Grade Synthetic Body Castors, two with brake, two w/o brake	
	Number of hooks in Telescopic I V Pole	2	2
	Urine Bag Holder	Yes	*
	Moulded Chart Holder	Yes	*
	Provision of mattress	Yes	*
	Number of sections in mattress	4 for fowler bed	4 for fowler bed
	Provision of collapsible Railing	Yes	Yes
Material and Dimensional Parameters	Overall Length of bed in mm with 5% tolerance	2050 to 2100	*
	Overall width of bed in mm with 5% tolerance	900 to 950	*
	Size of Buffer in mm	100	100
	Bed Platform frame size with 5% tolerance	2070 mm L x 910 mm W	*
	Mattress Platform size with 5% tolerance	1970 mm L x 790 mm W	*
	Buffer to Handle Length with 5% tolerance	NA for foldable and detachable bed	*
	Fixed Height	600 mm	*

Material and size of section	1.2 mm (18 G) CRCA M.S perforated sheet top	*
Overall length of Back Rest	775-800	775-800
Overall width of back rest	775-800	*
Overall length of Knee Rest	450-500	450-500
Overall width of Knee Rest	800-825	800-825
Overall length of Leg Rest	600-650	*
Overall width of Leg Rest	775-800	775-800
Overall length of Fix Section	100-150	100-150
Overall width of fix section	775-800	775-800
Raised Backrest Angle	65°	*
Raised Kneerest Angle	40°	*
Bed frame tube size	60 mm x 30 mm x 1.6 mm (16 G) Thick ERW tube	*
Dimensions for Fitting of frame	ERW tubes diameter 31.75 mm x 1.2 mm (18 G) thick and diameter 22.22 mm x 1.2 mm (18 G) thick and MS sheet having thickness 3.0 mm (11 G)	*
Diameter of Four corner rubber buffers in mm	75	*
Material of head and foot panels	ABS Plastic	*
Diameter of MS tubular in mm	30 to 50 mm	*
Diameter of SS Laminated	30 to 50 mm	*
Patient Working Load	135 Kg	*
Safe Working Load	150 Kg	*
Thickness of PU foam of mattress in inch	4	*
Density of PU foam of	40	*

	mattress in Kg/m3		
	Material of mattress cover of mattress	PVC	*
	Colour of mattress cover	Blue	Blue
	Material of collapsing railing	MS	MS
	Types of collapsing railing	Collapsable	Collapsable
Reports	Manufacturer Certificates	ISO 9001:2015	*
	Details of manufacturer certificates such as number and date	-	*
	Availability of certificates of quality system	ISO 13485	*
	Availability of test report from govt/ NABL/ILAC accredited lab covering all parameters	No	Yes, No
	Test report number , Incase test reports not availabble , put NA	-	*
	Test report date, Incase test reports not availabble , put NA	-	*
	Name of test lab , Incase test reports not availabble , put NA	-	*
	Address of test lab , Incase test reports not availabble , put NA	-	*
	Copies of all certifications and reports to be provided to buyer on demand at time of supplies	NA ,Incase test reports not availabble	Yes, NA ,Incase test reports not availabble

^{*} Specifications highlighted in bold are the Golden Parameters.

Additional Specification Documents

Consignees/Reporting Officer and Quantity

^{*} Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement (allowed Values) by the Buyer.

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	Akhilesh Rajbali	396445,3rd Floor, District Panchayat Bhavan, Juna Thana, B/h Court Building	3	15

Bid Specific Additional Terms and Conditions

1. Scope of supply (Bid price to include all cost components) : Supply Installation Testing and Commissioning of Goods

This Bid is also governed by the General Terms and Conditions

---Thank You---