

Bid Number: GEM/2020/B/708564

Dated: 13-07-2020

# **Bid Document**

Bid Document				
Bid Details				
Bid End Date/Time	23-07-2020 17:00:00			
Bid Opening Date/Time	23-07-2020 17:30:00			
Bid Life Cycle (From Publish Date)	90 (Days)			
Bid Offer Validity (From End Date)	30 (Days)			
Ministry/State Name	Jammu & Kashmir			
Department Name	Housing And Urban Development Department Jammu And Kashmir			
Organisation Name	N/a			
Office Name	Directorate Of Urban Local Bodies Kashmir			
Total Quantity	1			
Item Category	Backhoe Loaders			
Bidder Turnover (Last 3 Years)	14 Lakh (s)			
OEM Average Turnover (Last 3 Years)	14 Lakh (s)			
MSE Exemption for Years of Experience and Turnover	No			
Startup Exemption for Years of Experience and Turnover	No			
Document required from seller	Bidder Turnover,OEM Annual Turnover *In case any bidder is seeking exemption from Experience / Turnover Criteria, the supporting documents to prove his eligibility for exemption must be uploaded for evaluation by the buyer			
Bid to RA enabled	No			
Inspection Required	No			

## **EMD Detail**

11		
l I Required	l No	
Neguii eu	INO	
11 .		

#### ePBG Detail

Required	No
----------	----

# Splitting

Bid splitting not applied.

1. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.

# **Backhoe Loaders (1 pieces)**

#### **Technical Specifications**

## \* As per GeM Category Specification

Specification	Specification Name	Values	Bid Requirement (Allowed Values)
Certification Parameters	Vehicle Certification	ARAI	*
	Vehicle Certification ARAI/VRDE/ICAT No	-	*
	Compliance to IS 20474-4 for EARTH- MOVING MACHINERY—SAFETY REQUIREMENTS FOR BACKHOE LOADERS	Yes	*
	On Buyer's Demand,Test certificate	Yes	*
Generic Parameters	Engine Model	-	*
	Engine Maximum HP (BHP@ RPM) (range)	71-90	71-90
	Engine Maximum HP (BHP@ RPM)	80	*
	Engine Rated RPM	2200	*
	No of Cylinders (Nos)	4	*
	Engine Bore (mm)	102	*
	Engine Stroke (mm)	120	*
	Engine Cooling System	Water Cooled	*
	Max Torque (N- m@rpm)	325	325.0 - 430.0 Or higher
	Fuel Injection system	-	*
	Torque Backup (%)REM)-III A	-	*

Vehicle Emission Complaince	BS III	BS III, BS IV Or higher	
Vehicle Mileage ( declared by OEM as certified by Test Agency under Rule of CMVR 1989) (Km/Ltr)	4.5	*	
No of Air Cleaner	2	*	
No of Fuel Filters	2	*	
Type of Gear Box	Synchroshuttle type	*	
No of speeds Forward (Nos)	4	*	
Maximum Forward Speed (Km/hr)	40.44	*	
Maximum Reverse Speed (Km/Hr)	11.22	*	
Minimum Forward Speed (Km/Hr)	5.78	*	
Minimum Reverse Speed (Km/Hr)	7	*	
Power Steering	Yes	Yes	
Steering wheel dia (mm)	380	*	
Brake type	Disc Type(Oil submerged)	*	
Specific Fuel Consumption (SFC)in g/hp/hv (g/hp/hv)	254	*	
Minimum Turning Radius (mtrs or mm) with brakes	7950	*	
Minimum Turning Radius (mtrs or mm) without brakes	8900	*	
Fuel Tank Capacity (Litres)	128	*	
Fuel Tank Oil Pan Capacity (Litres)	14.5	*	
Type of Wheel Drive	Two wheel Drive	Two wheel Drive, Four Wheel Drive	
Front Tyre Size with ply rating (mm)	-	*	
Rear tyer Size with ply rating (mm)	-	*	
Minimum Ground Clearance (mm)	350	More than 350.0 Or higher	

Doolshoo Duolsot Width	752	*	
Backhoe Bucket Width	752		
Backhoe Bucket Capacities in Cubic Metre with locking/bolted teeth	0.26	More than 0.26 Or higher	
Backhoe Bucket Digging Depth	4.702	4.702	
Backhoe Bucket Digging Force in Kgf	5685	More than 5685.0 Or higher	
"Backhoe Bucket Dipper Tear out Force in Kgf"	3220	More than 3220.0 Or higher	
"Backhoe Bucket Loading Height in metres"	4.1-4.5	4.1-4.5 Or higher	
Backhoe Bucket Loading Reach in metres	5.7-8	5.7-8 Or higher	
"Backhoe Bucket Reach from swing Pivot"	2012	*	
Type of Loader Bucket	Bottom Dump Bucket	Bottom Dump Bucket	
Loader Bucket Minimum Capacity	1.1	More than 1.1 Or higher	
Loader Bucket Dump height in metres	2.51-2.80	2.51-2.80, 2.81-3.10 Or higher	
Loader Arm Break out Force in kgf	6580	More than 6580.0 Or higher	
Loader Bucket Maximum reach at full height in meter	1.341	1.341 - 1.5 Or higher	
Loader Bucket Pay Load in kgs	1920	1920.0	
Loader Bucket Dig depth	110	More than 110.0 Or higher	
Operating Weight (Kgs)	7800	7800	
Transmission Oil Capacity (Litres)	16	*	
Hydraulic Oil Capacity (Litres)	86	*	
Hydraulic Oil change period	2500	More than 2500.0 Or higher	
Di-Ethyl Ether Type Cold starting Kit (to start the CI engine upto -25°C)	No	*	

	Rock Breaker	No	*
	Rock Breaker Operating Weight	NA for without Rock Breaker	*
	Rock Breaker Operating Pressure (Kgf/cm2)	NA for without Rock Breaker	*
	Rock Breaker Strike rate (350 blows per minute)min	NA for without Rock Breaker	*
Constructional	Instrument Panel	Yes	*
Parameters	Hour Meter	Yes	*
	Fuel Gauge	Yes	*
	Temperature Gauge	Yes	*
	Battery Charge Indicator	Yes	*
	Horn	Yes	*
	Oil Pressure Gauge	Yes	*
	Battery Type	Dry	*
	Battery Rating	-	*
	Electrical Alternator	-	*
	Electrical Starter	-	*
	Front Lights	Yes	*
	Rear Lights	Yes	*
	Parking Lights	Yes	*
	Brake Lights	Yes	*
	Plough Lights	No	*
	Indicators Lights	Yes	*
	Overall Length (mm)	5915	*
	Overall Width (mm)	2352	2352.0
	Overall Height (mm)	3563	*
	Wheel Base (mm)	2150	2150.0
	Cabin/canopy All round visible cabin With easy Walk Through Access	Yes	Yes
	Cabin Instumental panel with audio indicators	Yes	*
	Cabin Instumental panel with visual indicators	Yes	*
	Rear view large convex mirror	Yes	*

	Front screen wiper	Yes	*
	Front and rear horn	Yes	*
	Seating Plan Co- Adjustable driver seat with one helper seat	Yes	*
	Doors Front door with fixed toughened glass & amp; locking mechanism with wiper	Yes	*
	Glasses	Yes	*
	Paint Standard automobile paint to the exterior body as per CVMR rules	Yes	*
Performance Parameters	Noise level at operator s ear level (dB)	85	*
	Vibration at seat	No	*
	Vibration at seat (if yes) (micron)	0	*
	Average travel speed (Km/hr)	20	*
	Average fuel consumption (litre/hr)	10	*
	Average distance travelled per litre of fuel(Km)	2	*
	Excavator loader to perform various functions such as digging	Yes	*
	Dozing,	Yes	*
	Grabbing,	Yes	*
	Grading	Yes	*
	Loading	Yes	*
	Spreading	Yes	*
	Warranty Time (Month)	12	12.0
	Operating hours during warranty period	2000	2000.0
* Chariffeetiana highligh	Battery Warranty (months)	12	12.0

<sup>\*</sup> Specifications highlighted in bold are the Golden Parameters.

\* Bidders may note that In respect of non-golden Parameters, the specifications 'Values' chosen by Buyer will generally be preferred over 'Bid requirement ( allowed Values) by the Buyer.

#### **Additional Specification Documents**

## **Consignees/Reporting Officer and Quantity**

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	Mushtaq Ahmad Parry	193222,Habitat Centre Bemina Srinagar	1	120

# **Bid Specific Additional Terms and Conditions**

- 1. Scope of supply (Bid price to include all cost components) : Supply Installation Testing and Commissioning of Goods
- 2. OEM Turn Over Criteria: The minimum average annual financial turnover of the OEM of the offered product during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the OEM is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria. In case of bunch bids, the OEM of CATEGORY RELATED TO primary product having highest bid value should meet this criterion.
- 3. Bidder Turn Over Criteria: The minimum average annual financial turnover of the bidder during the last three years, ending on 31st March of the previous financial year, should be as indicated in the bid document. Documentary evidence in the form of certified Audited Balance Sheets of relevant periods or a certificate from the Chartered Accountant / Cost Accountant indicating the turnover details for the relevant period shall be uploaded with the bid. In case the date of constitution / incorporation of the bidder is less than 3 year old, the average turnover in respect of the completed financial years after the date of constitution shall be taken into account for this criteria.
- 4. Dedicated /toll Free Telephone No. for Service Support : BIDDER/OEM must have Dedicated/toll Free Telephone No. for Service Support.
- 5. Availability of Service Centres: Bidder/OEM must have a Functional Service Centre in the State of each Consignee's Location in case of carry-in warranty. (Not applicable in case of goods having on-site warranty). If service center is not already there at the time of bidding, successful bidder / OEM shall have to establish one within 30 days of award of contract. Payment shall be released only after submission of documentary evidence of having Functional Service Centre.

This Bid is also governed by the General Terms and Conditions

---Thank You---