

The Buildroot user manual

Table of Contents

[I. Getting started](#)

- [1. About Buildroot](#)
- [2. System requirements](#)
 - [2.1. Mandatory packages](#)
 - [2.2. Optional packages](#)
- [3. Getting Buildroot](#)
- [4. Buildroot quick start](#)
- [5. Community resources](#)

[II. User guide](#)

- [6. Buildroot configuration](#)
 - [6.1. Cross-compilation toolchain](#)
 - [6.2. /dev management](#)
 - [6.3. init system](#)
- [7. Configuration of other components](#)
- [8. General Buildroot usage](#)
 - [8.1. *make* tips](#)
 - [8.2. Understanding when a full rebuild is necessary](#)
 - [8.3. Understanding how to rebuild packages](#)
 - [8.4. Offline builds](#)
 - [8.5. Building out-of-tree](#)
 - [8.6. Environment variables](#)
 - [8.7. Dealing efficiently with filesystem images](#)
 - [8.8. Graphing the dependencies between packages](#)
 - [8.9. Graphing the build duration](#)
 - [8.10. Graphing the filesystem size contribution of packages](#)
 - [8.11. Integration with Eclipse](#)
 - [8.12. Advanced usage](#)
- [9. Project-specific customization](#)
 - [9.1. Recommended directory structure](#)
 - [9.2. Keeping customizations outside of Buildroot](#)
 - [9.3. Storing the Buildroot configuration](#)
 - [9.4. Storing the configuration of other components](#)
 - [9.5. Customizing the generated target filesystem](#)
 - [9.6. Adding custom user accounts](#)
 - [9.7. Customization *after* the images have been created](#)
 - [9.8. Adding project-specific patches](#)
 - [9.9. Adding project-specific packages](#)
 - [9.10. Quick guide to storing your project-specific customizations](#)
- [10. Frequently Asked Questions & Troubleshooting](#)
 - [10.1. The boot hangs after *Starting network...*](#)
 - [10.2. Why is there no compiler on the target?](#)
 - [10.3. Why are there no development files on the target?](#)
 - [10.4. Why is there no documentation on the target?](#)
 - [10.5. Why are some packages not visible in the Buildroot config menu?](#)
 - [10.6. Why not use the target directory as a chroot directory?](#)
 - [10.7. Why doesn't Buildroot generate binary packages \(.deb, .ipkg...\)?](#)
 - [10.8. How to speed-up the build process?](#)
- [11. Known issues](#)
- [12. Legal notice and licensing](#)
 - [12.1. Complying with open source licenses](#)
 - [12.2. Complying with the Buildroot license](#)
- [13. Beyond Buildroot](#)
 - [13.1. Boot the generated images](#)
 - [13.2. Chroot](#)

[III. Developer guide](#)

- [14. How Buildroot works](#)
- [15. Coding style](#)
 - [15.1. `Config.in` file](#)
 - [15.2. The `.mk` file](#)
 - [15.3. The documentation](#)
 - [15.4. Support scripts](#)
- [16. Adding support for a particular board](#)
- [17. Adding new packages to Buildroot](#)
 - [17.1. Package directory](#)
 - [17.2. Config files](#)
 - [17.3. The `.mk` file](#)
 - [17.4. The `.hash` file](#)

- [17.5. Infrastructure for packages with specific build systems](#)
- [17.6. Infrastructure for autotools-based packages](#)
- [17.7. Infrastructure for CMake-based packages](#)
- [17.8. Infrastructure for Python packages](#)
- [17.9. Infrastructure for LuaRocks-based packages](#)
- [17.10. Infrastructure for Perl/CPAN packages](#)
- [17.11. Infrastructure for virtual packages](#)
- [17.12. Infrastructure for packages using kconfig for configuration files](#)
- [17.13. Infrastructure for rebar-based packages](#)
- [17.14. Infrastructure for Waf-based packages](#)
- [17.15. Infrastructure for packages building kernel modules](#)
- [17.16. Infrastructure for asciidoc documents](#)
- [17.17. Infrastructure specific to the Linux kernel package](#)
- [17.18. Hooks available in the various build steps](#)
- [17.19. Gettext integration and interaction with packages](#)
- [17.20. Tips and tricks](#)
- [17.21. Conclusion](#)
- [18. Patching a package](#)
 - [18.1. Providing patches](#)
 - [18.2. How patches are applied](#)
 - [18.3. Format and licensing of the package patches](#)
 - [18.4. Integrating patches found on the Web](#)
- [19. Download infrastructure](#)
- [20. Debugging Buildroot](#)
- [21. Contributing to Buildroot](#)
 - [21.1. Reproducing, analyzing and fixing bugs](#)
 - [21.2. Analyzing and fixing autobuild failures](#)
 - [21.3. Reviewing and testing patches](#)
 - [21.4. Work on items from the TODO list](#)
 - [21.5. Submitting patches](#)
 - [21.6. Reporting issues/bugs or getting help](#)
- [22. DEVELOPERS file and get-developers](#)
- [IV. Appendix](#)
 - [23. Makedev syntax documentation](#)
 - [24. Makeusers syntax documentation](#)
 - [25. Migrating from older Buildroot versions](#)
 - [25.1. Migrating to 2016.11](#)
 - [25.2. Migrating to 2017.08](#)

List of Examples

- 17.1. [Config script: *divine* package](#)
- 17.2. [Config script: *imagemagick* package:](#)

Buildroot 2017.11 manual generated on 2017-11-30 21:37:09 UTC from git revision 9dd76697cc

The Buildroot manual is written by the Buildroot developers. It is licensed under the GNU General Public License, version 2. Refer to the [COPYING](#) file in the Buildroot sources for the full text of this license.

Copyright © 2004-2017 The Buildroot developers



Part I. Getting started

Chapter 1. About Buildroot

Buildroot is a tool that simplifies and automates the process of building a complete Linux system for an embedded system, using cross-compilation.

In order to achieve this, Buildroot is able to generate a cross-compilation toolchain, a root filesystem, a Linux kernel image and a bootloader for your target. Buildroot can be used for any combination of these options, independently (you can for example use an existing cross-compilation toolchain, and build only your root filesystem with Buildroot).

Buildroot is useful mainly for people working with embedded systems. Embedded systems often use processors that are not the regular x86 processors everyone is used to having in his PC. They can be PowerPC processors, MIPS processors, ARM processors, etc.

Buildroot支持许多处理器及其变体;

Buildroot supports numerous processors and their variants; it also comes with default configurations for several boards available off-the-shelf. Besides this, a number of third-party projects are based on, or develop their BSP ^[1] or SDK ^[2] on top of Buildroot.

^[1]BSP: Board Support Package

^[2]SDK: Software Development Kit

Chapter 2. System requirements

Buildroot is designed to run on Linux systems.

虽然Buildroot本身将构建编译所需的大多数主机包，但某些标准Linux实用程序预计已经安装在主机系统上。While Buildroot itself will build most host packages it needs for the compilation, certain standard Linux utilities are expected to be already installed on the host system. Below you will find an overview of the mandatory and optional packages (note that package names may vary between distributions).

2.1. Mandatory packages

- Build tools:

- `which`
- `sed`
- `make` (version 3.81 or any later)
- `binutils`
- `build-essential` (only for Debian based systems)
- `gcc` (version 2.95 or any later)
- `g++` (version 2.95 or any later)
- `bash`
- `patch`
- `gzip`
- `bzip2`
- `perl` (version 5.8.7 or any later)
- `tar`
- `cpio`
- `python` (version 2.6 or any later)
- `unzip`
- `rsync`
- `file` (must be in `/usr/bin/file`)
- `bc`

- Source fetching tools:

- `wget`

2.2. Optional packages

- Configuration interface dependencies:

For these libraries, you need to install both runtime and development data, which in many distributions are packaged separately. The development packages typically have a *-dev* or *-devel* suffix.

- `ncurses5` to use the *menuconfig* interface
- `qt4` to use the *xconfig* interface
- `glib2`, `gtk2` and `glade2` to use the *gconfig* interface

- Source fetching tools:

In the official tree, most of the package sources are retrieved using `wget` from *ftp*, *http* or *https* locations. A few packages are only available through a version control system. Moreover, Buildroot is capable of downloading sources via other tools, like `rsync` or `scp` (refer to [Chapter 19, Download infrastructure](#) for more details). If you enable packages using any of these methods, you will need to install the corresponding tool on the host system:

- `bazaar`
- `cvs`
- `git`
- `mercurial`
- `rsync`
- `scp`
- `subversion`

- Java-related packages, if the Java Classpath needs to be built for the target system:

- The `javac` compiler
- The `jar` tool

- Documentation generation tools:

- `asciidoc`, version 8.6.3 or higher
- `w3m`
- `python` with the `argparse` module (automatically present in 2.7+ and 3.2+)
- `dblatex` (required for the pdf manual only)

- Graph generation tools:

- `graphviz` to use *graph-depends* and *<pkg>-graph-depends*
- `python-matplotlib` to use *graph-build*

Chapter 3. Getting Buildroot

Buildroot releases are made every 3 months, in February, May, August and November. Release numbers are in the format YYYY.MM, so for example 2013.02, 2014.08.

Release tarballs are available at <http://buildroot.org/downloads/>.

For your convenience, a [Vagrantfile](#) is available in `support/misc/Vagrantfile` in the Buildroot source tree to quickly set up a virtual machine with the needed dependencies to get started.

If you want to setup an isolated buildroot environment on Linux or Mac Os X, paste this line onto your terminal:

```
curl -O https://buildroot.org/downloads/Vagrantfile; vagrant up
```

If you are on Windows, paste this into your powershell:

```
(new-object System.Net.WebClient).DownloadFile(  
    "https://buildroot.org/downloads/Vagrantfile", "Vagrantfile");  
vagrant up
```

If you want to follow development, you can use the daily snapshots or make a clone of the Git repository. Refer to the [Download page](#) of the Buildroot website for more details.

Chapter 4. Buildroot quick start

Important: you can and should **build everything as a normal user**. There is no need to be root to configure and use Buildroot. By running all commands as a regular user, you protect your system against packages behaving badly during compilation and installation.

The first step when using Buildroot is to create a configuration. Buildroot has a nice configuration tool similar to the one you can find in the [Linux kernel](#) or in [BusyBox](#).

From the buildroot directory, run

```
$ make menuconfig
```

for the original curses-based configurator, or

```
$ make nconfig
```

for the new curses-based configurator, or

```
$ make xconfig
```

for the Qt-based configurator, or

```
$ make gconfig
```

for the GTK-based configurator.

所有这些“make”命令都需要构建一个配置实用程序(包括接口),因此您可能需要为配置实用程序使用的相关库安装“development”包。

All of these “make” commands will need to build a configuration utility (including the interface), so you may need to install “development” packages for relevant libraries used by the configuration utilities. Refer to [Chapter 2, System requirements](#) for more details, specifically the [optional requirements Section 2.2, “Optional packages”](#) to get the dependencies of your favorite interface.

For each menu entry in the configuration tool, you can find associated help that describes the purpose of the entry. Refer to [Chapter 6, Buildroot configuration](#) for details on some specific configuration aspects.

Once everything is configured, the configuration tool generates a `.config` file that contains the entire configuration. This file will be read by the top-level Makefile.

To start the build process, simply run:

```
$ make
```

You **should never** use `make -jN` with Buildroot: top-level parallel make is currently not supported. Instead, use the `BR2_JLEVEL` option to tell Buildroot to run the compilation of each individual package with `make -jN`.

The `make` command will generally perform the following steps:

- download source files (as required);
- configure, build and install the cross-compilation toolchain, or simply import an external toolchain;
- configure, build and install selected target packages;
- build a kernel image, if selected;
- build a bootloader image, if selected;
- create a root filesystem in selected formats.

Buildroot output is stored in a single directory, `output/`. This directory contains several subdirectories:

- `images/` where all the images (kernel image, bootloader and root filesystem images) are stored. These are the files you need to put on your target system.
- `build/` where all the components are built (this includes tools needed by Buildroot on the host and packages compiled for the target). This directory contains one subdirectory for each of these components.
- `staging/` which contains a hierarchy similar to a root filesystem hierarchy. This directory contains the headers and libraries of the cross-compilation toolchain and all the userspace packages selected for the

target. However, this directory is *not* intended to be the root filesystem for the target: it contains a lot of development files, unstripped binaries and libraries that make it far too big for an embedded system. These development files are used to compile libraries and applications for the target that depend on other libraries.

- `target/` which contains *almost* the complete root filesystem for the target: everything needed is present except the device files in `/dev/` (Buildroot can't create them because Buildroot doesn't run as root and doesn't want to run as root). Also, it doesn't have the correct permissions (e.g. `setuid` for the `busybox` binary). Therefore, this directory **should not be used on your target**. Instead, you should use one of the images built in the `images/` directory. If you need an extracted image of the root filesystem for booting over NFS, then use the tarball image generated in `images/` and extract it as root. Compared to `staging/`, `target/` contains only the files and libraries needed to run the selected target applications: the development files (headers, etc.) are not present, the binaries are stripped.
- `host/` contains the installation of tools compiled for the host that are needed for the proper execution of Buildroot, including the cross-compilation toolchain.

These commands, `make menuconfig|nconfig|gconfig|xconfig` and `make`, are the basic ones that allow to easily and quickly generate images fitting your needs, with all the features and applications you enabled.

More details about the "make" command usage are given in [Section 8.1, "make tips"](#).

Chapter 5. Community resources

Like any open source project, Buildroot has different ways to share information in its community and outside.

Each of those ways may interest you if you are looking for some help, want to understand Buildroot or contribute to the project.

Mailing List

Buildroot has a mailing list for discussion and development. It is the main method of interaction for Buildroot users and developers.

Only subscribers to the Buildroot mailing list are allowed to post to this list. You can subscribe via the [mailing list info page](#).

Mails that are sent to the mailing list are also available in the [mailing list archives](#) and via [Gmane](#), at gmane.comp.lib.uclibc.buildroot. Please search the mailing list archives before asking questions, since there is a good chance someone else has asked the same question before.

IRC

The Buildroot IRC channel [#buildroot](#) is hosted on [Freenode](#). It is a useful place to ask quick questions or discuss on certain topics.

When asking for help on IRC, share relevant logs or pieces of code using a code sharing website, such as <http://code.bulix.org>.

Note that for certain questions, posting to the mailing list may be better as it will reach more people, both developers and users.

Bug tracker

Bugs in Buildroot can be reported via the mailing list or alternatively via the [Buildroot bugtracker](#). Please refer to [Section 21.6, "Reporting issues/bugs or getting help"](#) before creating a bug report.

Wiki

[The Buildroot wiki page](#) is hosted on the [eLinux](#) wiki. It contains some useful links, an overview of past and upcoming events, and a TODO list.

Patchwork Patchwork是一个基于网络的补丁跟踪系统，旨在促进对开源项目的贡献和管理。

Patchwork is a web-based patch tracking system designed to facilitate the contribution and management of contributions to an open-source project. Patches that have been sent to a mailing list are 'caught' by the system, and appear on a web page. Any comments posted that reference the patch are appended to the patch page too. For more information on Patchwork see <http://jk.ozlabs.org/projects/patchwork/>.

Buildroot's Patchwork website is mainly for use by Buildroot's maintainer to ensure patches aren't missed. It is also used by Buildroot patch reviewers (see also [Section 21.3.1, "Applying Patches from Patchwork"](#)). However, since the website exposes patches and their corresponding review comments in a clean and concise web interface, it can be useful for all Buildroot developers.

The Buildroot patch management interface is available at <http://patchwork.buildroot.org>.

Part II. User guide

Chapter 6. Buildroot configuration

All the configuration options in `make *config` have a help text providing details about the option.

The `make *config` commands also offer a search tool. Read the help message in the different frontend menus to know how to use it:

- in `menuconfig`, the search tool is called by pressing `/`;
- in `xconfig`, the search tool is called by pressing `Ctrl + f`.

The result of the search shows the help message of the matching items. In `menuconfig`, numbers in the left column provide a shortcut to the corresponding entry. Just type this number to directly jump to the entry, or to the containing menu in case the entry is not selectable due to a missing dependency.

Although the menu structure and the help text of the entries should be sufficiently self-explanatory, a number of topics require additional explanation that cannot easily be covered in the help text and are therefore covered in the following sections.

6.1. Cross-compilation toolchain

编译工具链是一组工具，允许您为系统编译代码。

A compilation toolchain is the set of tools that allows you to compile code for your system. It consists of a compiler (in our case, `gcc`), binary `utils` like assembler and linker (in our case, `binutils`) and a C standard library (for example `GNU Libc`, `uClibc-ng`). n. 跑龙套 (util 的复数)

The system installed on your development station certainly already has a compilation toolchain that you can use to compile an application that runs on your system. If you're using a PC, your compilation toolchain runs on an x86 processor and generates code for an x86 processor. Under most Linux systems, the compilation toolchain uses the GNU libc (`glibc`) as the C standard library. This compilation toolchain is called the "host compilation toolchain". The machine on which it is running, and on which you're working, is called the "host system" ^[3].

The compilation toolchain is provided by your distribution, and Buildroot has nothing to do with it (other than using it to build a cross-compilation toolchain and other tools that are run on the development host).

As said above, the compilation toolchain that comes with your system runs on and generates code for the processor in your host system. As your embedded system has a different processor, you need a cross-compilation toolchain - a compilation toolchain that runs on your *host system* but generates code for your *target system* (and target processor). For example, if your host system uses x86 and your target system uses ARM, the regular compilation toolchain on your host runs on x86 and generates code for x86, while the cross-compilation toolchain runs on x86 and generates code for ARM.

Buildroot provides two solutions for the cross-compilation toolchain:

- The **internal toolchain backend**, called `Buildroot toolchain` in the configuration interface.
- The **external toolchain backend**, called `External toolchain` in the configuration interface.

The choice between these two solutions is done using the `Toolchain Type` option in the `Toolchain` menu. Once one solution has been chosen, a number of configuration options appear, they are detailed in the following sections.

6.1.1. Internal toolchain backend

The *internal toolchain backend* is the backend where Buildroot builds by itself a cross-compilation toolchain, before building the userspace applications and libraries for your target embedded system.

This backend supports several C libraries: `uClibc-ng`, `glibc` and `musl`.

Once you have selected this backend, a number of options appear. The most important ones allow to:

- Change the version of the Linux kernel headers used to build the toolchain. This item deserves a few explanations. In the process of building a cross-compilation toolchain, the C library is being built. This library provides the interface between userspace applications and the Linux kernel. In order to know how to "talk" to the Linux kernel, the C library needs to have access to the *Linux kernel headers* (i.e. the `.h` files from the kernel), which define the interface between userspace and the kernel (system calls, data structures, etc.). Since this interface is backward compatible, the version of the Linux kernel headers used to build your toolchain do not need to match *exactly* the version of the Linux kernel you intend to run on your embedded system. They only need to have a version equal or older to the version of the Linux kernel you intend to run. If you use kernel headers that are more recent than the Linux kernel you run on your embedded system, then the C library might be using interfaces that are not provided by your Linux kernel.

- Change the version of the GCC compiler, binutils and the C library.
- Select a number of toolchain options (uClibc only): whether the toolchain should have RPC support (used mainly for NFS), wide-char support, locale support (for internationalization), C++ support or thread support. Depending on which options you choose, the number of userspace applications and libraries visible in Buildroot menus will change: many applications and libraries require certain toolchain options to be enabled. Most packages show a comment when a certain toolchain option is required to be able to enable those packages. If needed, you can further refine the uClibc configuration by running `make uclibc-menuconfig`. Note however that all packages in Buildroot are tested against the default uClibc configuration bundled in Buildroot: if you deviate from this configuration by removing features from uClibc, some packages may no longer build.

It is worth noting that whenever one of those options is modified, then the entire toolchain and system must be rebuilt. See [Section 8.2, “Understanding when a full rebuild is necessary”](#).

Advantages of this backend:

- Well integrated with Buildroot
- Fast, only builds what’s necessary

Drawbacks of this backend:

- Rebuilding the toolchain is needed when doing `make clean`, which takes time. If you’re trying to reduce your build time, consider using the *External toolchain backend*.

6.1.2. External toolchain backend

The *external toolchain backend* allows to use existing pre-built cross-compilation toolchains. Buildroot knows about a number of well-known cross-compilation toolchains (from [Linaro](#) for ARM, [Sourcery CodeBench](#) for ARM, x86-64, PowerPC, and MIPS, and is capable of downloading them automatically, or it can be pointed to a custom toolchain, either available for download or installed locally.

Then, you have three solutions to use an external toolchain:

- Use a predefined external toolchain profile, and let Buildroot download, extract and install the toolchain. Buildroot already knows about a few CodeSourcery and Linaro toolchains. Just select the toolchain profile in `Toolchain` from the available ones. This is definitely the easiest solution.
- Use a predefined external toolchain profile, but instead of having Buildroot download and extract the toolchain, you can tell Buildroot where your toolchain is already installed on your system. Just select the toolchain profile in `Toolchain` through the available ones, unselect `Download toolchain automatically`, and fill the `Toolchain path` text entry with the path to your cross-compiling toolchain.
- Use a completely custom external toolchain. This is particularly useful for toolchains generated using crosstool-NG or with Buildroot itself. To do this, select the `Custom toolchain` solution in the `Toolchain` list. You need to fill the `Toolchain path`, `Toolchain prefix` and `External toolchain C library` options. Then, you have to tell Buildroot what your external toolchain supports. If your external toolchain uses the *glibc* library, you only have to tell whether your toolchain supports C++ or not and whether it has built-in RPC support. If your external toolchain uses the *uClibc* library, then you have to tell Buildroot if it supports RPC, wide-char, locale, program invocation, threads and C++. At the beginning of the execution, Buildroot will tell you if the selected options do not match the toolchain configuration.

Our external toolchain support has been tested with toolchains from CodeSourcery and Linaro, toolchains generated by [crosstool-NG](#), and toolchains generated by Buildroot itself. In general, all toolchains that support the *sysroot* feature should work. If not, do not hesitate to contact the developers.

[编译二进制工具连接器汇编链接器](#)

We do not support toolchains or SDK generated by OpenEmbedded or Yocto, because these toolchains are not pure toolchains (i.e. just the compiler, `binutils`, the C and C++ libraries). Instead these toolchains come with a very large set of pre-compiled libraries and programs. Therefore, Buildroot cannot import the *sysroot* of the toolchain, as it would contain hundreds of megabytes of pre-compiled libraries that are normally built by Buildroot.

We also do not support using the distribution toolchain (i.e. the gcc/binutils/C library installed by your distribution) as the toolchain to build software for the target. This is because your distribution toolchain is not a "pure" toolchain (i.e. only with the C/C++ library), so we cannot import it properly into the Buildroot build environment. So even if you are building a system for a x86 or x86_64 target, you have to generate a cross-compilation toolchain with Buildroot or crosstool-NG.

If you want to generate a custom toolchain for your project, that can be used as an external toolchain in Buildroot, our recommendation is definitely to build it with [crosstool-NG](#). We recommend to build the toolchain separately from Buildroot, and then *import* it in Buildroot using the external toolchain backend.

Advantages of this backend:

- Allows to use well-known and well-tested cross-compilation toolchains.
- Avoids the build time of the cross-compilation toolchain, which is often very significant in the overall build time of an embedded Linux system.

避免了交叉编译工具链的构建时间，这在嵌入式Linux系统的总体构建时间中通常是非常重要的

Drawbacks of this backend:

- If your pre-built external toolchain has a bug, may be hard to get a fix from the toolchain vendor, unless you build your external toolchain by yourself using Crosstool-NG.

External toolchain wrapper

When using an external toolchain, Buildroot generates a wrapper program, that transparently passes the appropriate options (according to the configuration) to the external toolchain programs. In case you need to debug this wrapper to check exactly what arguments are passed, you can set the environment variable

`BR2_DEBUG_WRAPPER` to either one of:

- 0, empty or not set: no debug
- 1: trace all arguments on a single line
- 2: trace one argument per line

6.2. /dev management

On a Linux system, the `/dev` directory contains special files, called *device files*, that allow userspace applications to access the hardware devices managed by the Linux kernel. Without these *device files*, your userspace applications would not be able to use the hardware devices, even if they are properly recognized by the Linux kernel. 如果没有这些设备文件，您的用户空间应用程序将无法使用硬件设备，即使它们被Linux内核正确地识别。

Under System configuration, /dev management, Buildroot offers four different solutions to handle the `/dev` directory :

- The first solution is **Static using device table**. This is the old classical way of handling device files in Linux. With this method, the device files are persistently stored in the root filesystem (i.e. they persist across reboots), and there is nothing that will automatically create and remove those device files when hardware devices are added or removed from the system. Buildroot therefore creates a standard set of device files using a *device table*, the default one being stored in `system/device_table_dev.txt` in the Buildroot source code. This file is processed when Buildroot generates the final root filesystem image, and the *device files* are therefore not visible in the `output/target` directory. The `BR2_ROOTFS_STATIC_DEVICE_TABLE` option allows to change the default device table used by Buildroot, or to add an additional device table, so that additional *device files* are created by Buildroot during the build. So, if you use this method, and a *device file* is missing in your system, you can for example create a `board/<yourcompany>/<yourproject>/device_table_dev.txt` file that contains the description of your additional *device files*, and then you can set `BR2_ROOTFS_STATIC_DEVICE_TABLE to system/device_table_dev.txt board/<yourcompany>/<yourproject>/device_table_dev.txt`. For more details about the format of the device table file, see [Chapter 23. Makedev syntax documentation](#).
- The second solution is **Dynamic using devtmpfs only**. *devtmpfs* is a virtual filesystem inside the Linux kernel that has been introduced in kernel 2.6.32 (if you use an older kernel, it is not possible to use this option). When mounted in `/dev`, this virtual filesystem will automatically make *device files* appear and disappear as hardware devices are added and removed from the system. This filesystem is not persistent across reboots: it is filled dynamically by the kernel. Using *devtmpfs* requires the following kernel configuration options to be enabled: `CONFIG_DEVTMPFS` and `CONFIG_DEVTMPFS_MOUNT`. When Buildroot is in charge of building the Linux kernel for your embedded device, it makes sure that those two options are enabled. However, if you build your Linux kernel outside of Buildroot, then it is your responsibility to enable those two options (if you fail to do so, your Buildroot system will not boot).
- The third solution is **Dynamic using devtmpfs + mdev**. This method also relies on the *devtmpfs* virtual filesystem detailed above (so the requirement to have `CONFIG_DEVTMPFS` and `CONFIG_DEVTMPFS_MOUNT` enabled in the kernel configuration still apply), but adds the *mdev* userspace utility on top of it. *mdev* is a program part of BusyBox that the kernel will call every time a device is added or removed. Thanks to the `/etc/mdev.conf` configuration file, *mdev* can be configured to for example, set specific permissions or ownership on a device file, call a script or application whenever a device appears or disappear, etc. Basically, it allows *userspace* to react on device addition and removal events. *mdev* can for example be used to automatically load kernel modules when devices appear on the system. *mdev* is also important if you have devices that require a firmware, as it will be responsible for pushing the firmware contents to the kernel. *mdev* is a lightweight implementation (with fewer features) of *udev*. For more details about *mdev* and the syntax of its configuration file, see <http://git.busybox.net/busybox/tree/docs/mdev.txt>.

- The fourth solution is **Dynamic using devtmpfs + eudev**. This method also relies on the *devtmpfs* virtual filesystem detailed above, but adds the *eudev* userspace daemon on top of it. *eudev* is a daemon that runs in the background, and gets called by the kernel when a device gets added or removed from the system. It is a more heavyweight solution than *mdev*, but provides higher flexibility. *eudev* is a standalone version of *udev*, the original userspace daemon used in most desktop Linux distributions, which is now part of Systemd. For more details, see <http://en.wikipedia.org/wiki/Udev>.

The Buildroot developers recommendation is to start with the **Dynamic using devtmpfs only** solution, until you have the need for userspace to be notified when devices are added/removed, or if firmwares are needed, in which case **Dynamic using devtmpfs + mdev** is usually a good solution.

Note that if *systemd* is chosen as init system, /dev management will be performed by the *udev* program provided by *systemd*.

6.3. init system

The *init* program is the first userspace program started by the kernel (it carries the PID number 1), and is responsible for starting the userspace services and programs (for example: web server, graphical applications, other network servers, etc.).

Buildroot allows to use three different types of init systems, which can be chosen from *System configuration*, *Init system*:

- The first solution is **BusyBox**. Amongst many programs, BusyBox has an implementation of a basic *init* program, which is sufficient for most embedded systems. Enabling the *BR2_INIT_BUSYBOX* will ensure BusyBox will build and install its *init* program. This is the default solution in Buildroot. The BusyBox *init* program will read the */etc/inittab* file at boot to know what to do. The syntax of this file can be found in <http://git.busybox.net/busybox/tree/examples/inittab> (note that BusyBox *inittab* syntax is special: do not use a random *inittab* documentation from the Internet to learn about BusyBox *inittab*). The default *inittab* in Buildroot is stored in *system/skeleton/etc/inittab*. Apart from mounting a few important filesystems, the main job the default *inittab* does is to start the */etc/init.d/rcS* shell script, and start a *getty* program (which provides a login prompt).
- The second solution is **systemV**. This solution uses the old traditional *sysvinit* program, packed in Buildroot in *package/sysvinit*. This was the solution used in most desktop Linux distributions, until they switched to more recent alternatives such as Upstart or Systemd. *sysvinit* also works with an *inittab* file (which has a slightly different syntax than the one from BusyBox). The default *inittab* installed with this *init* solution is located in *package/sysvinit/inittab*.
- The third solution is **systemd**. *systemd* is the new generation *init* system for Linux. It does far more than traditional *init* programs: aggressive parallelization capabilities, uses socket and D-Bus activation for starting services, offers on-demand starting of daemons, keeps track of processes using Linux control groups, supports snapshotting and restoring of the system state, etc. *systemd* will be useful on relatively complex embedded systems, for example the ones requiring D-Bus and services communicating between each other. It is worth noting that *systemd* brings a fairly big number of large dependencies: *dbus*, *udev* and more. For more details about *systemd*, see <http://www.freedesktop.org/wiki/Software/systemd>.

The solution recommended by Buildroot developers is to use the **BusyBox init** as it is sufficient for most embedded systems. **systemd** can be used for more complex situations.

^[3]This terminology differs from what is used by GNU configure, where the host is the machine on which the application will run (which is usually the same as target)

Chapter 7. Configuration of other components

Before attempting to modify any of the components below, make sure you have already configured Buildroot itself, and have enabled the corresponding package.

BusyBox

If you already have a BusyBox configuration file, you can directly specify this file in the Buildroot configuration, using *BR2_PACKAGE_BUSYBOX_CONFIG*. Otherwise, Buildroot will start from a default BusyBox configuration file.

To make subsequent changes to the configuration, use *make busybox-menuconfig* to open the BusyBox configuration editor.

It is also possible to specify a BusyBox configuration file through an environment variable, although this is not recommended. Refer to [Section 8.6, “Environment variables”](#) for more details.

uClibc

Configuration of uClibc is done in the same way as for BusyBox. The configuration variable to specify an existing configuration file is `BR2_UCLIBC_CONFIG`. The command to make subsequent changes is `make uclibc-menuconfig`.

Linux kernel

If you already have a kernel configuration file, you can directly specify this file in the Buildroot configuration, using `BR2_LINUX_KERNEL_USE_CUSTOM_CONFIG`.

If you do not yet have a kernel configuration file, you can either start by specifying a defconfig in the Buildroot configuration, using `BR2_LINUX_KERNEL_USE_DEFCONFIG`, or start by creating an empty file and specifying it as custom configuration file, using `BR2_LINUX_KERNEL_USE_CUSTOM_CONFIG`.

To make subsequent changes to the configuration, use `make linux-menuconfig` to open the Linux configuration editor.

Barebox

Configuration of Barebox is done in the same way as for the Linux kernel. The corresponding configuration variables are `BR2_TARGET_BAREBOX_USE_CUSTOM_CONFIG` and `BR2_TARGET_BAREBOX_USE_DEFCONFIG`. To open the configuration editor, use `make barebox-menuconfig`.

U-Boot

Configuration of U-Boot (version 2015.04 or newer) is done in the same way as for the Linux kernel. The corresponding configuration variables are `BR2_TARGET_UBOOT_USE_CUSTOM_CONFIG` and `BR2_TARGET_UBOOT_USE_DEFCONFIG`. To open the configuration editor, use `make uboot-menuconfig`.

Chapter 8. General Buildroot usage

8.1. *make* tips

This is a collection of tips that help you make the most of Buildroot. 这是一组技巧，帮助你充分利用Buildroot。

Display all commands executed by make:

```
$ make V=1 <target>
```

Display the list of boards with a defconfig:

```
$ make list-defconfigs
```

Display all available targets:

```
$ make help
```

Not all targets are always available, some settings in the `.config` file may hide some targets:

- `busybox-menuconfig` only works when `busybox` is enabled;
- `linux-menuconfig` and `linux-savedefconfig` only work when `linux` is enabled;
- `uClibc-menuconfig` is only available when the uClibc C library is selected in the internal toolchain backend;
- `barebox-menuconfig` and `barebox-savedefconfig` only work when the `barebox` bootloader is enabled.
- `uboot-menuconfig` and `uboot-savedefconfig` only work when the `U-Boot` bootloader is enabled.

Cleaning: Explicit cleaning is required when any of the architecture or toolchain configuration options are changed.

To delete all build products (including build directories, host, staging and target trees, the images and the toolchain):

```
$ make clean
```

Generating the manual: The present manual sources are located in the `docs/manual` directory. To generate the manual:

```
$ make manual-clean
$ make manual
```

The manual outputs will be generated in *output/docs/manual*.

Notes

- A few tools are required to build the documentation (see: [Section 2.2, “Optional packages”](#)).

Resetting Buildroot for a new target: To delete all build products as well as the configuration:

```
$ make distclean
```

Notes. If `ccache` is enabled, running `make clean` or `distclean` does not empty the compiler cache used by Buildroot. To delete it, refer to [Section 8.12.3, “Using ccache in Buildroot”](#).

Dumping the internal make variables: One can dump all the variables known to make, along with their values:

```
$ make -s printvars
VARIABLE=value_of_variable
...
```

It is possible to tweak the output using some variables:

- `VARS` will limit the listing to variables which names match the specified make-pattern
- `QUOTED_VARS`, if set to `YES`, will single-quote the value
- `RAW_VARS`, if set to `YES`, will print the unexpanded value

For example:

```
$ make -s printvars VARS=BUSYBOX_%DEPENDENCIES
BUSYBOX_DEPENDENCIES=skeleton toolchain
BUSYBOX_FINAL_ALL_DEPENDENCIES=skeleton toolchain
BUSYBOX_FINAL_DEPENDENCIES=skeleton toolchain
BUSYBOX_FINAL_PATCH_DEPENDENCIES=
BUSYBOX_RDEPENDENCIES=ncurses util-linux
```

n. 骨架，骨骼；纲要；骨瘦如柴的人
adj. 骨骼的；骨瘦如柴的；概略的

```
$ make -s printvars VARS=BUSYBOX_%DEPENDENCIES QUOTED_VARS=YES
BUSYBOX_DEPENDENCIES='skeleton toolchain'
BUSYBOX_FINAL_ALL_DEPENDENCIES='skeleton toolchain'
BUSYBOX_FINAL_DEPENDENCIES='skeleton toolchain'
BUSYBOX_FINAL_PATCH_DEPENDENCIES=''
BUSYBOX_RDEPENDENCIES='ncurses util-linux'
```

```
$ make -s printvars VARS=BUSYBOX_%DEPENDENCIES RAW_VARS=YES
BUSYBOX_DEPENDENCIES=skeleton toolchain
BUSYBOX_FINAL_ALL_DEPENDENCIES=$(sort $(BUSYBOX_FINAL_DEPENDENCIES) $(BUSYBOX_FINAL_PATCH_DEPENDENCIES))
BUSYBOX_FINAL_DEPENDENCIES=$(sort $(BUSYBOX_DEPENDENCIES))
BUSYBOX_FINAL_PATCH_DEPENDENCIES=$(sort $(BUSYBOX_PATCH_DEPENDENCIES))
BUSYBOX_RDEPENDENCIES=ncurses util-linux
```

The output of quoted variables can be reused in shell scripts, for example:

```
$ eval $(make -s printvars VARS=BUSYBOX_DEPENDENCIES QUOTED_VARS=YES)
$ echo $BUSYBOX_DEPENDENCIES
skeleton toolchain
```

8.2. Understanding when a full rebuild is necessary

Buildroot does not attempt to detect what parts of the system should be rebuilt when the system configuration is changed through `make menuconfig`, `make xconfig` or one of the other configuration tools. In some cases, Buildroot should rebuild the entire system, in some cases, only a specific subset of packages. But detecting this in a completely reliable manner is very difficult, and therefore the Buildroot developers have decided to simply not attempt to do this.

Instead, it is the responsibility of the user to know when a full rebuild is necessary. As a hint, here are a few rules of thumb that can help you understand how to work with Buildroot:

相反，用户有责任知道什么时候需要进行完整的重新构建。 作为提示，这里有一些经验法则可以帮助你理解如何使用Buildroot:

- When the target architecture configuration is changed, a complete rebuild is needed. **Changing the architecture variant, the binary format or the floating point strategy for example has an impact on the entire system.** 例如，更改架构变体、二进制格式或浮点策略会对整个系统产生影响。
- When the toolchain configuration is changed, a complete rebuild generally is needed. Changing the toolchain configuration often involves changing the compiler version, the type of C library or its configuration, or some other fundamental configuration item, and these changes **have an impact on the entire system.** 对整个系统产生影响。
- When an additional package is added to the configuration, a full rebuild is not necessarily needed. Buildroot will detect that this package has never been built, and will build it. However, if this package is a library that can optionally be used by packages that have already been built, Buildroot will not automatically rebuild those. Either you know which packages should be rebuilt, and you can rebuild them manually, or you should do a full rebuild. For example, let's suppose you have built a system with the `ctorrent` package, but without `openssl`. Your system works, but you realize you would like to have SSL support in `ctorrent`, so you enable the `openssl` package in Buildroot configuration and restart the build. Buildroot will detect that `openssl` should be built and will be build it, but it will not detect that `ctorrent` should be rebuilt to benefit from `openssl` to add OpenSSL support. You will either have to do a full rebuild, or rebuild `ctorrent` itself.
- When a package is removed from the configuration, Buildroot does not do anything special. It does not remove the files installed by this package from the target root filesystem or from the toolchain `sysroot`. A full rebuild is needed to get rid of this package. However, generally you don't necessarily need this package to be removed right now: you can wait for the next lunch break to restart the build from scratch.
- When the sub-options of a package are changed, the package is not automatically rebuilt. After making such changes, rebuilding only this package is often sufficient, unless enabling the package sub-option adds some features to the package that are useful for another package which has already been built. Again, Buildroot does not track when a package should be rebuilt: once a package has been built, it is never rebuilt unless explicitly told to do so.
- When a change to the root filesystem skeleton is made, a full rebuild is needed. However, when changes to the root filesystem overlay, a post-build script or a post-image script are made, there is no need for a full rebuild: a simple `make` invocation will take the changes into account.

Generally speaking, when you're facing a build error and you're unsure of the potential consequences of the configuration changes you've made, do a full rebuild. If you get the same build error, then you are sure that the error is not related to partial rebuilds of packages, and if this error occurs with packages from the official Buildroot, do not hesitate to report the problem! As your experience with Buildroot progresses, you will progressively learn when a full rebuild is really necessary, and you will save more and more time.

For reference, a full rebuild is achieved by running:

```
$ make clean all
```

8.3. Understanding how to rebuild packages

One of the most common questions asked by Buildroot users is how to rebuild a given package or how to remove a package without rebuilding everything from scratch.

Removing a package is unsupported by Buildroot without rebuilding from scratch. This is because Buildroot doesn't keep track of which package installs what files in the `output/staging` and `output/target` directories, or which package would be compiled differently depending on the availability of another package.

The easiest way to rebuild a single package from scratch is to remove its build directory in `output/build`. Buildroot will then re-extract, re-configure, re-compile and re-install this package from scratch. You can ask buildroot to do this with the `make <package>-dirclean` command.

On the other hand, if you only want to restart the build process of a package from its compilation step, you can run `make <package>-rebuild`, followed by `make` or `make <package>`. It will restart the compilation and installation of the package, but not from scratch: it basically re-executes `make` and `make install` inside the package, so it will only rebuild files that changed.

If you want to restart the build process of a package from its configuration step, you can run `make <package>-reconfigure`, followed by `make` or `make <package>`. It will restart the configuration, compilation and installation of the package.

Internally, Buildroot creates so-called *stamp files* to keep track of which build steps have been completed for each package. They are stored in the package build directory, `output/build/<package>-<version>/` and are named `.stamp_<step-name>`. The commands detailed above simply manipulate these stamp files to force Buildroot to restart a specific set of steps of a package build process.

Further details about package special make targets are explained in [Section 8.12.5. “Package-specific make targets”](#).

8.4. Offline builds

If you intend to do an offline build and just want to download all sources that you previously selected in the configurator (*menuconfig*, *nconfig*, *xconfig* or *gconfig*), then issue:

```
$ make source
```

You can now disconnect or copy the content of your `dl` directory to the build-host.

8.5. Building out-of-tree

As default, everything built by Buildroot is stored in the directory `output` in the Buildroot tree.

Buildroot also supports building out of tree with a syntax similar to the Linux kernel. To use it, add `O=<directory>` to the make command line:

```
$ make O=/tmp/build
```

Or:

```
$ cd /tmp/build; make O=$PWD -C path/to/buildroot
```

All the output files will be located under `/tmp/build`. If the `o` path does not exist, Buildroot will create it.

Note: the `o` path can be either an absolute or a relative path, but if it's passed as a relative path, it is important to note that it is interpreted relative to the main Buildroot source directory, **not** the current working directory.

When using out-of-tree builds, the Buildroot `.config` and temporary files are also stored in the output directory. This means that you can safely run multiple builds in parallel using the same source tree as long as they use unique output directories.

For ease of use, Buildroot generates a Makefile wrapper in the output directory - so after the first run, you no longer need to pass `O=<...>` and `-C <...>`, simply run (in the output directory):

```
$ make <target>
```

8.6. Environment variables

Buildroot also honors some environment variables, when they are passed to `make` or set in the environment:

- `HOSTCXX`, the host C++ compiler to use
- `HOSTCC`, the host C compiler to use
- `UCLIBC_CONFIG_FILE=<path/to/.config>`, path to the uClibc configuration file, used to compile uClibc, if an internal toolchain is being built. Note that the uClibc configuration file can also be set from the configuration interface, so through the Buildroot `.config` file; this is the recommended way of setting it.
- `BUSYBOX_CONFIG_FILE=<path/to/.config>`, path to the BusyBox configuration file. Note that the BusyBox configuration file can also be set from the configuration interface, so through the Buildroot `.config` file; this is the recommended way of setting it.
- `BR2_CCACHE_DIR` to override the directory where Buildroot stores the cached files when using ccache.
- `BR2_DL_DIR` to override the directory in which Buildroot stores/retrieves downloaded files. Note that the Buildroot download directory can also be set from the configuration interface, so through the Buildroot `.config` file. See [Section 8.12.4, “Location of downloaded packages”](#) for more details on how you can set the download directory.
- `BR2_GRAPH_ALT`, if set and non-empty, to use an alternate color-scheme in build-time graphs
- `BR2_GRAPH_OUT` to set the filetype of generated graphs, either `pdf` (the default), or `png`.
- `BR2_GRAPH_DEPS_OPTS` to pass extra options to the dependency graph; see [Section 8.8, “Graphing the dependencies between packages”](#) for the accepted options
- `BR2_GRAPH_DOT_OPTS` is passed verbatim as options to the `dot` utility to draw the dependency graph.

An example that uses config files located in the toplevel directory and in your \$HOME:

```
$ make UCLIBC_CONFIG_FILE=uClibc.config BUSYBOX_CONFIG_FILE=$HOME/bb.config
```

If you want to use a compiler other than the default `gcc` or `g++` for building helper-binaries on your host, then do

```
$ make HOSTCXX=g++-4.3-HEAD HOSTCC=gcc-4.3-HEAD
```

8.7. Dealing efficiently with filesystem images

Filesystem images can get pretty big, depending on the filesystem you choose, the number of packages, whether you provisioned free space... Yet, some locations in the filesystems images may just be *empty* (e.g. a long run of zeroes); such a file is called a *sparse* file.

Most tools can handle sparse files efficiently, and will only store or write those parts of a sparse file that are not empty.

For example:

- `tar` accepts the `-s` option to tell it to only store non-zero blocks of sparse files:
 - `tar cf archive.tar -s [files...]` will efficiently store sparse files in a tarball
 - `tar xf archive.tar -s` will efficiently store sparse files extracted from a tarball
- `cp` accepts the `--sparse=WHEN` option (`WHEN` is one of `auto`, `never` or `always`):
 - `cp --sparse=always source.file dest.file` will make `dest.file` a sparse file if `source.file` has long runs of zeroes

Other tools may have similar options. **Please consult their respective man pages.** 请参阅他们各自的手册页。

You can use sparse files if you need to store the filesystem images (e.g. to transfer from one machine to another), or if you need to send them (e.g. to the Q&A team).

Note however that flashing a filesystem image to a device while using the sparse mode of `dd` may result in a broken filesystem (e.g. the block bitmap of an ext2 filesystem may be corrupted; or, if you have sparse files in your filesystem, those parts may not be all-zeroes when read back). **You should only use sparse files when handling files on the build machine, not when transferring them to an actual device that will be used on the target.** 您应该只在处理构建机器上的文件时使用稀疏文件，而不是在将它们传输到将在目标上使用的实际设备时。

8.8. Graphing the dependencies between packages

One of Buildroot's jobs is to know the dependencies between packages, and make sure they are built in the right order. These dependencies can sometimes be quite complicated, and for a given system, it is often not easy to understand why such or such package was brought into the build by Buildroot.

In order to help understanding the dependencies, and therefore better understand what is the role of the different components in your embedded Linux system, Buildroot is capable of generating dependency graphs.

To generate a dependency graph of the full system you have compiled, simply run:

```
make graph-depends
```

You will find the generated graph in `output/graphs/graph-depends.pdf`.

If your system is quite large, the dependency graph may be too complex and difficult to read. It is therefore possible to generate the dependency graph just for a given package:

```
make <pkg>-graph-depends
```

You will find the generated graph in `output/graph/<pkg>-graph-depends.pdf`.

Note that the dependency graphs are generated using the `dot` tool from the *Graphviz* project, which you must have installed on your system to use this feature. In most distributions, it is available as the `graphviz` package.

By default, the dependency graphs are generated in the PDF format. However, by passing the `BR2_GRAPH_OUT` environment variable, you can switch to other output formats, such as PNG, PostScript or SVG. All formats supported by the `-T` option of the `dot` tool are supported.


```
BR2_GRAPH_OUT=svg make graph-depends
```

The `graph-depends` behaviour can be controlled by setting options in the `BR2_GRAPH_DEPS_OPTS` environment variable. The accepted options are:

- `--depth N`, `-d N`, to limit the dependency depth to `N` levels. The default, `0`, means no limit.
- `--stop-on PKG`, `-s PKG`, to stop the graph on the package `PKG`. `PKG` can be an actual package name, a glob, the keyword *virtual* (to stop on virtual packages), or the keyword *host* (to stop on host packages). The package is still present on the graph, but its dependencies are not.
- `--exclude PKG`, `-x PKG`, like `--stop-on`, but also omits `PKG` from the graph.
- `--transitive`, `--no-transitive`, to draw (or not) the transitive dependencies. The default is to not draw transitive dependencies.
- `--colours R,T,H`, the comma-separated list of colours to draw the root package (`R`), the target packages (`T`) and the host packages (`H`). Defaults to: `lightblue, grey, gainsboro`

```
BR2_GRAPH_DEPS_OPTS='-d 3 --no-transitive --colours=red,green,blue' make graph-depends
```

8.9. Graphing the build duration

When the build of a system takes a long time, it is sometimes useful to be able to understand which packages are the longest to build, to see if anything can be done to speed up the build. In order to help such build time analysis, Buildroot collects the build time of each step of each package, and allows to generate graphs from this data.

To generate the build time graph after a build, run:

```
make graph-build
```

This will generate a set of files in `output/graphs` :

- `build.hist-build.pdf`, a histogram of the build time for each package, ordered in the build order.
- `build.hist-duration.pdf`, a histogram of the build time for each package, ordered by duration (longest first)
- `build.hist-name.pdf`, a histogram of the build time for each package, order by package name.
- `build.pie-packages.pdf`, a pie chart of the build time per package
- `build.pie-steps.pdf`, a pie chart of the global time spent in each step of the packages build process.

This `graph-build` target requires the Python Matplotlib and Numpy libraries to be installed (`python-matplotlib` and `python-numpy` on most distributions), and also the `argparse` module if you're using a Python version older than 2.7 (`python-argparse` on most distributions).

By default, the output format for the graph is PDF, but a different format can be selected using the `BR2_GRAPH_OUT` environment variable. The only other format supported is PNG:

```
BR2_GRAPH_OUT=png make graph-build
```

8.10. Graphing the filesystem size contribution of packages

When your target system grows, it is sometimes useful to understand how much each Buildroot package is contributing to the overall root filesystem size. To help with such an analysis, Buildroot collects data about files installed by each package and using this data, generates a graph and CSV files detailing the size contribution of the different packages.

To generate these data after a build, run:

```
make graph-size
```

This will generate:

- `output/graphs/graph-size.pdf`, a pie chart of the contribution of each package to the overall root filesystem size
- `output/graphs/package-size-stats.csv`, a CSV file giving the size contribution of each package to the overall root filesystem size

- `output/graphs/file-size-stats.csv`, a CSV file giving the size contribution of each installed file to the package it belongs, and to the overall filesystem size.

This `graph-size` target requires the Python Matplotlib library to be installed (`python-matplotlib` on most distributions), and also the `argparse` module if you're using a Python version older than 2.7 (`python-argparse` on most distributions).

Just like for the duration graph, a `BR2_GRAPH_OUT` environment is supported to adjust the output file format. See [Section 8.8. “Graphing the dependencies between packages”](#) for details about this environment variable.

Note. The collected filesystem size data is only meaningful after a complete clean rebuild. Be sure to run `make clean all` before using `make graph-size`.

To compare the root filesystem size of two different Buildroot compilations, for example after adjusting the configuration or when switching to another Buildroot release, use the `size-stats-compare` script. It takes two `file-size-stats.csv` files (produced by `make graph-size`) as input. Refer to the help text of this script for more details:

```
utils/size-stats-compare -h
```

8.11. Integration with Eclipse

While a part of the embedded Linux developers like classical text editors like Vim or Emacs, and command-line based interfaces, a number of other embedded Linux developers like richer graphical interfaces to do their development work. Eclipse being one of the most popular Integrated Development Environment, Buildroot integrates with Eclipse in order to ease the development work of Eclipse users.

Our integration with Eclipse simplifies the compilation, remote execution and remote debugging of applications and libraries that are built on top of a Buildroot system. It does not integrate the Buildroot configuration and build processes themselves with Eclipse. Therefore, the typical usage model of our Eclipse integration would be:

- Configure your Buildroot system with `make menuconfig`, `make xconfig` or any other configuration interface provided with Buildroot.
- Build your Buildroot system by running `make`.
- Start Eclipse to develop, execute and debug your own custom applications and libraries, that will rely on the libraries built and installed by Buildroot.

The Buildroot Eclipse integration installation process and usage is described in detail at <https://github.com/mbats/eclipse-buildroot-bundle/wiki>.

8.12. Advanced usage

8.12.1. Using the generated toolchain outside Buildroot

You may want to compile, for your target, your own programs or other software that are not packaged in Buildroot. In order to do this you can use the toolchain that was generated by Buildroot.

The toolchain generated by Buildroot is located by default in `output/host/`. The simplest way to use it is to add `output/host/bin/` to your `PATH` environment variable and then to use `ARCH-linux-gcc`, `ARCH-linux-objdump`, `ARCH-linux-ld`, etc.

It is possible to relocate the toolchain - but then `--sysroot` must be passed every time the compiler is called to tell where the libraries and header files are.

It is also possible to generate the Buildroot toolchain in a directory other than `output/host` by using the `Build options → Host dir` option. This could be useful if the toolchain must be shared with other users.

8.12.2. Using gdb in Buildroot

Buildroot allows to do cross-debugging, where the debugger runs on the build machine and communicates with `gdbserver` on the target to control the execution of the program.

To achieve this:

- If you are using an *internal toolchain* (built by Buildroot), you must enable `BR2_PACKAGE_HOST_GDB`, `BR2_PACKAGE_GDB` and `BR2_PACKAGE_GDB_SERVER`. This ensures that both the cross `gdb` and `gdbserver` get built, and that `gdbserver` gets installed to your target.

- If you are using an *external toolchain*, you should enable `BR2_TOOLCHAIN_EXTERNAL_GDB_SERVER_COPY`, which will copy the gdbserver included with the external toolchain to the target. If your external toolchain does not have a cross gdb or gdbserver, it is also possible to let Buildroot build them, by enabling the same options as for the *internal toolchain backend*.

Now, to start debugging a program called `foo`, you should run on the target:

```
gdbserver :2345 foo
```

This will cause `gdbserver` to listen on TCP port 2345 for a connection from the cross gdb.

Then, on the host, you should start the cross gdb using the following command line:

```
<buildroot>/output/host/bin/<tuple>-gdb -x <buildroot>/output/staging/usr/share/buildroot/gdbinit foo
```

Of course, `foo` must be available in the current directory, built with debugging symbols. Typically you start this command from the directory where `foo` is built (and not from `output/target/` as the binaries in that directory are stripped).

The `<buildroot>/output/staging/usr/share/buildroot/gdbinit` file will tell the cross gdb where to find the libraries of the target.

Finally, to connect to the target from the cross gdb:

```
(gdb) target remote <target ip address>:2345
```

8.12.3. Using `ccache` in Buildroot

`ccache` is a compiler cache. It stores the object files resulting from each compilation process, and is able to skip future compilation of the same source file (with same compiler and same arguments) by using the pre-existing object files. When doing almost identical builds from scratch a number of times, it can nicely speed up the build process.

`ccache` support is integrated in Buildroot. You just have to enable `Enable compiler cache` in `Build options`. This will automatically build `ccache` and use it for every host and target compilation.

The cache is located in `$HOME/.buildroot-ccache`. It is stored outside of Buildroot output directory so that it can be shared by separate Buildroot builds. If you want to get rid of the cache, simply remove this directory.

You can get statistics on the cache (its size, number of hits, misses, etc.) by running `make ccache-stats`.

The make target `ccache-options` and the `CCACHE_OPTIONS` variable provide more generic access to the ccache. For example

```
# set cache limit size
make CCACHE_OPTIONS="--max-size=5G" ccache-options

# zero statistics counters
make CCACHE_OPTIONS="--zero-stats" ccache-options
```

`ccache` makes a hash of the source files and of the compiler options. If a compiler option is different, the cached object file will not be used. Many compiler options, however, contain an absolute path to the staging directory. Because of this, building in a different output directory would lead to many cache misses.

To avoid this issue, buildroot has the `Use relative paths` option (`BR2_CCACHE_USE_BASEDIR`). This will rewrite all absolute paths that point inside the output directory into relative paths. Thus, changing the output directory no longer leads to cache misses.

A disadvantage of the relative paths is that they also end up to be relative paths in the object file. Therefore, for example, the debugger will no longer find the file, unless you `cd` to the output directory first.

See [the ccache manual's section on "Compiling in different directories"](#) for more details about this rewriting of absolute paths.

8.12.4. Location of downloaded packages

The various tarballs that are downloaded by Buildroot are all stored in `BR2_DL_DIR`, which by default is the `dl` directory. If you want to keep a complete version of Buildroot which is known to be working with the associated

tarballs, you can make a copy of this directory. This will allow you to regenerate the toolchain and the target filesystem with exactly the same versions.

If you maintain several Buildroot trees, it might be better to have a shared download location. This can be achieved by pointing the `BR2_DL_DIR` environment variable to a directory. If this is set, then the value of `BR2_DL_DIR` in the Buildroot configuration is overridden. The following line should be added to `<~/.bashrc>`.

```
export BR2_DL_DIR=<shared download location>
```

The download location can also be set in the `.config` file, with the `BR2_DL_DIR` option. Unlike most options in the `.config` file, this value is overridden by the `BR2_DL_DIR` environment variable.

8.12.5. Package-specific *make* targets

Running `make <package>` builds and installs that particular package and its dependencies.

For packages relying on the Buildroot infrastructure, there are numerous special make targets that can be called independently like this:

```
make <package>--<target>
```

The package build targets are (in the order they are executed):

command/target	Description
<code>source</code>	Fetch the source (download the tarball, clone the source repository, etc)
<code>depends</code>	n. 依赖性, 相关性; 管理 Build and install all dependencies required to build the package
<code>extract</code>	Put the source in the package build directory (extract the tarball, copy the source, etc)
<code>patch</code>	Apply the patches, if any
<code>configure</code>	Run the configure commands, if any
<code>build</code>	Run the compilation commands
<code>install-staging</code>	target package: Run the installation of the package in the staging directory, if necessary
<code>install-target</code>	target package: Run the installation of the package in the target directory, if necessary
<code>install</code>	target package: Run the 2 previous installation commands host package: Run the installation of the package in the host directory

Additionally, there are some other useful make targets:

command/target	Description
<code>show-depends</code>	Displays the dependencies required to build the package
<code>graph-depends</code>	

command/target	Description
	Generate a dependency graph of the package, in the context of the current Buildroot configuration. See this section Section 8.8, “Graphing the dependencies between packages” for more details about dependency graphs.
<code>dirclean</code>	Remove the whole package build directory
<code>reinstall</code>	Re-run the install commands
<code>rebuild</code>	Re-run the compilation commands - this only makes sense when using the <code>OVERRIDE_SRCDIR</code> feature or when you modified a file directly in the build directory
<code>reconfigure</code>	Re-run the configure commands, then rebuild - this only makes sense when using the <code>OVERRIDE_SRCDIR</code> feature or when you modified a file directly in the build directory

8.12.6. Using Buildroot during development

n. 原始码；（Linux下最方便的）打包工具

The normal operation of Buildroot is to download a **tarball**, extract it, configure, compile and install the software component found inside this tarball. The source code is extracted in `output/build/<package>-<version>`, which is a temporary directory: whenever `make clean` is used, this directory is entirely removed, and re-created at the next `make` invocation. Even when a Git or Subversion repository is used as the input for the package source code, Buildroot creates a tarball out of it, and then behaves as it normally does with tarballs.

This behavior is well-suited when Buildroot is used mainly as an integration tool, to build and integrate all the components of an embedded Linux system. However, if one uses Buildroot during the development of certain components of the system, this behavior is not very convenient: one would instead like to make a small change to the source code of one package, and be able to quickly rebuild the system with Buildroot.

Making changes directly in `output/build/<package>-<version>` is not an appropriate solution, because this directory is removed on `make clean`.

Therefore, Buildroot provides a specific mechanism for this use case: the `<pkg>_OVERRIDE_SRCDIR` mechanism. Buildroot reads an *override* file, which allows the user to tell Buildroot the location of the source for certain packages. By default this *override* file is named `local.mk` and located in the top directory of the Buildroot source tree, but a different location can be specified through the `BR2_PACKAGE_OVERRIDE_FILE` configuration option.

In this *override* file, Buildroot expects to find lines of the form:

```
<pkg1>_OVERRIDE_SRCDIR = /path/to/pkg1/sources
<pkg2>_OVERRIDE_SRCDIR = /path/to/pkg2/sources
```

For example:

```
LINUX_OVERRIDE_SRCDIR = /home/bob/linux/
BUSYBOX_OVERRIDE_SRCDIR = /home/bob/busybox/
```

When Buildroot finds that for a given package, an `<pkg>_OVERRIDE_SRCDIR` has been defined, it will no longer attempt to download, extract and patch the package. Instead, it will directly use the source code available in the specified directory and `make clean` will not touch this directory. This allows to point Buildroot to your own directories, that can be managed by Git, Subversion, or any other version control system. To achieve this, Buildroot will use *rsync* to copy the source code of the component from the specified `<pkg>_OVERRIDE_SRCDIR` to `output/build/<package>-custom/`.

n. 结合；[语] 连接词；同时发生

This mechanism is best used in **conjunction** with the `make < pkg>-rebuild` and `make <pkg>-reconfigure` targets. A `make < pkg>-rebuild all` sequence will *rsync* the source code from `<pkg>_OVERRIDE_SRCDIR` to `output/build/<package>-custom` (thanks to *rsync*, only the modified files are copied), and restart the build process of just this package.

In the example of the `linux` package above, the developer can then make a source code change in `/home/bob/linux` and then run:

```
make linux-rebuild all
```

and in a matter of seconds gets the updated Linux kernel image in `output/images`. Similarly, a change can be made to the BusyBox source code in `/home/bob/busybox`, and after:

```
make busybox-rebuild all
```

the root filesystem image in `output/images` contains the updated BusyBox.

Chapter 9. Project-specific customization

Typical actions you may need to perform for a given project are:

- configuring Buildroot (including build options and toolchain, bootloader, kernel, package and filesystem image type selection)
- configuring other components, like the Linux kernel and BusyBox
- customizing the generated target filesystem
 - adding or overwriting files on the target filesystem (using `BR2_ROOTFS_OVERLAY`)
 - modifying or deleting files on the target filesystem (using `BR2_ROOTFS_POST_BUILD_SCRIPT`)
 - running arbitrary commands prior to generating the filesystem image (using `BR2_ROOTFS_POST_BUILD_SCRIPT`)
 - setting file permissions and ownership (using `BR2_ROOTFS_DEVICE_TABLE`)
 - adding custom devices nodes (using `BR2_ROOTFS_STATIC_DEVICE_TABLE`)
- adding custom user accounts (using `BR2_ROOTFS_USERS_TABLES`)
- running **arbitrary** commands after generating the filesystem image (using `BR2_ROOTFS_POST_IMAGE_SCRIPT`)
adj. [数] 任意的；武断的；专制的
- adding project-specific patches to some packages (using `BR2_GLOBAL_PATCH_DIR`)
- adding project-specific packages

关于此类特定于项目的定制的重要注意事项：

请仔细考虑哪些更改确实是特定于项目的，哪些更改对项目之外的开发人员也有用。

An important note regarding such *project-specific* customizations: please carefully consider which changes are indeed project-specific and which changes are also useful to developers outside your project. The Buildroot community highly recommends and encourages the upstreaming of improvements, packages and board support to the official Buildroot project. Of course, it is sometimes not possible or desirable to upstream because the changes are highly specific or proprietary.

This chapter describes how to make such project-specific customizations in Buildroot and how to store them in a way that you can build the same image in a reproducible way, even after running *make clean*. By following the recommended strategy, you can even use the same Buildroot tree to build multiple distinct projects!

9.1. Recommended directory structure

When customizing Buildroot for your project, you will be creating one or more project-specific files that need to be stored somewhere. While most of these files could be placed in *any* location as their path is to be specified in the Buildroot configuration, the Buildroot developers recommend a specific directory structure which is described in this section.

与此目录结构正交的是，你可以选择放置该结构本身的位置：

Orthogonal to this directory structure, you can choose *where* you place this structure itself: either inside the Buildroot tree, or outside of it using a br2-external tree. Both options are valid, the choice is up to you.

```
--- board/
|   +--- <company>/
|       +--- <boardname>/
|           +--- linux.config
|           +--- busybox.config
|           +--- <other configuration files>
|           +--- post_build.sh
|           +--- post_image.sh
|           +--- rootfs_overlay/
|               | +--- etc/
|               | +--- <some file>
|           +--- patches/
|               +--- foo/
|                   | +--- <some patch>
|               +--- libbar/
|                   +--- <some other patches>
```

```

|
+-- configs/
|   +-- <boardname>_defconfig
|
+-- package/
|   +-- <company>/
|       +-- Config.in (if not using a br2-external tree)
|       +-- <company>.mk (if not using a br2-external tree)
|       +-- package1/
|           |   +-- Config.in
|           |   +-- package1.mk
|       +-- package2/
|           +-- Config.in
|           +-- package2.mk
|
+-- Config.in (if using a br2-external tree)
+-- external.mk (if using a br2-external tree)

```

Details on the files shown above are given further in this chapter.

Note: if you choose to place this structure outside of the Buildroot tree but in a br2-external tree, the <company> and possibly <boardname> components may be superfluous and can be left out.

9.1.1. Implementing layered customizations 实现分层定制

It is quite common for a user to have several related projects that partly need the same customizations. Instead of duplicating these customizations for each project, it is recommended to use a layered customization approach, as explained in this section.

Almost all of the customization methods available in Buildroot, like post-build scripts and root filesystem overlays, accept a space-separated list of items. The specified items are always treated in order, from left to right. By creating more than one such item, one for the common customizations and another one for the really project-specific customizations, you can avoid unnecessary duplication. Each layer is typically embodied by a separate directory inside `board/<company>/`. Depending on your projects, you could even introduce more than two layers.

An example directory structure for where a user has two customization layers *common* and *fooboard* is:

```

+-- board/
|   +-- <company>/
|       +-- common/
|           |   +-- post_build.sh
|           |   +-- rootfs_overlay/
|           |       |   +-- ...
|           |       +-- patches/
|           |           +-- ...
|       +-- fooboard/
|           +-- linux.config
|           +-- busybox.config
|           +-- <other configuration files>
|           +-- post_build.sh
|           +-- rootfs_overlay/
|               |   +-- ...
|           +-- patches/
|               +-- ...

```

For example, if the user has the `BR2_GLOBAL_PATCH_DIR` configuration option set as:

```
BR2_GLOBAL_PATCH_DIR="board/<company>/common/patches board/<company>/fooboard/patches"
```

then first the patches from the *common* layer would be applied, followed by the patches from the *fooboard* layer.

9.2. Keeping customizations outside of Buildroot

As already briefly mentioned in [Section 9.1, “Recommended directory structure”](#), you can place project-specific customizations in two locations:

- directly within the Buildroot tree, typically maintaining them using branches in a version control system so that upgrading to a newer Buildroot release is easy.
- outside of the Buildroot tree, using the *br2-external* mechanism. This mechanism allows to keep package recipes, board support and configuration files outside of the Buildroot tree, while still having them nicely integrated in the build logic. We call this location a *br2-external tree*. This section explains how to use the br2-external mechanism and what to provide in a br2-external tree.

One can tell Buildroot to use one or more br2-external trees by setting the `BR2_EXTERNAL` make variable set to the path(s) of the br2-external tree(s) to use. It can be passed to any Buildroot `make` invocation. It is automatically saved in the hidden `.br-external.mk` file in the output directory. Thanks to this, there is no need to pass `BR2_EXTERNAL` at every `make` invocation. **It can however be changed at any time by passing a new value, and can be removed by passing an empty value.** 但是，可以通过传递一个新值在任何时候更改它，也可以通过传递一个空值来删除它。

Note. The path to a br2-external tree can be either absolute or relative. If it is passed as a relative path, it is important to note that it is interpreted relative to the main Buildroot source directory, **not** to the Buildroot output directory.

Note: If using an br2-external tree from before Buildroot 2016.11, you need to convert it before you can use it with Buildroot 2016.11 onward. See [Section 25.1, “Migrating to 2016.11”](#) for help on doing so.

Some examples:

```
buildroot/ $ make BR2_EXTERNAL=/path/to/foo menuconfig
```

From now on, definitions from the `/path/to/foo` br2-external tree will be used:

```
buildroot/ $ make
buildroot/ $ make legal-info
```

We can switch to another br2-external tree at any time:

```
buildroot/ $ make BR2_EXTERNAL=/where/we/have/bar xconfig
```

We can also use multiple br2-external trees:

```
buildroot/ $ make BR2_EXTERNAL=/path/to/foo:/where/we/have/bar menuconfig
```

Or disable the usage of any br2-external tree:

```
buildroot/ $ make BR2_EXTERNAL= xconfig
```

9.2.1. Layout of a br2-external tree

A br2-external tree must contain at least those three files, described in the following chapters:

- `external.desc`
- `external.mk`
- `Config.in`

Apart from those mandatory files, there may be additional and optional content that may be present in a br2-external tree, like the `configs/` directory. They are described in the following chapters as well.

A complete example br2-external tree layout is also described later.

The `external.desc` file

That file describes the br2-external tree: the *name* and *description* for that br2-external tree.

The format for this file is line based, with each line starting by a keyword, followed by a colon and one or more spaces, followed by the value assigned to that keyword. There are two keywords currently recognised:

- `name`, ^{adj. 强制的；托管的；命令的} **mandatory**, ^{n. 受托者（等于mandatory）} defines the name for that br2-external tree. That name must only use ASCII characters in the set `[A-Za-z0-9_]`; any other character is forbidden. Buildroot sets the variable `BR2_EXTERNAL_${NAME}_PATH` to the absolute path of the br2-external tree, so that you can use it to refer to your br2-external tree. This variable is available both in Kconfig, so you can use it to source your Kconfig files (see below) and in the Makefile, so that you can use it to include other Makefiles (see below) or refer to other files (like data files) from your br2-external tree.

Note: Since it is possible to use multiple br2-external trees at once, this name is used by Buildroot to generate variables for each of those trees. That name is used to identify your br2-external tree, so try to come up with a name that really describes your br2-external tree, in order for it to be relatively unique, so that it does not clash with another name from another br2-external tree, especially if you are planning on somehow sharing your br2-external tree with third parties or using br2-external trees from third parties.

- `desc`, optional, provides a short description for that br2-external tree. It shall fit on a single line, is mostly free-form (see below), and is used when displaying information about a br2-external tree (e.g. above the list of defconfig files, or as the prompt in the menuconfig); as such, it should be relatively brief (40 chars is probably a good upper limit). The description is available in the `BR2_EXTERNAL_${NAME}_DESC` variable.

Examples of names and the corresponding `BR2_EXTERNAL_${NAME}_PATH` variables:

- `FOO` → `BR2_EXTERNAL_FOO_PATH`
- `BAR_42` → `BR2_EXTERNAL_BAR_42_PATH`

In the following examples, it is assumed the name to be set to `BAR_42`.

Note: Both `BR2_EXTERNAL_${NAME}_PATH` and `BR2_EXTERNAL_${NAME}_DESC` are available in the Kconfig files and the Makefiles. They are also exported in the environment so are available in post-build, post-image and in-fakeroot scripts.

The `Config.in` and `external.mk` files

Those files (which may each be empty) can be used to define package recipes (i.e. `foo/Config.in` and `foo/foo.mk` like for packages bundled in Buildroot itself) or other custom configuration options or make logic.

Buildroot automatically includes the `Config.in` from each br2-external tree to make it appear in the top-level configuration menu, and includes the `external.mk` from each br2-external tree with the rest of the makefile logic.

The main usage of this is to store package recipes. The recommended way to do this is to write a `Config.in` file that looks like:

```
source "$BR2_EXTERNAL_BAR_42_PATH/package/package1/Config.in"
source "$BR2_EXTERNAL_BAR_42_PATH/package/package2/Config.in"
```

Then, have an `external.mk` file that looks like:

```
include $(sort $(wildcard $(BR2_EXTERNAL_BAR_42_PATH)/package/*/*.mk))
```

And then in `$(BR2_EXTERNAL_BAR_42_PATH)/package/package1` and `$(BR2_EXTERNAL_BAR_42_PATH)/package/package2` create normal Buildroot package recipes, as explained in [Chapter 17, Adding new packages to Buildroot](#). If you prefer, you can also group the packages in subdirectories called `<boardname>` and adapt the above paths accordingly.

You can also define custom configuration options in `Config.in` and custom make logic in `external.mk`.

The `configs/` directory

One can store Buildroot defconfigs in the `configs` subdirectory of the br2-external tree. Buildroot will automatically show them in the output of `make list-defconfigs` and allow them to be loaded with the normal `make <name>_defconfig` command. They will be visible in the `make list-defconfigs` output, below an `External configs` label that contains the name of the br2-external tree they are defined in.

Note: If a defconfig file is present in more than one br2-external tree, then the one from the last br2-external tree is used. It is thus possible to override a defconfig bundled in Buildroot or another br2-external tree.

Free-form content

One can store all the board-specific configuration files there, such as the kernel configuration, the root filesystem overlay, or any other configuration file for which Buildroot allows to set the location (by using the `BR2_EXTERNAL_${NAME}_PATH` variable). For example, you could set the paths to a global patch directory, to a rootfs overlay and to the kernel configuration file as follows (e.g. by running `make menuconfig` and filling in these options):

```
BR2_GLOBAL_PATCH_DIR=$(BR2_EXTERNAL_BAR_42_PATH)/patches/
BR2_ROOTFS_OVERLAY=$(BR2_EXTERNAL_BAR_42_PATH)/board/<boardname>/overlay/
BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE=$(BR2_EXTERNAL_BAR_42_PATH)/board/<boardname>/kernel.config
```

Example layout

Here is an example layout using all features of br2-external (the sample content is shown for the file above it, when it is relevant to explain the br2-external tree; this is all entirely made up just for the sake of illustration, of course):

```

/path/to/br2-ext-tree/
|- external.desc
|  |name: BAR_42
|  |desc: Example br2-external tree
|  `----
|
|- Config.in
|  |source "$BR2_EXTERNAL_BAR_42_PATH/package/pkg-1/Config.in"
|  |source "$BR2_EXTERNAL_BAR_42_PATH/package/pkg-2/Config.in"
|  |
|  |config BAR_42_FLASH_ADDR
|  |    hex "my-board flash address"
|  |    default 0x10AD
|  `----
|
|- external.mk
|  |include $(sort $(wildcard $(BR2_EXTERNAL_BAR_42_PATH)/package/*/*.mk))
|  |
|  |flash-my-board:
|  |    $(BR2_EXTERNAL_BAR_42_PATH)/board/my-board/flash-image \
|  |    --image $(BINARIES_DIR)/image.bin \
|  |    --address $(BAR_42_FLASH_ADDR)
|  `----
|
|- package/pkg-1/Config.in
|  |config BR2_PACKAGE_PKG_1
|  |    bool "pkg-1"
|  |    help
|  |        Some help about pkg-1
|  `----
|- package/pkg-1/pkg-1.hash
|- package/pkg-1/pkg-1.mk
|  |PKG_1_VERSION = 1.2.3
|  |PKG_1_SITE = /some/where/to/get/pkg-1
|  |PKG_1_LICENSE = blabla
|  |
|  |define PKG_1_INSTALL_INIT_SYSV
|  |    $(INSTALL) -D -m 0755 $(PKG_1_PKGDIR)/S99my-daemon \
|  |                          $(TARGET_DIR)/etc/init.d/S99my-daemon
|  |endef
|  |
|  |$(eval $(autotools-package))
|  `----
|- package/pkg-1/S99my-daemon
|
|- package/pkg-2/Config.in
|- package/pkg-2/pkg-2.hash
|- package/pkg-2/pkg-2.mk
|
|- configs/my-board_defconfig
|  |BR2_GLOBAL_PATCH_DIR="$(BR2_EXTERNAL_BAR_42_PATH)/patches/"
|  |BR2_ROOTFS_OVERLAY="$(BR2_EXTERNAL_BAR_42_PATH)/board/my-board/overlay/"
|  |BR2_ROOTFS_POST_IMAGE_SCRIPT="$(BR2_EXTERNAL_BAR_42_PATH)/board/my-board/post-image.sh"
|  |BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE="$(BR2_EXTERNAL_BAR_42_PATH)/board/my-board/kernel.config"
|  `----
|
|- patches/linux/0001-some-change.patch
|- patches/linux/0002-some-other-change.patch
|- patches/busybox/0001-fix-something.patch
|
|- board/my-board/kernel.config
|- board/my-board/overlay/var/www/index.html
|- board/my-board/overlay/var/www/my.css
|- board/my-board/flash-image
`- board/my-board/post-image.sh
   |#!/bin/sh
   |generate-my-binary-image \
   |    --root ${BINARIES_DIR}/rootfs.tar \
   |    --kernel ${BINARIES_DIR}/zImage \
   |    --dtb ${BINARIES_DIR}/my-board.dtb \
   |    --output ${BINARIES_DIR}/image.bin
   `----

```

The br2-external tree will then be visible in the menuconfig (with the layout expanded):

```

External options --->
*** Example br2-external tree (in /path/to/br2-ext-tree/)
[ ] pkg-1
[ ] pkg-2
(0x10AD) my-board flash address

```

If you are using more than one br2-external tree, it would look like (with the layout expanded and the second one with name FOO_27 but no desc: field in `external.desc`):

```
External options --->
  Example br2-external tree --->
    *** Example br2-external tree (in /path/to/br2-ext-tree)
    [ ] pkg-1
    [ ] pkg-2
    (0x10AD) my-board flash address
  FOO_27 --->
    *** FOO_27 (in /path/to/another-br2-ext)
    [ ] foo
    [ ] bar
```

9.3. Storing the Buildroot configuration

The Buildroot configuration can be stored using the command `make savedefconfig`.

n. 条 (strip的复数) ; 分割公债, 本息拆离; 简易机场
v. 剥夺 (strip的三单形式) ; 剥光...的外皮; 把...切成细条; 剥去; 拿走

This **strips** the Buildroot configuration down by removing configuration options that are at their default value. The result is stored in a file called `defconfig`. If you want to save it in another place, change the `BR2_DEFCONFIG` option in the Buildroot configuration itself, or call make with `make savedefconfig BR2_DEFCONFIG=<path-to-defconfig>`.

The recommended place to store this `defconfig` is `configs/<boardname>_defconfig`. If you follow this recommendation, the configuration will be listed in `make help` and can be set again by running `make <boardname>_defconfig`.

Alternatively, you can copy the file to any other place and rebuild with `make defconfig BR2_DEFCONFIG=<path-to-defconfig-file>`.

9.4. Storing the configuration of other components

The configuration files for BusyBox, the Linux kernel, Barebox, U-Boot and uClibc should be stored as well if changed. For each of these components, a Buildroot configuration option exists to point to an input configuration file, e.g. `BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE`. To store their configuration, set these configuration options to a path where you want to save the configuration files, and then use the helper targets described below to actually store the configuration.

As explained in [Section 9.1, “Recommended directory structure”](#), the recommended path to store these configuration files is `board/<company>/<boardname>/foo.config`.

Make sure that you create a configuration file *before* changing the `BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE` etc. options. Otherwise, Buildroot will try to access this config file, which doesn't exist yet, and will fail. You can create the configuration file by running `make linux-menuconfig` etc.

Buildroot provides a few helper targets to make the saving of configuration files easier.

- `make linux-update-defconfig` saves the linux configuration to the path specified by `BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE`. It simplifies the config file by removing default values. However, this only works with kernels starting from 2.6.33. For earlier kernels, use `make linux-update-config`.
- `make busybox-update-config` saves the busybox configuration to the path specified by `BR2_PACKAGE_BUSYBOX_CONFIG`.
- `make uclibc-update-config` saves the uClibc configuration to the path specified by `BR2_UCLIBC_CONFIG`.
- `make barebox-update-defconfig` saves the barebox configuration to the path specified by `BR2_TARGET_BAREBOX_CUSTOM_CONFIG_FILE`.
- `make uboot-update-defconfig` saves the U-Boot configuration to the path specified by `BR2_TARGET_UBOOT_CUSTOM_CONFIG_FILE`.
- For `at91bootstrap3`, no helper exists so you have to copy the config file manually to `BR2_TARGET_AT91BOOTSTRAP3_CUSTOM_CONFIG_FILE`.

9.5. Customizing the generated target filesystem

Besides changing the configuration through `make *config`, there are a few other ways to customize the resulting target filesystem.

The two recommended methods, which can co-exist, are root filesystem overlay(s) and post build script(s).

Root filesystem overlays (BR2_ROOTFS_OVERLAY)

A filesystem overlay is a tree of files that is copied directly over the target filesystem after it has been built. To enable this feature, set config option `BR2_ROOTFS_OVERLAY` (in the `System configuration` menu) to the root of the overlay. You can even specify multiple overlays, space-separated. If you specify a relative path, it will be relative to the root of the Buildroot tree. Hidden directories of version control systems, like `.git`, `.svn`, `.hg`, etc., files called `.empty` and files ending in `~` are excluded from the copy.

As shown in [Section 9.1, “Recommended directory structure”](#), the recommended path for this overlay is `board/<company>/<boardname>/rootfs-overlay`.

Post-build scripts (BR2_ROOTFS_POST_BUILD_SCRIPT)

Post-build scripts are shell scripts called *after* Buildroot builds all the selected software, but *before* the rootfs images are assembled. To enable this feature, specify a space-separated list of post-build scripts in config option `BR2_ROOTFS_POST_BUILD_SCRIPT` (in the `System configuration` menu). If you specify a relative path, it will be relative to the root of the Buildroot tree.

Using post-build scripts, you can remove or modify any file in your target filesystem. You should, however, use this feature with care. Whenever you find that a certain package generates wrong or unneeded files, you should fix that package rather than work around it with some post-build cleanup scripts.

As shown in [Section 9.1, “Recommended directory structure”](#), the recommended path for this script is `board/<company>/<boardname>/post_build.sh`.

The post-build scripts are run with the main Buildroot tree as current working directory. The path to the target filesystem is passed as the first argument to each script. If the config option `BR2_ROOTFS_POST_SCRIPT_ARGS` is not empty, these arguments will be passed to the script too. **All the scripts will be passed the exact same set of arguments, it is not possible to pass different sets of arguments to each script.** 所有脚本都将传递完全相同的参数集，不可能向每个脚本传递不同的参数集

In addition, you may also use these environment variables:

- `BR2_CONFIG`: the path to the Buildroot `.config` file
- `HOST_DIR`, `STAGING_DIR`, `TARGET_DIR`: see [Section 17.5.2, “generic-package reference”](#)
- `BUILD_DIR`: the directory where packages are extracted and built
- `BINARIES_DIR`: the place where all binary files (aka images) are stored
- `BASE_DIR`: the base output directory

Below three more methods of customizing the target filesystem are described, but they are not recommended.

Direct modification of the target filesystem

For temporary modifications, you can modify the target filesystem directly and rebuild the image. The target filesystem is available under `output/target/`. After making your changes, run `make` to rebuild the target filesystem image.

This method allows you to do anything to the target filesystem, but if you need to clean your Buildroot tree using `make clean`, these changes will be lost. Such cleaning is necessary in several cases, refer to [Section 8.2, “Understanding when a full rebuild is necessary”](#) for details. This solution is therefore only useful for quick tests: *changes do not survive the `make clean` command*. Once you have validated your changes, you should make sure that they will persist after a `make clean`, using a root filesystem overlay or a post-build script.

Custom target skeleton (BR2_ROOTFS_SKELETON_CUSTOM) 自定义目标骨架

The root filesystem image is created from a target skeleton, on top of which all packages install their files. The skeleton is copied to the target directory `output/target` before any package is built and installed. The default target skeleton provides the standard Unix filesystem layout and some basic init scripts and configuration files.

If the default skeleton (available under `system/skeleton`) does not match your needs, you would typically use a root filesystem overlay or post-build script to adapt it. **However, if the default skeleton is entirely different than what you need, using a custom skeleton may be more suitable.** 但是，如果默认骨架与您需要的骨架完全不同，那么使用自定义骨架可能更合适。

To enable this feature, enable config option `BR2_ROOTFS_SKELETON_CUSTOM` and set `BR2_ROOTFS_SKELETON_CUSTOM_PATH` to the path of your custom skeleton. Both options are available in the `System configuration` menu. **If you specify a relative path, it will be relative to the root of the Buildroot tree.** 如果您指定了一个相对路径，它将是相对于Buildroot树的根的。

不推荐使用此方法，因为它复制了整个框架，这会阻止利用稍后的Buildroot版本中对默认框架的修复或改进。

This method is not recommended because it duplicates the entire skeleton, which prevents taking advantage of the fixes or improvements brought to the default skeleton in later Buildroot releases.

Post-fakeroot scripts (`BR2_ROOTFS_POST_FAKEROOT_SCRIPT`) 在聚合最终图像时，该过程的某些部分需要根权限

When aggregating the final images, some parts of the process requires root rights: creating device nodes in `/dev`, setting permissions or ownership to files and directories... To avoid requiring actual root rights, Buildroot uses `fakeroot` to simulate root rights. **This is not a complete substitute for actually being root, but is enough for what Buildroot needs.** 这并不能完全替代实际的根，但对于Buildroot的需要已经足够了

Post-fakeroot scripts are shell scripts that are called at the *end* of the fakeroot phase, *right before* the filesystem image generator is called. As such, they are called in the fakeroot context.

Post-fakeroot scripts can be useful in case you need to tweak the filesystem to do modifications that are usually only available to the root user.

Note: It is recommended to use the existing mechanisms to set file permissions or create entries in `/dev` (see [Section 9.5.1, “Setting file permissions and ownership and adding custom devices nodes”](#)) or to create users (see [Section 9.6, “Adding custom user accounts”](#))

Note: The difference between post-build scripts (above) and fakeroot scripts, is that post-build scripts are not called in the fakeroot context.

Note: Using `fakeroot` is not an absolute substitute for actually being root. `fakeroot` only ever fakes the file access rights and types (regular, block-or-char device...) and uid/gid; these are emulated in-memory.

9.5.1. Setting file permissions and ownership and adding custom devices nodes

Sometimes it is needed to set specific permissions or ownership on files or device nodes. For example, certain files may need to be owned by root. Since the post-build scripts are not run as root, you cannot do such changes from there unless you use an explicit fakeroot from the post-build script.

Instead, Buildroot provides support for so-called *permission tables*. To use this feature, set config option `BR2_ROOTFS_DEVICE_TABLE` to a space-separated list of permission tables, regular text files following the [makedev syntax Chapter 23, Makedev syntax documentation](#).

If you are using a static device table (i.e. not using `devtmpfs`, `mdev`, or `(e)udev`) then you can add device nodes using the same syntax, in so-called *device tables*. To use this feature, set config option `BR2_ROOTFS_STATIC_DEVICE_TABLE` to a space-separated list of device tables.

As shown in [Section 9.1, “Recommended directory structure”](#), the recommended location for such files is `board/<company>/<boardname>/`.

It should be noted that if the specific permissions or device nodes are related to a specific application, you should set variables `FOO_PERMISSIONS` and `FOO_DEVICES` in the package's `.mk` file instead (see [Section 17.5.2, “generic-package reference”](#)).

9.6. Adding custom user accounts

Sometimes it is needed to add specific users in the target system. To cover this requirement, Buildroot provides support for so-called *users tables*. To use this feature, set config option `BR2_ROOTFS_USERS_TABLES` to a space-separated list of users tables, regular text files following the [makeusers syntax Chapter 24, Makeusers syntax documentation](#).

As shown in [Section 9.1, “Recommended directory structure”](#), the recommended location for such files is `board/<company>/<boardname>/`.

It should be noted that if the custom users are related to a specific application, you should set variable `FOO_USERS` in the package's `.mk` file instead (see [Section 17.5.2, “generic-package reference”](#)).

9.7. Customization after the images have been created

While post-build scripts ([Section 9.5, “Customizing the generated target filesystem”](#)) are run *before* building the filesystem image, kernel and bootloader, **post-image scripts** can be used to perform some specific actions *after* all images have been created.

Post-image scripts can for example be used to automatically extract your root filesystem tarball in a location exported by your NFS server, or to create a special firmware image that bundles your root filesystem and kernel image, or any other custom action required for your project.

To enable this feature, specify a space-separated list of post-image scripts in config option `BR2_ROOTFS_POST_IMAGE_SCRIPT` (in the [System configuration](#) menu). If you specify a relative path, it will be relative to the root of the Buildroot tree.

Just like post-build scripts, post-image scripts are run with the main Buildroot tree as current working directory. The path to the `images` output directory is passed as the first argument to each script. If the config option `BR2_ROOTFS_POST_SCRIPT_ARGS` is not empty, these arguments will be passed to the script too. All the scripts will be passed the exact same set of arguments, it is not possible to pass different sets of arguments to each script.

Again just like for the post-build scripts, the scripts have access to the environment variables `BR2_CONFIG`, `HOST_DIR`, `STAGING_DIR`, `TARGET_DIR`, `BUILD_DIR`, `BINARIES_DIR` and `BASE_DIR`.

The post-image scripts will be executed as the user that executes Buildroot, which should normally *not* be the root user. Therefore, any action requiring root permissions in one of these scripts will require special handling (usage of `fakeroot` or `sudo`), which is left to the script developer.

9.8. Adding project-specific patches

It is sometimes useful to apply *extra* patches to packages - on top of those provided in Buildroot. This might be used to support custom features in a project, for example, or when working on a new architecture.

The `BR2_GLOBAL_PATCH_DIR` configuration option can be used to specify a space separated list of one or more directories containing package patches.

For a specific version `<packageversion>` of a specific package `<packagename>`, patches are applied from `BR2_GLOBAL_PATCH_DIR` as follows:

1. For every directory - `<global-patch-dir>` - that exists in `BR2_GLOBAL_PATCH_DIR`, a `<package-patch-dir>` will be determined as follows:
 - `<global-patch-dir>/<packagename>/<packageversion>/` if the directory exists.
 - Otherwise, `<global-patch-dir>/<packagename>` if the directory exists.
2. Patches will then be applied from a `<package-patch-dir>` as follows:
 - If a `series` file exists in the package directory, then patches are applied according to the `series` file;
 - Otherwise, patch files matching `*.patch` are applied in alphabetical order. So, to ensure they are applied in the right order, it is highly recommended to name the patch files like this:
`<number>-<description>.patch`, where `<number>` refers to the *apply order*.

For information about how patches are applied for a package, see [Section 18.2, “How patches are applied”](#)

The `BR2_GLOBAL_PATCH_DIR` option is the preferred method for specifying a custom patch directory for packages. It can be used to specify a patch directory for any package in buildroot. It should also be used in place of the custom patch directory options that are available for packages such as U-Boot and Barebox. By doing this, it will allow a user to manage their patches from one top-level directory.

The exception to `BR2_GLOBAL_PATCH_DIR` being the preferred method for specifying custom patches is `BR2_LINUX_KERNEL_PATCH`. `BR2_LINUX_KERNEL_PATCH` should be used to specify kernel patches that are available at an URL. **Note:** `BR2_LINUX_KERNEL_PATCH` specifies kernel patches that are applied after patches available in `BR2_GLOBAL_PATCH_DIR`, as it is done from a post-patch hook of the Linux package.

9.9. Adding project-specific packages

In general, any new package should be added directly in the `package` directory and submitted to the Buildroot upstream project. How to add packages to Buildroot in general is explained in full detail in [Chapter 17, Adding new packages to Buildroot](#) and will not be repeated here. However, your project may need some proprietary packages that cannot be upstreamed. This section will explain how you can keep such project-specific packages in a project-specific directory.

As shown in [Section 9.1, “Recommended directory structure”](#), the recommended location for project-specific packages is `package/<company>/`. If you are using the br2-external tree feature (see [Section 9.2, “Keeping customizations outside of Buildroot”](#)) the recommended location is to put them in a sub-directory named `package/` in your br2-external tree.

However, Buildroot will not be aware of the packages in this location, unless we perform some additional steps. As explained in [Chapter 17, Adding new packages to Buildroot](#), a package in Buildroot basically consists of two

files: a `.mk` file (describing how to build the package) and a `Config.in` file (describing the configuration options for this package).

Buildroot will automatically include the `.mk` files in first-level subdirectories of the `package` directory (using the pattern `package/*/*.mk`). If we want Buildroot to include `.mk` files from deeper subdirectories (like `package/<company>/package1/`) then we simply have to add a `.mk` file in a first-level subdirectory that includes these additional `.mk` files. Therefore, create a file `package/<company>/<company>.mk` with following contents (assuming you have only one extra directory level below `package/<company>/`):

```
include $(sort $(wildcard package/<company>/*.mk))
```

For the `Config.in` files, create a file `package/<company>/Config.in` that includes the `Config.in` files of all your packages. An exhaustive list has to be provided since wildcards are not supported in the source command of `kconfig`. For example:

```
source "package/<company>/package1/Config.in"
source "package/<company>/package2/Config.in"
```

Include this new file `package/<company>/Config.in` from `package/Config.in`, preferably in a company-specific menu to make merges with future Buildroot versions easier.

If using a `br2-external` tree, refer to [Section 9.2, “Keeping customizations outside of Buildroot”](#) for how to fill in those files.

9.10. Quick guide to storing your project-specific customizations

Earlier in this chapter, the different methods for making project-specific customizations have been described. This section will now summarize all this by providing step-by-step instructions to storing your project-specific customizations. Clearly, the steps that are not relevant to your project can be skipped.

1. `make menuconfig` to configure toolchain, packages and kernel.
2. `make linux-menuconfig` to update the kernel config, similar for other configuration like busybox, uclibc, ...
3. `mkdir -p board/<manufacturer>/<boardname>`

4. Set the following options to `board/<manufacturer>/<boardname>/<package>.config` (as far as they are relevant):

- `BR2_LINUX_KERNEL_CUSTOM_CONFIG_FILE`
- `BR2_PACKAGE_BUSYBOX_CONFIG`
- `BR2_UCLIBC_CONFIG`
- `BR2_TARGET_AT91BOOTSTRAP3_CUSTOM_CONFIG_FILE`
- `BR2_TARGET_BAREBOX_CUSTOM_CONFIG_FILE`
- `BR2_TARGET_UBOOT_CUSTOM_CONFIG_FILE`

5. Write the configuration files:

- `make linux-update-defconfig`
- `make busybox-update-config`
- `make uclibc-update-config`
- `cp <output>/build/at91bootstrap3-*/.config board/<manufacturer>/<boardname>/at91bootstrap3.config`
- `make barebox-update-defconfig`
- `make uboot-update-defconfig`

6. Create `board/<manufacturer>/<boardname>/rootfs-overlay/` and fill it with additional files you need on your rootfs, e.g. `board/<manufacturer>/<boardname>/rootfs-overlay/etc/inittab`. Set `BR2_ROOTFS_OVERLAY` to `board/<manufacturer>/<boardname>/rootfs-overlay`.

7. Create a post-build script `board/<manufacturer>/<boardname>/post_build.sh`. Set `BR2_ROOTFS_POST_BUILD_SCRIPT` to `board/<manufacturer>/<boardname>/post_build.sh`

8. If additional `setuid` permissions have to be set or device nodes have to be created, create `board/<manufacturer>/<boardname>/device_table.txt` and add that path to `BR2_ROOTFS_DEVICE_TABLE`.

9. If additional user accounts have to be created, create `board/<manufacturer>/<boardname>/users_table.txt` and add that path to `BR2_ROOTFS_USERS_TABLES`.
10. To add custom patches to certain packages, set `BR2_GLOBAL_PATCH_DIR` to `board/<manufacturer>/<boardname>/patches/` and add your patches for each package in a subdirectory named after the package. Each patch should be called `<packagename>-<num>-<description>.patch`.
11. Specifically for the Linux kernel, there also exists the option `BR2_LINUX_KERNEL_PATCH` with as main advantage that it can also download patches from a URL. If you do not need this, `BR2_GLOBAL_PATCH_DIR` is preferred. U-Boot, Barebox, at91bootstrap and at91bootstrap3 also have separate options, but these do not provide any advantage over `BR2_GLOBAL_PATCH_DIR` and will likely be removed in the future.
12. If you need to add project-specific packages, create `package/<manufacturer>/` and place your packages in that directory. Create an overall `<manufacturer>.mk` file that includes the `.mk` files of all your packages. Create an overall `Config.in` file that sources the `Config.in` files of all your packages. Include this `Config.in` file from Buildroot's `package/Config.in` file.
13. `make savedefconfig` to save the buildroot configuration.
14. `cp defconfig configs/<boardname>_defconfig`

Chapter 10. Frequently Asked Questions & Troubleshooting

10.1. The boot hangs after *Starting network...*

If the boot process seems to hang after the following messages (messages not necessarily exactly similar, depending on the list of packages selected):

```
Freeing init memory: 3972K
Initializing random number generator... done.
Starting network...
Starting dropbear sshd: generating rsa key... generating dsa key... OK
```

then it means that your system is running, but didn't start a shell on the serial console. In order to have the system start a shell on your serial console, you have to go into the Buildroot configuration, in `System configuration`, modify `Run a getty (login prompt) after boot` and set the appropriate port and baud rate in the `getty options` submenu. This will automatically tune the `/etc/inittab` file of the generated system so that a shell starts on the correct serial port.

10.2. Why is there no compiler on the target?

It has been decided that support for the *native compiler on the target* would be stopped from the Buildroot-2012.11 release because:

- this feature was neither maintained nor tested, and often broken;
- this feature was only available for Buildroot toolchains;
- Buildroot mostly targets *small* or *very small* target hardware with limited resource onboard (CPU, ram, mass-storage), for which compiling on the target does not make much sense;
- Buildroot aims at easing the cross-compilation, making native compilation on the target unnecessary.

If you need a compiler on your target anyway, then Buildroot is not suitable for your purpose. In such case, you need a *real distribution* and you should opt for something like:

- [openembedded](#)
- [yocto](#)
- [emdebian](#)
- [Fedora](#)
- [openSUSE ARM](#)
- [Arch Linux ARM](#)
- ...

10.3. Why are there no development files on the target?

因为在目标上没有可用的编译器

Since there is no compiler available on the target (see [Section 10.2, “Why is there no compiler on the target?”](#)), it does not make sense to waste space with headers or static libraries.

浪费头文件或静态库的空间是没有意义的。

Therefore, those files are always removed from the target since the Buildroot-2012.11 release.

10.4. Why is there no documentation on the target?

Because Buildroot mostly targets *small* or *very small* target hardware with limited resource onboard (CPU, ram, mass-storage), it does not make sense to waste space with the documentation data.

If you need documentation data on your target anyway, then Buildroot is not suitable for your purpose, and you should look for a *real distribution* (see: [Section 10.2, “Why is there no compiler on the target?”](#)).

10.5. Why are some packages not visible in the Buildroot config menu?

如果一个包存在于Buildroot树中并且没有出现在配置菜单中，这很可能意味着这个包的一些依赖项没有得到满足。

If a package exists in the Buildroot tree and does not appear in the config menu, this most likely means that some of the package's dependencies are not met.

To know more about the dependencies of a package, search for the package symbol in the config menu (see [Section 8.1, “make tips”](#)).

Then, you may have to recursively enable several options (which correspond to the unmet dependencies) to finally be able to select the package.

If the package is not visible due to some unmet toolchain options, then you should certainly run a full rebuild (see [Section 8.1, “make tips”](#) for more explanations).

10.6. Why not use the target directory as a chroot directory?

不使用chroot目录的原因有很多，其中包括：

There are plenty of reasons to *not* use the target directory as a chroot one, among these:

- file ownerships, modes and permissions are not correctly set in the target directory;
- device nodes are not created in the target directory.

For these reasons, commands run through chroot, using the target directory as the new root, will most likely fail.

If you want to run the target filesystem inside a chroot, or as an NFS root, then use the tarball image generated in `images/` and extract it as root.

10.7. Why doesn't Buildroot generate binary packages (.deb, .ipkg...)?

One feature that is often discussed on the Buildroot list is the general topic of "package management". To summarize, the idea would be to add some tracking of which Buildroot package installs what files, with the goals of:

- being able to remove files installed by a package when this package gets unselected from the menuconfig;
- being able to generate binary packages (ipk or other format) that can be installed on the target without re-generating a new root filesystem image.

In general, most people think it is easy to do: just track which package installed what and remove it when the package is unselected. However, it is much more complicated than that:

- It is not only about the `target/` directory, but also the `sysroot` in `host/<tuple>/sysroot` and the `host/` directory itself. All files installed in those directories by various packages must be tracked.
当从配置中取消选择一个包时，仅仅删除它安装的文件是不够的。
- **When a package is unselected from the configuration, it is not sufficient to remove just the files it installed.** One must also remove all its reverse dependencies (i.e. packages relying on it) and rebuild all those packages. For example, package A depends optionally on the OpenSSL library. Both are selected, and Buildroot is built. Package A is built with crypto support using OpenSSL. Later on, OpenSSL gets unselected from the configuration, but package A remains (since OpenSSL is an optional dependency, this is possible.) If only OpenSSL files are removed, then the files installed by package A are broken: they use a library that is no longer present on the target. **Although this is technically doable, it adds a lot of complexity to Buildroot, which goes against the simplicity we try to stick to.** 虽然这在技术上是可行的，但它给Buildroot增加了很多复杂性，这与我们一直坚持的简单性背道而驰。
- In addition to the previous problem, there is the case where the optional dependency is not even known to Buildroot. For example, package A in version 1.0 never used OpenSSL, but in version 2.0 it automatically uses OpenSSL if available. If the Buildroot .mk file hasn't been updated to take this into account, then package A will not be part of the reverse dependencies of OpenSSL and will not be removed and rebuilt when OpenSSL is removed. For sure, the .mk file of package A should be fixed to mention this optional dependency, but in the mean time, you can have non-reproducible behaviors.

这个请求还允许对输出目录应用menuconfig中的更改，而不必从头重新构建所有内容。

- **The request is to also allow changes in the menuconfig to be applied on the output directory without having to rebuild everything from scratch.** However, this is very difficult to achieve in a reliable way: what happens when the suboptions of a package are changed (we would have to detect this, and rebuild the package from scratch and potentially all its reverse dependencies), what happens if toolchain options are changed, etc. At the moment, what Buildroot does is clear and simple so its behaviour is very reliable and it is easy to support users. If configuration changes done in menuconfig are applied after the next make, then it has to work correctly and properly in all situations, and not have some bizarre corner cases. The risk is to get bug reports like "I have enabled package A, B and C, then ran make, then disabled package C and enabled package D and ran make, then re-enabled package C and enabled package E and then there is a build failure". Or worse "I did some configuration, then built, then did some changes, built, some more changes, built, some more changes, built, and now it fails, but I don't remember all the changes I did and in which order". This will be impossible to support.

For all these reasons, the conclusion is that adding tracking of installed files to remove them when the package is unselected, or to generate a repository of binary packages, is something that is very hard to achieve reliably and will add a lot of complexity.

On this matter, the Buildroot developers make this position statement:

- Buildroot strives to make it easy to generate a root filesystem (hence the name, by the way.) That is what we want to make Buildroot good at: building root filesystems.
- **Buildroot is not meant to be a distribution (or rather, a distribution generator.) It is the opinion of most Buildroot developers that this is not a goal we should pursue.** We believe that there are other tools better suited to generate a distro than Buildroot is. For example, [Open Embedded](#), or [openWRT](#), are such tools.
- We prefer to push Buildroot in a direction that makes it easy (or even easier) to generate complete root filesystems. This is what makes Buildroot stand out in the crowd (among other things, of course!)
- We believe that for most embedded Linux systems, binary packages are not necessary, and potentially harmful. When binary packages are used, it means that the system can be partially upgraded, which creates an enormous number of possible combinations of package versions that should be tested before doing the upgrade on the embedded device. On the other hand, by doing complete system upgrades by upgrading the entire root filesystem image at once, the image deployed to the embedded system is guaranteed to really be the one that has been tested and validated.

10.8. How to speed-up the build process?

Since Buildroot often involves doing full rebuilds of the entire system that can be quite long, we provide below a number of tips to help reduce the build time:

- Use a pre-built external toolchain instead of the default Buildroot internal toolchain. By using a pre-built Linaro toolchain (on ARM) or a Sourcery CodeBench toolchain (for ARM, x86, x86-64, MIPS, etc.), you will save the build time of the toolchain at each complete rebuild, approximately 15 to 20 minutes. Note that temporarily using an external toolchain does not prevent you to switch back to an internal toolchain (that may provide a higher level of customization) once the rest of your system is working;
- Use the `ccache` compiler cache (see: [Section 8.12.3, "Using ccache in Buildroot"](#));
- Learn about rebuilding only the few packages you actually care about (see [Section 8.3, "Understanding how to rebuild packages"](#)), but beware that sometimes full rebuilds are anyway necessary (see [Section 8.2, "Understanding when a full rebuild is necessary"](#));
- **Make sure you are not using a virtual machine for the Linux system used to run Buildroot. Most of the virtual machine technologies are known to cause a significant performance impact on I/O, which is really important for building source code;** 众所周知，大多数虚拟机技术都会对I/O造成显著的性能影响，这对于构建源代码非常重要；
- Make sure that you're using only local files: do not attempt to do a build over NFS, which significantly slows down the build. Having the Buildroot download folder available locally also helps a bit.
- Buy new hardware. SSDs and lots of RAM are key to speeding up the builds.

Chapter 11. Known issues

- It is not possible to pass extra linker options via `BR2_TARGET_LDFLAGS` if such options contain a `$` sign. For example, the following is known to break: `BR2_TARGET_LDFLAGS="-Wl,-rpath='$ORIGIN/./lib'"`
- The `libffi` package is not supported on the SuperH 2 and ARC architectures.
- The `prboom` package triggers a compiler failure with the SuperH 4 compiler from Sourcery CodeBench, version 2012.09.

Chapter 12. Legal notice and licensing

12.1. Complying with open source licenses

All of the end products of Buildroot (toolchain, root filesystem, kernel, bootloaders) contain open source software, released under various licenses.

使用开源软件使您可以自由地构建丰富的嵌入式系统，从广泛的包中进行选择，但也强加了一些您必须了解和遵守的义务。

Using open source software gives you the freedom to build rich embedded systems, choosing from a wide range of packages, but also imposes some obligations that you must know and honour. Some licenses require you to publish the license text in the documentation of your product. Others require you to redistribute the source code of the software to those that receive your product.

The exact requirements of each license are documented in each package, and it is your responsibility (or that of your legal office) to comply with those requirements. To make this easier for you, Buildroot can collect for you some material you will probably need. To produce this material, after you have configured Buildroot with `make menuconfig`, `make xconfig` or `make gconfig`, run:

```
make legal-info
```

Buildroot will collect legally-relevant material in your output directory, under the `legal-info/` subdirectory. There you will find:

- A `README` file, that summarizes the produced material and contains warnings about material that Buildroot could not produce.
- `buildroot.config`: this is the Buildroot configuration file that is usually produced with `make menuconfig`, and which is necessary to reproduce the build.
- The source code for all packages; this is saved in the `sources/` and `host-sources/` subdirectories for target and host packages respectively. The source code for packages that set `<PKG>_REDISTRIBUTE = NO` will not be saved. Patches that were applied are also saved, along with a file named `series` that lists the patches in the order they were applied. Patches are under the same license as the files that they modify. Note: Buildroot applies additional patches to Libtool scripts of autotools-based packages. These patches can be found under `support/libtool` in the Buildroot source and, due to technical limitations, are not saved with the package sources. You may need to collect them manually.
- A manifest file (one for host and one for target packages) listing the configured packages, their version, license and related information. Some of this information might not be defined in Buildroot; such items are marked as "unknown".
- The license texts of all packages, in the `licenses/` and `host-licenses/` subdirectories for target and host packages respectively. If the license file(s) are not defined in Buildroot, the file is not produced and a warning in the `README` indicates this.

Please note that the aim of the `legal-info` feature of Buildroot is to produce all the material that is somehow relevant for legal compliance with the package licenses. Buildroot does not try to produce the exact material that you must somehow make public. Certainly, more material is produced than is needed for a strict legal compliance. For example, it produces the source code for packages released under BSD-like licenses, that you are not required to redistribute in source form.

Moreover, due to technical limitations, Buildroot does not produce some material that you will or may need, such as the toolchain source code and the Buildroot source code itself (including patches to packages for which source distribution is required).

When you run `make legal-info`, Buildroot produces warnings in the `README` file to inform you of relevant material that could not be saved. 当您运行 `make legal-info` 时，Buildroot 会在 `README` 文件中产生警告，通知您无法保存的相关材料。

Finally, keep in mind that the output of `make legal-info` is based on declarative statements in each of the packages recipes. The Buildroot developers try to do their best to keep those declarative statements as accurate as possible, to the best of their knowledge. However, it is very well possible that those declarative statements are not all fully accurate nor exhaustive. You (or your legal department) *have* to check the output of `make legal-info` before using it as your own compliance delivery. See the `NO WARRANTY` clauses (clauses 11 and 12) in the `COPYING` file at the root of the Buildroot distribution.

12.2. Complying with the Buildroot license

Buildroot itself is an open source software, released under the [GNU General Public License, version 2](#) or (at your option) any later version, with the exception of the package patches detailed below. However, being a build system, it is not normally part of the end product: if you develop the root filesystem, kernel, bootloader or toolchain for a device, the code of Buildroot is only present on the development machine, not in the device storage.

Nevertheless, the general view of the Buildroot developers is that you should release the Buildroot source code along with the source code of other packages when releasing a product that contains GPL-licensed software. This

is because the [GNU GPL](#) defines the "complete source code" for an executable work as "all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the executable". Buildroot is part of the scripts used to control compilation and installation of the executable, and as such it is considered part of the material that must be redistributed.

Keep in mind that this is only the Buildroot developers' opinion, and you should consult your legal department or lawyer in case of any doubt.

12.2.1. Patches to packages

Buildroot also bundles patch files, which are applied to the sources of the various packages. Those patches are not covered by the license of Buildroot. Instead, they are covered by the license of the software to which the patches are applied. When said software is available under multiple licenses, the Buildroot patches are only provided under the publicly accessible licenses.

See [Chapter 18. Patching a package](#) for the technical details.

Chapter 13. Beyond Buildroot

13.1. Boot the generated images

13.1.1. NFS boot

To achieve NFS-boot, enable *tar root filesystem* in the *Filesystem images* menu.

After a complete build, just run the following commands to setup the NFS-root directory:

```
sudo tar -xavf /path/to/output_dir/rootfs.tar -C /path/to/nfs_root_dir
```

Remember to add this path to `/etc/exports`.

Then, you can execute a NFS-boot from your target.

13.1.2. Live CD

To build a live CD image, enable the *iso image* option in the *Filesystem images* menu. Note that this option is only available on the x86 and x86-64 architectures, and if you are building your kernel with Buildroot.

You can build a live CD image with either IsoLinux, Grub or Grub 2 as a bootloader, but only Isolinux supports making this image usable both as a live CD and live USB (through the *Build hybrid image* option).

You can test your live CD image using QEMU:

```
qemu-system-i386 -cdrom output/images/rootfs.iso9660
```

Or use it as a hard-drive image if it is a hybrid ISO:

```
qemu-system-i386 -hda output/images/rootfs.iso9660
```

It can be easily flashed to a USB drive with `dd`:

```
dd if=output/images/rootfs.iso9660 of=/dev/sdb
```

13.2. Chroot

If you want to chroot in a generated image, then there are few thing you should be aware of:

- you should setup the new root from the *tar root filesystem* image;
- either the selected target architecture is compatible with your host machine, or you should use some `qemu-*` binary and correctly set it within the `binfmt` properties to be able to run the binaries built for the target on your host machine;
- Buildroot does not currently provide `host-qemu` and `binfmt` correctly built and set for that kind of use.

Part III. Developer guide

Chapter 14. How Buildroot works

As mentioned above, Buildroot is basically a set of Makefiles that download, configure, and compile software with the correct options. It also includes patches for various software packages - mainly the ones involved in the cross-compilation toolchain (`gcc`, `binutils` and `uClibc`).

There is basically one Makefile per software package, and they are named with the `.mk` extension. Makefiles are split into many different parts.

- The `toolchain/` directory contains the Makefiles and associated files for all software related to the cross-compilation toolchain: `binutils`, `gcc`, `gdb`, `kernel-headers` and `uClibc`.
- The `arch/` directory contains the definitions for all the processor architectures that are supported by Buildroot.
- The `package/` directory contains the Makefiles and associated files for all user-space tools and libraries that Buildroot can compile and add to the target root filesystem. There is one sub-directory per package.
- The `linux/` directory contains the Makefiles and associated files for the Linux kernel.
- The `boot/` directory contains the Makefiles and associated files for the bootloaders supported by Buildroot.
- The `system/` directory contains support for system integration, e.g. the target filesystem skeleton and the selection of an init system.
- The `fs/` directory contains the Makefiles and associated files for software related to the generation of the target root filesystem image.

Each directory contains at least 2 files:

- `something.mk` is the Makefile that downloads, configures, compiles and installs the package `something`.
- `Config.in` is a part of the configuration tool description file. It describes the options related to the package.

The main Makefile performs the following steps (once the configuration is done):

- Create all the output directories: `staging`, `target`, `build`, etc. in the output directory (`output/` by default, another value can be specified using `O=`)
- Generate the toolchain target. When an internal toolchain is used, this means generating the cross-compilation toolchain. When an external toolchain is used, this means checking the features of the external toolchain and importing it into the Buildroot environment.
- Generate all the targets listed in the `TARGETS` variable. This variable is filled by all the individual components' Makefiles. Generating these targets will trigger the compilation of the userspace packages (libraries, programs), the kernel, the bootloader and the generation of the root filesystem images, depending on the configuration.

Chapter 15. Coding style

Overall, these coding style rules are here to help you to add new files in Buildroot or refactor existing ones.

If you slightly modify some existing file, the important thing is to keep the consistency of the whole file, so you can:

- either follow the potentially deprecated coding style used in this file, 要么遵循该文件中使用的可能已弃用的编码风格 ,
- or entirely rework it in order to make it comply with these rules. 或者为了让它符合这些规则而完全重做。

15.1. Config.in file

`Config.in` files contain entries for almost anything configurable in Buildroot.

An entry has the following pattern:

```
config BR2_PACKAGE_LIBFOO
    bool "libfoo"
    depends on BR2_PACKAGE_LIBBAZ
    select BR2_PACKAGE_LIBBAR
    help
        This is a comment that explains what libfoo is. The help text
        should be wrapped.

    http://foosoftware.org/libfoo/
```

- The `bool`, `depends on`, `select` and `help` lines are indented with one tab.

- The help text itself should be indented with one tab and two spaces.
- The help text should be wrapped to fit 72 columns, where tab counts for 8, so 62 characters in the text itself.

The `Config.in` files are the input for the configuration tool used in Buildroot, which is the regular *Kconfig*. For further details about the *Kconfig* language, refer to <http://kernel.org/doc/Documentation/kbuild/kconfig-language.txt>.

15.2. The `.mk` file

- Header: The file starts with a header. It contains the module name, preferably in lowercase, enclosed between separators made of 80 hashes. A blank line is mandatory after the header:

```
#####
#
# libfoo
#
#####
```

- Assignment: use `=` preceded and followed by one space:

```
LIBFOO_VERSION = 1.0
LIBFOO_CONF_OPTS += --without-python-support
```

Do not align the `=` signs.

- Indentation: use tab only:

```
define LIBFOO_REMOVE_DOC
    $(RM) -fr $(TARGET_DIR)/usr/share/libfoo/doc \
          $(TARGET_DIR)/usr/share/man/man3/libfoo*
endef
```

Note that commands inside a `define` block should always start with a tab, so *make* recognizes them as commands.

- Optional dependency:
 - Prefer multi-line syntax.

YES:

```
ifneq ($(BR2_PACKAGE_PYTHON),y)
LIBFOO_CONF_OPTS += --with-python-support
LIBFOO_DEPENDENCIES += python
else
LIBFOO_CONF_OPTS += --without-python-support
endif
```

NO:

```
LIBFOO_CONF_OPTS += --with$(if $(BR2_PACKAGE_PYTHON),,out)-python-support
LIBFOO_DEPENDENCIES += $(if $(BR2_PACKAGE_PYTHON),python,)
```

- Keep configure options and dependencies close together.
- Optional hooks: keep hook definition and assignment together in one if block.

YES:

```
ifneq ($(BR2_LIBFOO_INSTALL_DATA),y)
define LIBFOO_REMOVE_DATA
    $(RM) -fr $(TARGET_DIR)/usr/share/libfoo/data
endef
LIBFOO_POST_INSTALL_TARGET_HOOKS += LIBFOO_REMOVE_DATA
endif
```

NO:

```
define LIBFOO_REMOVE_DATA
    $(RM) -fr $(TARGET_DIR)/usr/share/libfoo/data
endef
```

```
ifneq ($(BR2_LIBFOO_INSTALL_DATA),y)
LIBFOO_POST_INSTALL_TARGET_HOOKS += LIBFOO_REMOVE_DATA
endif
```

15.3. The documentation

The documentation uses the [asciidoc](#) format.

For further details about the [asciidoc](#) syntax, refer to <http://www.methods.co.nz/asciidoc/userguide.html>.

15.4. Support scripts

Some scripts in the `support/` and `utils/` directories are written in Python and should follow the [PEP8 Style Guide for Python Code](#).

Chapter 16. Adding support for a particular board

Buildroot contains basic configurations for several publicly available hardware boards, so that users of such a board can easily build a system that is known to work. You are welcome to add support for other boards to Buildroot too.

To do so, you need to create a normal Buildroot configuration that builds a basic system for the hardware: toolchain, kernel, bootloader, filesystem and a simple BusyBox-only userspace. No specific package should be selected: the configuration should be as minimal as possible, and should only build a working basic BusyBox system for the target platform. You can of course use more complicated configurations for your internal projects, but the Buildroot project will only integrate basic board configurations. This is because package selections are highly application-specific.

Once you have a known working configuration, run `make savedefconfig`. This will generate a minimal `defconfig` file at the root of the Buildroot source tree. Move this file into the `configs/` directory, and rename it `<boardname>_defconfig`.

It is recommended to use as much as possible upstream versions of the Linux kernel and bootloaders, and to use as much as possible default kernel and bootloader configurations. If they are incorrect for your board, or no default exists, we encourage you to send fixes to the corresponding upstream projects.

However, in the mean time, you may want to store kernel or bootloader configuration or patches specific to your target platform. To do so, create a directory `board/<manufacturer>` and a subdirectory `board/<manufacturer>/<boardname>`. You can then store your patches and configurations in these directories, and reference them from the main Buildroot configuration. Refer to [Chapter 9. Project-specific customization](#) for more details.

Chapter 17. Adding new packages to Buildroot

This section covers how new packages (userspace libraries or applications) can be integrated into Buildroot. It also shows how existing packages are integrated, which is needed for fixing issues or tuning their configuration.

When you add a new package, be sure to test it in various conditions; see [Section 17.20.2, “How to test your package”](#)

17.1. Package directory

First of all, create a directory under the `package` directory for your software, for example `libfoo`.

Some packages have been grouped by topic in a sub-directory: `x11r7`, `qt5` and `gststreamer`. If your package fits in one of these categories, then create your package directory in these. New subdirectories are discouraged, however.

17.2. Config files

For the package to be displayed in the configuration tool, you need to create a Config file in your package directory. There are two types: `Config.in` and `Config.in.host`.

17.2.1. Config.in file

For packages used on the target, create a file named `Config.in`. This file will contain the option descriptions related to our `libfoo` software that will be used and displayed in the configuration tool. It should basically contain:

```
config BR2_PACKAGE_LIBFOO
    bool "libfoo"
    help
        This is a comment that explains what libfoo is. The help text
        should be wrapped.

    http://foosoftware.org/libfoo/
```

The `bool` line, `help` line and other metadata information about the configuration option must be indented with one tab. The help text itself should be indented with one tab and two spaces, lines should be wrapped to fit 72 columns, where tab counts for 8, so 62 characters in the text itself. The help text must mention the upstream URL of the project after an empty line.

As a convention specific to Buildroot, the ordering of the attributes is as follows:

1. The type of option: `bool`, `string`... with the prompt
2. If needed, the `default` value(s)
3. Any dependency of the `depends on` form
4. Any dependency of the `select` form
5. The help keyword and help text.

You can add other sub-options into a `if BR2_PACKAGE_LIBFOO...endif` statement to configure particular things in your software. You can look at examples in other packages. The syntax of the `Config.in` file is the same as the one for the kernel `Kconfig` file. The documentation for this syntax is available at <http://kernel.org/doc/Documentation/kbuild/kconfig-language.txt>

Finally you have to add your new `libfoo/Config.in` to `package/Config.in` (or in a category subdirectory if you decided to put your package in one of the existing categories). The files included there are *sorted alphabetically* per category and are *NOT* supposed to contain anything but the *bare* name of the package.

```
source "package/libfoo/Config.in"
```

17.2.2. `Config.in.host` file

Some packages also need to be built for the host system. There are two options here:

- The host package is only required to satisfy build-time dependencies of one or more target packages. In this case, add `host-foo` to the target package's `BAR_DEPENDENCIES` variable. No `Config.in.host` file should be created.
- The host package should be explicitly selectable by the user from the configuration menu. In this case, create a `Config.in.host` file for that host package:

```
config BR2_PACKAGE_HOST_FOO
    bool "host foo"
    help
        This is a comment that explains what foo for the host is.

    http://foosoftware.org/foo/
```

The same coding style and options as for the `Config.in` file are valid.

Finally you have to add your new `libfoo/Config.in.host` to `package/Config.in.host`. The files included there are *sorted alphabetically* and are *NOT* supposed to contain anything but the *bare* name of the package.

```
source "package/foo/Config.in.host"
```

The host package will then be available from the `Host utilities` menu.

17.2.3. Choosing `depends on` or `select`

The `Config.in` file of your package must also ensure that dependencies are enabled. Typically, Buildroot uses the following rules:

- Use a `select` type of dependency for dependencies on libraries. These dependencies are generally not obvious and it therefore make sense to have the `kconfig` system ensure that the dependencies are selected. For example, the `libgtk2` package uses `select BR2_PACKAGE_LIBGLIB2` to make sure this library is also enabled. The `select` keyword expresses the dependency with a backward semantic. `select`关键字用向后语义表示依赖关系
- Use a `depends on` type of dependency when the user really needs to be aware of the dependency. Typically, Buildroot uses this type of dependency for dependencies on target architecture, MMU support and toolchain options (see [Section 17.2.4, “Dependencies on target and toolchain options”](#)), or for dependencies on "big" things, such as the X.org system. The `depends on` keyword expresses the dependency with a forward semantic.

Note. The current problem with the `kconfig` language is that these two dependency semantics are not internally linked. Therefore, it may be possible to select a package, whom one of its dependencies/requirement is not met.

An example illustrates both the usage of `select` and `depends on`.

```
config BR2_PACKAGE_RRDTOOL
    bool "rrdtool"
    depends on BR2_USE_WCHAR
    select BR2_PACKAGE_FREETYPE
    select BR2_PACKAGE_LIBART
    select BR2_PACKAGE_LIBPNG
    select BR2_PACKAGE_ZLIB
    help
        RRDtool is the OpenSource industry standard, high performance
        data logging and graphing system for time series data.

        http://oss.oetiker.ch/rrdtool/

comment "rrdtool needs a toolchain w/ wchar"
    depends on !BR2_USE_WCHAR
```

Note that these two dependency types are only transitive with the dependencies of the same kind.

请注意，这两种依赖类型仅在具有相同类型的依赖时是可传递的。

This means, in the following example:

```
config BR2_PACKAGE_A
    bool "Package A"

config BR2_PACKAGE_B
    bool "Package B"
    depends on BR2_PACKAGE_A

config BR2_PACKAGE_C
    bool "Package C"
    depends on BR2_PACKAGE_B

config BR2_PACKAGE_D
    bool "Package D"
    select BR2_PACKAGE_B

config BR2_PACKAGE_E
    bool "Package E"
    select BR2_PACKAGE_D
```

- Selecting `Package C` will be visible if `Package B` has been selected, which in turn is only visible if `Package A` has been selected.
- Selecting `Package E` will select `Package D`, which will select `Package B`, it will not check for the dependencies of `Package B`, so it will not select `Package A`.
- Since `Package B` is selected but `Package A` is not, this violates the dependency of `Package B` on `Package A`. Therefore, in such a situation, the transitive dependency has to be added explicitly:

```
config BR2_PACKAGE_D
    bool "Package D"
    select BR2_PACKAGE_B
    depends on BR2_PACKAGE_A

config BR2_PACKAGE_E
    bool "Package E"
    select BR2_PACKAGE_D
    depends on BR2_PACKAGE_A
```

Overall, for package library dependencies, `select` should be preferred.

总的来说，对于包库依赖项，选择应该是首选的

Note that such dependencies will ensure that the dependency option is also enabled, but not necessarily built before your package. To do so, the dependency also needs to be expressed in the `.mk` file of the package.

Further formatting details: see [the coding style Section 15.1, “Config.in file”](#).

17.2.4. Dependencies on target and toolchain options

Many packages depend on certain options of the toolchain: the choice of C library, C++ support, thread support, RPC support, wchar support, or dynamic library support. Some packages can only be built on certain target architectures, or if an MMU is available in the processor.

These dependencies have to be expressed with the appropriate *depends on* statements in the Config.in file. Additionally, for dependencies on toolchain options, a `comment` should be displayed when the option is not enabled, so that the user knows why the package is not available. Dependencies on target architecture or MMU support should not be made visible in a comment: **since it is unlikely that the user can freely choose another target, it makes little sense to show these dependencies explicitly.** 因为用户不太可能自由地选择另一个目标，所以显式地显示这些依赖关系没有什么意义。只有当满足工具链选项依赖项时，配置选项本身是可见的，注释才应该是可见的。

The `comment` should only be visible if the `config` option itself would be visible when the toolchain option dependencies are met. This means that all other dependencies of the package (including dependencies on target architecture and MMU support) have to be repeated on the `comment` definition. To keep it clear, the `depends on` statement for these non-toolchain option should be kept separate from the `depends on` statement for the toolchain options. If there is a dependency on a config option in that same file (typically the main package) it is preferable to have a global `if ... endif` construct rather than repeating the `depends on` statement on the comment and other config options.

The general format of a dependency `comment` for package foo is:

```
foo needs a toolchain w/ featA, featB, featC
```

for example:

```
mpd needs a toolchain w/ C++, threads, wchar
```

or

```
crda needs a toolchain w/ threads
```

Note that this text is kept brief on purpose, so that it will fit on a 80-character terminal.

请注意，本文故意保持简短，以便适合80个字符的终端。

The rest of this section enumerates the different target and toolchain options, the corresponding config symbols to depend on, and the text to use in the comment.

- Target architecture
 - Dependency symbol: `BR2_powerpc`, `BR2_mips`, ... (see `arch/Config.in`)
 - Comment string: no comment to be added
- MMU support
 - Dependency symbol: `BR2_USE_MMU`
 - Comment string: no comment to be added
- Gcc `_sync*` built-ins used for atomic operations. They are available in variants operating on 1 byte, 2 bytes, 4 bytes and 8 bytes. Since different architectures support atomic operations on different sizes, one dependency symbol is available for each size:
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_SYNC_1` for 1 byte, `BR2_TOOLCHAIN_HAS_SYNC_2` for 2 bytes, `BR2_TOOLCHAIN_HAS_SYNC_4` for 4 bytes, `BR2_TOOLCHAIN_HAS_SYNC_8` for 8 bytes.
 - Comment string: no comment to be added
- Gcc `_atomic*` built-ins used for atomic operations.
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_ATOMIC`.
 - Comment string: no comment to be added
- Kernel headers

- Dependency symbol: `BR2_TOOLCHAIN_HEADERS_AT_LEAST_X_Y`, (replace `X_Y` with the proper version, see `toolchain/toolchain-common.in`)
- Comment string: `headers >= X.Y` and/or `headers <= X.Y` (replace `X.Y` with the proper version)
- GCC version
 - Dependency symbol: `BR2_TOOLCHAIN_GCC_AT_LEAST_X_Y`, (replace `X_Y` with the proper version, see `toolchain/toolchain-common.in`)
 - Comment string: `gcc >= X.Y` and/or `gcc <= X.Y` (replace `X.Y` with the proper version)
- Host GCC version
 - Dependency symbol: `BR2_HOST_GCC_AT_LEAST_X_Y`, (replace `X_Y` with the proper version, see `Config.in`)
 - Comment string: no comment to be added
 - **Note that it is usually not the package itself that has a minimum host GCC version, but rather a host-package on which it depends.** 注意，通常不是包本身具有最小主机GCC版本，而是它所依赖的主机包。
- C library
 - Dependency symbol: `BR2_TOOLCHAIN_USES_GLIBC`, `BR2_TOOLCHAIN_USES_MUSL`, `BR2_TOOLCHAIN_USES_UCLIBC`
 - Comment string: for the C library, **a slightly different comment text is used:** `foo needs a glibc toolchain, or foo needs a glibc toolchain w/ C++` 使用了稍微不同的注释文本:
- C++ support
 - Dependency symbol: `BR2_INSTALL_LIBSTDCPP`
 - Comment string: `C++`
- Fortran support
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_FORTRAN`
 - Comment string: `fortran`
- thread support
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_THREADS`
 - Comment string: `threads` (unless `BR2_TOOLCHAIN_HAS_THREADS_NPTL` is also needed, in which case, specifying only `NPTL` is sufficient)
- NPTL thread support
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_THREADS_NPTL`
 - Comment string: `NPTL`
- RPC support
 - Dependency symbol: `BR2_TOOLCHAIN_HAS_NATIVE_RPC`
 - Comment string: `RPC`
- wchar support
 - Dependency symbol: `BR2_USE_WCHAR`
 - Comment string: `wchar`
- dynamic library
 - Dependency symbol: `!BR2_STATIC_LIBS`
 - Comment string: `dynamic library`

17.2.5. Dependencies on a Linux kernel built by buildroot

依赖于由bui l droot构建的Linux内核

Some packages need a Linux kernel to be built by buildroot. These are typically kernel modules or firmware. A comment should be added in the `Config.in` file to express this dependency, similar to dependencies on toolchain options. The general format is:

```
foo needs a Linux kernel to be built
```

If there is a dependency on both toolchain options and the Linux kernel, use this format:

如果同时依赖于工具链选项和Linux内核，请使用以下格式：

```
foo needs a toolchain w/ featA, featB, featC and a Linux kernel to be built
```

17.2.6. Dependencies on udev /dev management

If a package needs udev /dev management, it should depend on symbol `BR2_PACKAGE_HAS_UDEV`, and the following comment should be added:

```
foo needs udev /dev management
```

If there is a dependency on both toolchain options and udev /dev management, use this format:

```
foo needs udev /dev management and a toolchain w/ featA, featB, featC
```

17.2.7. Dependencies on features provided by virtual packages

Some features can be provided by more than one package, such as the OpenGL libraries.

adj. (与)大学导师(有关)的; (与)家庭教师(有关)的; (与)大学助教(有关)的; (与)辅导(有关)的
n. (大学导师)个别指导时间, 辅导课; 辅导材料, 使用说明书; 软件教程

See [Section 17.11, “Infrastructure for virtual packages”](#) for more on the virtual packages.

17.3. The .mk file

Finally, here's the hardest part. Create a file named `libfoo.mk`. It describes how the package should be downloaded, configured, built, installed, etc.

Depending on the package type, the .mk file must be written in a different way, using different infrastructures:

根据包类型的不同，.mk文件必须使用不同的基础结构以不同的方式编写：

- **Makefiles for generic packages** (not using autotools or CMake): These are based on an infrastructure similar to the one used for autotools-based packages, but require a little more work from the developer. They specify what should be done for the configuration, compilation and installation of the package. This infrastructure must be used for all packages that do not use the autotools as their build system. In the future, other specialized infrastructures might be written for other build systems. We cover them through in a [tutorial Section 17.5.1, “generic-package tutorial”](#) and a [reference Section 17.5.2, “generic-package reference”](#).
- **Makefiles for autotools-based software** (autoconf, automake, etc.): We provide a dedicated infrastructure for such packages, since autotools is a very common build system. This infrastructure *must* be used for new packages that rely on the autotools as their build system. We cover them through a [tutorial Section 17.6.1, “autotools-package tutorial”](#) and a [reference Section 17.6.2, “autotools-package reference”](#).
- **Makefiles for cmake-based software**: We provide a dedicated infrastructure for such packages, as CMake is a more and more commonly used build system and has a standardized behaviour. This infrastructure *must* be used for new packages that rely on CMake. We cover them through a [tutorial Section 17.7.1, “cmake-package tutorial”](#) and a [reference Section 17.7.2, “cmake-package reference”](#).
- **Makefiles for Python modules**: We have a [dedicated infrastructure](#) for Python modules that use either the `distutils` or the `setuptools` mechanism. We cover them through a [tutorial Section 17.8.1, “python-package tutorial”](#) and a [reference Section 17.8.2, “python-package reference”](#).
- **Makefiles for Lua modules**: We have a dedicated infrastructure for Lua modules available through the LuaRocks web site. We cover them through a [tutorial Section 17.9.1, “luarocks-package tutorial”](#) and a [reference Section 17.9.2, “luarocks-package reference”](#).

adj. (与)大学导师(有关)的; (与)家庭教师(有关)的; (与)大学助教(有关)的; (与)辅导(有关)的
n. (大学导师)个别指导时间, 辅导课; 辅导材料, 使用说明书; 软件教程

专门的基础设施

Further formatting details: see [the writing rules Section 15.2, “The .mk file”](#).

17.4. The .hash file

When possible, you must add a third file, named `libfoo.hash`, that contains the hashes of the downloaded files for the `libfoo` package. **The only reason for not adding a .hash file is when hash checking is not possible due to how the package is downloaded.** 不添加.hash文件的唯一原因是由于包的下载方式而无法进行hash检查

The hashes stored in that file are used to validate the integrity of the downloaded files and of the license files.

The format of this file is one line for each file for which to check the hash, each line being space-separated, with these three fields:

- the type of hash, one of:
 - `md5`, `sha1`, `sha224`, `sha256`, `sha384`, `sha512`, `none`
- the hash of the file:
 - for `none`, one or more non-space chars, usually just the string `xxx`
 - for `md5`, 32 hexadecimal characters
 - for `sha1`, 40 hexadecimal characters
 - for `sha224`, 56 hexadecimal characters
 - for `sha256`, 64 hexadecimal characters
 - for `sha384`, 96 hexadecimal characters
 - for `sha512`, 128 hexadecimal characters
- the name of the file:
 - for a source archive: the basename of the file, without any directory component,
 - for a license file: the path as it appears in `FOO_LICENSE_FILES`.

Lines starting with a `#` sign are considered comments, and ignored. Empty lines are ignored.

There can be more than one hash for a single file, each on its own line. In this case, all hashes must match.

Note. Ideally, the hashes stored in this file should match the hashes published by upstream, e.g. on their website, in the e-mail announcement... If upstream provides more than one type of hash (e.g. `sha1` and `sha512`), then it is best to add all those hashes in the `.hash` file. If upstream does not provide any hash, or only provides an `md5` hash, then compute at least one strong hash yourself (preferably `sha256`, but not `md5`), and mention this in a comment line above the hashes.

Note. The hashes for license files are used to detect a license change when a package version is bumped. The hashes are checked during the `make legal-info` target run. For a package with multiple versions (like Qt5), create the hash file in a subdirectory `<packageversion>` of that package (see also [Section 18.2, “How patches are applied”](#)).

Note. The number of spaces does not matter, so one can use spaces (or tabs) to properly align the different fields.

The `none` hash type is reserved to those archives downloaded from a repository, like a *git clone*, a *subversion checkout*...

The example below defines a `sha1` and a `sha256` published by upstream for the main `libfoo-1.2.3.tar.bz2` tarball, an `md5` from upstream and a locally-computed `sha256` hashes for a binary blob, a `sha256` for a downloaded patch, and an archive with no hash:

```
# Hashes from: http://www.foosoftware.org/download/libfoo-1.2.3.tar.bz2.{sha1,sha256}:
sha1    486fb55c3efa71148fe07895fd713ea3a5ae343a    libfoo-1.2.3.tar.bz2
sha256  efc8103cc3bcb06bda6a781532d12701eb081ad83e8f90004b39ab81b65d4369 libfoo-1.2.3.tar.bz2

# md5 from: http://www.foosoftware.org/download/libfoo-1.2.3.tar.bz2.md5, sha256 locally computed:
md5     2d608f3c318c6b7557d551a5a09314f03452f1a1    libfoo-data.bin
sha256  01ba4719c80b6fe911b091a7c05124b64eece964e09c058ef8f9805daca546b libfoo-data.bin

# Locally computed:
sha256  ff52101fb90bbfc3fe9475e425688c660f46216d7e751c4bbdb1dc85cdccac9 libfoo-fix-blabla.patch

# No hash for 1234:
none    xxx                                           libfoo-1234.tar.gz

# Hash for license files:
sha256  a45a845012742796534f7e91fe623262ccfb99460a2bd04015bd28d66fba95b8 COPYING
sha256  01b1f9f2c8ee648a7a596alabe8aa4ed7899b1c9e5551bda06da6e422b04aa55 doc/COPYING.LGPL
```

If the `.hash` file is present, and it contains one or more hashes for a downloaded file, the hash(es) computed by Buildroot (after download) must match the hash(es) stored in the `.hash` file. If one or more hashes do not match, Buildroot considers this an error, deletes the downloaded file, and aborts.

If the `.hash` file is present, but it does not contain a hash for a downloaded file, Buildroot considers this an error and aborts. However, the downloaded file is left in the download directory since this typically indicates that the `.hash` file is wrong but the downloaded file is probably OK.

Hashes are currently checked for files fetched from http/ftp servers, Git repositories, files copied using scp and local files. Hashes are not checked for other version control systems (such as Subversion, CVS, etc.) because Buildroot currently does not generate reproducible tarballs when source code is fetched from such version control systems. 不检查其他版本控制系统(如Subversion, CVS等)的哈希值, 因为从这些版本控制系统获取源代码时, 目前Buildroot不会生成可复制的tarball

Hashes should only be added in .hash files for files that are guaranteed to be stable. For example, patches auto-generated by Github are not guaranteed to be stable, and therefore their hashes can change over time. Such patches should not be downloaded, and instead be added locally to the package folder.

If the .hash file is missing, then no check is done at all.

17.5. Infrastructure for packages with specific build systems

通过带有特定构建系统的包, 我们指的是其构建系统不是标准系统之一的所有包, 如autotools或CMake。

By packages with specific build systems we mean all the packages whose build system is not one of the standard ones, such as autotools or CMake. This typically includes packages whose build system is based on hand-written Makefiles or shell scripts. 这通常包括构建系统基于手写makefile或shell脚本的包。

17.5.1. generic-package tutorial

```
01: #####
02: #
03: # libfoo
04: #
05: #####
06:
07: LIBFOO_VERSION = 1.0
08: LIBFOO_SOURCE = libfoo-$(LIBFOO_VERSION).tar.gz
09: LIBFOO_SITE = http://www.foosoftware.org/download
10: LIBFOO_LICENSE = GPL-3.0+
11: LIBFOO_LICENSE_FILES = COPYING
12: LIBFOO_INSTALL_STAGING = YES
13: LIBFOO_CONFIG_SCRIPTS = libfoo-config
14: LIBFOO_DEPENDENCIES = host-libaaa libbbb
15:
16: define LIBFOO_BUILD_CMDS
17:     $(MAKE) $(TARGET_CONFIGURE_OPTS) -C $(@D) all
18: endef
19:
20: define LIBFOO_INSTALL_STAGING_CMDS
21:     $(INSTALL) -D -m 0755 $(@D)/libfoo.a $(STAGING_DIR)/usr/lib/libfoo.a
22:     $(INSTALL) -D -m 0644 $(@D)/foo.h $(STAGING_DIR)/usr/include/foo.h
23:     $(INSTALL) -D -m 0755 $(@D)/libfoo.so* $(STAGING_DIR)/usr/lib
24: endef
25:
26: define LIBFOO_INSTALL_TARGET_CMDS
27:     $(INSTALL) -D -m 0755 $(@D)/libfoo.so* $(TARGET_DIR)/usr/lib
28:     $(INSTALL) -d -m 0755 $(TARGET_DIR)/etc/foo.d
29: endef
30:
31: define LIBFOO_USERS
32:     foo -l libfoo -l * - - - LibFoo daemon
33: endef
34:
35: define LIBFOO_DEVICES
36:     /dev/foo c 666 0 0 42 0 - - -
37: endef
38:
39: define LIBFOO_PERMISSIONS
40:     /bin/foo f 4755 foo libfoo - - - - -
41: endef
42:
43: $(eval $(generic-package))
```

The Makefile begins on line 7 to 11 with metadata information: the version of the package (`LIBFOO_VERSION`), the name of the tarball containing the package (`LIBFOO_SOURCE`) (xz-ed tarball recommended) the Internet location at which the tarball can be downloaded from (`LIBFOO_SITE`), the license (`LIBFOO_LICENSE`) and file with the license text (`LIBFOO_LICENSE_FILES`). All variables must start with the same prefix, `LIBFOO_` in this case. This prefix is always the uppercased version of the package name (see below to understand where the package name is defined).

On line 12, we specify that this package wants to install something to the staging space. This is often needed for libraries, since they must install header files and other development files in the staging space. This will ensure that the commands listed in the `LIBFOO_INSTALL_STAGING_CMDS` variable will be executed.

On line 13, we specify that there is some fixing to be done to some of the `libfoo-config` files that were installed during `LIBFOO_INSTALL_STAGING_CMDS` phase. These `*-config` files are executable shell script files that are located

in $\$(STAGING_DIR)/usr/bin$ directory and are executed by other 3rd party packages to find out the location and the linking flags of this particular package.

The problem is that all these *-config files by default give wrong, host system linking flags that are unsuitable for cross-compiling.

For example: $-I/usr/include$ instead of $-I\$(STAGING_DIR)/usr/include$ or: $-L/usr/lib$ instead of $-L\$(STAGING_DIR)/usr/lib$

So some sed magic is done to these scripts to make them give correct flags. The argument to be given to `LIBFOO_CONFIG_SCRIPTS` is the file name(s) of the shell script(s) needing fixing. All these names are relative to $\$(STAGING_DIR)/usr/bin$ and if needed multiple names can be given.

In addition, the scripts listed in `LIBFOO_CONFIG_SCRIPTS` are removed from $\$(TARGET_DIR)/usr/bin$, since they are not needed on the target.

Example 17.1. Config script: *divine* package

配置脚本: 神圣包

divine
adj. 神圣的; 非凡的; 天赐的; 极好的
vt. 占卜; 预言; 用占卜勘探
vi. 占卜; 预言; 使用占卜勘探
n. 牧师; 神学家
n. (Divine)人名; (英)迪万

Package *divine* installs shell script $\$(STAGING_DIR)/usr/bin/divine-config$.

So its fixup would be:

```
DIVINE_CONFIG_SCRIPTS = divine-config
```

Example 17.2. Config script: *imagemagick* package:

Package *imagemagick* installs the following scripts: $\$(STAGING_DIR)/usr/bin/\{Magick,Magick++,MagickCore,MagickWand,Wand\}-config$

So its fixup would be:

```
IMAGEMAGICK_CONFIG_SCRIPTS = \  
Magick-config Magick++-config \  
MagickCore-config MagickWand-config Wand-config
```

On line 14, we specify the list of dependencies this package relies on. These dependencies are listed in terms of lower-case package names, which can be packages for the target (without the `host-` prefix) or packages for the host (with the `host-` prefix). Buildroot will ensure that all these packages are built and installed *before* the current package starts its configuration.

The rest of the Makefile, lines 16..29, defines what should be done at the different steps of the package configuration, compilation and installation. `LIBFOO_BUILD_CMDS` tells what steps should be performed to build the package. `LIBFOO_INSTALL_STAGING_CMDS` tells what steps should be performed to install the package in the staging space. `LIBFOO_INSTALL_TARGET_CMDS` tells what steps should be performed to install the package in the target space.

All these steps rely on the $\$(@D)$ variable, which contains the directory where the source code of the package has been extracted.

On lines 31..43, we define a user that is used by this package (e.g. to run a daemon as non-root) (`LIBFOO_USERS`).

On line 35..37, we define a device-node file used by this package (`LIBFOO_DEVICES`).

On line 39..41, we define the permissions to set to specific files installed by this package (`LIBFOO_PERMISSIONS`).

Finally, on line 43, we call the `generic-package` function, which generates, according to the variables defined previously, all the Makefile code necessary to make your package working.

17.5.2. generic-package reference

There are two variants of the generic target. The `generic-package` macro is used for packages to be cross-compiled for the target. The `host-generic-package` macro is used for host packages, natively compiled for the host. It is possible to call both of them in a single `.mk` file: once to create the rules to generate a target package and once to create the rules to generate a host package:

```
$(eval $(generic-package))  
$(eval $(host-generic-package))
```

This might be useful if the compilation of the target package requires some tools to be installed on the host. If the package name is `libfoo`, then the name of the package for the target is also `libfoo`, while the name of the package for the host is `host-libfoo`. These names should be used in the `DEPENDENCIES` variables of other packages, if they depend on `libfoo` or `host-libfoo`.

The call to the `generic-package` and/or `host-generic-package` macro **must** be at the end of the `.mk` file, after all variable definitions.

For the target package, the `generic-package` uses the variables defined by the `.mk` file and prefixed by the uppcased package name: `LIBFOO_*`. `host-generic-package` uses the `HOST_LIBFOO_*` variables. For *some* variables, if the `HOST_LIBFOO_*` prefixed variable doesn't exist, the package infrastructure uses the corresponding variable prefixed by `LIBFOO_*`. This is done for variables that are likely to have the same value for both the target and host packages. See below for details.

The list of variables that can be set in a `.mk` file to give metadata information is (assuming the package name is `libfoo`):

- `LIBFOO_VERSION`, mandatory, must contain the version of the package. Note that if `HOST_LIBFOO_VERSION` doesn't exist, it is assumed to be the same as `LIBFOO_VERSION`. It can also be a revision number, branch or tag for packages that are fetched directly from their revision control system. Examples: `LIBFOO_VERSION = 0.1.2`
`LIBFOO_VERSION = cb9d6aa9429e838f0e54faa3d455bcbab5eef057` `LIBFOO_VERSION = stable`
- `LIBFOO_SOURCE` may contain the name of the tarball of the package, which Buildroot will use to download the tarball from `LIBFOO_SITE`. If `HOST_LIBFOO_SOURCE` is not specified, it defaults to `LIBFOO_SOURCE`. If none are specified, then the value is assumed to be `libfoo-$(LIBFOO_VERSION).tar.gz`. Example: `LIBFOO_SOURCE = foobar-$(LIBFOO_VERSION).tar.bz2`
- `LIBFOO_PATCH` may contain a space-separated list of patch file names, that Buildroot will download and apply to the package source code. If an entry contains `://`, then Buildroot will assume it is a full URL and download the patch from this location. Otherwise, Buildroot will assume that the patch should be downloaded from `LIBFOO_SITE`. If `HOST_LIBFOO_PATCH` is not specified, it defaults to `LIBFOO_PATCH`. Note that patches that are included in Buildroot itself use a different mechanism: all files of the form `*.patch` present in the package directory inside Buildroot will be applied to the package after extraction (see [patching a package Chapter 18. Patching a package](#)). Finally, patches listed in the `LIBFOO_PATCH` variable are applied *before* the patches stored in the Buildroot package directory.
- `LIBFOO_SITE` 提供包的位置，可以是URL或本地文件系统路径。 **provides the location of the package, which can be a URL or a local filesystem path.** HTTP, FTP and SCP are supported URL types for retrieving package tarballs. In these cases don't include a trailing slash: it will be added by Buildroot between the directory and the filename as appropriate. Git, Subversion, Mercurial, and Bazaar are supported URL types for retrieving packages directly from source code management systems. There is a helper function to make it easier to download source tarballs from GitHub (refer to [Section 17.20.3, "How to add a package from GitHub"](#) for details). **A filesystem path may be used to specify either a tarball or a directory containing the package source code.** See `LIBFOO_SITE_METHOD` below for more details on how retrieval works. Note that SCP URLs should be of the form `scp://[user@]host:filepath`, and that filepath is relative to the user's home directory, so you may want to prepend the path with a slash for absolute paths: `scp://[user@]host:/absolutepath`. If `HOST_LIBFOO_SITE` is not specified, it defaults to `LIBFOO_SITE`. Examples: `LIBFOO_SITE=http://www.libfoosoftware.org/libfoo`
`LIBFOO_SITE=http://svn.xiph.org/trunk/Tremor` `LIBFOO_SITE=/opt/software/libfoo.tar.gz`
`LIBFOO_SITE=$(TOPDIR)/../src/libfoo`
n. 代理人；委托书；代用品
- `LIBFOO_DL_OPTS` 是要传递给下载器的附加选项的空格分隔列表。 **is a space-separated list of additional options to pass to the downloader.** Useful for retrieving documents with server-side checking for user logins and passwords, or to use a **proxy**. All download methods valid for `LIBFOO_SITE_METHOD` are supported; valid options depend on the download method (consult the man page for the respective download utilities).
- `LIBFOO_EXTRA_DOWNLOADS` is a space-separated list of additional files that Buildroot should download. If an entry contains `://` then Buildroot will assume it is a complete URL and will download the file using this URL. Otherwise, Buildroot will assume the file to be downloaded is located at `LIBFOO_SITE`. Buildroot will not do anything with those additional files, except download them: it will be up to the package recipe to use them from `$(DL_DIR)`.
- `LIBFOO_SITE_METHOD` determines the method used to fetch or copy the package source code. In many cases, Buildroot guesses the method from the contents of `LIBFOO_SITE` and setting `LIBFOO_SITE_METHOD` is unnecessary. When `HOST_LIBFOO_SITE_METHOD` is not specified, it defaults to the value of `LIBFOO_SITE_METHOD`. The possible values of `LIBFOO_SITE_METHOD` are:
 - `wget` for normal FTP/HTTP downloads of tarballs. Used by default when `LIBFOO_SITE` begins with `http://`, `https://` or `ftp://`.

文件系统路径可用于指定 tarball 或包含源代码的目录。

- `scp` for downloads of tarballs over SSH with `scp`. Used by default when `LIBFOO_SITE` begins with `scp://`.
- `svn` for retrieving source code from a Subversion repository. Used by default when `LIBFOO_SITE` begins with `svn://`. When a `http://` Subversion repository URL is specified in `LIBFOO_SITE`, one *must* specify `LIBFOO_SITE_METHOD=svn`. Buildroot performs a checkout which is preserved as a tarball in the download cache; subsequent builds use the tarball instead of performing another checkout.
- `cvs` for retrieving source code from a CVS repository. Used by default when `LIBFOO_SITE` begins with `cvs://`. The downloaded source code is cached as with the `svn` method. Anonymous pserver mode is assumed otherwise explicitly defined on `LIBFOO_SITE`. Both `LIBFOO_SITE=cvs://libfoo.net:/cvsroot/libfoo` and `LIBFOO_SITE=cvs://:ext:libfoo.net:/cvsroot/libfoo` are accepted, on the former anonymous pserver access mode is assumed. `LIBFOO_SITE` *must* contain the source URL as well as the remote repository directory. The module is the package name. `LIBFOO_VERSION` is *mandatory* and *must* be a tag, a branch, or a date (e.g. "2014-10-20", "2014-10-20 13:45", "2014-10-20 13:45+01" see "man cvs" for further details).
- `git` for retrieving source code from a Git repository. Used by default when `LIBFOO_SITE` begins with `git://`. The downloaded source code is cached as with the `svn` method.
- `hg` for retrieving source code from a Mercurial repository. One *must* specify `LIBFOO_SITE_METHOD=hg` when `LIBFOO_SITE` contains a Mercurial repository URL. The downloaded source code is cached as with the `svn` method.
- `bzr` for retrieving source code from a Bazaar repository. Used by default when `LIBFOO_SITE` begins with `bzr://`. The downloaded source code is cached as with the `svn` method.
- `file` for a local tarball. One should use this when `LIBFOO_SITE` specifies a package tarball as a local filename. Useful for software that isn't available publicly or in version control.
- `local` for a local source code directory. One should use this when `LIBFOO_SITE` specifies a local directory path containing the package source code. Buildroot copies the contents of the source directory into the package's build directory. Note that for `local` packages, no patches are applied. If you need to still patch the source code, use `LIBFOO_POST_RSYNC_HOOKS`, see [Section 17.18.1, "Using the POST_RSYNC hook"](#).
- `LIBFOO_GIT_SUBMODULES` can be set to `YES` to create an archive with the git submodules in the repository. This is only available for packages downloaded with git (i.e. when `LIBFOO_SITE_METHOD=git`). Note that we try not to use such git submodules when they contain bundled libraries, in which case we prefer to use those libraries from their own package.
- `LIBFOO_STRIP_COMPONENTS` is the number of leading components (directories) that tar must strip from file names on extraction. The tarball for most packages has one leading component named "<pkg-name>-<pkg-version>", thus Buildroot passes `--strip-components=1` to tar to remove it. For non-standard packages that don't have this component, or that have more than one leading component to strip, set this variable with the value to be passed to tar. Default: 1.
- `LIBFOO_EXCLUDES` is a space-separated list of patterns to exclude when extracting the archive. Each item from that list is passed as a tar's `--exclude` option. By default, empty.
- `LIBFOO_DEPENDENCIES` lists the dependencies (in terms of package name) that are required for the current target package to compile. These dependencies are guaranteed to be compiled and installed before the configuration of the current package starts. In a similar way, `HOST_LIBFOO_DEPENDENCIES` lists the dependencies for the current host package.
- `LIBFOO_PATCH_DEPENDENCIES` lists the dependencies (in terms of package name) that are required for the current package to be patched. These dependencies are guaranteed to be extracted and patched before the current package is patched. In a similar way, `HOST_LIBFOO_PATCH_DEPENDENCIES` lists the dependencies for the current host package. This is seldom used; usually, `LIBFOO_DEPENDENCIES` is what you really want to use.
- `LIBFOO_PROVIDES` lists all the virtual packages `libfoo` is an implementation of. See [Section 17.11, "Infrastructure for virtual packages"](#).
- `LIBFOO_INSTALL_STAGING` can be set to `YES` or `NO` (default). If set to `YES`, then the commands in the `LIBFOO_INSTALL_STAGING_CMDS` **variables are executed to install the package into the staging directory**. 执行变量将包安装到暂存目录中。
- `LIBFOO_INSTALL_TARGET` can be set to `YES` (default) or `NO`. If set to `YES`, then the commands in the `LIBFOO_INSTALL_TARGET_CMDS` variables are executed to install the package into the target directory.
- `LIBFOO_INSTALL_IMAGES` can be set to `YES` or `NO` (default). If set to `YES`, then the commands in the `LIBFOO_INSTALL_IMAGES_CMDS` variable are executed to install the package into the images directory.
- `LIBFOO_CONFIG_SCRIPTS` lists the names of the files in `$(STAGING_DIR)/usr/bin` that need some special fixing to make them cross-compiling friendly. Multiple file names separated by space can be given and all are relative to `$(STAGING_DIR)/usr/bin`. The files listed in `LIBFOO_CONFIG_SCRIPTS` are also removed from `$(TARGET_DIR)/usr/bin` since they are not needed on the target.

- `LIBFOO_DEVICES` lists the device files to be created by Buildroot when using the static device table. The syntax to use is the `makedevs` one. You can find some documentation for this syntax in the [Chapter 23, Makedev syntax documentation](#). This variable is optional.
- `LIBFOO_PERMISSIONS` lists the changes of permissions to be done at the end of the build process. The syntax is once again the `makedevs` one. You can find some documentation for this syntax in the [Chapter 23, Makedev syntax documentation](#). This variable is optional.
- `LIBFOO_USERS` lists the users to create for this package, if it installs a program you want to run as a specific user (e.g. as a daemon, or as a cron-job). The syntax is similar in spirit to the `makedevs` one, and is described in the [Chapter 24, Makeusers syntax documentation](#). This variable is optional.
- `LIBFOO_LICENSE` defines the license (or licenses) under which the package is released. This name will appear in the manifest file produced by `make legal-info`. If the license appears in [the SPDX License List](#), use the SPDX short identifier to make the manifest file uniform. **Otherwise, describe the license in a precise and concise way, avoiding ambiguous names such as `BSD` which actually name a family of licenses.** This variable is optional. If it is not defined, `unknown` will appear in the `license` field of the manifest file for this package. The expected format for this variable must comply with the following rules:
 - If different parts of the package are released under different licenses, then `comma` separate licenses (e.g. `LIBFOO_LICENSE = GPL-2.0+, LGPL-2.1+`). If there is clear distinction between which component is licensed under what license, then annotate the license with that component, between parenthesis (e.g. `LIBFOO_LICENSE = GPL-2.0+ (programs), LGPL-2.1+ (libraries)`).
 - If the package is dual licensed, then separate licenses with the `or` keyword (e.g. `LIBFOO_LICENSE = AFL-2.1 or GPL-2.0+`).
- `LIBFOO_LICENSE_FILES` is a space-separated list of files in the package tarball that contain the license(s) under which the package is released. `make legal-info` copies all of these files in the `legal-info` directory. See [Chapter 12, Legal notice and licensing](#) for more information. This variable is optional. If it is not defined, a warning will be produced to let you know, and `not saved` will appear in the `license files` field of the manifest file for this package.
- `LIBFOO_ACTUAL_SOURCE_TARBALL` only applies to packages whose `LIBFOO_SITE` / `LIBTOO_SOURCE` pair points to an archive that does not actually contain source code, but binary code. This is a very uncommon case, only known to apply to external toolchains which come already compiled, although theoretically it might apply to other packages. In such cases a separate tarball is usually available with the actual source code. Set `LIBFOO_ACTUAL_SOURCE_TARBALL` to the name of the actual source code archive and Buildroot will download it and use it when you run `make legal-info` to collect legally-relevant material. Note this file will not be downloaded during regular builds nor by `make source`.
- `LIBFOO_ACTUAL_SOURCE_SITE` provides the location of the actual source tarball. The default value is `LIBFOO_SITE`, so you don't need to set this variable if the binary and source archives are hosted on the same directory. If `LIBFOO_ACTUAL_SOURCE_TARBALL` is not set, it doesn't make sense to define `LIBFOO_ACTUAL_SOURCE_SITE`.
- `LIBFOO_REDISTRIBUTE` can be set to `YES` (default) or `NO` to indicate if the package source code is allowed to be redistributed. Set it to `NO` for non-opensource packages: Buildroot will not save the source code for this package when collecting the `legal-info`.
- `LIBFOO_FLAT_STACKSIZE` defines the stack size of an application built into the FLAT binary format. The application stack size on the NOMMU architecture processors can't be enlarged at run time. The default stack size for the FLAT binary format is only 4k bytes. If the application consumes more stack, append the required number here.

The recommended way to define these variables is to use the following syntax:

```
LIBFOO_VERSION = 2.32
```

Now, the variables that define what should be performed at the different steps of the build process.

- `LIBFOO_EXTRACT_CMDS` lists the actions to be performed to extract the package. This is generally not needed as tarballs are automatically handled by Buildroot. However, if the package uses a non-standard archive format, such as a ZIP or RAR file, or has a tarball with a non-standard organization, this variable allows to override the package infrastructure default behavior.
- `LIBFOO_CONFIGURE_CMDS` lists the actions to be performed to configure the package before its compilation.
- `LIBFOO_BUILD_CMDS` lists the actions to be performed to compile the package.
- `HOST_LIBFOO_INSTALL_CMDS` lists the actions to be performed to install the package, when the package is a host package. The package must install its files to the directory given by `$(HOST_DIR)`. All files, including

否则，请以精确和简洁的方式描述许可证，避免使用诸如BSD这样的模糊名称，因为BSD实际上是一组许可证的名称。

development files such as headers should be installed, since other packages might be compiled on top of this package.

- `LIBFOO_INSTALL_TARGET_CMDS` lists the actions to be performed to install the package to the target directory, when the package is a target package. The package must install its files to the directory given by `$(TARGET_DIR)`. Only the files required for *execution* of the package have to be installed. Header files, static libraries and documentation will be removed again when the target filesystem is finalized.
- `LIBFOO_INSTALL_STAGING_CMDS` lists the actions to be performed to install the package to the staging directory, when the package is a target package. The package must install its files to the directory given by `$(STAGING_DIR)`. All development files should be installed, since they might be needed to compile other packages.
- `LIBFOO_INSTALL_IMAGES_CMDS` lists the actions to be performed to install the package to the images directory, when the package is a target package. The package must install its files to the directory given by `$(BINARIES_DIR)`. Only files that are binary images (aka images) that do not belong in the `TARGET_DIR` but are necessary for booting the board should be placed here. For example, a package should utilize this step if it has binaries which would be similar to the kernel image, bootloader or root filesystem images.
- `LIBFOO_INSTALL_INIT_SYSV` and `LIBFOO_INSTALL_INIT_SYSTEMD` list the actions to install init scripts either for the systemV-like init systems (busybox, sysvinit, etc.) or for the systemd units. These commands will be run only when the relevant init system is installed (i.e. if systemd is selected as the init system in the configuration, only `LIBFOO_INSTALL_INIT_SYSTEMD` will be run).
- `LIBFOO_HELP_CMDS` lists the actions to print the package help, which is included to the main `make help` output. These commands can print anything in any format. This is seldom used, as packages rarely have custom rules. **Do not use this variable**, unless you really know that you need to print help.

The preferred way to define these variables is:

```
define LIBFOO_CONFIGURE_CMDS
    action 1
    action 2
    action 3
endef
```

In the action definitions, you can use the following variables:

- `$(LIBFOO_PKGDIR)` contains the path to the directory containing the `libfoo.mk` and `Config.in` files. This variable is useful when it is necessary to install a file bundled in Buildroot, like a runtime configuration file, a splashscreen image...
- `$(@D)`, which contains the directory in which the package source code has been uncompressed.
- `$(DL_DIR)` contains the path to the directory where all the downloads made by Buildroot are stored.
- `$(TARGET_CC)`, `$(TARGET_LD)`, etc. to get the target cross-compilation utilities
- `$(TARGET_CROSS)` to get the cross-compilation toolchain prefix
- Of course the `$(HOST_DIR)`, `$(STAGING_DIR)` and `$(TARGET_DIR)` variables to install the packages properly.

Finally, you can also use hooks. See [Section 17.18, “Hooks available in the various build steps”](#) for more information.

17.6. Infrastructure for autotools-based packages

17.6.1. autotools-package tutorial

First, let's see how to write a `.mk` file for an autotools-based package, with an example :

```
01: #####
02: #
03: # libfoo
04: #
05: #####
06:
07: LIBFOO_VERSION = 1.0
08: LIBFOO_SOURCE = libfoo-$(LIBFOO_VERSION).tar.gz
09: LIBFOO_SITE = http://www.fooosoftware.org/download
10: LIBFOO_INSTALL_STAGING = YES
11: LIBFOO_INSTALL_TARGET = NO
12: LIBFOO_CONF_OPTS = --disable-shared
13: LIBFOO_DEPENDENCIES = libglib2 host-pkgconf
14:
15: $(eval $(autotools-package))
```


On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball (xz-ed tarball recommended) and the location of the tarball on the Web. Buildroot will automatically download the tarball from this location.

On line 10, we tell Buildroot to install the package to the staging directory. The staging directory, located in `output/staging/` is the directory where all the packages are installed, including their development files, etc. By default, packages are not installed to the staging directory, since usually, only libraries need to be installed in the staging directory: their development files are needed to compile other libraries or applications depending on them. Also by default, when staging installation is enabled, packages are installed in this location using the `make install` command.

On line 11, we tell Buildroot to not install the package to the target directory. This directory contains what will become the root filesystem running on the target. For purely static libraries, it is not necessary to install them in the target directory because they will not be used at runtime. By default, target installation is enabled; setting this variable to NO is almost never needed. Also by default, packages are installed in this location using the `make install` command.

On line 12, we tell Buildroot to pass a custom configure option, that will be passed to the `./configure` script before configuring and building the package.

On line 13, we declare our dependencies, so that they are built before the build process of our package starts.

Finally, on line 15, we invoke the `autotools-package` macro that generates all the Makefile rules that actually allows the package to be built.

17.6.2. autotools-package reference

The main macro of the autotools package infrastructure is `autotools-package`. It is similar to the `generic-package` macro. The ability to have target and host packages is also available, with the `host-autotools-package` macro.

Just like the generic infrastructure, the autotools infrastructure works by defining a number of variables before calling the `autotools-package` macro.

n. 元数据, 诠释数据

First, all the package **metadata** information variables that exist in the generic infrastructure also exist in the autotools infrastructure: `LIBFOO_VERSION`, `LIBFOO_SOURCE`, `LIBFOO_PATCH`, `LIBFOO_SITE`, `LIBFOO_SUBDIR`, `LIBFOO_DEPENDENCIES`, `LIBFOO_INSTALL_STAGING`, `LIBFOO_INSTALL_TARGET`.

还可以定义一些特定于autotools基础结构的其他变量。

A few additional variables, specific to the autotools infrastructure, can also be defined. Many of them are only useful in very specific cases, typical packages will therefore only use a few of them.

- `LIBFOO_SUBDIR` may contain the name of a subdirectory inside the package that contains the configure script. This is useful, if for example, the main configure script is not at the root of the tree extracted by the tarball. If `HOST_LIBFOO_SUBDIR` is not specified, it defaults to `LIBFOO_SUBDIR`.
- `LIBFOO_CONF_ENV`, to specify additional environment variables to pass to the configure script. By default, empty.
- `LIBFOO_CONF_OPTS`, to specify additional configure options to pass to the configure script. By default, empty.
- `LIBFOO_MAKE`, to specify an alternate `make` command. This is typically useful when parallel make is enabled in the configuration (using `BR2_JLEVEL`) but that this feature should be disabled for the given package, for one reason or another. By default, set to `$(MAKE)`. If parallel building is not supported by the package, then it should be set to `LIBFOO_MAKE=$(MAKE1)`.
- `LIBFOO_MAKE_ENV`, to specify additional environment variables to pass to make in the build step. These are passed before the `make` command. By default, empty.
- `LIBFOO_MAKE_OPTS`, to specify additional variables to pass to make in the build step. These are passed after the `make` command. By default, empty.
- `LIBFOO_AUTORECONF`, tells whether the package should be autoreconfigured or not (i.e. if the configure script and Makefile.in files should be re-generated by re-running `autoconf`, `automake`, `libtool`, etc.). Valid values are `YES` and `NO`. By default, the value is `NO`.
- `LIBFOO_AUTORECONF_ENV`, to specify additional environment variables to pass to the `autoreconf` program if `LIBFOO_AUTORECONF=YES`. These are passed in the environment of the `autoreconf` command. By default, empty.
- `LIBFOO_AUTORECONF_OPTS` to specify additional options passed to the `autoreconf` program if `LIBFOO_AUTORECONF=YES`. By default, empty.

告诉包是否应该被获取

- `LIBFOO_GETTEXTIZE`, tells whether the package should be gettextized or not (i.e. if the package uses a different gettext version than Buildroot provides, and it is needed to run *gettextize*.) Only valid when `LIBFOO_AUTORECONF=YES`. Valid values are `YES` and `NO`. The default is `NO`.
- `LIBFOO_GETTEXTIZE_OPTS`, to specify additional options passed to the *gettextize* program, if `LIBFOO_GETTEXTIZE=YES`. You may use that if, for example, the `.po` files are not located in the standard place (i.e. in `po/` at the root of the package.) By default, `-f`.
- `LIBFOO_LIBTOOL_PATCH` tells whether the Buildroot patch to fix libtool cross-compilation issues should be applied or not. Valid values are `YES` and `NO`. By default, the value is `YES`.
- `LIBFOO_INSTALL_STAGING_OPTS` contains the make options used to install the package to the staging directory. By default, the value is `DESTDIR=$(STAGING_DIR) install`, which is correct for most autotools packages. It is still possible to override it.
- `LIBFOO_INSTALL_TARGET_OPTS` contains the make options used to install the package to the target directory. By default, the value is `DESTDIR=$(TARGET_DIR) install`. The default value is correct for most autotools packages, but it is still possible to override it if needed.

With the autotools infrastructure, all the steps required to build and install the packages are already defined, and they generally work well for most autotools-based packages. However, when required, it is still possible to customize what is done in any particular step:

- By adding a post-operation hook (after extract, patch, configure, build or install). See [Section 17.18, “Hooks available in the various build steps”](#) for details.
- By overriding one of the steps. For example, even if the autotools infrastructure is used, if the package `.mk` file defines its own `LIBFOO_CONFIGURE_CMDS` variable, it will be used instead of the default autotools one. However, using this method should be restricted to very specific cases. Do not use it in the general case.

17.7. Infrastructure for CMake-based packages

17.7.1. cmake-package tutorial

First, let's see how to write a `.mk` file for a CMake-based package, with an example :

```
01: #####
02: #
03: # libfoo
04: #
05: #####
06:
07: LIBFOO_VERSION = 1.0
08: LIBFOO_SOURCE = libfoo-$(LIBFOO_VERSION).tar.gz
09: LIBFOO_SITE = http://www.foosoftware.org/download
10: LIBFOO_INSTALL_STAGING = YES
11: LIBFOO_INSTALL_TARGET = NO
12: LIBFOO_CONF_OPTS = -DBUILD_DEMOS=ON
13: LIBFOO_DEPENDENCIES = libglib2 host-pkgconf
14:
15: $(eval $(cmake-package))
```

On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball (xz-ed tarball recommended) and the location of the tarball on the Web. Buildroot will automatically download the tarball from this location.

On line 10, we tell Buildroot to install the package to the staging directory. The staging directory, located in `output/staging/` is the directory where all the packages are installed, including their development files, etc. By default, packages are not installed to the staging directory, since usually, only libraries need to be installed in the staging directory: their development files are needed to compile other libraries or applications depending on them. Also by default, when staging installation is enabled, packages are installed in this location using the `make install` command.

On line 11, we tell Buildroot to not install the package to the target directory. This directory contains what will become the root filesystem running on the target. For purely static libraries, it is not necessary to install them in the target directory because they will not be used at runtime. By default, target installation is enabled; setting this variable to `NO` is almost never needed. Also by default, packages are installed in this location using the `make install` command.

On line 12, we tell Buildroot to pass custom options to CMake when it is configuring the package.

On line 13, we declare our dependencies, so that they are built before the build process of our package starts.

Finally, on line 15, we invoke the `cmake-package` macro that generates all the Makefile rules that actually allows the package to be built.

17.7.2. `cmake-package` reference

The main macro of the CMake package infrastructure is `cmake-package`. It is similar to the `generic-package` macro. The ability to have target and host packages is also available, with the `host-cmake-package` macro.

Just like the generic infrastructure, the CMake infrastructure works by defining a number of variables before calling the `cmake-package` macro.

First, all the package metadata information variables that exist in the generic infrastructure also exist in the CMake infrastructure: `LIBFOO_VERSION`, `LIBFOO_SOURCE`, `LIBFOO_PATCH`, `LIBFOO_SITE`, `LIBFOO_SUBDIR`, `LIBFOO_DEPENDENCIES`, `LIBFOO_INSTALL_STAGING`, `LIBFOO_INSTALL_TARGET`.

A few additional variables, specific to the CMake infrastructure, can also be defined. Many of them are only useful in very specific cases, typical packages will therefore only use a few of them.

- `LIBFOO_SUBDIR` may contain the name of a subdirectory inside the package that contains the main `CMakeLists.txt` file. This is useful, if for example, the main `CMakeLists.txt` file is not at the root of the tree extracted by the tarball. If `HOST_LIBFOO_SUBDIR` is not specified, it defaults to `LIBFOO_SUBDIR`.
- `LIBFOO_CONF_ENV`, to specify additional environment variables to pass to CMake. By default, empty.
- `LIBFOO_CONF_OPTS`, to specify additional configure options to pass to CMake. By default, empty. A number of common CMake options are set by the `cmake-package` infrastructure; so it is normally not necessary to set them in the package's `*.mk` file unless you want to override them:
 - `CMAKE_BUILD_TYPE` is driven by `BR2_ENABLE_DEBUG`;
 - `CMAKE_INSTALL_PREFIX`;
 - `BUILD_SHARED_LIBS` is driven by `BR2_STATIC_LIBS`;
 - `BUILD_DOC`, `BUILD_DOCS` are disabled;
 - `BUILD_EXAMPLE`, `BUILD_EXAMPLES` are disabled;
 - `BUILD_TEST`, `BUILD_TESTS`, `BUILD_TESTING` are disabled.
- `LIBFOO_SUPPORTS_IN_SOURCE_BUILD = NO` should be set when the package cannot be built inside the source tree but needs a separate build directory.
- `LIBFOO_MAKE`, to specify an alternate `make` command. This is typically useful when parallel make is enabled in the configuration (using `BR2_JLEVEL`) but that this feature should be disabled for the given package, for one reason or another. By default, set to `$(MAKE)`. If parallel building is not supported by the package, then it should be set to `LIBFOO_MAKE=$(MAKE1)`.
- `LIBFOO_MAKE_ENV`, to specify additional environment variables to pass to make in the build step. These are passed before the `make` command. By default, empty.
- `LIBFOO_MAKE_OPTS`, 在构建步骤中指定要传递给make的其他变量 to specify additional variables to pass to make in the build step. These are passed after the `make` command. By default, empty.
- `LIBFOO_INSTALL_STAGING_OPTS` contains the make options used to install the package to the staging directory. By default, the value is `DESTDIR=$(STAGING_DIR) install`, which is correct for most CMake packages. **It is still possible to override it.** 还是有可能覆盖它的。
- `LIBFOO_INSTALL_TARGET_OPTS` contains the make options used to install the package to the target directory. By default, the value is `DESTDIR=$(TARGET_DIR) install`. The default value is correct for most CMake packages, but it is still possible to override it if needed.

使用CMake基础结构，构建和安装包所需的所有步骤都已经定义好了，而且对于大多数基于CMake的包来说，这些步骤通常都工作得很好。

With the CMake infrastructure, all the steps required to build and install the packages are already defined, and they generally work well for most CMake-based packages. However, when required, it is still possible to customize what is done in any particular step: 然而，在需要时，仍然可以自定义在任何特定步骤中所做的事情。

- By adding a post-operation hook (after extract, patch, configure, build or install). See [Section 17.18, “Hooks available in the various build steps”](#) for details.

通过重写其中一个步骤。

- **By overriding one of the steps.** For example, even if the CMake infrastructure is used, if the package `.mk` file defines its own `LIBFOO_CONFIGURE_CMDS` variable, it will be used instead of the default CMake one. However, **using this method should be restricted to very specific cases. Do not use it in the general case.** 使用这种方法应仅限于非常具体的情况。一般情况下不使用

17.8. Infrastructure for Python packages

该基础结构适用于使用标准Python `setuptools`机制作为构建系统的Python包，通常可以通过使用`setup.py`脚本识别。

This infrastructure applies to Python packages that use the standard Python `setuptools` mechanism as their build system, generally recognizable by the usage of a `setup.py` script.

17.8.1. python-package tutorial

First, let's see how to write a `.mk` file for a Python package, with an example :

```
01: #####
02: #
03: # python-foo
04: #
05: #####
06:
07: PYTHON_FOO_VERSION = 1.0
08: PYTHON_FOO_SOURCE = python-foo-$(PYTHON_FOO_VERSION).tar.xz
09: PYTHON_FOO_SITE = http://www.foosoftware.org/download
10: PYTHON_FOO_LICENSE = BSD-3-Clause
11: PYTHON_FOO_LICENSE_FILES = LICENSE
12: PYTHON_FOO_ENV = SOME_VAR=1
13: PYTHON_FOO_DEPENDENCIES = libmad
14: PYTHON_FOO_SETUP_TYPE = distutils
15:
16: $(eval $(python-package))
```

On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball (xz-ed tarball recommended) and the location of the tarball on the Web. Buildroot will automatically download the tarball from this location.

On line 10 and 11, we give licensing details about the package (its license on line 10, and the file containing the license text on line 11).

On line 12, we tell Buildroot to pass custom options to the Python `setup.py` script when it is configuring the package. 我们告诉Buildroot在配置包时将自定义选项递给Python `setup.py`脚本。

On line 13, we declare our dependencies, so that they are built before the build process of our package starts.

On line 14, we declare the specific Python build system being used. In this case the `distutils` Python build system is used. The two supported ones are `distutils` and `setuptools`.

在这种情况下，使用的是`distutils` Python构建系统。受支持的两个工具是`distutils`和`setuptools`

Finally, on line 16, we invoke the `python-package` macro that generates all the Makefile rules that actually allow the package to be built.

17.8.2. python-package reference

作为一种策略，仅提供Python模块的包都应该在Buildroot中命名为Python `-<something>`。

As a policy, packages that merely provide Python modules should all be named `python-<something>` in Buildroot. Other packages that use the Python build system, but are not Python modules, can freely choose their name (existing examples in Buildroot are `scons` and `supervisor`).

In their `Config.in` file, they should depend on `BR2_PACKAGE_PYTHON` so that when Buildroot will enable Python 3 usage for modules, we will be able to enable Python modules progressively on Python 3.

The main macro of the Python package infrastructure is `python-package`. It is similar to the `generic-package` macro. It is also possible to create Python host packages with the `host-python-package` macro.

Just like the generic infrastructure, the Python infrastructure works by defining a number of variables before calling the `python-package` or `host-python-package` macros.

All the package metadata information variables that exist in the [generic package infrastructure Section 17.5.2, “generic-package reference”](#) also exist in the Python infrastructure: `PYTHON_FOO_VERSION`, `PYTHON_FOO_SOURCE`, `PYTHON_FOO_PATCH`, `PYTHON_FOO_SITE`, `PYTHON_FOO_SUBDIR`, `PYTHON_FOO_DEPENDENCIES`, `PYTHON_FOO_LICENSE`, `PYTHON_FOO_LICENSE_FILES`, `PYTHON_FOO_INSTALL_STAGING`, etc.

Note that:

没有必要在包的`PYTHON_FOO_DEPENDENCIES`变量中添加`python`或`host-python`，因为这些基本依赖项会在python包基础设施需要时自动添加。

- It is not necessary to add `python` or `host-python` in the `PYTHON_FOO_DEPENDENCIES` variable of a package, since these basic dependencies are automatically added as needed by the Python package infrastructure.
- Similarly, it is not needed to add `host-setuptools` and/or `host-distutilscross` dependencies to `PYTHON_FOO_DEPENDENCIES` for `setuptools`-based packages, since these are automatically added by the Python infrastructure as needed.

adv. 自动地；机械地；无意识地
adj. 不经思索的

一个特定于Python基础设施的变量是强制性的:

One variable specific to the Python infrastructure is mandatory:

- `PYTHON_FOO_SETUP_TYPE`, to define which Python build system is used by the package. The two supported values are `distutils` and `setuptools`. If you don't know which one is used in your package, look at the `setup.py` file in your package source code, and see whether it imports things from the `distutils` module or the `setuptools` module.

A few additional variables, specific to the Python infrastructure, can optionally be defined, depending on the package's needs. **Many of them are only useful in very specific cases, typical packages will therefore only use a few of them, or none.** 它们中的许多只在非常特定的情况下有用，因此典型的包将只使用其中的一小部分，或者根本不使用。

- `PYTHON_FOO_ENV`, to specify additional environment variables to pass to the Python `setup.py` script (for both the build and install steps). Note that the infrastructure is automatically passing several standard variables, defined in `PKG_PYTHON_DISTUTILS_ENV` (for `distutils` target packages), `HOST_PKG_PYTHON_DISTUTILS_ENV` (for `distutils` host packages), `PKG_PYTHON_SETUPTOOLS_ENV` (for `setuptools` target packages) and `HOST_PKG_PYTHON_SETUPTOOLS_ENV` (for `setuptools` host packages).
- `PYTHON_FOO_BUILD_OPTS`, to specify additional options to pass to the Python `setup.py` script during the build step. For target `distutils` packages, the `PKG_PYTHON_DISTUTILS_BUILD_OPTS` options are already passed automatically by the infrastructure.
- `PYTHON_FOO_INSTALL_TARGET_OPTS`, `PYTHON_FOO_INSTALL_STAGING_OPTS`, `HOST_PYTHON_FOO_INSTALL_OPTS` to specify additional options to pass to the Python `setup.py` script during the target installation step, the staging installation step or the host installation, respectively. Note that the infrastructure is automatically passing some options, defined in `PKG_PYTHON_DISTUTILS_INSTALL_TARGET_OPTS` or `PKG_PYTHON_DISTUTILS_INSTALL_STAGING_OPTS` (for target `distutils` packages), `HOST_PKG_PYTHON_DISTUTILS_INSTALL_OPTS` (for host `distutils` packages), `PKG_PYTHON_SETUPTOOLS_INSTALL_TARGET_OPTS` or `PKG_PYTHON_SETUPTOOLS_INSTALL_STAGING_OPTS` (for target `setuptools` packages) and `HOST_PKG_PYTHON_SETUPTOOLS_INSTALL_OPTS` (for host `setuptools` packages).
- `HOST_PYTHON_FOO_NEEDS_HOST_PYTHON`, to define the host python interpreter. The usage of this variable is limited to host packages. The two supported value are `python2` and `python3`. **It will ensure the right host python package is available and will invoke it for the build. If some build steps are overloaded, the right python interpreter must be explicitly called in the commands.**

它将确保正确的宿主python包可用，并将在构建时调用它。 如果某些构建步骤被重载，则必须在命令中显式调用正确的python解释器。

With the Python infrastructure, all the steps required to build and install the packages are already defined, and they generally work well for most Python-based packages. However, when required, it is still possible to customize what is done in any particular step:

- By adding a post-operation hook (after extract, patch, configure, build or install). See [Section 17.18, “Hooks available in the various build steps”](#) for details.
- By overriding one of the steps. For example, even if the Python infrastructure is used, if the package `.mk` file defines its own `PYTHON_FOO_BUILD_CMDS` variable, it will be used instead of the default Python one. However, using this method should be restricted to very specific cases. Do not use it in the general case.

17.8.3. Generating a python-package from a PyPI repository

If the Python package for which you would like to create a Buildroot package is available on PyPI, you may want to use the `scanpypi` tool located in `utils/` to automate the process.

You can find the list of existing PyPI packages [here](#).

`scanpypi` requires Python's `setuptools` package to be installed on your host.

When at the root of your buildroot directory just do :

```
utils/scanpypi foo bar -o package
```

This will generate packages `python-foo` and `python-bar` in the package folder if they exist on <https://pypi.python.org>.

Find the `external python modules` menu and insert your package inside. Keep in mind that the items inside a menu should be in **alphabetical** order.

adj. 字母的; [计] 依字母顺序的

Please keep in mind that you'll most likely have to manually check the package for any mistakes as there are things that cannot be guessed by the generator (e.g. dependencies on any of the python core modules such as `BR2_PACKAGE_PYTHON_ZLIB`). Also, please take note that the license and license files are guessed and must be checked. You also need to manually add the package to the `package/Config.in` file.

If your Buildroot package is not in the official Buildroot tree but in a br2-external tree, use the `-o` flag as follows:

```
utils/scanpypi foo bar -o other_package_dir
```

This will generate packages `python-foo` and `python-bar` in the `other_package_directory` instead of `package`.

Option `-h` will list the available options:

```
utils/scanpypi -h
```

17.8.4. python-package CFFI backend

C Foreign Function Interface for Python (CFFI) provides a convenient and reliable way to call compiled C code from Python using interface declarations written in C. Python packages relying on this backend can be identified by the appearance of a `cffi` dependency in the `install_requires` field of their `setup.py` file.

Such a package should:

- add `python-cffi` as a runtime dependency in order to install the compiled C library wrapper on the target. This is achieved by adding `select BR2_PACKAGE_PYTHON_CFFI` to the package `Config.in`.

```
config BR2_PACKAGE_PYTHON_FOO
    bool "python-foo"
    select BR2_PACKAGE_PYTHON_CFFI # runtime
```

n. 包装材料; [包装] 包装纸; 书皮

- add `host-python-cffi` as a build-time dependency in order to cross-compile the C `wrapper`. This is achieved by adding `host-python-cffi` to the `PYTHON_FOO_DEPENDENCIES` variable.

```
#####
#
# python-foo
#
#####
...

PYTHON_FOO_DEPENDENCIES = host-python-cffi

$(eval $(python-package))
```

17.9. Infrastructure for LuaRocks-based packages

17.9.1. luarocks-package tutorial

First, let's see how to write a `.mk` file for a LuaRocks-based package, with an example :

```
01: #####
02: #
03: # lua-foo
04: #
05: #####
06:
07: LUA_FOO_VERSION = 1.0.2-1
08: LUA_FOO_NAME_UPSTREAM = foo
09: LUA_FOO_DEPENDENCIES = bar
10:
11: LUA_FOO_BUILD_OPTS += BAR_INCDIR=$(STAGING_DIR)/usr/include
12: LUA_FOO_BUILD_OPTS += BAR_LIBDIR=$(STAGING_DIR)/usr/lib
13: LUA_FOO_LICENSE = luaFoo license
14: LUA_FOO_LICENSE_FILES = $(LUA_FOO_SUBDIR)/COPYING
15:
16: $(eval $(luarocks-package))
```

与rockspec相同，它是上游版本和rockspec修订版本的连接，用连字符隔开

On line 7, we declare the version of the package (the same as in the rockspec, which is the concatenation of the upstream version and the rockspec revision, separated by a hyphen -).

On line 8, we declare that the package is called "foo" on LuaRocks. In Buildroot, we give Lua-related packages a name that starts with "lua", so the Buildroot name is different from the upstream name. `LUA_FOO_NAME_UPSTREAM` makes the link between the two names.

On line 9, we declare our dependencies against native libraries, so that they are built before the build process of our package starts. 我们针对本地库声明依赖关系，以便在包的构建过程开始之前构建它们。

On lines 11-12, we tell Buildroot to pass custom options to LuaRocks when it is building the package.

On lines 13-14, we specify the licensing terms for the package.

Finally, on line 16, we invoke the `luarocks-package` macro that generates all the Makefile rules that actually allows the package to be built.

17.9.2. luarocks-package reference

LuaRocks is a deployment and management system for Lua modules, and supports various `build.type: builtin`, `make` and `cmake`. In the context of Buildroot, the `luarocks-package` infrastructure only supports the `builtin` mode. LuaRocks packages that use the `make` or `cmake` build mechanisms should instead be packaged using the `generic-package` and `cmake-package` infrastructures in Buildroot, **respectively**. *adv. 分别地；各自地，独自地*

The main macro of the LuaRocks package infrastructure is `luarocks-package`: like `generic-package` it works by defining a number of variables providing metadata information about the package, and then calling `luarocks-package`. **It is worth mentioning that building LuaRocks packages for the host is not supported, so the macro `host-luarocks-package` is not implemented.** *值得一提的是，不支持为主机构建LuaRocks包，因此不实现宏`host-luarocks-package`。*

Just like the generic infrastructure, the LuaRocks infrastructure works by defining a number of variables before calling the `luarocks-package` macro.

First, all the package metadata information variables that exist in the generic infrastructure also exist in the LuaRocks infrastructure: `LUA_FOO_VERSION`, `LUA_FOO_SOURCE`, `LUA_FOO_SITE`, `LUA_FOO_DEPENDENCIES`, `LUA_FOO_LICENSE`, `LUA_FOO_LICENSE_FILES`.

Two of them are populated by the LuaRocks infrastructure (for the `download` step). If your package is not hosted on the LuaRocks mirror `$(BR2_LUAROCKS_MIRROR)`, you can override them:

- `LUA_FOO_SITE`, which defaults to `$(BR2_LUAROCKS_MIRROR)`
- `LUA_FOO_SOURCE`, which defaults to `$(lowercase LUA_FOO_NAME_UPSTREAM) - $(LUA_FOO_VERSION).src.rock`

A few additional variables, specific to the LuaRocks infrastructure, are also defined. They can be overridden in specific cases.

- `LUA_FOO_NAME_UPSTREAM`, which defaults to `lua-foo`, i.e. the Buildroot package name
- `LUA_FOO_ROCKSPEC`, which defaults to `$(lowercase LUA_FOO_NAME_UPSTREAM) - $(LUA_FOO_VERSION).rockspec`
- `LUA_FOO_SUBDIR`, which defaults to `$(LUA_FOO_NAME_UPSTREAM) - $(LUA_FOO_VERSION_WITHOUT_ROCKSPEC_REVISION)`
- `LUA_FOO_BUILD_OPTS` contains additional build options for the `luarocks build` call.

17.10. Infrastructure for Perl/CPAN packages

17.10.1. perl-package tutorial

First, let's see how to write a `.mk` file for a Perl/CPAN package, with an example :

```
01: #####
02: #
03: # perl-foo-bar
04: #
05: #####
06:
07: PERL_FOO_BAR_VERSION = 0.02
08: PERL_FOO_BAR_SOURCE = Foo-Bar-$(PERL_FOO_BAR_VERSION).tar.gz
09: PERL_FOO_BAR_SITE = $(BR2_CPAN_MIRROR)/authors/id/M/MO/MONGER
10: PERL_FOO_BAR_DEPENDENCIES = perl-strictures
11: PERL_FOO_BAR_LICENSE = Artistic or GPL-1.0+
12: PERL_FOO_BAR_LICENSE_FILES = LICENSE
13:
14: $(eval $(perl-package))
```

On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball and the location of the tarball on a CPAN server. Buildroot will automatically download the tarball from this location.

On line 10, we declare our dependencies, so that they are built before the build process of our package starts.

On line 11 and 12, we give licensing details about the package (its license on line 11, and the file containing the license text on line 12).

Finally, on line 14, we invoke the `perl-package` macro that generates all the Makefile rules that actually allow the package to be built.

Most of these data can be retrieved from <https://metacpan.org/>. So, this file and the `Config.in` can be generated by running the script `supports/scripts/scancpan Foo-Bar` in the Buildroot directory (or in a `br2-external` tree). This script creates a `Config.in` file and `foo-bar.mk` file for the requested package, and also recursively for all dependencies specified by CPAN. You should still manually edit the result. In particular, the following things should be checked.

- If the perl module links with a shared library that is provided by another (non-perl) package, this dependency is not added automatically. It has to be added manually to `PERL_FOO_BAR_DEPENDENCIES`.
- The `package/Config.in` file has to be updated manually to include the generated `Config.in` files. As a hint, the `scancpan` script prints out the required `source` `"..."` statements, sorted alphabetically.

17.10.2. perl-package reference

As a policy, packages that provide Perl/CPAN modules should all be named `perl-<something>` in Buildroot.

This infrastructure handles various Perl build systems : `ExtUtils-MakeMaker` (EUMM), `Module-Build` (MB) and `Module-Build-Tiny`. `Build.PL` is preferred by default when a package provides a `Makefile.PL` and a `Build.PL`.

The main macro of the Perl/CPAN package infrastructure is `perl-package`. It is similar to the `generic-package` macro. The ability to have target and host packages is also available, with the `host-perl-package` macro.

Just like the generic infrastructure, the Perl/CPAN infrastructure works by defining a number of variables before calling the `perl-package` macro.

First, all the package metadata information variables that exist in the generic infrastructure also exist in the Perl/CPAN infrastructure: `PERL_FOO_VERSION`, `PERL_FOO_SOURCE`, `PERL_FOO_PATCH`, `PERL_FOO_SITE`, `PERL_FOO_SUBDIR`, `PERL_FOO_DEPENDENCIES`, `PERL_FOO_INSTALL_TARGET`.

Note that setting `PERL_FOO_INSTALL_STAGING` to `YES` has no effect unless a `PERL_FOO_INSTALL_STAGING_CMDS` variable is defined. The perl infrastructure doesn't define these commands since Perl modules generally don't need to be installed to the `staging` directory.

A few additional variables, specific to the Perl/CPAN infrastructure, can also be defined. Many of them are only useful in very specific cases, typical packages will therefore only use a few of them.

- `PERL_FOO_PREFER_INSTALLER/HOST_PERL_FOO_PREFER_INSTALLER`, specifies the preferred installation method. Possible values are `EUMM` (for `Makefile.PL` based installation using `ExtUtils-MakeMaker`) and `MB` (for `Build.PL` based installation using `Module-Build`). This variable is only used when the package provides both installation methods.
- `PERL_FOO_CONF_ENV/HOST_PERL_FOO_CONF_ENV`, to specify additional environment variables to pass to the `perl Makefile.PL` or `perl Build.PL`. By default, empty.
- `PERL_FOO_CONF_OPTS/HOST_PERL_FOO_CONF_OPTS`, to specify additional configure options to pass to the `perl Makefile.PL` or `perl Build.PL`. By default, empty.
- `PERL_FOO_BUILD_OPTS/HOST_PERL_FOO_BUILD_OPTS`, to specify additional options to pass to `make pure_all` or `perl Build build` in the build step. By default, empty.
- `PERL_FOO_INSTALL_TARGET_OPTS`, to specify additional options to pass to `make pure_install` or `perl Build install` in the install step. By default, empty.
- `HOST_PERL_FOO_INSTALL_OPTS`, to specify additional options to pass to `make pure_install` or `perl Build install` in the install step. By default, empty.

17.11. Infrastructure for virtual packages

In Buildroot, a virtual package is a package whose functionalities are provided by one or more packages, referred to as *providers*. The virtual package management is an extensible mechanism allowing the user to choose the provider used in the rootfs.

For example, *OpenGL ES* is an API for 2D and 3D graphics on embedded systems. The implementation of this API is different for the *Allwinner Tech Sunxi* and the *Texas Instruments OMAP35xx* platforms. So `libgles` will be a virtual package and `sunxi-mali` and `ti-gfx` will be the providers.

17.11.1. virtual-package tutorial

In the following example, we will explain how to add a new virtual package (*something-virtual*) and a provider for it (*some-provider*).

First, let's create the virtual package.

17.11.2. Virtual package's Config.in file

The `Config.in` file of virtual package *something-virtual* should contain:

```
01: config BR2_PACKAGE_HAS_SOMETHING_VIRTUAL
02:     bool
03:
04: config BR2_PACKAGE_PROVIDES_SOMETHING_VIRTUAL
05:     depends on BR2_PACKAGE_HAS_SOMETHING_VIRTUAL
06:     string
```

In this file, we declare two options, `BR2_PACKAGE_HAS_SOMETHING_VIRTUAL` and `BR2_PACKAGE_PROVIDES_SOMETHING_VIRTUAL`, whose values will be used by the providers.

17.11.3. Virtual package's .mk file

The `.mk` for the virtual package should just evaluate the `virtual-package` macro:

```
01: #####
02: #
03: # something-virtual
04: #
05: #####
06:
07: $(eval $(virtual-package))
```

The ability to have target and host packages is also available, with the `host-virtual-package` macro.

17.11.4. Provider's Config.in file

When adding a package as a provider, only the `Config.in` file requires some modifications.

The `Config.in` file of the package *some-provider*, which provides the functionalities of *something-virtual*, should contain:

```
01: config BR2_PACKAGE_SOME_PROVIDER
02:     bool "some-provider"
03:     select BR2_PACKAGE_HAS_SOMETHING_VIRTUAL
04:     help
05:         This is a comment that explains what some-provider is.
06:
07:     http://foosoftware.org/some-provider/
08:
09: if BR2_PACKAGE_SOME_PROVIDER
10: config BR2_PACKAGE_PROVIDES_SOMETHING_VIRTUAL
11:     default "some-provider"
12: endif
```

On line 3, we select `BR2_PACKAGE_HAS_SOMETHING_VIRTUAL`, and on line 11, we set the value of `BR2_PACKAGE_PROVIDES_SOMETHING_VIRTUAL` to the name of the provider, but only if it is selected.

17.11.5. Provider's .mk file

The `.mk` file should also declare an additional variable `SOME_PROVIDER_PROVIDES` to contain the names of all the virtual packages it is an implementation of:

```
01: SOME_PROVIDER_PROVIDES = something-virtual
```

Of course, do not forget to add the proper build and runtime dependencies for this package!

17.11.6. Notes on depending on a virtual package

When adding a package that requires a certain `FEATURE` provided by a virtual package, you have to use `depends on BR2_PACKAGE_HAS_FEATURE`, like so:

```
config BR2_PACKAGE_HAS_FEATURE
    bool

config BR2_PACKAGE_FOO
    bool "foo"
    depends on BR2_PACKAGE_HAS_FEATURE
```

17.11.7. Notes on depending on a specific provider

If your package really requires a specific provider, then you'll have to make your package `depends on` this provider; you can *not* `select` a provider.

Let's take an example with two providers for a `FEATURE`:

```
config BR2_PACKAGE_HAS_FEATURE
    bool

config BR2_PACKAGE_FOO
    bool "foo"
    select BR2_PACKAGE_HAS_FEATURE

config BR2_PACKAGE_BAR
    bool "bar"
    select BR2_PACKAGE_HAS_FEATURE
```

And you are adding a package that needs `FEATURE` as provided by `foo`, but not as provided by `bar`.

If you were to use `select BR2_PACKAGE_FOO`, then the user would still be able to select `BR2_PACKAGE_BAR` in the `menuconfig`. This would create a configuration inconsistency, whereby two providers of the same `FEATURE` would be enabled at once, one explicitly set by the user, the other implicitly by your `select`.

Instead, you have to use `depends on BR2_PACKAGE_FOO`, which avoids any implicit configuration inconsistency.

17.12. Infrastructure for packages using `kconfig` for configuration files

A popular way for a software package to handle user-specified configuration is `kconfig`. Among others, it is used by the Linux kernel, Busybox, and Buildroot itself. The presence of a `.config` file and a `menuconfig` target are two well-known symptoms of `kconfig` being used.

Buildroot features an infrastructure for packages that use `kconfig` for their configuration. This infrastructure provides the necessary logic to expose the package's `menuconfig` target as `foo-menuconfig` in Buildroot, and to handle the copying back and forth of the configuration file in a correct way.

The `kconfig-package` infrastructure is based on the `generic-package` infrastructure. All variables supported by `generic-package` are available in `kconfig-package` as well. See [Section 17.5.2, “generic-package reference”](#) for more details.

In order to use the `kconfig-package` infrastructure for a Buildroot package, the minimally required lines in the `.mk` file, in addition to the variables required by the `generic-package` infrastructure, are:

```
FOO_KCONFIG_FILE = reference-to-source-configuration-file

$(eval $(kconfig-package))
```

This snippet creates the following make targets: 这个代码片段创建了以下make目标:

- `foo-menuconfig`, which calls the package's `menuconfig` target
- `foo-update-config`, which copies the configuration back to the source configuration file. It is not possible to use this target when fragment files are set.
- `foo-update-defconfig`, which copies the configuration back to the source configuration file. The configuration file will only list the options that differ from the default values. It is not possible to use this target when fragment files are set.

and ensures that the source configuration file is copied to the build directory at the right moment.

There are two options to specify a configuration file to use, either `FOO_KCONFIG_FILE` (as in the example, above) or `FOO_KCONFIG_DEFCONFIG`. It is mandatory to provide either, but not both:

- `FOO_KCONFIG_FILE` specifies the path to a defconfig or full-config file to be used to configure the package.
- `FOO_KCONFIG_DEFCONFIG` specifies the defconfig *make* rule to call to configure the package.

In addition to these minimally required lines, several optional variables can be set to suit the needs of the package under consideration:

- `FOO_KCONFIG_EDITORS`: a space-separated list of kconfig editors to support, for example *menuconfig xconfig*. By default, *menuconfig*.
- `FOO_KCONFIG_FRAGMENT_FILES`: a space-separated list of configuration fragment files that are merged to the main configuration file. Fragment files are typically used when there is a desire to stay in sync with an upstream (def)config file, with some minor modifications.
- `FOO_KCONFIG_OPTS`: extra options to pass when calling the kconfig editors. This may need to include `$(FOO_MAKE_OPTS)`, for example. By default, empty.
- `FOO_KCONFIG_FIXUP_CMDS`: a list of shell commands needed to fixup the configuration file after copying it or running a kconfig editor. Such commands may be needed to ensure a configuration consistent with other configuration of Buildroot, for example. By default, empty.
- `FOO_KCONFIG_DOTCONFIG`: path (with filename) of the `.config` file, relative to the package source tree. The default, `.config`, should be well suited for all packages that use the standard kconfig infrastructure as inherited from the Linux kernel; **some packages use a derivative of kconfig that use a different location.**
有些包使用kconfig的派生版本，使用不同的位置。

17.13. Infrastructure for rebar-based packages

17.13.1. rebar-package tutorial

First, let's see how to write a `.mk` file for a rebar-based package, with an example :

```
01: #####
02: #
03: # erlang-foobar
04: #
05: #####
06:
07: ERLANG_FOOBAR_VERSION = 1.0
08: ERLANG_FOOBAR_SOURCE = erlang-foobar-$(ERLANG_FOOBAR_VERSION).tar.xz
09: ERLANG_FOOBAR_SITE = http://www.fooftware.org/download
10: ERLANG_FOOBAR_DEPENDENCIES = host-libaaa libbbb
11:                               n. 地点；位置；场所
12: $(eval $(rebar-package))      vt. 设置；为...选址
```

On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball (xz-ed tarball recommended) and the location of the tarball on the Web. Buildroot will automatically download the tarball from this location.

On line 10, we declare our dependencies, so that they are built before the build process of our package starts.

Finally, on line 12, we invoke the `rebar-package` macro that generates all the Makefile rules that actually allows the package to be built.

17.13.2. rebar-package reference

The main macro of the `rebar` package infrastructure is `rebar-package`. It is similar to the `generic-package` macro. **The ability to have host packages is also available, with the `host-rebar-package` macro.**
使用host-rebar-package宏，也可以使用主机包。

Just like the generic infrastructure, the `rebar` infrastructure works by defining a number of variables before calling the `rebar-package` macro.

First, all the package metadata information variables that exist in the generic infrastructure also exist in the `rebar` infrastructure: `ERLANG_FOOBAR_VERSION`, `ERLANG_FOOBAR_SOURCE`, `ERLANG_FOOBAR_PATCH`, `ERLANG_FOOBAR_SITE`, `ERLANG_FOOBAR_SUBDIR`, `ERLANG_FOOBAR_DEPENDENCIES`, `ERLANG_FOOBAR_INSTALL_STAGING`, `ERLANG_FOOBAR_INSTALL_TARGET`, `ERLANG_FOOBAR_LICENSE` and `ERLANG_FOOBAR_LICENSE_FILES`.

A few additional variables, specific to the `rebar` infrastructure, can also be defined. **Many of them are only useful in very specific cases, typical packages will therefore only use a few of them.**
它们中的许多只在非常特定的情况下有用，因此典型的包只会使用其中的一小部分。

- `ERLANG_FOOBAR_USE_AUTOCONF`, to specify that the package uses *autoconf* at the configuration step. When a package sets this variable to `YES`, the `autotools` infrastructure is used.

Note. You can also use some of the variables from the `autotools` infrastructure: `ERLANG_FOOBAR_CONF_ENV`, `ERLANG_FOOBAR_CONF_OPTS`, `ERLANG_FOOBAR_AUTORECONF`, `ERLANG_FOOBAR_AUTORECONF_ENV` and `ERLANG_FOOBAR_AUTORECONF_OPTS`.

- `ERLANG_FOOBAR_USE_BUNDLED_REBAR`, to specify that the package has a bundled version of *rebar* **and** that it shall be used. Valid values are `YES` or `NO` (the default).

如果包了一个rebar实用程序，但是可以使用Buildroot提供的通用实用程序，只需说NO(也就是说，不要指定这个变量)。

Note. If the package bundles a *rebar* utility, but can use the generic one that Buildroot provides, just say `NO` (i.e., do not specify this variable). Only set it if it is mandatory to use the *rebar* utility bundled in this package.

- `ERLANG_FOOBAR_REBAR_ENV`, to specify additional environment variables to pass to the *rebar* utility.

With the *rebar* infrastructure, all the steps required to build and install the packages are already defined, and they generally work well for most *rebar*-based packages. However, when required, it is still possible to customize what is done in any particular step:

- By adding a post-operation hook (after extract, patch, configure, build or install). See [Section 17.18, “Hooks available in the various build steps”](#) for details.
- By overriding one of the steps. For example, even if the *rebar* infrastructure is used, if the package `.mk` file defines its own `ERLANG_FOOBAR_BUILD_CMDS` variable, it will be used instead of the default *rebar* one. However, using this method should be restricted to very specific cases. Do not use it in the general case.

17.14. Infrastructure for Waf-based packages

17.14.1. waf-package tutorial

First, let's see how to write a `.mk` file for a Waf-based package, with an example :

```
01: #####
02: #
03: # libfoo
04: #
05: #####
06:
07: LIBFOO_VERSION = 1.0
08: LIBFOO_SOURCE = libfoo-$(LIBFOO_VERSION).tar.gz
09: LIBFOO_SITE = http://www.fooftware.org/download
10: LIBFOO_CONF_OPTS = --enable-bar --disable-baz
11: LIBFOO_DEPENDENCIES = bar
12:
13: $(eval $(waf-package))
```

On line 7, we declare the version of the package.

On line 8 and 9, we declare the name of the tarball (xz-ed tarball recommended) and the location of the tarball on the Web. Buildroot will automatically download the tarball from this location.

On line 10, we tell Buildroot what options to enable for libfoo.

On line 11, we tell Buildroot the dependencies of libfoo.

Finally, on line 13, we invoke the `waf-package` macro that generates all the Makefile rules that actually allows the package to be built.

17.14.2. waf-package reference

The main macro of the Waf package infrastructure is `waf-package`. It is similar to the `generic-package` macro.

Just like the generic infrastructure, the Waf infrastructure works by defining a number of variables before calling the `waf-package` macro.

First, all the package metadata information variables that exist in the generic infrastructure also exist in the Waf infrastructure: `LIBFOO_VERSION`, `LIBFOO_SOURCE`, `LIBFOO_PATCH`, `LIBFOO_SITE`, `LIBFOO_SUBDIR`, `LIBFOO_DEPENDENCIES`, `LIBFOO_INSTALL_STAGING`, `LIBFOO_INSTALL_TARGET`.

An additional variable, specific to the Waf infrastructure, can also be defined.

- `LIBFOO_NEEDS_EXTERNAL_WAF` can be set to `YES` or `NO` to tell Buildroot to use the bundled *waf* executable. If set to `NO`, the default, then Buildroot will use the *waf* executable provided in the package source tree; if set to `YES`, then Buildroot will download, install *waf* as a host tool and use it to build the package.

- `LIBFOO_WAF_OPTS`, to specify additional options to pass to the `waf` script at every step of the package build process: configure, build and installation. By default, empty.
- `LIBFOO_CONF_OPTS`, to specify additional options to pass to the `waf` script for the configuration step. By default, empty.
- `LIBFOO_BUILD_OPTS`, to specify additional options to pass to the `waf` script during the build step. By default, empty.
- `LIBFOO_INSTALL_STAGING_OPTS`, to specify additional options to pass to the `waf` script during the staging installation step. By default, empty.
- `LIBFOO_INSTALL_TARGET_OPTS`, to specify additional options to pass to the `waf` script during the target installation step. By default, empty.

17.15. Infrastructure for packages building kernel modules

Buildroot offers a helper infrastructure to make it easy to write packages that build and install Linux kernel modules. Some packages only contain a kernel module, other packages contain programs and libraries in addition to kernel modules. Buildroot's helper infrastructure supports either case.

17.15.1. `kernel-module` tutorial

Let's start with an example on how to prepare a simple package that only builds a kernel module, and no other component:

```
01: #####
02: #
03: # foo
04: #
05: #####
06:
07: FOO_VERSION = 1.2.3
08: FOO_SOURCE = foo-$(FOO_VERSION).tar.xz
09: FOO_SITE = http://www.foosoftware.org/download
10: FOO_LICENSE = GPL-2.0
11: FOO_LICENSE_FILES = COPYING
12:
13: $(eval $(kernel-module))
14: $(eval $(generic-package))
```

Lines 7-11 define the usual meta-data to specify the version, archive name, remote URI where to find the package source, licensing information.

On line 13, we invoke the `kernel-module` helper infrastructure, that generates all the appropriate Makefile rules and variables to build that kernel module.

Finally, on line 14, we invoke the [generic-package infrastructure Section 17.5.1, “generic-package tutorial”](#).

The dependency on `linux` is automatically added, so it is not needed to specify it in `FOO_DEPENDENCIES`.

What you may have noticed is that, unlike other package infrastructures, we explicitly invoke a second infrastructure. This allows a package to build a kernel module, but also, if needed, use any one of other package infrastructures to build normal userland components (libraries, executables...). Using the `kernel-module` infrastructure on its own is not sufficient; another package infrastructure **must** be used.

Let's look at a more complex example:

```
01: #####
02: #
03: # foo
04: #
05: #####
06:
07: FOO_VERSION = 1.2.3
08: FOO_SOURCE = foo-$(FOO_VERSION).tar.xz
09: FOO_SITE = http://www.foosoftware.org/download
10: FOO_LICENSE = GPL-2.0
11: FOO_LICENSE_FILES = COPYING
12:
13: FOO_MODULE_SUBDIRS = driver/base
14: FOO_MODULE_MAKE_OPTS = KVERSION=$(LINUX_VERSION_PROBED)
15:
16: ifeq ($(BR2_PACKAGE_LIBBAR),y)
17: FOO_DEPENDENCIES = libbar
18: FOO_CONF_OPTS = --enable-bar
```

```

19: FOO_MODULE_SUBDIRS += driver/bar
20: else
21: FOO_CONF_OPTS = --disable-bar
22: endif
23:
24: $(eval $(kernel-module))
26: $(eval $(autotools-package))

```

Here, we see that we have an autotools-based package, that also builds the kernel module located in sub-directory `driver/base` and, if `libbar` is enabled, the kernel module located in sub-directory `driver/bar`, and defines the variable `KVERSION` to be passed to the Linux buildsystem when building the module(s).

17.15.2. kernel-module reference

The main macro for the kernel module infrastructure is `kernel-module`. Unlike other package infrastructures, it is not stand-alone, and requires any of the other `*-package` macros be called after it.

The `kernel-module` macro defines post-build and post-target-install hooks to build the kernel modules. If the package's `.mk` needs access to the built kernel modules, it should do so in a post-build hook, **registered after** the call to `kernel-module`. Similarly, if the package's `.mk` needs access to the kernel module after it has been installed, it should do so in a post-install hook, **registered after** the call to `kernel-module`. Here's an example:

```

$(eval $(kernel-module))

define FOO_DO_STUFF_WITH_KERNEL_MODULE
    # Do something with it...
endef
FOO_POST_BUILD_HOOKS += FOO_DO_STUFF_WITH_KERNEL_MODULE

$(eval $(generic-package))

```

Finally, unlike the other package infrastructures, there is no `host-kernel-module` variant to build a host kernel module.

可以选择定义以下附加变量，以进一步配置内核模块的构建:

The following additional variables can optionally be defined to further configure the build of the kernel module:

- `FOO_MODULE_SUBDIRS` may be set to one or more sub-directories (relative to the package source top-directory) where the kernel module sources are. If empty or not set, the sources for the kernel module(s) are considered to be located at the top of the package source tree.
- `FOO_MODULE_MAKE_OPTS` may be set to contain extra variable definitions to pass to the Linux buildsystem.

You may also reference (but you may **not** set!) those variables:

- `LINUX_DIR` contains the path to where the Linux kernel has been extracted and built.
- `LINUX_VERSION` contains the version string as configured by the user.
- `LINUX_VERSION_PROBED` contains the real version string of the kernel, retrieved with running `make -C $(LINUX_DIR) kernelrelease`
- `KERNEL_ARCH` contains the name of the current architecture, like `arm`, `mips`...

17.16. Infrastructure for asciidoc documents

The Buildroot manual, which you are currently reading, is entirely written using the [AsciiDoc](#) mark-up syntax.

The manual is then rendered to many formats: 手册然后呈现为许多格式:

- `html`
- `split-html`
- `pdf`
- `epub`
- `text`

Although Buildroot only contains one document written in AsciiDoc, there is, as for packages, an infrastructure for rendering documents using the AsciiDoc syntax.

Also as for packages, the AsciiDoc infrastructure is available from a [br2-external tree Section 9.2, “Keeping customizations outside of Buildroot”](#). This allows documentation for a br2-external tree to match the Buildroot documentation, as it will be rendered to the same formats and use the same layout and theme.

17.16.1. asciidoc-document tutorial

Whereas package infrastructures are suffixed with `-package`, the document infrastructures are suffixed with `-document`. So, the AsciiDoc infrastructure is named `asciidoc-document`.

Here is an example to render a simple AsciiDoc document.

```
01: #####
02: #
03: # foo-document
04: #
05: #####
06:
07: FOO_SOURCES = $(sort $(wildcard $(pkgdir)/*))
08: $(eval $(call asciidoc-document))
```

On line 7, the Makefile declares what the sources of the document are. Currently, it is expected that the document's sources are only local; Buildroot will not attempt to download anything to render a document. Thus, you must indicate where the sources are. Usually, the string above is sufficient for a document with no sub-directory structure.

On line 8, we call the `asciidoc-document` function, which generates all the Makefile code necessary to **render** the document.

v. 致使；提供，回报；援助；提交，提出；作出（裁决）；放弃；表达；演奏；翻译；绘制；粉刷；熔化；从（动物身体）提取（蛋白质）；秘密偷渡
n. 底灰，底泥；交纳

17.16.2. asciidoc-document reference

The list of variables that can be set in a `.mk` file to give metadata information is (assuming the document name is `foo`):

- `FOO_SOURCES`, mandatory, defines the source files for the document.
- `FOO_RESOURCES`, optional, may contain a space-separated list of paths to one or more directories containing so-called resources (like CSS or images). By default, empty.
- `FOO_DEPENDENCIES`, optional, the list of packages (most probably, host-packages) that must be built before building this document. If a hook of your document needs to access the *Kconfig* structure, you may add `prepare-kconfig` to the list of dependencies.

There are also additional hooks (see [Section 17.18, “Hooks available in the various build steps”](#) for general information on hooks), that a document may set to define extra actions to be done at various steps:

- `FOO_POST_RSYNC_HOOKS` to run additional commands after the sources have been copied by Buildroot. This can for example be used to generate part of the manual with information extracted from the tree. As an example, **Buildroot uses this hook to generate the tables in the appendices**. Buildroot使用这个钩子来生成附录中的表。
- `FOO_CHECK_DEPENDENCIES_HOOKS` to run additional tests on required components to generate the document. In AsciiDoc, it is possible to call filters, that is, programs that will parse an AsciiDoc block and render it appropriately (e.g. [dita](#) or [afigure](#)).
- `FOO_CHECK_DEPENDENCIES_<FMT>_HOOKS`, to run additional tests for the specified format `<FMT>` (see the list of rendered formats, above).

Here is a complete example that uses all variables and all hooks:

```
01: #####
02: #
03: # foo-document
04: #
05: #####
06:
07: FOO_SOURCES = $(sort $(wildcard $(pkgdir)/*))
08: FOO_RESOURCES = $(sort $(wildcard $(pkgdir)/ressources))
09:
10: define FOO_GEN_EXTRA_DOC
11:     /path/to/generate-script --outdir=$(@D)
12: endef
13: FOO_POST_RSYNC_HOOKS += FOO_GEN_EXTRA_DOC
14:
15: define FOO_CHECK_MY_PROG
16:     if ! which my-prog >/dev/null 2>&1; then \
17:         echo "You need my-prog to generate the foo document"; \
18:         exit 1; \
19:     fi
20: endef
21: FOO_CHECK_DEPENDENCIES_HOOKS += FOO_CHECK_MY_PROG
```

```

22:
23: define FOO_CHECK_MY_OTHER_PROG
24:     if ! which my-other-prog >/dev/null 2>&1; then \
25:         echo "You need my-other-prog to generate the foo document as PDF"; \
26:         exit 1; \
27:     fi
28: endef
29: FOO_CHECK_DEPENDENCIES_PDF_HOOKS += FOO_CHECK_MY_OTHER_PROG
30:
31: $(eval $(call asciidoc-document))

```

17.17. Infrastructure specific to the Linux kernel package 特定于Linux内核包的基础设施

The Linux kernel package can use some specific infrastructures based on package hooks for building Linux kernel tools or/and building Linux kernel extensions.

17.17.1. linux-kernel-tools

Buildroot offers a helper infrastructure to build some userspace tools for the target available within the Linux kernel sources. Since their source code is part of the kernel source code, a special package, `linux-tools`, exists and re-uses the sources of the Linux kernel that runs on the target.

Let's look at an example of a Linux tool. For a new Linux tool named `foo`, create a new menu entry in the existing `package/linux-tools/Config.in`. This file will contain the option descriptions related to each kernel tool that will be used and displayed in the configuration tool. It would basically look like:

```

01: config BR2_PACKAGE_LINUX_TOOLS_FOO
02:     bool "foo"
03:     select BR2_PACKAGE_LINUX_TOOLS
04:     help
05:         This is a comment that explains what foo kernel tool is.
06:
07:     http://foosoftware.org/foo/

```

The name of the option starts with the prefix `BR2_PACKAGE_LINUX_TOOLS_`, followed by the uppercase name of the tool (like is done for packages).

Note. Unlike other packages, the `linux-tools` package options appear in the `linux` kernel menu, under the `Linux Kernel Tools` sub-menu, not under the `Target packages` main menu.

Then for each linux tool, add a new `.mk.in` file named `package/linux-tools/linux-tool-foo.mk.in`. It would basically look like:

```

01: #####
02: #
03: # foo
04: #
05: #####
06:
07: LINUX_TOOLS += foo
08:
09: FOO_DEPENDENCIES = libbbb
10:
11: define FOO_BUILD_CMDS
12:     $(TARGET_MAKE_ENV) $(MAKE) -C $(LINUX_DIR)/tools foo
13: endef
14:
15: define FOO_INSTALL_STAGING_CMDS
16:     $(TARGET_MAKE_ENV) $(MAKE) -C $(LINUX_DIR)/tools \
17:         DESTDIR=$(STAGING_DIR) \
18:         foo_install
19: endef
20:
21: define FOO_INSTALL_TARGET_CMDS
22:     $(TARGET_MAKE_ENV) $(MAKE) -C $(LINUX_DIR)/tools \
23:         DESTDIR=$(TARGET_DIR) \
24:         foo_install
25: endef

```

On line 7, we register the Linux tool `foo` to the list of available Linux tools.

On line 9, we specify the list of dependencies this tool relies on. These dependencies are added to the Linux package dependencies list only when the `foo` tool is selected.

The rest of the Makefile, lines 11-25 defines what should be done at the different steps of the Linux tool build process like for a [generic package Section 17.5.1, “generic-package tutorial”](#). They will actually be used only when the `foo` tool is selected. The only supported commands are `_BUILD_CMDS`, `_INSTALL_STAGING_CMDS` and `_INSTALL_TARGET_CMDS`.

Note. One **must not** call `$(eval $(generic-package))` or any other package infrastructure! Linux tools are not packages by themselves, they are part of the `linux-tools` package.

17.17.2. linux-kernel-extensions

Some packages provide new features that require the Linux kernel tree to be modified. This can be in the form of patches to be applied on the kernel tree, or in the form of new files to be added to the tree. The Buildroot's Linux kernel extensions infrastructure provides a simple solution to automatically do this, just after the kernel sources are extracted and before the kernel patches are applied. Examples of extensions packaged using this mechanism are the real-time extensions Xenomai and RTAI, as well as the set of out-of-tree LCD screens drivers `fbtft`.

Let's look at an example on how to add a new Linux extension `foo`.

First, create the package `foo` that provides the extension: this package is a standard package; see the previous chapters on how to create such a package. This package is in charge of downloading the sources archive, checking the hash, defining the licence informations and building user space tools if any.

Then create the *Linux extension* proper: create a new menu entry in the existing `linux/Config.ext.in`. This file contains the option descriptions related to each kernel extension that will be used and displayed in the configuration tool. It would basically look like:

```
01: config BR2_LINUX_KERNEL_EXT_FOO
02:     bool "foo"
03:     help
04:         This is a comment that explains what foo kernel extension is.
05:
06:     http://foosoftware.org/foo/
```

Then for each linux extension, add a new `.mk` file named `linux/linux-ext-foo.mk`. It should basically contain:

```
01: #####
02: #
03: # foo
04: #
05: #####
06:
07: LINUX_EXTENSIONS += foo
08:
09: define FOO_PREPARE_KERNEL
10:     $(FOO_DIR)/prepare-kernel-tree.sh --linux-dir=$(@D)
11: endef
```

On line 7, we add the Linux extension `foo` to the list of available Linux extensions.

On line 9-11, we define what should be done by the extension to modify the Linux kernel tree; this is specific to the linux extension and can use the variables defined by the `foo` package, like: `$(FOO_DIR)` or `$(FOO_VERSION)` ... as well as all the Linux variables, like: `$(LINUX_VERSION)` or `$(LINUX_VERSION_PROBED)`, `$(KERNEL_ARCH)` ... See the [definition of those kernel variables Section 17.15.2, “kernel-module reference”](#).

17.18. Hooks available in the various build steps

The generic infrastructure (and as a result also the derived autotools and cmake infrastructures) allow packages to specify hooks. These define further actions to perform after existing steps. Most hooks aren't really useful for generic packages, since the `.mk` file already has full control over the actions performed in each step of the package construction.

The following hook points are available:

- `LIBFOO_PRE_DOWNLOAD_HOOKS`
- `LIBFOO_POST_DOWNLOAD_HOOKS`
- `LIBFOO_PRE_EXTRACT_HOOKS`
- `LIBFOO_POST_EXTRACT_HOOKS`
- `LIBFOO_PRE_RSYNC_HOOKS`

- `LIBFOO_POST_RSYNC_HOOKS`
- `LIBFOO_PRE_PATCH_HOOKS`
- `LIBFOO_POST_PATCH_HOOKS`
- `LIBFOO_PRE_CONFIGURE_HOOKS`
- `LIBFOO_POST_CONFIGURE_HOOKS`
- `LIBFOO_PRE_BUILD_HOOKS`
- `LIBFOO_POST_BUILD_HOOKS`
- `LIBFOO_PRE_INSTALL_HOOKS` (for host packages only)
- `LIBFOO_POST_INSTALL_HOOKS` (for host packages only)
- `LIBFOO_PRE_INSTALL_STAGING_HOOKS` (for target packages only)
- `LIBFOO_POST_INSTALL_STAGING_HOOKS` (for target packages only)
- `LIBFOO_PRE_INSTALL_TARGET_HOOKS` (for target packages only)
- `LIBFOO_POST_INSTALL_TARGET_HOOKS` (for target packages only)
- `LIBFOO_PRE_INSTALL_IMAGES_HOOKS`
- `LIBFOO_POST_INSTALL_IMAGES_HOOKS`
- `LIBFOO_PRE_LEGAL_INFO_HOOKS`
- `LIBFOO_POST_LEGAL_INFO_HOOKS`

These variables are *lists* of variable names containing actions to be performed at this hook point. This allows several hooks to be registered at a given hook point. Here is an example:

```
define LIBFOO_POST_PATCH_FIXUP
    action1
    action2
endef

LIBFOO_POST_PATCH_HOOKS += LIBFOO_POST_PATCH_FIXUP
```

17.18.1. Using the `POST_RSYNC` hook

The `POST_RSYNC` hook is run only for packages that use a local source, either through the `local` site method or the `OVERRIDE_SRCDIR` mechanism. In this case, package sources are copied using `rsync` from the local location into the buildroot build directory. The `rsync` command does not copy all files from the source directory, though. Files belonging to a version control system, like the directories `.git`, `.hg`, etc. are not copied. For most packages this is sufficient, but a given package can perform additional actions using the `POST_RSYNC` hook.

In principle, the hook can contain any command you want. One specific use case, though, is the intentional copying of the version control directory using `rsync`. The `rsync` command you use in the hook can, among others, use the following variables:

- `$(SRCDIR)`: the path to the overridden source directory
- `$(@D)`: the path to the build directory

17.18.2. Target-finalize hook

Packages may also register hooks in `LIBFOO_TARGET_FINALIZE_HOOKS`. These hooks are run after all packages are built, but before the filesystem images are generated. They are seldom used, and your package probably do not need them.

17.19. Gettext integration and interaction with packages

许多支持国际化的包都使用gettext库。

Many packages that support internationalization use the gettext library. Dependencies for this library are fairly complicated and therefore, deserve some explanation. 这个库的依赖关系相当复杂，因此需要一些解释。

The *glibc* C library integrates a full-blown implementation of *gettext*, supporting translation. Native Language Support is therefore built-in in *glibc*. *glibc* C库集成了完整的gettext实现，支持翻译。因此，*glibc*中内置了本机语言支持。

On the other hand, the *uClibc* and *musl* C libraries only provide a stub implementation of the gettext functionality, which allows to compile libraries and programs using gettext functions, but without providing the

translation capabilities of a full-blown gettext implementation. With such C libraries, if real Native Language Support is necessary, it can be provided by the `libintl` library of the `gettext` package.

Due to this, and in order to make sure that Native Language Support is properly handled, packages in Buildroot that can use NLS support should:

1. Ensure NLS support is enabled when `BR2_SYSTEM_ENABLE_NLS=y`. This is done automatically for *autotools* packages and therefore should only be done for packages using other package infrastructures.
2. Add `$(TARGET_NLS_DEPENDENCIES)` to the package `<pkg>_DEPENDENCIES` variable. This addition should be done unconditionally: the value of this variable is automatically adjusted by the core infrastructure to contain the relevant list of packages. If NLS support is disabled, this variable is empty. If NLS support is enabled, this variable contains `host-gettext` so that tools needed to compile translation files are available on the host. In addition, if *uClibc* or *musl* are used, this variable also contains `gettext` in order to get the full-blown *gettext* implementation.
3. If needed, add `$(TARGET_NLS_LIBS)` to the linker flags, so that the package gets linked with `libintl`. This is generally not needed with *autotools* packages as they usually detect automatically that they should link with `libintl`. However, packages using other build systems, or problematic *autotools*-based packages may need this. `$(TARGET_NLS_LIBS)` should be added unconditionally to the linker flags, as the core automatically makes it empty or defined to `-lintl` depending on the configuration.

No changes should be made to the `Config.in` file to support NLS.

Finally, certain packages need some gettext utilities on the target, such as the *gettext* program itself, which allows to retrieve translated strings, from the command line. In such a case, the package should:

最后, 某些包需要目标上的一些gettext实用程序, 例如gettext程序本身, 它允许从命令行检索翻译后的字符串。在这种情况下, 一揽子措施应:

- use `select BR2_PACKAGE_GETTEXT` in their `Config.in` file, indicating in a comment above that it's a runtime dependency only.
- not add any *gettext* dependency in the `DEPENDENCIES` variable of their `.mk` file.

17.20. Tips and tricks 提示和技巧

17.20.1. Package name, config entry name and makefile variable relationship

In Buildroot, there is some relationship between:

- the *package name*, which is the package directory name (and the name of the `*.mk` file);
- the config entry name that is declared in the `Config.in` file;
- the makefile variable prefix.

It is mandatory to maintain consistency between these elements, using the following rules:

- the package directory and the `*.mk` name are the *package name* itself (e.g.: `package/foo-bar_boo/foo-bar_boo.mk`);
- the *make* target name is the *package name* itself (e.g.: `foo-bar_boo`);
- the config entry is the upper case *package name* with `.` and `-` characters substituted with `_`, prefixed with `BR2_PACKAGE_` (e.g.: `BR2_PACKAGE_FOO_BAR_BOO`);
- the `*.mk` file variable prefix is the upper case *package name* with `.` and `-` characters substituted with `_` (e.g.: `FOO_BAR_BOO_VERSION`).

17.20.2. How to test your package

Once you have added your new package, it is important that you test it under various conditions: does it build for all architectures? Does it build with the different C libraries? Does it need threads, NPTL? And so on...

Buildroot runs *autobuilders* which continuously test random configurations. However, these only build the *master* branch of the git tree, and your new fancy package is not yet there.

Buildroot provides a script in `utils/test-pkg` that uses the same base configurations as used by the autobuilders so you can test your package in the same conditions.

First, create a config snippet that contains all the necessary options needed to enable your package, but without any architecture or toolchain option. For example, let's create a config snippet that just enables `libcurl`, without any TLS backend:

```
$ cat libcurl.config
BR2_PACKAGE_LIBCURL=y
```

If your package needs more configuration options, you can add them to the config snippet. For example, here's how you would test `libcurl` with `openssl` as a TLS backend and the `curl` program:

```
$ cat libcurl.config
BR2_PACKAGE_LIBCURL=y
BR2_PACKAGE_CURL=y
BR2_PACKAGE_OPENSSL=y
```

Then run the `test-pkg` script, by telling it what config snippet to use and what package to test:

```
$ ./utils/test-pkg -c libcurl.config -p libcurl
```

这将尝试根据autobuilders使用的所有工具链来构建您的包

This will try to build your package against all the toolchains used by the autobuilders (except for the internal toolchains, because it takes too long to do so). The output lists all toolchains and the corresponding result (excerpt, results are fake):

```
$ ./utils/test-pkg -c libcurl.config -p libcurl
    armv5-ctng-linux-gnueabi [ 1/11]: OK
    armv7-ctng-linux-gnueabi [ 2/11]: OK
        br-aarch64-glibc [ 3/11]: SKIPPED
        br-armle-hs38 [ 4/11]: SKIPPED
        br-arm-basic [ 5/11]: FAILED
    br-arm-cortex-a9-glibc [ 6/11]: OK
    br-arm-cortex-a9-musl [ 7/11]: FAILED
    br-arm-cortex-m4-full [ 8/11]: OK
        br-arm-full [ 9/11]: OK
        br-arm-full-nothread [10/11]: FAILED
        br-arm-full-static [11/11]: OK
11 builds, 2 skipped, 2 build failed, 1 legal-info failed
```

The results mean:

- **OK:** the build was successful.
- **SKIPPED:** one or more configuration options listed in the config snippet were not present in the final configuration. This is due to options having dependencies not satisfied by the toolchain, such as for example a package that depends on `BR2_USE_MMU` with a noMMU toolchain. The missing options are reported in `missing.config` in the output build directory (`~/br-test-pkg/TOOLCHAIN_NAME/` by default).
- **FAILED:** the build failed. Inspect the `logfile` file in the output build directory to see what went wrong:
 - the actual build failed,
 - the legal-info failed,
 - one of the preliminary steps (downloading the config file, applying the configuration, running `dirclean` for the package) failed.

When there are failures, you can just re-run the script with the same options (after you fixed your package); the script will attempt to re-build the package specified with `-p` for all toolchains, without the need to re-build all the dependencies of that package.

The `test-pkg` script accepts a few options, for which you can get some help by running:

```
$ ./utils/test-pkg -h
```

17.20.3. How to add a package from GitHub

Packages on GitHub often don't have a download area with release tarballs. However, it is possible to download tarballs directly from the repository on GitHub. As GitHub is known to have changed download mechanisms in the past, the `github` helper function should be used as shown below.

```
# Use a tag or a full commit ID
FOO_VERSION = v1.0
FOO_SITE = $(call github,<user>,<package>,$(FOO_VERSION))
```

Notes

- The `FOO_VERSION` can either be a tag or a commit ID.

- The tarball name generated by github matches the default one from Buildroot (e.g.: `foo-f6fb6654af62045239caed5950bc6c7971965e60.tar.gz`), so it is not necessary to specify it in the `.mk` file.
- When using a commit ID as version, you should use the full 40 hex characters.

If the package you wish to add does have a release section on GitHub, the maintainer may have uploaded a release tarball, or the release may just point to the automatically generated tarball from the git tag. If there is a release tarball uploaded by the maintainer, we prefer to use that since it may be slightly different (e.g. it contains a configure script so we don't need to do AUTORECONF).

You can see on the release page if it's an uploaded tarball or a git tag:

Downloads

 [mongrel2-v1.9.2.tar.bz2](#)

 [Source code \(zip\)](#)

 [Source code \(tar.gz\)](#)

- If it looks like the image above then it was uploaded by the maintainer and you should use that link (in that example: `mongrel2-v1.9.2.tar.bz2`) to specify `FOO_SITE`, and not use the *github* helper.
- On the other hand, if there's **only** the "Source code" link, then it's an automatically generated tarball and you should use the *github* helper function.

17.21. Conclusion n. 结论；结局；推论

As you can see, adding a software package to Buildroot is simply a matter of writing a Makefile using an existing example and modifying it according to the compilation process required by the package.

如您所见，将软件包添加到Buildroot只是简单地使用现有示例编写一个Makefile，并根据包所需的编译过程修改它。

If you package software that might be useful for other people, don't forget to send a patch to the Buildroot mailing list (see [Section 21.5. "Submitting patches"](#))!

Chapter 18. Patching a package

While integrating a new package or updating an existing one, it may be necessary to patch the source of the software to get it cross-built within Buildroot.

Buildroot offers an infrastructure to automatically handle this during the builds. It supports three ways of applying patch sets: downloaded patches, patches supplied within buildroot and patches located in a user-defined global patch directory.

Buildroot提供了一个在构建期间自动处理此问题的基础架构。它支持三种应用补丁集的方法：下载的补丁、在buildroot中提供的补丁和位于用户定义的全局补丁目录中的补丁。

18.1. Providing patches

18.1.1. Downloaded

If it is necessary to apply a patch that is available for download, then add it to the `<packagename>_PATCH` variable. If an entry contains `::/`, then Buildroot will assume it is a full URL and download the patch from this location. Otherwise, Buildroot will assume that the patch should be downloaded from `<packagename>_SITE`. It can be a single patch, or a tarball containing a patch series.

Like for all downloads, a hash should be added to the `<packagename>.hash` file.

This method is typically used for packages from Debian.

18.1.2. Within Buildroot

Most patches are provided within Buildroot, in the package directory; these typically aim to fix cross-compilation, libc support, or other such issues.

These patch files should be named `<number>-<description>.patch`.

Notes

- The patch files coming with Buildroot should not contain any package version reference in their filename.
- The field `<number>` in the patch file name refers to the *apply order*, and shall start at 1; It is preferred to pad the number with zeros up to 4 digits, like *git-format-patch* does. E.g.: `0001-foobar-the-buz.patch`
- Previously, it was mandatory for patches to be prefixed with the name of the package, like `<package>-<number>-<description>.patch`, but that is no longer the case. Existing packages will be fixed as time passes. *Do not prefix patches with the package name.*
- **Previously, a `series` file, as used by `quilt`, could also be added in the package directory. In that case, the `series` file defines the patch application order. This is deprecated, and will be removed in the future. Do not use a `series` file.** 以前，还可以在包目录中添加被子使用的系列文件。 在这种情况下，`series`文件定义了补丁应用程序的顺序。这已弃用，并将在未来删除。 不要使用系列文件。

18.1.3. Global patch directory

The `BR2_GLOBAL_PATCH_DIR` configuration file option can be used to specify a space separated list of one or more directories containing global package patches. See [Section 9.8, “Adding project-specific patches”](#) for details.

`BR2_GLOBAL_PATCH_DIR`配置文件选项可用于指定一个以空格分隔的列表，其中包含一个或多个包含全局补丁的目录。

18.2. How patches are applied

1. Run the `<packagename>_PRE_PATCH_HOOKS` commands if defined;
2. Cleanup the build directory, removing any existing `*.rej` files;
3. If `<packagename>_PATCH` is defined, then patches from these tarballs are applied;
4. If there are some `*.patch` files in the package’s Buildroot directory or in a package subdirectory named `<packageversion>`, then:
 - If a `series` file exists in the package directory, then patches are applied according to the `series` file;
 - Otherwise, patch files matching `*.patch` are applied in alphabetical order. So, to ensure they are applied in the right order, it is highly recommended to name the patch files like this: `<number>-<description>.patch`, where `<number>` refers to the *apply order*.
5. If `BR2_GLOBAL_PATCH_DIR` is defined, the directories will be enumerated in the order they are specified. The patches are applied as described in the previous step.
6. Run the `<packagename>_POST_PATCH_HOOKS` commands if defined.

If something goes wrong in the steps 3 or 4, then the build fails.

18.3. Format and licensing of the package patches

Patches are released under the same license as the software they apply to (see [Section 12.2, “Complying with the Buildroot license”](#)).

A message explaining what the patch does, and why it is needed, should be added in the header commentary of the patch.

You should add a `Signed-off-by` statement in the header of the each patch to help with keeping track of the changes and to certify that the patch is released under the same license as the software that is modified.

您应该在每个补丁的头部添加一个Signed-off-by声明，以帮助跟踪更改，并证明补丁是在与被修改的软件相同的许可下发布的。

If the software is under version control, it is recommended to use the upstream SCM software to generate the patch set.

v. 连接，连结，使连锁
adj. 连接的，连结的，连锁的

Otherwise, **concatenate** the header with the output of the `diff -purN package-version.orig/ package-version/` command.

If you update an existing patch (e.g. when bumping the package version), make sure the existing From header and Signed-off-by tags are not removed, but do update the rest of the patch comment when appropriate.

At the end, the patch should look like:

```
configure.ac: add C++ support test

Signed-off-by: John Doe <john.doe@noname.org>

--- configure.ac.orig
+++ configure.ac
@@ -40,2 +40,12 @@

AC_PROG_MAKE_SET
+
```

```
+AC_CACHE_CHECK([whether the C++ compiler works],
+                [rw_cv_prog_cxx_works],
+                [AC_LANG_PUSH([C++])
+                 AC_LINK_IFELSE([AC_LANG_PROGRAM([], [])],
+                               [rw_cv_prog_cxx_works=yes],
+                               [rw_cv_prog_cxx_works=no])
+                 AC_LANG_POP([C++])])
+
+AM_CONDITIONAL([CXX_WORKS], [test "x$rw_cv_prog_cxx_works" = "xyes"])
```

18.4. Integrating patches found on the Web

When integrating a patch of which you are not the author, you have to add a few things in the header of the patch itself.

Depending on whether the patch has been obtained from the project repository itself, or from somewhere on the web, add one of the following tags:

```
Backported from: <some commit id>
```

or

```
Fetch from: <some url>
```

It is also sensible to add a few words about any changes to the patch that may have been necessary.

Chapter 19. Download infrastructure

TODO

Chapter 20. Debugging Buildroot

It is possible to instrument the steps `Buildroot` does when building packages. Define the variable `BR2_INSTRUMENTATION_SCRIPTS` to contain the path of one or more scripts (or other executables), in a space-separated list, you want called before and after each step. The scripts are called in sequence, with three parameters:

- `start` or `end` to denote the start (resp. the end) of a step;
- the name of the step about to be started, or which just ended;
- the name of the package.

For example :

```
make BR2_INSTRUMENTATION_SCRIPTS="/path/to/my/script1 /path/to/my/script2"
```

The list of steps is:

- `extract`
- `patch`
- `configure`
- `build`
- `install-host`, when a host-package is installed in `$(HOST_DIR)`
- `install-target`, when a target-package is installed in `$(TARGET_DIR)`
- `install-staging`, when a target-package is installed in `$(STAGING_DIR)`
- `install-image`, when a target-package installs files in `$(BINARIES_DIR)`

The script has access to the following variables:

- `BR2_CONFIG`: the path to the Buildroot `.config` file
- `HOST_DIR`, `STAGING_DIR`, `TARGET_DIR`: see [Section 17.5.2, “generic-package reference”](#)
- `BUILD_DIR`: the directory where packages are extracted and built
- `BINARIES_DIR`: the place where all binary files (aka images) are stored

- `BASE_DIR`: the base output directory

Chapter 21. Contributing to Buildroot

There are many ways in which you can contribute to Buildroot: analyzing and fixing bugs, analyzing and fixing package build failures detected by the autobuilders, testing and reviewing patches sent by other developers, working on the items in our TODO list and sending your own improvements to Buildroot or its manual. The following sections give a little more detail on each of these items.

If you are interested in contributing to Buildroot, the first thing you should do is to subscribe to the Buildroot mailing list. This list is the main way of interacting with other Buildroot developers and to send contributions to. If you aren't subscribed yet, then refer to [Chapter 5, Community resources](#) for the subscription link.

If you are going to touch the code, it is highly recommended to use a git repository of Buildroot, rather than starting from an extracted source code tarball. Git is the easiest way to develop from and directly send your patches to the mailing list. Refer to [Chapter 3, Getting Buildroot](#) for more information on obtaining a Buildroot git tree.

21.1. Reproducing, analyzing and fixing bugs

A first way of contributing is to have a look at the open bug reports in the [Buildroot bug tracker](#). As we strive to keep the bug count as small as possible, all help in reproducing, analyzing and fixing reported bugs is more than welcome. Don't hesitate to add a comment to bug reports reporting your findings, even if you don't yet see the full picture.

21.2. Analyzing and fixing autobuild failures

The Buildroot autobuilders are a set of build machines that continuously run Buildroot builds based on random configurations. This is done for all architectures supported by Buildroot, with various toolchains, and with a random selection of packages. With the large commit activity on Buildroot, these autobuilders are a great help in detecting problems very early after commit.

All build results are available at <http://autobuild.buildroot.org>, statistics are at <http://autobuild.buildroot.org/stats.php>. Every day, an overview of all failed packages is sent to the mailing list.

Detecting problems is great, but obviously these problems have to be fixed as well. Your contribution is very welcome here! There are basically two things that can be done:

- Analyzing the problems. The daily summary mails do not contain details about the actual failures: in order to see what's going on you have to open the build log and check the last output. Having someone doing this for all packages in the mail is very useful for other developers, as they can make a quick initial analysis based on this output alone.
- Fixing a problem. When fixing autobuild failures, you should follow these steps:
 1. Check if you can reproduce the problem by building with the same configuration. You can do this manually, or use the [br-reproduce-build](#) script that will automatically clone a Buildroot git repository, checkout the correct revision, download and set the right configuration, and start the build.
 2. Analyze the problem and create a fix.
 3. Verify that the problem is really fixed by starting from a clean Buildroot tree and only applying your fix.
 4. Send the fix to the Buildroot mailing list (see [Section 21.5, "Submitting patches"](#)). In case you created a patch against the package sources, you should also send the patch upstream so that the problem will be fixed in a later release, and the patch in Buildroot can be removed. In the commit message of a patch fixing an autobuild failure, add a reference to the build result directory, as follows:

Fixes <http://autobuild.buildroot.org/results/51000a9d4656afe9e0ea6f07b9f8ed374c2e4069>

21.3. Reviewing and testing patches

由于每天发送到邮件列表的补丁数量很大，维护人员很难判断哪些补丁可以应用，哪些还不能。

With the amount of patches sent to the mailing list each day, the maintainer has a very hard job to judge which patches are ready to apply and which ones aren't. Contributors can greatly help here by reviewing and testing these patches. 贡献者可以通过评审和测试这些补丁来提供很大的帮助。

In the review process, do not hesitate to respond to patch submissions for remarks, suggestions or anything that will help everyone to understand the patches and make them better. Please use internet style replies in plain text emails when responding to patch submissions. 当回复补丁提交时，请使用网络风格的纯文本邮件回复。

为了表示对补丁的批准，有三个正式标签跟踪该批准。

To indicate approval of a patch, there are three formal tags that keep track of this approval. To add your tag to a patch, reply to it with the approval tag below the original author's Signed-off-by line. These tags will be picked up automatically by patchwork (see [Section 21.3.1, "Applying Patches from Patchwork"](#)) and will be part of the commit log when the patch is accepted.

Tested-by

Indicates that the patch has been tested successfully. You are encouraged to specify what kind of testing you performed (compile-test on architecture X and Y, runtime test on target A, ...). This additional information helps other testers and the maintainer.

Reviewed-by

Indicates that you code-reviewed the patch and did your best in spotting problems, but you are not sufficiently familiar with the area touched to provide an Acked-by tag. This means that there may be remaining problems in the patch that would be spotted by someone with more experience in that area. Should such problems be detected, your Reviewed-by tag remains appropriate and you cannot be blamed.

Acked-by

Indicates that you code-reviewed the patch and you are familiar enough with the area touched to feel that the patch can be committed as-is (no additional changes required). In case it later turns out that something is wrong with the patch, your Acked-by could be considered inappropriate. The difference between Acked-by and Reviewed-by is thus mainly that you are prepared to take the blame on Acked patches, but not on Reviewed ones.

If you reviewed a patch and have comments on it, you should simply reply to the patch stating these comments, without providing a Reviewed-by or Acked-by tag. These tags should only be provided if you judge the patch to be good as it is.

It is important to note that neither Reviewed-by nor Acked-by imply that testing has been performed. To indicate that you both reviewed and tested the patch, provide two separate tags (Reviewed/Acked-by and Tested-by).

Note also that *any developer* can provide Tested/Reviewed/Acked-by tags, without exception, and we encourage everyone to do this. Buildroot does not have a defined group of *core* developers, it just so happens that some developers are more active than others. The maintainer will value tags according to the track record of their submitter. Tags provided by a regular contributor will naturally be trusted more than tags provided by a newcomer. As you provide tags more regularly, your *trustworthiness* (in the eyes of the maintainer) will go up, but *any* tag provided is valuable.

Buildroot's Patchwork website can be used to pull in patches for testing purposes. Please see [Section 21.3.1, "Applying Patches from Patchwork"](#) for more information on using Buildroot's Patchwork website to apply patches.

21.3.1. Applying Patches from Patchwork

The main use of Buildroot's Patchwork website for a developer is for pulling in patches into their local git repository for testing purposes. 对于开发者来说，buildroot的Patchwork网站的主要用途是将补丁拉入他们本地的git仓库中进行测试。

When browsing patches in the patchwork management interface, an `mbbox` link is provided at the top of the page. Copy this link address and run the following commands:

```
$ git checkout -b <test-branch-name>
$ wget -O - <mbbox-url> | git am
```

Another option for applying patches is to create a bundle. A bundle is a set of patches that you can group together using the patchwork interface. Once the bundle is created and the bundle is made public, you can copy the `mbbox` link for the bundle and apply the bundle using the above commands.

21.4. Work on items from the TODO list

If you want to contribute to Buildroot but don't know where to start, and you don't like any of the above topics, you can always work on items from the [Buildroot TODO list](#). Don't hesitate to discuss an item first on the mailing list or on IRC. Do edit the wiki to indicate when you start working on an item, so we avoid duplicate efforts.

21.5. Submitting patches 提交补丁

Note

Please, do not attach patches to bugs, send them to the mailing list instead. 请不要给漏洞附加补丁，而是将它们发送到邮件列表。

If you made some changes to Buildroot and you would like to contribute them to the Buildroot project, proceed as follows.

21.5.1. The formatting of a patch

We expect patches to be formatted in a specific way. This is necessary to make it easy to review patches, to be able to apply them easily to the git repository, to make it easy to find back in the history how and why things have changed, and to make it possible to use `git bisect` to locate the origin of a problem.

First of all, it is essential that the patch has a good commit message. The commit message should start with a separate line with a brief summary of the change, starting with the name of the affected package. The body of the commit message should describe *why* this change is needed, and if necessary also give details about *how* it was done. **When writing the commit message, think of how the reviewers will read it, but also think about how you will read it when you look at this change again a few years down the line.**

在编写提交消息时，要考虑审阅者将如何阅读它，但也要考虑几年后当您再次查看此更改时将如何阅读它。

Second, the patch itself should do only one change, but do it completely. Two unrelated or weakly related changes should usually be done in two separate patches. This usually means that a patch affects only a single package. If several changes are related, it is often still possible to split them up in small patches and apply them in a specific order. Small patches make it easier to review, and often make it easier to understand afterwards why a change was done. However, each patch must be complete. It is not allowed that the build is broken when only the first but not the second patch is applied. This is necessary to be able to use `git bisect` afterwards.

Of course, while you're doing your development, you're probably going back and forth between packages, and certainly not committing things immediately in a way that is clean enough for submission. So most developers rewrite the history of commits to produce a clean set of commits that is appropriate for submission. To do this, you need to use *interactive rebasing*. You can learn about it [in the Pro Git book](#). Sometimes, it is even easier to discard you history with `git reset --soft origin/master` and select individual changes with `git add -i` or `git add -p`.

Finally, the patch should be signed off. This is done by adding `Signed-off-by: Your Real Name <your@email.address>` at the end of the commit message. `git commit -s` does that for you, if configured properly. The `Signed-off-by` tag means that you publish the patch under the Buildroot license (i.e. GPL-2.0+, except for package patches, which have the upstream license), and that you are allowed to do so. See [the Developer Certificate of Origin](#) for details.

当添加新包时，您应该在一个单独的补丁中提交每个包。这个补丁应该有包/配置的更新。在，包Config，In文件，.mk文件，.hash文件、任何初始化脚本和所有包补丁。

When adding new packages, you should submit every package in a separate patch. This patch should have the update to package/Config.in, the package Config.in file, the .mk file, the .hash file, any init script, and all package patches. If the package has many sub-options, these are sometimes better added as separate follow-up patches. The summary line should be something like `<packagename>: new package`. The body of the commit message can be empty for simple packages, or it can contain the description of the package (like the Config.in help text). **If anything special has to be done to build the package, this should also be explained explicitly in the commit message body.**

如果需要做任何特殊的事情来构建包，也应该在提交消息中明确解释。

当您将一个包升级到一个新版本时，您还应该为每个包提交一个单独的补丁。

When you bump a package to a new version, you should also submit a separate patch for each package. Don't forget to update the `.hash` file, or add it if it doesn't exist yet. Also don't forget to check if the `_LICENSE` and `_LICENSE_FILES` are still valid. The summary line should be something like `<packagename>: bump to version <new version>`. If the new version only contains security updates compared to the existing one, the summary should be `<packagename>: security bump to version <new version>` and the commit message body should show the CVE numbers that are fixed. If some package patches can be removed in the new version, it should be explained explicitly why they can be removed, preferably with the upstream commit ID. Also any other required changes should be explained explicitly, like configure options that no longer exist or are no longer needed.

如果您有兴趣在添加或修改的包中被通知构建失败和进一步更改，请将您添加到开发人员文件中。

If you are interested in getting notified of build failures and of further changes in the packages you added or modified, please add yourself to the DEVELOPERS file. This should be done in the same patch creating or modifying the package. See [the DEVELOPERS file Chapter 22, DEVELOPERS file and get-developers](#) for more information.

21.5.2. Preparing a patch series 准备补丁系列

Starting from the changes committed in your local git view, *rebase* your development branch on top of the upstream tree before generating a patch set. To do so, run:

```
$ git fetch --all --tags
$ git rebase origin/master
```

Now, you are ready to generate then submit your patch set.

To generate it, run:

```
$ git format-patch -M -n -s -o outgoing origin/master
```

This will generate patch files in the `outgoing` subdirectory, automatically adding the `Signed-off-by` line.

t. 犯罪；把.....交给给；指派.....作战；使.....承担义务；（公开地）表示意见
vi. 忠于（某个人、机构等）；承诺
提交

Once patch files are generated, you can review/edit the **commit** message before **submitting** them, using your favorite text editor.

Buildroot提供了一个方便的工具来知道你的补丁应该发送给谁，

Buildroot provides a handy tool to know to whom your patches should be sent, called `get-developers` (see [Chapter 22, DEVELOPERS file and get-developers](#) for more information). This tool reads your patches and outputs the appropriate `git send-email` command to use:

```
$ ./utils/get-developers outgoing/*
```

Use the output of `get-developers` to send your patches:

```
$ git send-email --to buildroot@buildroot.org --cc bob --cc alice outgoing/*
```

Note that `git` should be configured to use your mail account. To configure `git`, see `man git-send-email` or google it.

If you do not use `git send-email`, make sure posted **patches are not line-wrapped**, otherwise they cannot easily be applied. In such a case, fix your e-mail client, or better yet, learn to use `git send-email`.

21.5.3. Cover letter 附信

If you want to present the whole patch set in a separate mail, add `--cover-letter` to the `git format-patch` command (see `man git-format-patch` for further information). This will generate a template for an introduction e-mail to your patch series.

A *cover letter* may be useful to introduce the changes you propose in the following cases:

- **large number of commits in the series;** 系列中大量的提交;
- deep impact of the changes in the rest of the project;
- RFC [\[4\]](#);
- whenever you feel it will help presenting your work, your choices, the review process, etc.

21.5.4. Patch revision changelog

When improvements are requested, the new revision of each commit should include a changelog of the modifications between each submission. Note that when your patch series is introduced by a cover letter, an overall changelog may be added to the cover letter in addition to the changelog in the individual commits. **The best thing to rework a patch series is by interactive rebasing;** `git rebase -i origin/master`. Consult the git manual for more information. 修改补丁系列的最佳方法是通过交互式重基:

When added to the individual commits, this changelog is added when editing the commit message. Below the `Signed-off-by` section, add `---` and your changelog.

Although the changelog will be visible for the reviewers in the mail thread, as well as in [patchwork](#), `git` will automatically ignore lines below `---` **when the patch will be merged. This is the intended behavior: the changelog is not meant to be preserved forever in the git history of the project.**

何时补丁将被合并。 这是预期的行为:更改日志并不意味着要永远保存在项目的git历史中。

Hereafter the recommended layout:

```
Patch title: short explanation, max 72 chars

A paragraph that explains the problem, and how it manifests itself. If
the problem is complex, it is OK to add more paragraphs. All paragraphs
should be wrapped at 72 characters.

A paragraph that explains the root cause of the problem. Again, more
than on paragraph is OK.

Finally, one or more paragraphs that explain how the problem is solved.
Don't hesitate to explain complex solutions in detail.

Signed-off-by: John DOE <john.doe@example.net>

---
Changes v2 -> v3:
- foo bar (suggested by Jane)
- bar buz

Changes v1 -> v2:
- alpha bravo (suggested by John)
- charly delta
```

Any patch revision should include the version number. The version number is simply composed of the letter `v` followed by an `integer` greater or equal to two (i.e. "PATCH v2", "PATCH v3" ...).

This can be easily handled with `git format-patch` by using the option `--subject-prefix`:

```
$ git format-patch --subject-prefix "PATCH v4" \
-M -s -o outgoing origin/master
```

Since git version 1.8.1, you can also use `-v <n>` (where `<n>` is the version number):

```
$ git format-patch -v4 -M -s -o outgoing origin/master
```

When you provide a new version of a patch, please mark the old one as superseded in [patchwork](#). You need to create an account on [patchwork](#) to be able to modify the status of your patches. Note that you can only change the status of patches you submitted yourself, which means the email address you register in [patchwork](#) should match the one you use for sending patches to the mailing list.

You can also add the `--in-reply-to <message-id>` option when submitting a patch to the mailing list. The id of the mail to reply to can be found under the "Message Id" tag on [patchwork](#). The advantage of `in-reply-to` is that [patchwork](#) will automatically mark the previous version of the patch as superseded.

`in-reply-to`的优点是，[patchwork](#)会自动将补丁的前一个版本标记为已取代。

21.6. Reporting issues/bugs or getting help

Before reporting any issue, please check in [the mailing list archive](#) [Chapter 5. Community resources](#) whether someone has already reported and/or fixed a similar problem.

However you choose to report bugs or get help, either by opening a bug in the [bug tracker](#) [Chapter 5. Community resources](#) or by [sending a mail to the mailing list](#) [Chapter 5. Community resources](#), there are a number of details to provide in order to help people reproduce and find a solution to the issue.

Try to think as if you were trying to help someone else; in that case, what would you need?

Here is a short list of details to provide in such case:

- host machine (OS/release)
- version of Buildroot
- target for which the build fails
- package(s) for which the build fails
- the command that fails and its output
- any information you think that may be relevant

Additionally, you should add the `.config` file (or if you know how, a `defconfig`; see [Section 9.3, "Storing the Buildroot configuration"](#)).

If some of these details are too large, do not hesitate to use a pastebin service. Note that not all available pastebin services will preserve Unix-style line terminators when downloading raw pastes. Following pastebin services are known to work correctly: - <https://gist.github.com/> - <http://code.bulix.org/>

^[4]RFC: (Request for comments) change proposal

Chapter 22. DEVELOPERS file and get-developers

The main Buildroot directory contains a file named `DEVELOPERS` that lists the developers involved with various areas of Buildroot. Thanks to this file, the `get-developer` tool allows to:

通过解析补丁并将修改后的文件与相关的开发人员进行匹配，计算应该将补丁发送给哪些开发人员。

- Calculate the list of developers to whom patches should be sent, by parsing the patches and matching the modified files with the relevant developers. See [Section 21.5, "Submitting patches"](#) for details.
- Find which developers are taking care of a given architecture or package, so that they can be notified when a build failure occurs on this architecture or package. This is done in interaction with Buildroot's autobuild infrastructure. 这是通过与Buildroot的自动构建基础设施交互完成的。

We ask developers adding new packages, new boards, or generally new functionality in Buildroot, to register themselves in the `DEVELOPERS` file. As an example, we expect a developer contributing a new package to include in his patch the appropriate modification to the `DEVELOPERS` file.

The `DEVELOPERS` file format is documented in detail inside the file itself.

The `get-developer` tool, located in `utils/` allows to use the `DEVELOPERS` file for various tasks:

- When passing one or several patches as command line argument, `get-developer` will return the appropriate `git send-email` command.
- When using the `-a <arch>` command line option, `get-developer` will return the list of developers in charge of the given architecture.
- When using the `-p <package>` command line option, `get-developer` will return the list of developers in charge of the given package.
- When using the `-c` command line option, `get-developer` will look at all files under version control in the Buildroot repository, and list the ones that are not handled by any developer. The purpose of this option is to help completing the `DEVELOPERS` file. 当使用-c命令行选项时，get-developer将查看Buildroot存储库中版本控制下的所有文件，并列出生没有开发人员处理的文件。此选项的目的是帮助完成developer文件。
- When using without any arguments, it validates the integrity of the `DEVELOPERS` file and will note **WARNINGS** for items that don't match. 在不带任何参数的情况下使用时，它会验证developer文件的完整性，并会注意到不匹配的项的WARNINGS。

Part IV. Appendix

Chapter 23. Makedev syntax documentation

为了避免调用mknod，在Buildroot的几个地方使用了makedev语法来定义要对权限进行的更改，或者要创建哪些设备文件以及如何创建它们。
The makedev syntax is used in several places in Buildroot to define changes to be made for permissions, or which device files to create and how to create them, in order to avoid calls to `mknod`.

此语法派生自makedev实用程序

This syntax is derived from the makedev utility, and more complete documentation can be found in the `package/makedevs/README` file.

It takes the form of a space separated list of fields, one file per line; the fields are:

name	type	mode	uid	gid	major	minor	start	inc	count
------	------	------	-----	-----	-------	-------	-------	-----	-------

There are a few non-trivial blocks:

- `name` is the path to the file you want to create/modify
- `type` is the type of the file, being one of:
 - `f`: a regular file
 - `d`: a directory
 - `r`: a directory recursively
 - `c`: a character device file
 - `b`: a block device file
 - `p`: a named pipe
- `mode` are the usual permissions settings (only numerical values are allowed)
- `uid` and `gid` are the UID and GID to set on this file; can be either numerical values or actual names
- `major` and `minor` are here for device files, set to `-` for other files
- `start`, `inc` and `count` are for when you want to create a batch of files, and can be reduced to a loop, beginning at `start`, incrementing its counter by `inc` until it reaches `count`

Start、inc和count用于创建一批文件，可以减少为一个循环，从Start开始，用inc递增计数器，直到达到count

Let's say you want to change the permissions of a given file; using this syntax, you will need to write:

```
/usr/bin/foo f 755 0 0 - - - -  
/usr/bin/bar f 755 root root - - - -  
/data/buz f 644 buz-user buz-group - - - -
```

Alternatively, if you want to change owner/permission of a directory recursively, you can write (to set UID to foo, GID to bar and access rights to rwxr-x--- for the directory /usr/share/myapp and all files and directories below it):

```
/usr/share/myapp r 750 foo bar - - - - -
```

On the other hand, if you want to create the device file /dev/hda and the corresponding 15 files for the partitions, you will need for /dev/hda:

```
/dev/hda b 640 root root 3 0 0 0 -
```

and then for device files corresponding to the partitions of /dev/hda, /dev/hdaX, X ranging from 1 to 15:

```
/dev/hda b 640 root root 3 1 1 1 15
```

Extended attributes are supported if BR2_ROOTFS_DEVICE_TABLE_SUPPORTS_EXTENDED_ATTRIBUTES is enabled. This is done by adding a line starting with |xattr after the line describing the file. Right now, only capability is supported as extended attribute.

xattr	capability
-------	------------

- |xattr is a "flag" that indicate an extended attribute 是指示扩展属性的“标志”
- capability is a capability to add to the previous file

If you want to add the capability cap_sys_admin to the binary foo, you will write :

```
/usr/bin/foo f 755 root root - - - - -  
|xattr cap_sys_admin+eip
```

可以通过使用几个|xattr行向文件添加几个功能。

You can add several capabilities to a file by using several |xattr lines. If you want to add the capability cap_sys_admin and cap_net_admin to the binary foo, you will write :

```
/usr/bin/foo f 755 root root - - - - -  
|xattr cap_sys_admin+eip  
|xattr cap_net_admin+eip
```

Chapter 24. Makeusers syntax documentation

The syntax to create users is inspired by the makedev syntax, above, but is specific to Buildroot.

创建用户的语法受到了上面的makedev语法的启发，但它是特定于Buildroot的

The syntax for adding a user is a space-separated list of fields, one user per line; the fields are:

username	uid	group	gid	password	home	shell	groups	comment
----------	-----	-------	-----	----------	------	-------	--------	---------

Where:

- username is the desired user name (aka login name) for the user. It can not be root, and must be unique. If set to -, then just a group will be created.
- uid is the desired UID for the user. It must be unique, and not 0. If set to -1, then a unique UID will be computed by Buildroot in the range [1000...1999]
- group is the desired name for the user's main group. It can not be root. If the group does not exist, it will be created.
- gid is the desired GID for the user's main group. It must be unique, and not 0. If set to -1, and the group does not already exist, then a unique GID will be computed by Buildroot in the range [1000..1999]
- password is the crypt(3)-encoded password. If prefixed with !, then login is disabled. If prefixed with =, then it is interpreted as clear-text, and will be crypt-encoded (using MD5). If prefixed with !=, then the password will be crypt-encoded (using MD5) and login will be disabled. If set to *, then login is not allowed. If set to -, then no password value will be set.
- home is the desired home directory for the user. If set to -, no home directory will be created, and the user's home will be /. Explicitly setting home to / is not allowed.

- `shell` is the desired shell for the user. If set to `-`, then `/bin/false` is set as the user's shell.
- `groups` is the comma-separated list of additional groups the user should be part of. If set to `-`, then the user will be a member of no additional group. **Missing groups will be created with an arbitrary gid.** 缺失的组将用一个任意的gid创建。
- `comment` (aka [GECOS](#) field) is an almost-free-form text.

There are a few restrictions on the content of each field: 每个字段的内容有一些限制:

- except for `comment`, all fields are mandatory.
- except for `comment`, fields may not contain spaces.
- no field may contain a colon (`:`).

If `home` is not `-`, then the home directory, and all files below, will belong to the user and its main group.

Examples:

```
foo -l bar -l !=blabla /home/foo /bin/sh alpha,bravo Foo user
```

This will create this user:

- `username` (aka login name) is: `foo`
- `uid` is computed by Buildroot
- main group is: `bar`
- main group `gid` is computed by Buildroot
- clear-text password is: `blabla`, will be crypt(3)-encoded, and login is disabled.
- `home` is: `/home/foo`
- `shell` is: `/bin/sh`
- `foo` is also a member of groups: `alpha` and `bravo`
- `comment` is: `Foo user`

```
test 8000 wheel -l = - /bin/sh - Test user
```

This will create this user:

- `username` (aka login name) is: `test`
- `uid` is : `8000`
- main group is: `wheel`
- main group `gid` is computed by Buildroot, and will use the value defined in the rootfs skeleton
- `password` is empty (aka no password).
- `home` is `/` but will not belong to `test`
- `shell` is: `/bin/sh`
- `test` is not a member of any additional groups
- `comment` is: `Test user`

Chapter 25. Migrating from older Buildroot versions

Some versions have introduced backward incompatibilities. This section explains those incompatibilities, and for each explains what to do to complete the migration.

25.1. Migrating to 2016.11

Before Buildroot 2016.11, it was possible to use only one br2-external tree at once. **With Buildroot 2016.11 came the possibility to use more than one simultaneously** (for details, see [Section 9.2, “Keeping customizations outside of Buildroot”](#)). 随着 Buildroot 2016.11 的出现，可以同时使用多个

This however means that older br2-external trees are not usable as-is. A minor change has to be made: adding a name to your br2-external tree.

然而，这意味着较老的br2外部树不能按原样使用。必须做一些小的更改：为br2-external树添加一个名称。

This can be done very easily in just a few steps:

- First, create a new file named `external.desc`, at the root of your br2-external tree, with a single line defining the name of your br2-external tree:

```
$ echo 'name: NAME_OF_YOUR_TREE' >external.desc
```

Note. Be careful when choosing a name: It has to be unique and be made with only ASCII characters from the set `[A-Za-z0-9_]`.

- Then, change every occurrence of `BR2_EXTERNAL` in your br2-external tree with the new variable:

```
$ find . -type f | xargs sed -i 's/BR2_EXTERNAL/BR2_EXTERNAL_NAME_OF_YOUR_TREE_PATH/g'
```

Now, your br2-external tree can be used with Buildroot 2016.11 onward.

Note: This change makes your br2-external tree incompatible with Buildroot before 2016.11.

25.2. Migrating to 2017.08

Before Buildroot 2017.08, host packages were installed in `$(HOST_DIR)/usr` (with e.g. the autotools' `--prefix=$(HOST_DIR)/usr`). With Buildroot 2017.08, they are now installed directly in `$(HOST_DIR)`.

Whenever a package installs an executable that is linked with a library in `$(HOST_DIR)/lib`, it must have an `RPATH` pointing to that directory.

当一个包安装一个与`$(HOST_DIR)/lib`中的库链接的可执行文件时，它必须有一个指向该目录的`RPATH`。
An `RPATH` pointing to `$(HOST_DIR)/usr/lib` is no longer accepted.