

# Install MetaMask

Metamask is an Ethereum Wallet that allows you to run Ethereum dApps right in your browser without running a full Ethereum node. To install MetaMask go to <https://metamask.io/> and follow the installation instructions.

## Create Account

After installing MetaMask a new tab will automatically open. It will guide you to create your first wallet.

1. Click "Get Started".



### Welcome to MetaMask



Connecting you to Ethereum and the Decentralized Web.  
We're happy to see you.

GET STARTED

2. Click "Create wallet".



## New to MetaMask?

 <b>No, I already have a seed phrase</b> Import your existing wallet using a 12 word seed phrase <a href="#">IMPORT WALLET</a>	 <b>Yes, let's get set up!</b> This will create a new wallet and seed phrase <a href="#">CREATE A WALLET</a>
--	---

3. Choose a strong password.



[< Back](#)

## Create Password

New Password (min 8 chars)

Confirm Password



I have read and agree to the [Terms of Use](#)

[CREATE](#)


4. Next your seed phrase will be shown. Store it in a secure location. **WARNING:** If you lose your seed phrase you will not be able to recover any Ether you may have in this wallet.



## Secret Backup Phrase

Your secret backup phrase makes it easy to back up and restore your account.

**WARNING:** Never disclose your backup phrase. Anyone with this phrase can take your Ether forever.



NEXT

Tips:

Store this phrase in a password manager like 1Password.

Write this phrase on a piece of paper and store in a secure location. If you want even more security, write it down on multiple pieces of paper and store each in 2 - 3 different locations.

Memorize this phrase.

[Download this Secret Backup Phrase and keep it stored safely on an external encrypted hard drive or storage medium.](#)

### 5. Confirm your seed phrase.



< Back

## Confirm your Secret Backup Phrase

Please select each phrase in order to make sure it is correct.

forum verb tumble pizza leave  
ankle awake segment spider bulb  
improve divert

CONFIRM

### 6. You are ready to use your account to send and receive Ether!



Account 1

DETAILS

0xac40...BF18



0 ETH  
\$0.00 USD

Don't see your tokens?  
Click on Add Token to add them to  
your account  
[ADD TOKEN](#)



0 ETH  
\$0.00 USD

DEPOSIT


SEND

History


You have no transactions

# Get Ether from a faucet for Ropsten testnet

1. Login to your wallet and select the Ropsten testnet network



2. Press "Deposit"



3. Press "Get Ether".

---

## Deposit Ether



To interact with decentralized applications using MetaMask, you'll need Ether in your wallet.

---

### Directly Deposit Ether

If you already have some Ether, the quickest way to get Ether in your new wallet by direct deposit.

[VIEW ACCOUNT](#)

---



### Test Faucet

Get Ether from a faucet for the Ropsten

[GET ETHER](#)

4. On the [page](#) that opened press "request 1 ether from faucet"


## MetaMask Ether Faucet

**faucet**  
  
address: 0x81b7e08f65bdf5648606c89998a9cc8164397647  
balance: 99687138.62 ether  
request 1 ether from faucet

**user**  
  
address: 0xac4072ae3c29a8f2a4c3f52771fa3c73896ebff8  
balance: 0.00 ether  
donate to faucet:  
1 ether 10 ether 100 ether

**transactions**

### 5. Press "Connect"



### 6. Wait for the transaction to be mined. You can see the transaction details at <https://ropsten.etherscan.io/>



## Transaction Details

## Overview

[ This is a Ropsten Testnet Transaction Only ]

Transaction Hash: 0x6f9e645b0b9ee384d018457ca07488424aa86ff11a7c59df48d98923462d1c26

Status: ✔ Success

Block: 5288471 4 Block Confirmations

TimeStamp: 46 secs ago (Mar-27-2019 06:19:20 PM +UTC)

From: 0x81b7e08f65bdf5648606c89998a9cc8164397647

To: 0xac4072ae3c29a8f2a4c3f52771fa3c73896ebff8

Value: 1 Ether (\$0.00)

Transaction Fee: 0.000021 Ether (\$0.000000)

[Click to see more](#)

## faucet

address: 0x81b7e08f65bdf5648606c89998a9cc8164397647  
balance: 99641822.76 ether

[request 1 ether from faucet](#)


## user

address: 0xac4072ae3c29a8f2a4c3f52771fa3c73896ebff8  
balance: 1.00 ether  
donate to faucet:


[1 ether](#) [10 ether](#) [100 ether](#)

## transactions

0x6f9e645b0b9ee384d018457ca07488424aa86ff11a7c59df48d98923462d1c26


Ropsten Test Network

Account 1  
0xac40...BFF8

  
1 ETH


[DEPOSIT](#) [SEND](#)

History  
You have no transactions



# Interacting with Remix

[Remix](https://remix.ethereum.org) is a browser-based compiler and IDE that enables users to build Ethereum contracts with Solidity language and to debug transactions.

1. Go to <https://remix.ethereum.org>. You will see a screen with an editor in the middle and two sidebars, one on the left and one on the right. In the editor you can write Ethereum smart contracts with the use of the [Solidity](#) programming language.



2. Write your contract you want to test and debug in the editor, select the desired compiler version (on the right) and press “Start to compile” (if auto compile is not enabled).



- On the right sidebar click "Run" and then select "Environment -> JavaScript VM". If you want to interact with a testnet network you must install MetaMask, select your testnet, and then select "Environment -> Injected Web3" from Remix.



5. You are ready to interact with your contract. At the right sidebar, at deployed contracts section, you can see all the functions of the contract. You can call each function, pass parameters and get outputs.

The screenshot displays the Remix IDE interface. On the left, a file explorer shows 'browser' and 'config'. The main editor displays a Solidity contract named 'EthInteraction' with the following code:

```
1 pragma solidity >=0.4.22;
2
3 contract EthInteraction {
4     mapping(address => bytes32) public students;
5     address owner;
6
7     modifier onlyOwner {
8         require(msg.sender == owner);
9     }
10
11
12     constructor () public {
13         owner = msg.sender;
14     }
15
16     function put (string memory token) public {
17         students[msg.sender] = keccak256(abi.encodePacked(token));
18     }
19 }
20
```

Below the code editor, a console window shows the following logs:

```
creation of EthInteraction pending...
[vm] from:0xca3...a733c to:EthInteraction.(constructor) value:0 wei data:0x608...90029 logs:0
hash:0x42a...dale7
transact to EthInteraction.put pending ...
[vm] from:0xca3...a733c to:EthInteraction.put(string) 0x692...77b3a value:0 wei data:0x4c2...00000
logs:0 hash:0x826...63d78
```

On the right sidebar, the 'Deployed Contracts' section shows the 'EthInteraction' contract at address '0x692...77b3a (memory)'. The contract's functions are listed, and the 'put' function is selected with the parameter 'my\_token'.