Pull Me Under -- Dream Theater

Revised 2026-10-16 following the approved library audit.
Type: Song. Instrument: Harley Benton passive 5-string P/J.
GP-5 only.
Patch screen name: Pull Me Un. Patch VOL: 55.
Preset tempo: 116 BPM.

Images and Words, 1992. ~116 BPM, est.
DT's biggest radio hit -- driving verse groove, big anthemic chorus, and a heavier mid-song instrumental break before the final chorus. John Myung's part underneath all of it is full, modern, and precise -- not a vintage tone. GP-5 only, P/J bass, no pedalboard.

Revision intent

Keep the musical role of the original patch while reducing redundant gain, excessive space and unclear switching where identified in audit entry 94.
The module settings and section map below are the active revision.
Audited capture volumes and Michael's explicit patch-level adjustments are preserved.
No hardware audition or measured level match has been performed.

GP-5 settings

Module order: NR -> PRE -> DST -> AMP -> CAB -> EQ -> MOD -> DLY -> RVB.
The encoded N->S block sits between DST and AMP when a SnapTone is used.

Cab IR: Mesa215. Encoded as User IR 7.

NR - Gate

THRE: 30.
Fixed on. Not on CTL.
Use the lowest threshold that keeps rests quiet. Check soft notes and held-note decay. This gate is before the drives and amp; it does not directly gate noise generated after it.

PRE - Module off

Not used.

DST - Bass OD

Gain: 25.
Blend: 35.
VOL: 65.
Bass: 60.
Treble: 50.
CTL assigned. Loads off; first CTL press switches it on.
Supplies the selected additional drive voice. Use its level and gain as separate controls. A pre-amp boost may add compression instead of a proportional solo-volume increase.

AMP - Mess Bass

Gain: 42.
VOL: 68.
Bass: 55.
Middle: 55.
Treble: 50.
Fixed on. Not on CTL.
Provides one fixed amp voice for the complete preset. CTL does not change its knobs or select another amp channel.

CAB - User IR 7

VOL: 62.
Fixed on. Not on CTL.
Keeps the required speaker response in the exported preset. Use the documented loaded IR slot; no extra cab goes after a SnapTone.

EQ - Bass EQ 2

50Hz: 3.
120Hz: 2.
400Hz: -3.
800Hz: 1.
4.5kHz: 4.
VOL: 55.
Fixed on. Not on CTL.
Shapes note body and cut after the amp/capture. Where assigned to CTL, its output adds the specified lift after the gain stages. Numbers are GP-5 control values, not a calibrated loudness guarantee.

MOD - Module off

Not used.

DLY - Module off

Not used.

RVB - Room

Mix: 5.
Decay: 35.
Trail: on.
CTL assigned. Loads off; first CTL press switches it on.
Adds the specified room or ambient tail. The revised mix keeps the initial note audible. Trail behavior follows the saved setting.

Switching and section map

CTL blocks: DST, RVB.

- CTL off / loaded state: main verse/chorus groove. GP-5 active: NR, AMP, CAB, EQ.
- First CTL press: heavier instrumental section. GP-5 active: NR, DST, AMP, CAB, EQ, RVB.
- Press CTL again to return to the loaded block pattern, provided no shared MIDI block has been changed.

Revision record

Approved audit entry 94.

- DST Gain: 55 -> 25.
- DST Blend: 70 -> 35.
- AMP Bass: 62 -> 55.
- EQ 800Hz: -2 -> 1.
- RVB Mix: 22 -> 5.

Pre-revision JSON, Markdown and original file hashes are preserved in Documents/patch-audit-2026-10-16/inventory.json and implementation-manifest.json.
The site piece title and on-disk filenames stay stable; only the short pedal display name may change.