This Is Halloween -- The Nightmare Before Christmas

Revised 2026-10-16 following the approved library audit.
Type: Song. Instrument: Harley Benton passive 5-string P/J.
Full board. Board Option: American Sound (bypassed; retained for legacy full-board builds).
Patch screen name: ThisIsHlwn. Patch VOL: 55.
Preset BPM: 120 encoder default; song tempo unverified.

Bass: Harley Benton P/J, 5-string, passive. Full board.
From *The Nightmare Before Christmas* (1993). Music and lyrics by Danny Elfman.
The recording is an orchestral ensemble number. The low end I hear described is low brass and orchestral bass playing a stalking, oom-pah minor-key march. I can't confirm an electric bass on it, so this patch translates that low end to bass guitar.
Tempo and key: not verified. Moderate march feel. No delay in the patch, so nothing needs to lock to tempo.
Play with fingers, short and detached, like a tuba. Mute each note with the fretting hand. Neck (P) full, bridge (J) at about 50%, tone at about 50%.
One GP-5 sound, so no CTL. That's allowed on bass per the patch rules.
The lift for the full-ensemble shouts ("This is Halloween!") comes from the Tidal Wave drive footswitch.

Revision intent

Keep the musical role of the original patch while reducing redundant gain, excessive space and unclear switching where identified in audit entry 116.
The module settings and section map below are the active revision.
Audited capture volumes and Michael's explicit patch-level adjustments are preserved.
No hardware audition or measured level match has been performed.

GP-5 settings

Module order: NR -> PRE -> DST -> AMP -> CAB -> EQ -> MOD -> DLY -> RVB.
The encoded N->S block sits between DST and AMP when a SnapTone is used.

AMP/CAB replacement: SnapTone FullB15 (slot 54): Ampeg B18 - Head DI - Bass Chan - Vol 5 (B-18N) + Apg115410 (User IR 2).
Slot: 54. Always on.
Gain: 52, VOL: 80, Bass: 58, Middle: 55, Treble: 42.
AMP and CAB are both off; the capture already includes its cab/DI character.
The capture voice is fixed across CTL states. Audited VOL is preserved for this slot.

NR - Gate

THRE: 15.
Fixed on. Not on CTL.
Use the lowest threshold that keeps rests quiet. Check soft notes and held-note decay. This gate is before the drives and amp; it does not directly gate noise generated after it.

PRE - Module off

Not used.

DST - Module off

Not used.

AMP - Module off

Not used.

CAB - Module off

Not used.

EQ - Bass EQ 2

50Hz: 1.
120Hz: 2.
400Hz: 1.
800Hz: -1.
4.5kHz: -2.
VOL: 50.
Fixed on. Not on CTL.
Shapes note body and cut after the amp/capture. Where assigned to CTL, its output adds the specified lift after the gain stages. Numbers are GP-5 control values, not a calibrated loudness guarantee.

MOD - Module off

Not used.

DLY - Module off

Not used.

RVB - Hall

Mix: 5.
Decay: 30.
Trail: on.
Fixed on. Not on CTL.
Adds the specified room or ambient tail. The revised mix keeps the initial note audible. Trail behavior follows the saved setting.

Switching and section map

CTL blocks: None.

- CTL off / loaded state: Creeping verses. GP-5 active: NR, EQ, RVB, N->S.
- No GP-5 CTL change. Use the board stomps listed below when the arrangement needs another sound.

Full pedalboard

Flamma FS-08 Octave -> Donner Ultimate Comp -> Donner Stylish Fuzz -> Joyo Tidal Wave -> Joyo American Sound -> Joyo Narcissus -> Valeton GP-5.
Board settings are set by hand and are not encoded in the .prst.
All numeric pedal positions use the existing 0-100 position shorthand unless a clock position is specified.

Flamma FS-08 Octave

On throughout.
-2OCT: 0.
-OCT: 25.
+OCT: 0.
+2OCT: 0.
Dry: 100.

Donner Ultimate Comp

On throughout.
COMP: 40.
TONE: 45.
LEVEL: 55.

Mode: NORMAL.

Donner Stylish Fuzz

Bypassed throughout.
Sustain: 25.
Treble: 50.
Bass: 50.
Volume: 50.

Joyo Tidal Wave

Drive off for creeping verses; on for ensemble shouts and ending; preamp active.
Drive: 25.
Blend: 35.
Presence: 45.
Level: 55.
Treble: 45.
Middle: 55.
Bass: 58.
Mid-Frequency: 500Hz.
Bass-Shift: 80Hz.
Cab-Sim (DI out): Off.
Ground Lift: Off.
The footswitch toggles drive only. Preamp EQ and Level stay active in both states. Cab-Sim/Ground Lift affect the DI path; main instrument output is unchanged.

Joyo American Sound

Bypassed throughout.
Level: 50.
Drive: 10.
Voice: 50.
Low: 50.
Mid: 50.
High: 50.

Joyo Narcissus

Bypassed throughout.
Width: 30.
Depth: 20.

Rate: 20.
Mode: Vintage.

Board choreography

- Flamma FS-08 Octave: On throughout.
- Donner Ultimate Comp: On throughout.
- Donner Stylish Fuzz: Bypassed throughout.
- Joyo Tidal Wave: Drive off for creeping verses; on for ensemble shouts and ending; preamp active.
- Joyo American Sound: Bypassed throughout.
- Joyo Narcissus: Bypassed throughout.

Set the board switches for the section you are entering. Intro-only or clean-only effects may need to start on. Return each pedal to its documented state at the next section. Board pedals are independent of CTL.

Revision record

Approved audit entry 116.
- RVB Mix: 10 -> 5.
- Board Tidal Wave: Drive 25.

Pre-revision JSON, Markdown and original file hashes are preserved in Documents/patch-audit-2026-10-16/inventory.json and implementation-manifest.json.
The site piece title and on-disk filenames stay stable; only the short pedal display name may change.