Bright Size Life (Guitar) -- Pat Metheny

Revised 2026-10-16 following the approved library audit.
Type: Song. Instrument: HSS Stratocaster.
GP-5 only.
Patch screen name: G-BrightSi. Patch VOL: 50.
Preset tempo: 170 BPM.

Pat Metheny, 1976. BPM est., brisk swing. Metheny is known for a warm, round, dark clean tone on a hollowbody, neck pickup, with a fluid, slightly compressed legato feel on the head and solos. The exact amp and studio chain on this record are not verified, so this is built from his general sound.
Instrument: Stratocaster (HSS). A Strat is much brighter and snappier than a hollowbody, so the patch pulls the highs down hard. Use the neck pickup, tone knob around 4-5, and pick with the fleshy part of the pick or thumb-side to soften the attack.
GP-5 only, Stratocaster (HSS), no pedalboard.

Revision intent

Keep the musical role of the original patch while reducing redundant gain, excessive space and unclear switching where identified in audit entry 144.
The module settings and section map below are the active revision.
Audited capture volumes and Michael's explicit patch-level adjustments are preserved.
No hardware audition or measured level match has been performed.

GP-5 settings

Module order: NR -> PRE -> DST -> AMP -> CAB -> EQ -> MOD -> DLY -> RVB.
The encoded N->S block sits between DST and AMP when a SnapTone is used.

AMP/CAB replacement: SnapTone BrightTwin (slot 64): CLEANEST - Fender Deluxe Reverb 1965 [Hyper Accuracy] + TWIN REVERB __ BALANCED (vulturized Twin).
Slot: 64. Always on.
Gain: 50, VOL: 75, Bass: 55, Middle: 50, Treble: 42.
AMP and CAB are both off; the capture already includes its cab/DI character.
The capture voice is fixed across CTL states. Audited VOL is preserved for this slot.

NR - Gate

THRE: 10.
Fixed on. Not on CTL.
Use the lowest threshold that keeps rests quiet. Check soft notes and held-note decay. This gate is before the drives and amp; it does not directly gate noise generated after it.

PRE - COMP

Sustain: 30.
VOL: 55.
Fixed on. Not on CTL.
Controls the source dynamics or adds the specified push/filter before distortion and amp processing. The settings stay fixed; only its on/off state can change.

DST - Module off

Not used.

AMP - Module off

Not used.

CAB - Module off

Not used.

EQ - Guitar EQ 1

125Hz: 0.
400Hz: 2.
800Hz: 0.
1.6kHz: -2.
4kHz: -5.
VOL: 50.
Fixed on. Not on CTL.
Shapes note body and cut after the amp/capture. Where assigned to CTL, its output adds the specified lift after the gain stages. Numbers are GP-5 control values, not a calibrated loudness guarantee.

MOD - Module off

Not used.

DLY - Tape

Mix: 14.
Time: 320.
F.Back: 22.

Trail: on.
CTL assigned. Loads off; first CTL press switches it on.
Adds repeats only in the listed states. Trail preserves the remaining repeats when this block is bypassed; it does not change delay time or mix.

RVB - Room

Mix: 8.
Decay: 25.
Trail: off.
Fixed on. Not on CTL.
Adds the specified room or ambient tail. The revised mix keeps the initial note audible. Trail behavior follows the saved setting.

Switching and section map

CTL blocks: DLY.

- CTL off / loaded state: Warm clean comping/head. GP-5 active: NR, PRE, EQ, RVB, N->S.
- First CTL press: Clean melodic lead with Tape. GP-5 active: NR, PRE, EQ, DLY, RVB, N->S.
- Press CTL again to return to the loaded block pattern, provided no shared MIDI block has been changed.

Revision record

Approved audit entry 144.

- Pedal display name: BrightSizeLife-Metheny-Gtr -> G-BrightSi. Filenames stay unchanged.
- SnapTone Treble: 35 -> 42.
- DST: Green OD -> off.
- DST: removed from CTL.
- RVB Mix: 12 -> 8.

Pre-revision JSON, Markdown and original file hashes are preserved in Documents/patch-audit-2026-10-16/inventory.json and implementation-manifest.json.
The site piece title and on-disk filenames stay stable; only the short pedal display name may change.