Creep - Radiohead

Revised 2026-10-16 following the approved library audit.
Type: Song. Instrument: HSS Stratocaster.
Full board. Board Option: American Sound (bypassed; retained for legacy full-board builds).
Patch screen name: Creep - Ra. Patch VOL: 50.
Preset tempo: 92 BPM.

Stratocaster (HSS), Full Board. Two sounds in this song: the clean, chorused verse arpeggios, and the famous distorted "chunk" hits that slam in right before each chorus line. Tempo: 92 BPM.

Revision intent

Keep the musical role of the original patch while reducing redundant gain, excessive space and unclear switching where identified in audit entry 150.
The module settings and section map below are the active revision.
Audited capture volumes and Michael's explicit patch-level adjustments are preserved.
Keep the loaded Foxy cab so the patch remains self-contained; British Alnico remains a manual audition alternative.
No hardware audition or measured level match has been performed.

GP-5 settings

Module order: NR -> PRE -> DST -> AMP -> CAB -> EQ -> MOD -> DLY -> RVB.
The encoded N->S block sits between DST and AMP when a SnapTone is used.

NR - Gate

THRE: 25.
Fixed on. Not on CTL.
Use the lowest threshold that keeps rests quiet. Check soft notes and held-note decay. This gate is before the drives and amp; it does not directly gate noise generated after it.

PRE - Module off

Not used.

DST - SM Dist

Gain: 65.
Tone: 55.
VOL: 80.

CTL assigned. Loads off; first CTL press switches it on.
Supplies the selected additional drive voice. Use its level and gain as separate controls. A pre-amp boost may add compression instead of a proportional solo-volume increase.

AMP - Foxy 30N

Gain: 45.
Tone Cut: 40.
VOL: 50.
Bright: on.
Fixed on. Not on CTL.
Provides one fixed amp voice for the complete preset. CTL does not change its knobs or select another amp channel.

CAB - Foxy 2x12

VOL: 50.
Fixed on. Not on CTL.
Keeps the required speaker response in the exported preset. Use the documented loaded IR slot; no extra cab goes after a SnapTone.

EQ - Guitar EQ 1

125Hz: 0.
400Hz: -3.
800Hz: 0.
1.6kHz: 2.
4kHz: 3.
VOL: 50.
Fixed on. Not on CTL.
Shapes note body and cut after the amp/capture. Where assigned to CTL, its output adds the specified lift after the gain stages. Numbers are GP-5 control values, not a calibrated loudness guarantee.

MOD - Module off

Not used.

DLY - Module off

Not used.

RVB - Room

Mix: 10.
Decay: 30.
Trail: on.
Fixed on. Not on CTL.
Adds the specified room or ambient tail. The revised mix keeps the initial note audible. Trail behavior follows the saved setting.

Switching and section map

CTL blocks: DST.

- CTL off / loaded state: Clean verses. GP-5 active: NR, AMP, CAB, EQ, RVB.
- First CTL press: Distorted pre-chorus hits and chorus chords. GP-5 active: NR, DST, AMP, CAB, EQ, RVB.
- Press CTL again to return to the loaded block pattern, provided no shared MIDI block has been changed.

Full pedalboard

Flamma FS-08 Octave -> Donner Ultimate Comp -> Donner Stylish Fuzz -> Joyo King of Kings -> Joyo American Sound -> Joyo Narcissus -> Valeton GP-5.
Board settings are set by hand and are not encoded in the .prst.
All numeric pedal positions use the existing 0-100 position shorthand unless a clock position is specified.

Flamma FS-08 Octave

Bypassed throughout.
-2OCT: 0.
-OCT: 0.
+OCT: 0.
+2OCT: 0.
Dry: 100.

Donner Ultimate Comp

On throughout.
COMP: 30.
TONE: 50.
LEVEL: unity.
Mode: NORMAL.

Donner Stylish Fuzz

Bypassed throughout.
Sustain: 70.
Treble: 60.
Bass: 50.
Volume: 50.

King of Kings Left

Bypassed throughout.
Volume: 50.
Gain: 20.
Tone: 50.
Clipping toggle: Softer position.
Feedback toggle: Standard position.

King of Kings Right

Bypassed throughout.
Volume: 50.
Gain: 20.
Tone: 50.
Clipping toggle: Softer position.
Feedback toggle: Standard position.

Joyo American Sound

Bypassed throughout.
Level: 50.
Drive: 10.
Voice: 50.
Low: 50.
Mid: 50.
High: 50.

Joyo Narcissus

On throughout.
Width: 60.
Depth: 40.

Rate: 40.
Mode: Vintage.

Board choreography

- Flamma FS-08 Octave: Bypassed throughout.
- Donner Ultimate Comp: On throughout.
- Donner Stylish Fuzz: Bypassed throughout.
- King of Kings Left: Bypassed throughout.
- King of Kings Right: Bypassed throughout.
- Joyo American Sound: Bypassed throughout.
- Joyo Narcissus: On throughout.

Set the board switches for the section you are entering. Intro-only or clean-only effects may need to start on.
Return each pedal to its documented state at the next section. Board pedals are independent of CTL.

Revision record

Approved audit entry 150.

- PRE: Boost -> off.
- PRE: removed from CTL.
- EQ 1.6kHz: 6 -> 2.
- EQ 4kHz: 10 -> 3.
- EQ VOL: 60 -> 50.
- RVB Mix: 18 -> 10.
- Board Stylish Fuzz: ; Bypassed throughout.

Pre-revision JSON, Markdown and original file hashes are preserved in Documents/patch-audit-2026-10-16/inventory.json and implementation-manifest.json.
The site piece title and on-disk filenames stay stable; only the short pedal display name may change.