- Callex REST API Documentation
  - 📂 Section 1: PDF Knowledge Upload (Frontend Guide)
    - 1. Create an Agent with a Document
    - 2. Append Document to Existing Agent
  - 🔌 Section 2: External Developer APIs (API Key Auth)
    - 📞 2.1 Call History & Management
      - Get All Calls
      - Get Specific Call Details
      - Update Call Disposition (Outcome)
      - Get Only Transcript
    - 🕵️ 2.2 Live Supervisor APIs
      - List Active Live Calls
      - Whisper (Private Message to AI)
      - Barge (Takeover Call)
    - 🏷️ 2.3 Disposition Tags (CRUD)
      - List All Dispositions
      - Create a Disposition
      - Update a Disposition
      - Delete a Disposition
    - 🤖 2.4 Agent Management APIs
      - List Agents
      - Create Agent (JSON alternative)
      - Get Specific Agent
      - Update Agent Settings
      - Delete Agent
      - Delete Agent Knowledge Base
    - 📊 2.5 General & Debugging
      - Get KPIs and Stats
      - Check API Key Identity

Callex REST API Documentation

> **Version:** 2.1 | **Updated:** March 23, 2026

Welcome to the comprehensive Callex API documentation. This guide covers how frontend developers can upload PDF/Excel knowledge bases, as well as providing the full schema for all external 3rd-party integration APIs.

📂 Section 1: PDF Knowledge Upload (Frontend Guide)

The backend handles automatic parsing and vectorization of PDF, DOC, CSV, and Excel files.

1. Create an Agent with a Document

Create a new AI agent and immediately feed it a knowledge base document in one request.

- **Method:** `POST`
- **URL:** `/api/agents`
- **Auth:** Bearer Token (JWT User Session)
- **Content-Type:** `multipart/form-data`

Request Body (FormData):

Key	Type	Required	Description
`name`	String	Yes	The internal name for the agent
`systemPrompt`	String	No	The core behavior instructions. Optional if relying solely on the document.
`file`	File	Yes	The PDF/Excel/Word document. Max size 20MB.
`voice`	String	No	ElevenLabs voice ID (e.g., `MF4J4IDTRo0AxOO4dpFR`)

Success Response (201 Created):

```
{
  "id": "agent-uuid-string",
  "name": "Support Agent",
  "hasKnowledgeBase": true,
  "createdAt": "2026-03-23T10:00:00.000Z"
}
```

2. Append Document to Existing Agent

Upload a document to an agent that has already been created.

- **Method:** `POST`
- **URL:** `/api/agents/:id/knowledge`
- **Auth:** Bearer Token (JWT User Session)
- **Content-Type:** `multipart/form-data`

Request Body (FormData):

Key	Type	Required	Description
`file`	File	Yes	The PDF/Excel document to append to the agent's memory.

Success Response (200 OK):

```
{
  "message": "Knowledge base successfully processed and embedded."
}
```

🔌 Section 2: External Developer APIs (API Key Auth)

These APIs are meant for server-to-server integration by developers embedding Callex into their own platforms (CRMs, dashboards).

- **Base URL:** `https://your-server.com/api/v1`
- **Authentication:** `Authorization: Bearer <API_KEY>`
- **Content-Type:** `application/json`

📞 2.1 Call History & Management

Get All Calls

Retrieve a paginated list of all calls (active and completed) associated with the API Key's account.

- **Method:** `GET`
- **URL:** `/v1/calls`
- **Query Parameters:** `page` (default 1), `limit` (default 50), `status` (active/completed)

Response:

```
{
  "calls": [
    {
      "id": "call-uuid",
      "phoneNumber": "+1234567890",
      "agentId": "agent-uuid",
      "status": "completed",
      "duration": 45,
      "disposition": "Interested"
    }
  ],
  "pagination": { "page": 1, "limit": 50, "total": 120, "totalPages": 3 }
}
```

Get Specific Call Details

Get comprehensive analytics, full transcript, and summary for a single call.

- **Method:** `GET`
- **URL:** `/v1/calls/:id`

Response:

```
{
  "id": "call-uuid",
  "status": "completed",
  "duration": 120,
  "sentiment": "positive",
  "transcript": "Agent: Hello...\nUser: Hi there...",
  "disposition": "Follow Up",
  "recordingUrl": "https://storage.../recording.wav",
  "summary": "The customer is interested in buying the premium plan next
week.",
  "startedAt": "2026-03-23T10:00:00.000Z"
}
```

Update Call Disposition (Outcome)

Update the sales disposition or outcome tag of a specific call remotely.

- **Method:** `PATCH`
- **URL:** `/v1/calls/:id/disposition`

Request Body:

```
{
  "disposition": "Call Back Later"
}
```

Response:

```
{
  "message": "Disposition updated successfully",
  "id": "call-uuid",
  "disposition": "Call Back Later"
}
```

Get Only Transcript

Fetch solely the raw text conversation history for ingestion into a CRM.

- **Method:** `GET`
- **URL:** `/v1/calls/:id/transcript`

Response:

```
{
  "transcript": "Agent: Hello...\nUser: Hi there..."
}
```

🕵️ 2.2 Live Supervisor APIs

APIs to monitor and intervene in phone queries as they happen in absolute real-time.

List Active Live Calls

Get a list of calls that are currently ongoing / active right now.

- **Method:** `GET`
- **URL:** `/v1/supervisor/calls`

Response:

```
[
  {
    "id": "active-call-uuid",
    "phoneNumber": "+1234567890",
    "agentName": "Sales Rep",
    "status": "active"
  }
]
```

Whisper (Private Message to AI)

Send a hidden system instruction to the AI while it is speaking to the customer. The customer will not hear this instruction, but the AI will act on it.

- **Method:** `POST`
- **URL:** `/v1/supervisor/calls/:id/whisper`

Request Body:

```
{
  "message": "Offer them a 20% discount if they sign up today."
}
```

Barge (Takeover Call)

Immediately disconnect the AI and forward the live customer call to a human agent's SIP or phone number.

- **Method:** `POST`
- **URL:** `/v1/supervisor/calls/:id/barge`

Request Body:

```
{
  "destinationNumber": "+19876543210"
}
```

2.3 Disposition Tags (CRUD)

Manage the dropdown list of possible call outcomes (e.g., "Not Interested", "Sale Made").

List All Dispositions

- **Method:** `GET`
- **URL:** `/v1/dispositions`

Response:

```
{
  "dispositions": [
    {
      "id": "disp-uuid",
      "name": "Callback Requested",
      "category": "Lead",
      "requiresNote": true
    }
  ]
}
```

Create a Disposition

- **Method:** `POST`
- **URL:** `/v1/dispositions`

Request Body:

```
{
  "name": "Busy / No Answer",
  "category": "Unreachable",
  "requiresNote": false
}
```

Response: `201 Created` with full object tree.

Update a Disposition

- **Method:** `PUT`
- **URL:** `/v1/dispositions/:id`

Request Body: (All fields optional)

```
{
  "active": false,
  "name": "Do Not Call (DNC)"
}
```

Delete a Disposition

- **Method:** `DELETE`
- **URL:** `/v1/dispositions/:id`

Response:

```
{
  "message": "Disposition deleted successfully",
  "id": "disp-uuid"
}
```

🤖 2.4 Agent Management APIs

Programmatically create, update, and manage your AI voice bots.

List Agents

- **Method:** `GET`
- **URL:** `/v1/agents`

Create Agent (JSON alternative)

If you don't need to upload a PDF file, you can use pure JSON to create an agent.

- **Method:** `POST`
- **URL:** `/v1/agents`
- **Content-Type:** `application/json`

Request Body:

```
{
  "name": "API Agent",
  "systemPrompt": "You are a helpful assistant...",
  "voice": "MF4J4IDTRo0AxOO4dpFR"
}
```

Get Specific Agent

- **Method:** `GET`
- **URL:** `/v1/agents/:id`

Update Agent Settings

- **Method:** `PUT`
- **URL:** `/v1/agents/:id`

Request Body:

```
{
  "language": "es-ES",
  "temperature": 0.5
}
```

Delete Agent

- **Method:** `DELETE`
- **URL:** `/v1/agents/:id`

Delete Agent Knowledge Base

Clears all uploaded PDF context from the agent, resetting its memory.

- **Method:** `DELETE`
- **URL:** `/v1/agents/:id/knowledge`

📊 2.5 General & Debugging

Get KPIs and Stats

Fetch account statistics for custom dashboard rendering.

- **Method:** `GET`
- **URL:** `/v1/dashboard/kpis`

Response:

```
{
  "totalCalls": 450,
  "totalMinutes": 1200,
  "averageCallLengthSeconds": 160,
  "topAgent": "Support Bot"
}
```

Check API Key Identity

If you are seeing missing data, check which user account is actually tied to your API Key.

- **Method:** `GET`
- **URL:** `/v1/debug/my-identity`

Response:

```
{
  "userId": "user-uuid",
  "ownedAgents": 3,
  "callsWithUserId": 150
}
```