Callex AI — Developer API Documentation

> ***Version:*** *1.0* | ***Base URL:*** `http://62.171.170.48:4000` | ***Last Updated:*** *March 12, 2026*

Table of Contents

1. Admin Panel
2. Getting Your API Key
3. Authentication
4. API Endpoints
   - List Agents (Paginated)
   - Create Agent
   - Get Agent Details
   - Edit Agent
   - Delete Agent
5. Agent Configuration Reference
6. Error Reference
7. Best Practices

Admin Panel

Everything you can do via the API can also be done through the **Callex Admin Panel** — a full-featured web dashboard.

🔗 **Admin Panel URL:** http://62.171.170.48:4000

What You Get in the Admin Panel

Feature	Where to Find
Create, Edit & Delete Agents	Sidebar → **Agent Studio**
Generate & Revoke API Keys	Sidebar → **Settings** → API Keys
Configure Webhooks	Sidebar → **Settings** → Webhooks
Live Call Monitoring	Sidebar → **Live Supervisor**
Call Analytics & Logs	Sidebar → **Analytics**
Knowledge Base Management	Sidebar → **Knowledge Base**
Campaign Management (Dialer)	Sidebar → **Dialer**
Call Routing Rules	Sidebar → **Routing**
CRM & Tool Integrations	Sidebar → **Integrations**
Security & Voice Signatures	Sidebar → **Security**
Quality Assurance	Sidebar → **QA**
Reports & Exports	Sidebar → **Reports**

Billing & Usage	Sidebar → **Billing**
Agent Simulation & Testing	Sidebar → **Simulation**

> 💡 ***Use the Admin Panel to visually manage everything.*** *The API below is for developers who want to integrate agent management into their own dashboards or automate workflows programmatically.*

Getting Your API Key

Before making any API calls, you need to generate an API key from the Admin Panel.

Step-by-step

1. **Open the Admin Panel** → http://62.171.170.48:4000 and **log in**.
2. Click **Settings** in the left sidebar.
3. You'll see the **"API Keys"** section at the top.
4. Enter a **Key Name** (e.g., "Production App", "My Dashboard").
5. Select the **Environment**:
   - **Test** — for development/staging (prefix: `ck_test_`)
   - **Live** — for production (prefix: `ck_live_`)
6. Click **"Generate"**.
7. Your new API key appears in an **orange highlighted box**.

> ⚠️ ***IMPORTANT:*** *The full API key is shown **only once**. Copy it immediately using the **Copy** button and store it securely. You will not be able to see the full key again.*

Managing API Keys

Action	How
View all keys	Admin Panel → Settings → API Keys section
See last used date	Shown next to each key
Revoke a key	Click the 🗑 trash icon next to any key

Key Format

Environment	Prefix	Example
Test	`ck_test_`	`ck_test_a1b2c3d4_e5f6g7h8i9j0k1l2m3n4o5p6`
Live	`ck_live_`	`ck_live_f8e7d6c5_b4a3z2y1x0w9v8u7t6s5r4q3`

Authentication

All API requests must include your API key in the `Authorization` header.

```
Authorization: Bearer <YOUR_API_KEY>
```

Example:

```
Authorization: Bearer ck_live_a1b2c3d4_e5f6g7h8i9j0k1l2m3n4o5p6
```

API Endpoints

1. List All Agents (Paginated)

Retrieve a paginated list of all your AI agents.

```
GET /api/v1/agents
```

Query Parameters

Parameter	Type	Default	Description
`page`	integer	`1`	Page number
`limit`	integer	`10`	Items per page (max 100)
`status`	string	—	Filter: `draft`, `active`, `paused`

cURL Example

```
curl -X GET "http://62.171.170.48:4000/api/v1/agents?page=1&limit=5&status=active" \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "agents": [
    {
      "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
      "name": "Jane - Support",
      "status": "active",
      "language": "en-US",
      "createdAt": "2026-03-12T10:00:00.000Z"
    }
  ],
  "pagination": {
    "page": 1,
    "limit": 5,
    "total": 12,
    "totalPages": 3
  }
}
```

Pagination Fields

Field	Description
`page`	Current page number

`limit`	Items per page
`total`	Total agents matching filter
`totalPages`	Total pages available

---

2. Create a New Agent

Create a new AI agent. Automatically creates the first prompt version.

```
POST /api/v1/agents
```

Headers

```
Content-Type: application/json
Authorization: Bearer <YOUR_API_KEY>
```

Body (JSON)

Only `name` is required. Everything else has smart defaults.

Parameter	Type	Required	Default	Description
`name`	string	**Yes**	—	Agent name
`description`	string	No	`""`	Agent description
`systemPrompt`	string	No	`""`	LLM instructions & personality
`openingLine`	string	No	`""`	First thing AI says on call
`voice`	string	No	`"alloy"`	ElevenLabs Voice ID
`language`	string	No	`"en-US"`	Language code
`temperature`	float	No	`0.7`	Creativity (0.0 – 1.0)
`maxDuration`	integer	No	`30`	Max call minutes
`bargeInMode`	string	No	`"balanced"`	`aggressive`, `balanced`, `polite`
`voicemailLogic`	string	No	`"hangup"`	`hangup`, `leave_message`, `human_escalate`

> 📘 *See the full [Agent Configuration Reference](#) for all 50+ fields.*

cURL Example

```
curl -X POST http://62.171.170.48:4000/api/v1/agents \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Premium",
    "systemPrompt": "You are a professional sales agent. Be persuasive but polite.",
```

```
    "openingLine": "Hello! I am calling from Acme Corp regarding an exclusive
offer.",
    "voice": "nova",
    "temperature": 0.6,
    "maxDuration": 15
  }'
```

Response — `201 Created`

```
{
  "message": "Agent successfully created.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": {
    "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
    "name": "Sales Agent - Premium",
    "status": "draft",
    "createdAt": "2026-03-12T10:00:00.000Z"
  }
}
```

> 💡 *New agents start as `draft`. Activate via the Admin Panel or the Edit API.*

---

3. Get Agent Details

Retrieve full configuration and prompt history of an agent.

```
GET /api/v1/agents/{agentId}
```

cURL Example

```
curl -X GET http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "name": "Sales Agent - Premium",
  "systemPrompt": "You are a professional sales agent.",
  "voice": "nova",
  "language": "en-US",
  "temperature": 0.6,
  "PromptVersion": [
    {
      "version": 1,
      "prompt": "You are a professional sales agent.",
      "isActive": true
    }
```

```
  ]
}
```

---

4. Edit / Update an Agent

Update any fields of an existing agent. Send **only the fields you want to change**.

```
PUT /api/v1/agents/{agentId}
```

Headers

```
Content-Type: application/json
Authorization: Bearer <YOUR_API_KEY>
```

Body

All fields are optional. Only included fields are updated.

cURL Example

```
curl -X PUT http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Enterprise",
    "temperature": 0.5,
    "status": "active"
  }'
```

Response — `200 OK`

```
{
  "message": "Agent updated successfully.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": {
    "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
    "name": "Sales Agent - Enterprise",
    "temperature": 0.5,
    "status": "active"
  }
}
```

---

5. Delete an Agent

Permanently delete an agent and all its prompt versions and follow-ups.

```
DELETE /api/v1/agents/{agentId}
```

> ⚠️ ***This action is irreversible.***

cURL Example

```
curl -X DELETE http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "message": "Agent deleted successfully.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1"
}
```

Agent Configuration Reference

Complete list of configurable fields (all optional except `name` on create).

Core

Field	Type	Default	Description
`name`	string	—	Agent name
`description`	string	`""`	Description
`systemPrompt`	string	`""`	LLM instructions
`openingLine`	string	`""`	First sentence on call
`voice`	string	`"alloy"`	Voice ID
`language`	string	`"en-US"`	Language code
`status`	string	`"draft"`	`draft`, `active`, `paused`

LLM

Field	Type	Default	Description
`temperature`	float	`0.7`	Creativity (0.0–1.0)
`maxTokens`	integer	`250`	Max tokens per response
`sttEngine`	string	`"callex-1.1"`	Speech-to-text engine
`llmModel`	string	`"callex-1.3"`	LLM model

Voice & Speech

Field	Type	Default	Description

`prosodyRate`	float	`1.0`	Speech speed
`prosodyPitch`	float	`1.0`	Pitch
`fillerPhrases`	array	`["Let me check..."]`	Filler phrases
`speakingStyle`	string	`"professional"`	`professional`, `friendly`, `urgent`, `empathetic`
`backgroundAmbience`	string	`"none"`	`none`, `office`, `call_center`

Call Behavior

Field	Type	Default	Description
`bargeInMode`	string	`"balanced"`	`aggressive`, `balanced`, `polite`, `disabled`
`patienceMs`	integer	`800`	End-of-turn timeout (ms)
`maxDuration`	integer	`30`	Max call minutes
`ringTimeout`	integer	`30`	Ring timeout (seconds)
`voicemailLogic`	string	`"hangup"`	`hangup`, `leave_message`, `human_escalate`
`fallbackMessage`	string	`"I'm sorry..."`	Fallback response

Advanced

Field	Type	Default	Description
`sentimentRouting`	boolean	`false`	Transfer on angry caller
`piiRedaction`	boolean	`true`	Redact credit cards, SSN
`emotionalMirroring`	boolean	`true`	Match caller's energy
`dynamicCodeSwitching`	boolean	`true`	Switch languages mid-call
`objectionHandling`	string	`"standard"`	`standard` or `persistent`
`autoSummary`	boolean	`true`	Auto call summary
`autoSentiment`	boolean	`true`	Auto sentiment analysis
`recordCall`	boolean	`true`	Record calls
`webhookUrl`	string	`null`	Post-call webhook URL
`autoFollowUp`	boolean	`true`	Auto schedule follow-ups

Error Reference

Status	Meaning	Example
`200`	Success	`{ "message": "Agent updated successfully." }`

201	Created	`{ "message": "Agent successfully created." }`
400	Bad Request	`{ "error": "Agent 'name' is required." }`
401	Unauthorized	`{ "error": "Missing or invalid Authorization header." }`
403	Forbidden	`{ "error": "Invalid or revoked API Key." }`
404	Not Found	`{ "error": "Agent not found" }`
500	Server Error	`{ "error": "Internal server error" }`

Best Practices

1. **Store your API key securely** — never expose in client-side code or public repos.
2. **Use Test keys** (`ck_test_`) for development, **Live keys** (`ck_live_`) for production.
3. **Paginate** when listing agents — use `page` and `limit` params.
4. **Send only changed fields** when editing — PUT accepts partial updates.
5. **Revoke compromised keys** immediately from **Admin Panel → Settings**.

Quick Reference

Action	Method	Endpoint
List agents	`GET`	`/api/v1/agents?page=1&limit=10`
Create agent	`POST`	`/api/v1/agents`
Get agent	`GET`	`/api/v1/agents/{id}`
Edit agent	`PUT`	`/api/v1/agents/{id}`
Delete agent	`DELETE`	`/api/v1/agents/{id}`

> 📌 ***Remember:*** *Everything available via API is also available in the* ***Admin Panel*** *with a full visual interface — agent creation, editing, deletion, API key management, analytics, and more.*

For support, contact the Callex engineering team.