Callex AI — Complete Developer API Documentation

> ***Version:*** *3.0* | ***API Base URL:*** `http://62.171.170.48:4500` | ***Last Updated:*** *March 17, 2026*

⚠️ Important: URL Guide

Service	URL	Purpose
Admin Dashboard (GUI)	`http://62.171.170.48:5173`	Human-facing web panel
API Server	`http://62.171.170.48:4500`	All REST API calls from apps/Postman
AI Voice Engine (WebSocket)	`ws://62.171.170.48:8085`	FreeSWITCH / live call WebSocket

---

Table of Contents

1. Admin Panel
2. Getting Your API Key
3. Authentication
4. Quick Start — Postman
5. External API — API Key Auth
   - Agents
   - Calls & Transcripts
   - Voices
   - Supervisor — Live Calls
   - Dashboard KPIs
   - Debug Utilities
6. Internal Dashboard API — JWT Auth
   - Auth (Login/Register)
   - Agents (Internal)
   - Analytics & Call Logs
   - Settings — API Keys & Webhooks
   - Dialer & Campaigns
   - Follow-Ups
   - Knowledge Base
   - Routing Rules
7. WebSocket — AI Voice Engine
8. Available Voices Reference
9. Agent Configuration Reference
10. Error Reference
11. Best Practices

Admin Panel

Everything below is also available via the **Callex Dashboard UI**:

🔗 **Dashboard URL:** http://62.171.170.48:5173

Feature	Dashboard Location

Create/Edit/Delete Agents	Sidebar → **Agent Studio**
Generate/Revoke API Keys	Sidebar → **Settings** → API Keys
Live Call Monitoring	Sidebar → **Live Supervisor**
Call Analytics & Full Logs	Sidebar → **Analytics**
Campaign / Dialer Management	Sidebar → **Dialer**
Knowledge Base	Sidebar → **Knowledge Base**
Call Routing Rules	Sidebar → **Routing**
Webhooks	Sidebar → **Settings** → Webhooks
Reports & Exports	Sidebar → **Reports**
Billing & Usage	Sidebar → **Billing**
Agent Simulation	Sidebar → **Simulation**

Getting Your API Key

1. Open the Dashboard → http://62.171.170.48:5173 and log in.
2. Click **Settings** in the left sidebar.
3. Enter a **Key Name** (e.g., `Production App`).
4. Select the **Environment**: **Test** (`ck_test_`) or **Live** (`ck_live_`).
5. Click **Generate** and **copy the key immediately** — it is shown only once.

> ⚠️ *The full key is displayed **only once at creation time**.*

Authentication

External API (API Key)

All `/api/v1/*` endpoints require an API key in the `Authorization` header:

```
Authorization: Bearer <YOUR_API_KEY>
```

Environment	Prefix	Example
Test	`ck_test_`	`ck_test_a1b2c3d4_e5f6g7h8i9j0...`
Live	`ck_live_`	`ck_live_f8e7d6c5_b4a3z2y1x0w9...`

Internal Dashboard API (JWT)

All `/api/*` (non-v1) endpoints use a **JWT Bearer token** obtained from the login endpoint.

```
Authorization: Bearer <JWT_TOKEN>
```

Quick Start — Postman

1. Get an API Key from the Dashboard.
2. Open Postman → New Request → `GET`
3. URL: `http://62.171.170.48:4500/api/v1/calls`
4. Headers tab → Add:
   - **Key:** `Authorization`
   - **Value:** `Bearer ck_live_YOUR_KEY_HERE`
5. Click **Send** — you should see your call history.

External API — API Key Auth (`/api/v1`)

All endpoints below use `Authorization: Bearer <API_KEY>` and are at base URL `http://62.171.170.48:4500`.

Agents API

1. List All Agents

```
GET /api/v1/agents
```

Query Parameters:

Param	Type	Default	Description
`page`	integer	`1`	Page number
`limit`	integer	`10`	Items per page (max 100)
`status`	string	—	Filter: `draft`, `active`, `paused`

```
curl -X GET "http://62.171.170.48:4500/api/v1/agents?page=1&limit=10&status=active"
\
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "agents": [
    {
      "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
      "name": "Priya - Sales",
      "status": "active",
      "language": "hi-IN",
      "voice": "MF4J4IDTRo0AxOO4dpFR",
      "createdAt": "2026-03-12T10:00:00.000Z"
    }
  ],
```

```
  "pagination": { "page": 1, "limit": 10, "total": 12, "totalPages": 2 }
}
```

---

2. Create a New Agent

```
POST /api/v1/agents
```

Only `name` is required. All other fields have smart defaults.

Body (JSON):

Field	Type	Required	Default	Description
`name`	string	**Yes**	—	Agent display name
`description`	string	No	`""`	Internal description
`systemPrompt`	string	No	`""`	LLM instructions & personality
`openingLine`	string	No	`""`	First sentence AI speaks
`voice`	string	No	`"MF4J4IDTRo0AxOO4dpFR"`	Callex Voice ID
`language`	string	No	`"en-US"`	Language code
`temperature`	float	No	`0.7`	Creativity 0.0–1.0
`maxTokens`	integer	No	`250`	Max LLM tokens per reply
`maxDuration`	integer	No	`30`	Max call duration (minutes)
`bargeInMode`	string	No	`"balanced"`	`aggressive`, `balanced`, `polite`, `disabled`
`voicemailLogic`	string	No	`"hangup"`	`hangup`, `leave_message`, `human_escalate`
`webhookUrl`	string	No	`null`	Post-call webhook URL
`recordCall`	boolean	No	`true`	Record the call
`piiRedaction`	boolean	No	`true`	Auto-redact sensitive info
`autoSummary`	boolean	No	`true`	Generate AI call summary

> 📘 *See full [Agent Configuration Reference]() for all 50+ fields.*

```
curl -X POST http://62.171.170.48:4500/api/v1/agents \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Premium",
    "systemPrompt": "You are a professional sales agent. Be persuasive but polite.",
    "openingLine": "Hello! I am calling regarding an exclusive offer.",
    "voice": "MF4J4IDTRo0AxOO4dpFR",
```

```
    "temperature": 0.6,
    "maxDuration": 15
  }'
```

Response — `201 Created`

```
{
  "message": "Agent successfully created.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": {
    "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
    "name": "Sales Agent - Premium",
    "status": "draft",
    "createdAt": "2026-03-17T10:00:00.000Z"
  }
}
```

> 💡 *New agents start as `draft`. Activate with `PUT /api/v1/agents/{id}` → `"status": "active"`.*

---

3. Get Agent Details

```
GET /api/v1/agents/{agentId}
```

```
curl -X GET http://62.171.170.48:4500/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "name": "Sales Agent - Premium",
  "systemPrompt": "You are a professional sales agent.",
  "voice": "MF4J4IDTRo0AxOO4dpFR",
  "language": "hi-IN",
  "temperature": 0.6,
  "status": "active",
  "PromptVersion": [
    { "version": 2, "prompt": "Updated prompt...", "isActive": true },
    { "version": 1, "prompt": "Original prompt...", "isActive": false }
  ]
}
```

---

4. Update an Agent

Send only the fields you want to change.

```
PUT /api/v1/agents/{agentId}
```

```
curl -X PUT http://62.171.170.48:4500/api/v1/agents/5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1 \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Enterprise",
    "temperature": 0.5,
    "status": "active"
  }'
```

Response — `200 OK`

```
{
  "message": "Agent updated successfully.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": { "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1", "name": "Sales Agent - Enterprise", "status": "active" }
}
```

---

5. Delete an Agent

> ⚠️ ***Irreversible.*** *Permanently deletes the agent, all prompt versions, and follow-ups linked to it.*

```
DELETE /api/v1/agents/{agentId}
```

```
curl -X DELETE http://62.171.170.48:4500/api/v1/agents/5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{ "message": "Agent deleted successfully.", "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1" }
```

Calls & Transcripts API

6. List All Calls

Retrieve a paginated list of all calls made through your agents (active + completed).

```
GET /api/v1/calls
```

Query Parameters:

Param	Type	Default	Description
page	integer	1	Page number

`limit`	integer	`20`	Items per page (max 100)
`status`	string	—	Filter: `active`, `completed`, `failed`
`agentId`	string	—	Filter by specific agent

```
curl -X GET "http://62.171.170.48:4500/api/v1/calls?
page=1&limit=20&status=completed" \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "calls": [
    {
      "id": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
      "phoneNumber": "+919876543210",
      "agentId": "1a81e4bb-f51d-4f22-abc1-c7b9686e3019",
      "agentName": "Priya - Sales",
      "status": "completed",
      "duration": 145,
      "sentiment": "positive",
      "hasTranscript": true,
      "hasRecording": true,
      "recordingUrl": "https://storage.callex.ai/...",
      "startedAt": "2026-03-17T12:30:00.000Z",
      "endedAt": "2026-03-17T12:32:25.000Z"
    }
  ],
  "pagination": { "page": 1, "limit": 20, "total": 47, "totalPages": 3 }
}
```

---

7. Get Call Details

Full call details including the complete transcript, recording URL, and AI summary.

```
GET /api/v1/calls/{callId}
```

```
curl -X GET http://62.171.170.48:4500/api/v1/calls/d9e4ff50-eeba-465d-a68a-
fca353fafcf7 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "id": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
  "phoneNumber": "+919876543210",
  "agentId": "1a81e4bb-f51d-4f22-abc1-c7b9686e3019",
  "agentName": "Priya - Sales",
```

```
  "status": "completed",
  "duration": 145,
  "sentiment": "positive",
  "transcript": "AI: नमस्ते...\nCustomer: हाँ बोलिए...",
  "transcriptMessages": [
    { "role": "ai", "text": "नमस्ते, मैं Callex से बोल रही हूँ...", "timestamp": 1710340200
},
    { "role": "customer", "text": "हाँ बोलिए...", "timestamp": 1710340205 }
  ],
  "recordingUrl": "https://storage.callex.ai/recordings/...",
  "summary": "Customer agreed to recharge within 24 hours.",
  "outcome": null,
  "startedAt": "2026-03-17T12:30:00.000Z",
  "endedAt": "2026-03-17T12:32:25.000Z"
}
```

---

8. Get Call Transcript Only

```
GET /api/v1/calls/{callId}/transcript
```

```
curl -X GET http://62.171.170.48:4500/api/v1/calls/d9e4ff50-eeba-465d-a68a-
fca353fafcf7/transcript \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "callId": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
  "transcript": "AI: नमस्ते...\nCustomer: हाँ बोलिए...",
  "messages": [
    { "role": "ai", "text": "नमस्ते...", "timestamp": 1710340200 },
    { "role": "customer", "text": "हाँ बोलिए...", "timestamp": 1710340205 }
  ],
  "messageCount": 2
}
```

Voices API

9. List Available Voices

```
GET /api/v1/voices
```

```
curl -X GET http://62.171.170.48:4500/api/v1/voices \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "voices": [
    { "id": "MF4J4IDTRo0AxOO4dpFR", "name": "Devi", "description": "Clear Hindi
female voice", "language": "hi-IN", "gender": "female", "style": "professional",
"isDefault": true },
    { "id": "1qEiC6qsybMkmnNdVMbK", "name": "Monika", "description": "Modulated
professional female voice", "language": "hi-IN", "gender": "female", "style":
"professional", "isDefault": false },
    { "id": "qDuRKMlYmrm8trt5QyBn", "name": "Taksh", "description": "Powerful and
commanding male voice", "language": "hi-IN", "gender": "male", "style":
"authoritative", "isDefault": false },
    { "id": "LQ2auZHpAQ9h4azztqMT", "name": "Parveen", "description": "Confident
male voice — warm and persuasive", "language": "hi-IN", "gender": "male", "style":
"confident", "isDefault": false },
    { "id": "s6cZdgI3j07hf4frz4Q8", "name": "Arvi", "description": "Desi
conversational female voice", "language": "hi-IN", "gender": "female", "style":
"conversational", "isDefault": false }
  ],
  "total": 5
}
```

> 💡 *Use the `id` value as the `voice` field when creating or updating agents.*

Supervisor API (Live Calls)

10. Get All Active Calls

Returns all currently active (in-progress) calls for your account.

```
GET /api/v1/supervisor/calls
```

```
curl -X GET http://62.171.170.48:4500/api/v1/supervisor/calls \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
[
  {
    "id": "ac544763-dda7-474e-87e2-926789874ff1",
    "phoneNumber": "+919876543210",
    "agentId": "Z7z52IQOsdUgG5ivAiB5",
    "agentName": "Sales Agent - Premium",
    "status": "active",
    "sentiment": "neutral",
    "startedAt": "2026-03-17T12:00:00.000Z"
  }
]
```

> *Returns an **array** (not an object). Empty array `[]` means no active calls right now.*

---

11. Whisper to AI Agent

Send a hidden instruction to the AI mid-call. The caller does **not** hear this. The AI incorporates it naturally into its next responses.

```
POST /api/v1/supervisor/calls/{callId}/whisper
```

Body (JSON):

Field	Type	Required	Description
`message`	string	**Yes**	Instruction to send to the AI

```
curl -X POST http://62.171.170.48:4500/api/v1/supervisor/calls/ac544763/whisper \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{ "message": "Offer the customer a 10% discount to close the deal." }'
```

Response — `200 OK`

```
{ "success": true, "message": "Offer the customer a 10% discount to close the deal."
}
```

---

12. Barge Into a Call

Take over an active AI call. The AI stops immediately and call status changes to `transferred`.

```
POST /api/v1/supervisor/calls/{callId}/barge
```

```
curl -X POST http://62.171.170.48:4500/api/v1/supervisor/calls/ac544763/barge \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{ "success": true }
```

Dashboard KPIs

13. Get Platform KPIs

Real-time statistics including active calls, completed today, queue depth.

```
GET /api/v1/dashboard/kpis
```

```
curl -X GET http://62.171.170.48:4500/api/v1/dashboard/kpis \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "activeCalls": 2,
  "completedToday": 145,
  "avgMOS": 4.12,
  "slaPercent": 95,
  "apiFallbackRate": 0.5,
  "aiAgentsAvailable": 8,
  "humanAgentsAvailable": 2,
  "queueDepth": 0
}
```

Debug Utilities

14. Check My Identity (Debug)

Verify which `userId` your API key is linked to. Useful for debugging empty call/agent responses.

```
GET /api/v1/debug/my-identity
```

```
curl -X GET http://62.171.170.48:4500/api/v1/debug/my-identity \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "userId": "abc123xyz",
  "env": "live",
  "keyId": "key-doc-id",
  "ownedAgents": 3,
  "agentIds": ["agent1", "agent2", "agent3"],
  "callsWithUserId": 47,
  "message": "If ownedAgents is 0, your API key may be linked to the wrong user
account."
}
```

> 💡 *If `ownedAgents` is `0` and you have created agents, your API key may belong to a different user account in the system.*

Internal Dashboard API — JWT Auth (`/api`)

These endpoints are used by the Callex web dashboard. They require a **JWT token** from the login endpoint (stored in browser `localStorage`). For external integrations, prefer the `/api/v1/` endpoints above.

Base URL: `http://62.171.170.48:4500`

Auth

Login

```
POST /api/auth/login
```

Body (JSON):

```
{ "email": "your@email.com", "password": "yourpassword" }
```

Response — `200 OK`

```
{
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...",
  "user": { "id": "abc123", "email": "your@email.com", "name": "Daksh", "role":
"user" }
}
```

> *Use the `token` value as `Bearer <token>` in all subsequent dashboard API calls.*

Register

```
POST /api/auth/register
```

```
{ "email": "new@email.com", "password": "securepassword", "name": "Your Name" }
```

Agents (Internal)

Method	Endpoint	Description
`GET`	`/api/agents`	List your agents (newest first)
`GET`	`/api/agents/{id}`	Get agent + all prompt versions
`POST`	`/api/agents`	Create agent
`PATCH`	`/api/agents/{id}`	Update agent fields
`DELETE`	`/api/agents/{id}`	Delete agent
`PATCH`	`/api/agents/{id}/status`	Quick status toggle
`POST`	`/api/agents/{id}/prompt-version`	Save new prompt version
`GET`	`/api/agents/{id}/prompt-versions`	List all prompt versions
`POST`	`/api/agents/tts-preview`	Preview a voice (returns audio stream)
`POST`	`/api/agents/clone-voice`	Clone a custom voice (multipart audio upload)

Analytics & Call Logs

List Call Logs ✅ (Fixed March 17, 2026)

```
GET /api/analytics/calls
```

Returns all calls for the authenticated user — both calls directly linked by `userId` and calls linked through agent ownership. Sorted newest first.

Query Parameters:

Param	Type	Default	Description
`page`	integer	`1`	Page number
`limit`	integer	`50`	Items per page (max 200)
`status`	string	—	Filter: `active`, `completed`
`sentiment`	string	—	Filter: `positive`, `neutral`, `negative`, `angry`
`minDuration`	integer	—	Minimum call duration in seconds

```bash
# With JWT token
curl -X GET "http://62.171.170.48:4500/api/analytics/calls?page=1&limit=50" \
  -H "Authorization: Bearer YOUR_JWT_TOKEN"
```

Response — `200 OK`

```json
{
  "calls": [
    {
      "id": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
      "phoneNumber": "+919876543210",
      "agentId": "1a81e4bb-f51d-4f22-abc1-c7b9686e3019",
      "agentName": "Priya - Sales",
      "status": "completed",
      "duration": 145,
      "sentiment": "positive",
      "transcript": "AI: नमस्ते...",
      "startedAt": "2026-03-17T12:30:00.000Z",
      "endedAt": "2026-03-17T12:32:25.000Z"
    }
  ],
  "total": 47,
  "pagination": { "page": 1, "limit": 50, "totalPages": 1 }
}
```

Get Call Detail

```
GET /api/analytics/calls/{callId}
```

Returns full call record including transcript, recording URL, summary.

Trigger AI Summary (ACW)

```
POST /api/analytics/calls/{callId}/acw
```

Triggers Gemini AI to generate a summary of the call transcript.

```
{
  "summary": "Customer agreed to recharge. High intent.",
  "structuredData": "{\"intent\": \"subscription renewal\", \"agreed\": true,
\"followUpRequired\": false}",
  "redactedTranscript": "AI: Hello...\nCustomer: [REDACTED PHONE]..."
}
```

Analytics Stats (Global)

```
GET /api/analytics/stats
```

```
{
  "total": 523,
  "completed": 498,
  "sentiment": { "positive": 210, "neutral": 195, "negative": 58, "angry": 35 }
}
```

Settings — API Keys & Webhooks

API Keys

Method	Endpoint	Description
`GET`	`/api/settings/api-keys`	List all active API keys
`POST`	`/api/settings/api-keys`	Create a new API key
`DELETE`	`/api/settings/api-keys/{id}`	Revoke an API key

Create API Key — Body:

```
{ "name": "Production App", "env": "live" }
```

Response includes `fullKey` — save it, it is shown only once:

```
{
  "id": "key-doc-id",
  "name": "Production App",
```

```
  "prefix": "ck_live_a1b2c3d4",
  "env": "live",
  "fullKey": "ck_live_a1b2c3d4_e5f6g7h8i9j0k1l2m3n4o5p6q7r8s9"
}
```

Webhooks

Method	Endpoint	Description
GET	/api/settings/webhooks	List webhooks
POST	/api/settings/webhooks	Create webhook
PATCH	/api/settings/webhooks/{id}	Update webhook
DELETE	/api/settings/webhooks/{id}	Delete webhook
POST	/api/settings/webhooks/{id}/test	Send a test event

Create Webhook — Body:

```
{
  "url": "https://yourdomain.com/webhook",
  "events": ["call.completed", "call.started"],
  "secret": "your-webhook-secret"
}
```

Dialer & Campaigns

Method	Endpoint	Description
GET	/api/dialer/campaigns	List campaigns
POST	/api/dialer/campaigns	Create campaign
PATCH	/api/dialer/campaigns/{id}	Update campaign
PATCH	/api/dialer/campaigns/{id}/status	Start/pause campaign
DELETE	/api/dialer/campaigns/{id}	Delete campaign

Create Campaign — Body:

```
{
  "name": "March Recharge Drive",
  "agentId": "5fa23d1b-...",
  "contacts": ["+919876543210", "+919812345678"],
  "scheduledAt": "2026-03-18T09:00:00Z",
  "maxConcurrent": 5
}
```

Follow-Ups

Method	Endpoint	Description
`GET`	`/api/followups`	List due follow-ups
`POST`	`/api/followups`	Create follow-up
`PATCH`	`/api/followups/{id}/status`	Mark done/pending

Knowledge Base

Method	Endpoint	Description
`GET`	`/api/knowledge`	List knowledge documents
`POST`	`/api/knowledge`	Upload document (multipart/form-data)
`DELETE`	`/api/knowledge/{id}`	Delete document
`POST`	`/api/knowledge/{id}/resync`	Re-process document for embeddings

Routing Rules

Method	Endpoint	Description
`GET`	`/api/routing/rules`	List routing rules
`POST`	`/api/routing/rules`	Create rule
`PATCH`	`/api/routing/rules/{id}`	Update rule
`DELETE`	`/api/routing/rules/{id}`	Delete rule

WebSocket — AI Voice Engine

The Python AI engine is accessible at **port 8085** via WebSocket.

Agent-Specific WebSocket

```
ws://62.171.170.48:8085/agent/{agentId}
```

FreeSWITCH connects to this URL and the AI loads the specific agent config from Firestore.

Default WebSocket

```
ws://62.171.170.48:8085/
```

Uses the first `active` agent as fallback.

List All Agents with WebSocket URLs

```
GET http://62.171.170.48:8085/agents
```

```
{
  "agents": [
    {
      "id": "Z7z52IQOsdUgG5ivAiB5",
      "name": "Recharge Assistant",
      "status": "active",
      "websocket_url": "ws://62.171.170.48:8085/agent/Z7z52IQOsdUgG5ivAiB5"
    }
  ],
  "total": 1
}
```

Headers Passed by FreeSWITCH

The AI engine reads these headers to identify each call:

Header	Description
`x-call-id`	Unique call UUID
`x-agent-id`	Agent to load
`x-phone-number`	Caller's phone number
`Caller-Caller-ID-Number`	FreeSWITCH caller ID
`variable_sip_from_user`	SIP from user

URL Routing Patterns

Pattern	Behavior
`ws://server:8085/agent/{id}`	Load specific agent
`ws://server:8085/?agent_id={id}`	Query param alternative
`ws://server:8085/`	Default/fallback agent

FreeSWITCH Integration Example

```
execute_on_answer='socket 127.0.0.1:8085/agent/Z7z52IQOsdUgG5ivAiB5 async full'
```

Live Transcript WebSocket (Supervisor)

```
ws://62.171.170.48:4500/?type=supervisor&callId={callId}
```

Stream real-time transcript as a call progresses.

Messages from server:

```
{ "type": "transcript_line", "line": "Bot: Hello! How can I help?" }
{ "type": "sentiment_update", "sentiment": "positive" }
{ "type": "call_ended", "callId": "abc123" }
```

Available Voices Reference

Voice ID	Name	Gender	Style	Default
`MF4J4IDTRo0AxOO4dpFR`	**Devi**	Female	Professional, Clear Hindi	✅ Yes
`1qEiC6qsybMkmnNdVMbK`	**Monika**	Female	Modulated, Professional	No
`qDuRKMlYmrm8trt5QyBn`	**Taksh**	Male	Powerful, Commanding	No
`LQ2auZHpAQ9h4azztqMT`	**Parveen**	Male	Confident, Warm	No
`s6cZdgI3j07hf4frz4Q8`	**Arvi**	Female	Conversational, Friendly	No

Agent Configuration Reference

All fields are optional on `PUT` / `PATCH`. Only `name` is required on `POST`.

Core Fields

Field	Type	Default	Description
`name`	string	—	Agent name
`description`	string	`""`	Internal description
`systemPrompt`	string	`""`	LLM personality & instructions
`openingLine`	string	`""`	First words spoken on call
`voice`	string	`"MF4J4IDTRo0AxOO4dpFR"`	Callex Voice ID
`language`	string	`"en-US"`	Language code (`hi-IN`, `en-US`)
`status`	string	`"draft"`	`draft`, `active`, `paused`

LLM Settings

Field	Type	Default	Description
`temperature`	float	`0.7`	Creativity 0.0–1.0

`maxTokens`	integer	`250`	Max tokens per response
`sttEngine`	string	`"callex-1.1"`	Speech-to-text engine
`llmModel`	string	`"callex-1.3"`	LLM model identifier
`strictToolCalling`	boolean	`true`	Enforce tool calling schema
`topK`	integer	`5`	Knowledge base top-K results
`similarityThresh`	float	`0.75`	Knowledge base similarity threshold

Voice & TTS

Field	Type	Default	Description
`prosodyRate`	float	`1.0`	Speech speed (0.5–2.0)
`prosodyPitch`	float	`1.0`	Voice pitch
`fillerPhrases`	array	`["Let me check..."]`	Mid-sentence filler phrases
`speakingStyle`	string	`"professional"`	`professional`, `friendly`, `urgent`, `empathetic`
`backgroundAmbience`	string	`"none"`	`none`, `office`, `call_center`

Call Behavior

Field	Type	Default	Description
`bargeInMode`	string	`"balanced"`	`aggressive`, `balanced`, `polite`, `disabled`
`patienceMs`	integer	`800`	End-of-turn silence timeout (ms)
`maxDuration`	integer	`30`	Max call duration (minutes)
`ringTimeout`	integer	`30`	Ring timeout before hangup (seconds)
`voicemailLogic`	string	`"hangup"`	`hangup`, `leave_message`, `human_escalate`
`voicemailDropAudio`	string	`null`	Audio URL to play when voicemail detected
`fallbackMessage`	string	`"I'm sorry..."`	Response when AI is unsure
`processDtmf`	boolean	`true`	Process DTMF keypress tones
`amdPrecision`	string	`"balanced"`	Answering Machine Detection: `fast`, `balanced`, `precise`

Compliance & Safety

Field	Type	Default	Description
`profanityFilter`	string	`"redact"`	`redact`, `allow`, `hangup`

`topicRestriction`	boolean	`false`	Restrict to agent's topic only
`piiRedaction`	boolean	`true`	Auto-redact credit cards, phone numbers
`dncLitigatorScrub`	boolean	`true`	Skip known litigators
`complianceScript`	string	`null`	Mandatory compliance intro text

Integrations

Field	Type	Default	Description
`webhookUrl`	string	`null`	URL to POST call result after hanging up
`postCallSms`	string	`null`	SMS template to send post-call
`tools`	array	`[]`	Tool definitions for function calling
`ipaLexicon`	object	`{}`	Custom pronunciation dictionary

Intelligence

Field	Type	Default	Description
`sentimentRouting`	boolean	`false`	Transfer to human if caller is angry
`emotionalMirroring`	boolean	`true`	Match caller energy/tone
`dynamicCodeSwitching`	boolean	`true`	Auto switch languages mid-call
`multiAgentHandoff`	boolean	`false`	Hand off to another agent
`objectionHandling`	string	`"standard"`	`standard` or `persistent`
`competitorAlerts`	string	`""`	Comma-separated competitor names to flag
`supervisorWhisper`	boolean	`true`	Allow supervisor whisper mid-call

Post-Call Automation

Field	Type	Default	Description
`autoSummary`	boolean	`true`	Generate AI summary after call
`autoSentiment`	boolean	`true`	Analyze sentiment automatically
`recordCall`	boolean	`true`	Record and store the call audio
`autoFollowUp`	boolean	`true`	Schedule follow-up automatically
`followUpDefaultDays`	integer	`1`	Days after call to follow up
`followUpDefaultTime`	string	`"10:00"`	Time of day for follow-up

Billing

Field	Type	Default	Description
`costCapTokens`	integer	`5000`	Max tokens before billing cutoff
`callBlending`	boolean	`false`	Blend inbound + outbound calls
`geoCallerId`	boolean	`false`	Use local caller ID based on geography

Error Reference

Status	Code	Meaning
`200`	OK	Success
`201`	Created	Resource created
`204`	No Content	Deleted successfully
`400`	Bad Request	Missing required field — `{ "error": "Agent 'name' is required." }`
`401`	Unauthorized	Missing or malformed Authorization header
`403`	Forbidden	Invalid or revoked API key / expired JWT
`404`	Not Found	Resource doesn't exist or doesn't belong to you
`409`	Conflict	Duplicate resource (e.g., email already registered)
`500`	Server Error	Internal error — check server logs

Best Practices

1. **Store API keys securely** — never expose in frontend code or public repos.
2. **Use Test keys** (`ck_test_`) for development, **Live keys** (`ck_live_`) for production.
3. **Paginate** all list calls — always use `page` and `limit` params.
4. **Partial updates** — on PUT/PATCH, send only changed fields.
5. **Revoke compromised keys** immediately from Dashboard → Settings.
6. **Use `/api/v1/debug/my-identity`** to troubleshoot empty call/agent responses.
7. **Call `GET /api/v1/voices`** to get the latest voice IDs before creating agents.
8. **JWT tokens expire** — re-login or refresh on 403 response from dashboard APIs.

Quick Reference Table

Action	Method	Endpoint
EXTERNAL API		
List agents	`GET`	`/api/v1/agents?page=1&limit=10`
Create agent	`POST`	`/api/v1/agents`

Get agent	`GET`	`/api/v1/agents/{id}`
Edit agent	`PUT`	`/api/v1/agents/{id}`
Delete agent	`DELETE`	`/api/v1/agents/{id}`
List all calls (history)	`GET`	`/api/v1/calls?page=1&limit=20`
Get call details	`GET`	`/api/v1/calls/{id}`
Get transcript	`GET`	`/api/v1/calls/{id}/transcript`
List voices	`GET`	`/api/v1/voices`
Active calls (live)	`GET`	`/api/v1/supervisor/calls`
Whisper to AI	`POST`	`/api/v1/supervisor/calls/{id}/whisper`
Barge into call	`POST`	`/api/v1/supervisor/calls/{id}/barge`
Dashboard KPIs	`GET`	`/api/v1/dashboard/kpis`
Debug my identity	`GET`	`/api/v1/debug/my-identity`
DASHBOARD API		
Login	`POST`	`/api/auth/login`
Call logs (full history)	`GET`	`/api/analytics/calls`
Call detail	`GET`	`/api/analytics/calls/{id}`
AI call summary	`POST`	`/api/analytics/calls/{id}/acw`
List API keys	`GET`	`/api/settings/api-keys`
Create API key	`POST`	`/api/settings/api-keys`
Revoke API key	`DELETE`	`/api/settings/api-keys/{id}`
List webhooks	`GET`	`/api/settings/webhooks`
Create webhook	`POST`	`/api/settings/webhooks`
List campaigns	`GET`	`/api/dialer/campaigns`

> 📌 ***Remember:*** *Everything available via API is also accessible in the* ***Admin Dashboard*** *with a visual interface.*