Callex AI — Developer API Documentation

> ***Version:*** *2.0* | ***API Base URL:*** `http://62.171.170.48:4000` | ***Last Updated:*** *March 16, 2026*

⚠️ **IMPORTANT NOTE ON URLS:**

- Your Dashboard (GUI) is hosted at **Port 5173** (`http://62.171.170.48:5173`). This is for human users.
- ALL API requests from external apps, webhooks, or Postman MUST go to **Port 4000** (`http://62.171.170.48:4000`).

Table of Contents

1. Admin Panel
2. Getting Your API Key
3. Testing with Postman (Quick Start)
4. Authentication
5. API Endpoints
   - **Agents**
     - List Agents
     - Create Agent
     - Get Agent Details
     - Edit Agent
     - Delete Agent
   - **Calls & Transcripts**
     - List Calls
     - Get Call Details
     - Get Call Transcript
   - **Voices**
     - List Available Voices
6. Available Voices Reference
7. Agent Configuration Reference
8. Error Reference
9. Best Practices

Admin Panel

Everything you can do via the API can also be done through the **Callex Admin Panel**.

🔗 **Admin Panel URL:** http://62.171.170.48:5173

Feature	Where to Find
Create, Edit & Delete Agents	Sidebar → **Agent Studio**
Generate & Revoke API Keys	Sidebar → **Settings** → API Keys
Live Call Monitoring	Sidebar → **Live Supervisor**
Call Analytics & Logs	Sidebar → **Analytics**

Campaign Management (Dialer)	Sidebar → **Dialer**
Knowledge Base Management	Sidebar → **Knowledge Base**
Call Routing Rules	Sidebar → **Routing**
CRM & Tool Integrations	Sidebar → **Integrations**
Quality Assurance	Sidebar → **QA**
Reports & Exports	Sidebar → **Reports**
Billing & Usage	Sidebar → **Billing**
Agent Simulation & Testing	Sidebar → **Simulation**

Getting Your API Key

1. Open the **Admin Panel** → http://62.171.170.48:5173 and **log in**.
2. Click **Settings** in the left sidebar.
3. Enter a **Key Name** (e.g., "Production App").
4. Select the **Environment**: **Test** (`ck_test_`) or **Live** (`ck_live_`).
5. Click **Generate** and **copy the API Key immediately** (it will only be shown once).

> ⚠️ *The full API key is shown **only once**. Copy it immediately.*

Testing with Postman (Quick Start)

The easiest way to verify your API connection before writing code is to use Postman.

1. **Get an API Key** from the Dashboard as described above.
2. Open **Postman** (or Hoppscotch).
3. Create a **New Request** and change the method to **POST**.
4. Set the **URL** to: `http://62.171.170.48:4000/api/v1/agents`
5. Go to the **Headers** tab and add:
   - **Key:** `Authorization`
   - **Value:** `Bearer ck_live_YOUR_KEY_HERE`
6. Go to the **Body** tab, select **raw** -> **JSON**, and paste:

```
{
  "name": "Postman Test Agent",
  "systemPrompt": "You are a test assistant.",
  "openingLine": "Hello, how can I help?",
  "voice": "MF4J4IDTRo0AxOO4dpFR"
}
```

7. Click **Send**! You should receive a `200 OK` response with your new Agent ID, and it will instantly appear in your live Admin Dashboard.

Authentication

All API requests require your API key in the `Authorization` header:

```
Authorization: Bearer <YOUR_API_KEY>
```

Environment	Prefix	Example
Test	`ck_test_`	`ck_test_a1b2c3d4_e5f6g7h8i9j0k1l2m3n4o5p6`
Live	`ck_live_`	`ck_live_f8e7d6c5_b4a3z2y1x0w9v8u7t6s5r4q3`

Authentication

All API requests require your API key in the `Authorization` header:

```
Authorization: Bearer <YOUR_API_KEY>
```

API Endpoints

---

1. List All Agents

```
GET /api/v1/agents
```

Parameter	Type	Default	Description
`page`	integer	`1`	Page number
`limit`	integer	`10`	Items per page (max 100)
`status`	string	—	Filter: `draft`, `active`, `paused`

```
curl -X GET "http://62.171.170.48:4000/api/v1/agents?page=1&limit=5&status=active" \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "agents": [
    {
      "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
      "name": "Priya - Sales",
      "status": "active",
      "language": "hi-IN",
      "createdAt": "2026-03-12T10:00:00.000Z"
    }
  ],
  "pagination": { "page": 1, "limit": 5, "total": 12, "totalPages": 3 }
}
```

---

2. Create a New Agent

```
POST /api/v1/agents
```

Only `name` is required. Everything else has smart defaults.

Parameter	Type	Required	Default	Description
`name`	string	**Yes**	—	Agent name
`description`	string	No	`""`	Agent description
`systemPrompt`	string	No	`""`	LLM instructions & personality
`openingLine`	string	No	`""`	First thing AI says on call
`voice`	string	No	`"MF4J4IDTRo0AxOO4dpFR"`	Callex Voice ID (see Voices)
`language`	string	No	`"en-US"`	Language code
`temperature`	float	No	`0.7`	Creativity (0.0 – 1.0)
`maxDuration`	integer	No	`30`	Max call minutes
`bargeInMode`	string	No	`"balanced"`	`aggressive`, `balanced`, `polite`
`voicemailLogic`	string	No	`"hangup"`	`hangup`, `leave_message`, `human_escalate`

> 📘 *See the full Agent Configuration Reference for all 50+ fields.*

```
curl -X POST http://62.171.170.48:4000/api/v1/agents \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Premium",
    "systemPrompt": "You are a professional sales agent. Be persuasive but polite.",
    "openingLine": "Hello! I am calling from Acme Corp regarding an exclusive
offer.",
    "voice": "MF4J4IDTRo0AxOO4dpFR",
    "temperature": 0.6,
    "maxDuration": 15
  }'
```

Response — `201 Created`

```
{
  "message": "Agent successfully created.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": {
    "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
    "name": "Sales Agent - Premium",
    "status": "draft",
```

```
    "createdAt": "2026-03-12T10:00:00.000Z"
  }
}
```

> 💡 *New agents start as `draft`. Activate via the Admin Panel or the Edit API.*

---

3. Get Agent Details

```
GET /api/v1/agents/{agentId}
```

```
curl -X GET http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "name": "Sales Agent - Premium",
  "systemPrompt": "You are a professional sales agent.",
  "voice": "MF4J4IDTRo0AxOO4dpFR",
  "language": "hi-IN",
  "temperature": 0.6,
  "PromptVersion": [
    { "version": 1, "prompt": "You are a professional sales agent.", "isActive":
true }
  ]
}
```

---

4. Edit an Agent

Update any fields of an existing agent. Send **only the fields you want to change**.

```
PUT /api/v1/agents/{agentId}
```

```
curl -X PUT http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Content-Type: application/json" \
  -H "Authorization: Bearer ck_live_YOUR_KEY" \
  -d '{
    "name": "Sales Agent - Enterprise",
    "temperature": 0.5,
    "status": "active"
  }'
```

Response — `200 OK`

```
{
  "message": "Agent updated successfully.",
  "agentId": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1",
  "agent": { "id": "5fa23d1b-722a-4318-aecc-6e6ad9d1a8e1", "name": "Sales Agent -
Enterprise", "status": "active" }
}
```

---

5. Delete an Agent

> ⚠️ ***This action is irreversible.*** *Deletes the agent, all prompt versions, and follow-ups.*

```
DELETE /api/v1/agents/{agentId}
```

```
curl -X DELETE http://62.171.170.48:4000/api/v1/agents/5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{ "message": "Agent deleted successfully.", "agentId": "5fa23d1b-722a-4318-aecc-
6e6ad9d1a8e1" }
```

---

6. List All Calls

Retrieve a paginated list of all calls made through your agents.

```
GET /api/v1/calls
```

Parameter	Type	Default	Description
`page`	integer	`1`	Page number
`limit`	integer	`20`	Items per page (max 100)
`status`	string	—	Filter: `active`, `completed`, `failed`
`agentId`	string	—	Filter by specific agent ID

```
curl -X GET "http://62.171.170.48:4000/api/v1/calls?
page=1&limit=10&status=completed" \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "calls": [
    {
      "id": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
```

```
      "phoneNumber": "+919876543210",
      "agentId": "1a81e4bb-f51d-4f22-abc1-c7b9686e3019",
      "agentName": "Priya - Sales",
      "status": "completed",
      "duration": 145,
      "sentiment": "positive",
      "hasTranscript": true,
      "hasRecording": true,
      "recordingUrl": "https://storage.callex.ai/...",
      "startedAt": "2026-03-13T12:30:00.000Z",
      "endedAt": "2026-03-13T12:32:25.000Z"
    }
  ],
  "pagination": { "page": 1, "limit": 10, "total": 47, "totalPages": 5 }
}
```

---

7. Get Call Details

Retrieve full call details including the complete transcript and recording URL.

```
GET /api/v1/calls/{callId}
```

```
curl -X GET http://62.171.170.48:4000/api/v1/calls/d9e4ff50-eeba-465d-a68a-
fca353fafcf7 \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "id": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
  "phoneNumber": "+919876543210",
  "agentId": "1a81e4bb-f51d-4f22-abc1-c7b9686e3019",
  "agentName": "Priya - Sales",
  "status": "completed",
  "duration": 145,
  "sentiment": "positive",
  "transcript": "AI: नमस्ते, मैं Callex से बोल रही हूँ...\nCustomer: हाँ बोलिए...\nAI: आपका
कनेक्शन बंद होने वाला है...",
  "transcriptMessages": [
    { "role": "ai", "text": "नमस्ते, मैं Callex से बोल रही हूँ...", "timestamp": 1710340200
},
    { "role": "customer", "text": "हाँ बोलिए...", "timestamp": 1710340205 },
    { "role": "ai", "text": "आपका कनेक्शन बंद होने वाला है...", "timestamp": 1710340210 }
  ],
  "recordingUrl": "https://storage.callex.ai/...",
  "summary": "Customer agreed to recharge within 24 hours.",
  "outcome": { "result": "agreed", "followUpRequired": false },
  "startedAt": "2026-03-13T12:30:00.000Z",
```

```
  "endedAt": "2026-03-13T12:32:25.000Z"
}
```

---

8. Get Call Transcript

Retrieve just the transcript for a specific call.

```
GET /api/v1/calls/{callId}/transcript
```

```
curl -X GET http://62.171.170.48:4000/api/v1/calls/d9e4ff50-eeba-465d-a68a-fca353fafcf7/transcript \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "callId": "d9e4ff50-eeba-465d-a68a-fca353fafcf7",
  "transcript": "AI: नमस्ते, मैं Callex से बोल रही हूँ...\nCustomer: हाँ बोलिए...",
  "messages": [
    { "role": "ai", "text": "नमस्ते, मैं Callex से बोल रही हूँ...", "timestamp": 1710340200
},
    { "role": "customer", "text": "हाँ बोलिए...", "timestamp": 1710340205 }
  ],
  "messageCount": 2
}
```

---

9. List Available Voices

Get all available Callex voices that can be assigned to agents.

```
GET /api/v1/voices
```

```
curl -X GET http://62.171.170.48:4000/api/v1/voices \
  -H "Authorization: Bearer ck_live_YOUR_KEY"
```

Response — `200 OK`

```
{
  "voices": [
    {
      "id": "MF4J4IDTRo0AxOO4dpFR",
      "name": "Devi",
      "description": "Clear Hindi female voice — crisp and natural",
      "language": "hi-IN",
      "gender": "female",
      "style": "professional",
      "isDefault": true
    },
```

```
    {
      "id": "1qEiC6qsybMkmnNdVMbK",
      "name": "Monika",
      "description": "Modulated professional female voice",
      "language": "hi-IN",
      "gender": "female",
      "style": "professional",
      "isDefault": false
    },
    {
      "id": "qDuRKMlYmrm8trt5QyBn",
      "name": "Taksh",
      "description": "Powerful and commanding male voice",
      "language": "hi-IN",
      "gender": "male",
      "style": "authoritative",
      "isDefault": false
    },
    {
      "id": "LQ2auZHpAQ9h4azztqMT",
      "name": "Parveen",
      "description": "Confident male voice — warm and persuasive",
      "language": "hi-IN",
      "gender": "male",
      "style": "confident",
      "isDefault": false
    },
    {
      "id": "s6cZdgI3j07hf4frz4Q8",
      "name": "Arvi",
      "description": "Desi conversational female voice — friendly and casual",
      "language": "hi-IN",
      "gender": "female",
      "style": "conversational",
      "isDefault": false
    }
  ],
  "total": 5
}
```


> 💡 *Use the `id` from this response as the `voice` field when creating or editing agents.*

Available Voices Reference

Voice ID	Name	Gender	Style	Default
`MF4J4IDTRo0AxOO4dpFR`	**Devi**	Female	Professional, Clear Hindi	✅ Yes
`1qEiC6qsybMkmnNdVMbK`	**Monika**	Female	Modulated, Professional	No
`qDuRKMlYmrm8trt5QyBn`	**Taksh**	Male	Powerful, Commanding	No

`LQ2auZHpAQ9h4azztqMT`	**Parveen**	Male	Confident, Warm	No
`s6cZdgI3j07hf4frz4Q8`	**Arvi**	Female	Conversational, Friendly	No

Agent Configuration Reference

Complete list of configurable fields (all optional except `name` on create).

Core

Field	Type	Default	Description
`name`	string	—	Agent name
`description`	string	`""`	Description
`systemPrompt`	string	`""`	LLM instructions
`openingLine`	string	`""`	First sentence on call
`voice`	string	`"MF4J4IDTRo0AxOO4dpFR"`	Callex Voice ID (see Voices)
`language`	string	`"en-US"`	Language code
`status`	string	`"draft"`	`draft`, `active`, `paused`

LLM

Field	Type	Default	Description
`temperature`	float	`0.7`	Creativity (0.0–1.0)
`maxTokens`	integer	`250`	Max tokens per response
`sttEngine`	string	`"callex-1.1"`	Speech-to-text engine
`llmModel`	string	`"callex-1.3"`	LLM model

Voice & Speech

Field	Type	Default	Description
`prosodyRate`	float	`1.0`	Speech speed
`prosodyPitch`	float	`1.0`	Pitch
`fillerPhrases`	array	`["Let me check..."]`	Filler phrases
`speakingStyle`	string	`"professional"`	`professional`, `friendly`, `urgent`, `empathetic`
`backgroundAmbience`	string	`"none"`	`none`, `office`, `call_center`

Call Behavior

Field	Type	Default	Description
`bargeInMode`	string	`"balanced"`	`aggressive`, `balanced`, `polite`, `disabled`
`patienceMs`	integer	`800`	End-of-turn timeout (ms)
`maxDuration`	integer	`30`	Max call minutes
`ringTimeout`	integer	`30`	Ring timeout (seconds)
`voicemailLogic`	string	`"hangup"`	`hangup`, `leave_message`, `human_escalate`
`fallbackMessage`	string	`"I'm sorry..."`	Fallback response

Advanced

Field	Type	Default	Description
`sentimentRouting`	boolean	`false`	Transfer on angry caller
`piiRedaction`	boolean	`true`	Redact credit cards, SSN
`emotionalMirroring`	boolean	`true`	Match caller's energy
`dynamicCodeSwitching`	boolean	`true`	Switch languages mid-call
`objectionHandling`	string	`"standard"`	`standard` or `persistent`
`autoSummary`	boolean	`true`	Auto call summary
`autoSentiment`	boolean	`true`	Auto sentiment analysis
`recordCall`	boolean	`true`	Record calls
`webhookUrl`	string	`null`	Post-call webhook URL
`autoFollowUp`	boolean	`true`	Auto schedule follow-ups

Error Reference

Status	Meaning	Example
`200`	Success	`{ "message": "Agent updated successfully." }`
`201`	Created	`{ "message": "Agent successfully created." }`
`400`	Bad Request	`{ "error": "Agent 'name' is required." }`
`401`	Unauthorized	`{ "error": "Missing or invalid Authorization header." }`
`403`	Forbidden	`{ "error": "Invalid or revoked API Key." }`
`404`	Not Found	`{ "error": "Agent not found" }`
`500`	Server Error	`{ "error": "Internal server error" }`

Best Practices

1. **Store your API key securely** — never expose in client-side code or public repos.
2. **Use Test keys** (`ck_test_`) for development, **Live keys** (`ck_live_`) for production.
3. **Paginate** when listing agents or calls — use `page` and `limit` params.
4. **Send only changed fields** when editing — PUT accepts partial updates.
5. **Revoke compromised keys** immediately from **Admin Panel → Settings**.
6. **Use the Voices API** to fetch available voice IDs before creating agents.

Quick Reference

Action	Method	Endpoint
List agents	`GET`	`/api/v1/agents?page=1&limit=10`
Create agent	`POST`	`/api/v1/agents`
Get agent	`GET`	`/api/v1/agents/{id}`
Edit agent	`PUT`	`/api/v1/agents/{id}`
Delete agent	`DELETE`	`/api/v1/agents/{id}`
List calls	`GET`	`/api/v1/calls?page=1&limit=20`
Get call details	`GET`	`/api/v1/calls/{id}`
Get transcript	`GET`	`/api/v1/calls/{id}/transcript`
List voices	`GET`	`/api/v1/voices`

> 📌 ***Remember:*** *Everything available via API is also available in the* ***Admin Panel*** *with a full visual interface.*

For support, contact the Callex engineering team.