MMDBHDSNet

mmdbhdsnet_research_paper.docx

Shri Vile Parle Kelavani Mandal

Document Details

Submission ID

trn:oid:::9832:135288178

Submission Date

Apr 15, 2026, 2:25 PM GMT+5:30

Download Date

Apr 15, 2026, 2:28 PM GMT+5:30

File Name

mmdbhdsnet_research_paper.docx

File Size

2.3 MB

14 Pages

4,917 Words

29,539 Characters

0% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups

0 AI-generated only 0%
Likely AI-generated text from a large-language model.

0 AI-generated text that was AI-paraphrased 0%
Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer
Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (i.e., our AI models may produce either false positive results or false negative results), so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?
The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI paraphrase tool or word spinner.

False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?
Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.

MMDBHDSNet: A MultiModal Dual-Branch Hazard-Discriminative Framework for Real-Time Medical Waste Segmentation and Risk-Aware Analysis

Daksh Soni[1], Priyanshu Nayak[2], Samarth Sharma[3],

Dr. Shruti Sharma[4], Dr. Jayesh Gangrade[5]

[1,2,3] SVKM's NMIMS Indore

Abstract

Medical waste management has been a thorny issue in hospital facilities, with improper segregation still presenting concrete risks to the sanitation sector and the local communities. Automated vision systems provide stable, 24 hour detection but all available solutions have three basic shortcomings: lack of class coverage, lack of hazard level reasoning and lack of a method to measure the uncertainty of predictions. This paper introduces MMDBHDSNet, a MultiModal Dual-Branch Hazard-Discriminative Segmentation Network that performs real-time pixel-level detection and risk-stratified classification of medical waste across 38 clinically defined categories. Two parallel decoder branches share a common BiFPN encoder — one optimised for instance segmentation quality, the other encoding hazard semantics — and exchange information through a Cross-Branch Fusion Gate that prevents gradient interference. A spatial contamination risk module aggregates co-occurrence relationships among detections into a scene-level score, and a Monte Carlo Dropout block estimates epistemic uncertainty per detection. To support training and evaluation, seven independently annotated source datasets were merged through a six-stage engineering pipeline that resolved cross-corpus class-naming conflicts, removed 8,260 duplicate images via MD5 hashing and polygon-structure comparison, remapped all label IDs to a unified 38-class ontology, and rebalanced the train–validation–test partition to 70/20/10. The resulting benchmark contains 14,445 annotated images — the most thoroughly documented medical waste segmentation collection of its kind. On the held-out test partition, MMDBHDSNet achieves mAP@0.5 of 0.9474 and mAP@0.5:0.95 of 0.7613, with precision 0.951 and recall 0.9168. The deployment interface sustains up to 55 frames per second with live webcam inference, an EMA-smoothed risk trajectory graph, spatial heatmap overlays, and a three-tier escalation alert system suitable for supervised clinical integration.

Keywords: Medical waste detection, Dual-branch deep learning, Hazard-aware classification, Uncertainty estimation, Real-time instance segmentation, Contamination risk scoring, Healthcare AI, Monte Carlo Dropout

1. Introduction

Healthcare systems worldwide generate considerable hazardous waste daily. The World Health Organization estimates that clinical activities produce approximately 5.5 kg of hazardous material per hospital bed per day, including sharps, infectious biologicals, pharmaceutical residues, and radioactive substances [1]. Lack of proper sorting of waste at the time of disposal, which is still mostly done manually, leads to contaminated material entering municipal waste streams, higher needle injuries among collection workers, and chemical leachate harming the local eco systems [2, 3]. Human sorters are fallible: the result of repeated classification under time; poor training; packaging that appears the same of hazard levels all combine to produce fallible results, which no supervision system can remove completely.

Computer vision does not have those problems. It does not tire, processes a frame in milliseconds, and once deployed its behaviour is consistent. Yet the field has been slow to deliver a robust clinical-grade system for medical waste specifically, held back by three gaps: (i) existing datasets cover only five to fifteen waste classes, far below the true diversity of clinical streams; (ii) architectures treat medical waste as a generic detection task with no awareness that a needle misclassified as LOW-hazard has different consequences from a misidentified mask; and (iii) no published system includes uncertainty quantification — indispensable when a wrong call routes a sharp instrument to household waste. CNN-based classifiers reach above 90% accuracy on benchmarks like TrashNet, yet performance degrades sharply on out-of-distribution footage [4]. Instance segmentation work on Mask R-CNN improved localisation but medical waste evaluations remain on small private datasets [5, 6]. No prior work combines risk scoring, uncertainty quantification, and multi-source dataset harmonisation.

All three gaps are covered in this paper in five concrete contributions:

(1) **MMDBHDSNet —** a dual-branch encoder-decoder with a Cross-Branch Fusion Gate and hazard-weighted multi-task loss.
(2) **A 38-class benchmark —** 14,445 images from seven source datasets, processed through a six-stage deduplication and rebalancing pipeline.
(3) **A contamination risk scoring model —** computing a dynamic scene-level index from spatial co-occurrence, hazard weights, and detection confidence.
(4) **A Monte Carlo Dropout uncertainty estimator —** flagging ambiguous detections for human review before disposal decisions are made.
(5) **A real-time deployment interface —** live webcam inference at up to 55 fps, smoothed risk trajectory, spatial heatmaps, and three-tier alerts.

2. Related Work

Deep-learning based waste detection. TrashNet defined the possibility of CNN-based classification of garbage in six material types [7]. Later studies using ResNet-50, EfficientNet-B4, DenseNet-121 and MobileNetV2 all consistently achieve 90 percent on controlled benchmarks. This was further generalised to object-level localisation in natural scenes by region-proposal and feature-pyramid networks on the TACO dataset [4, 8]. Medical waste in particular is a sparse literature - the bulk of published material considers it a sub-topic of general hazardous waste or assesses on small internally curated datasets. Lack of standardised multi-class benchmark has been pointed out as the major bottleneck more than once [9, 10].

Instance segmentation architectures. Mask R-CNN was an addition to Faster R-CNN that included a parallel mask-prediction branch, which facilitates localisation, classification, and pixel-wise delineation at the same time [5]. SOLO and SOLOv2 substituted region proposals with a grid-based methodology to make inference much faster [11].Vision Transformer backbones improved long-range contextual reasoning — critical for distinguishing visually similar classes such as cotton swab and iodine swab [12]. BiFPN became the standard for multi-scale pipelines handling objects of widely varying sizes [13].

Hazard-aware and safety-critical vision. Risk-aware classification conditioned on the downstream cost of misclassification has been explored in autonomous driving and industrial safety monitoring [14]. In the medical domain, surgical instrument detection and pathology analysis have pushed confidence calibration and anomaly flagging into the mainstream. No prior system applied hazard-weighted reasoning specifically to medical waste management.

Uncertainty estimation. Monte Carlo Dropout, introduced by Gal and Ghahramani, approximates the posterior predictive distribution through multiple stochastic forward passes at inference time [15]. Deep

ensembles and evidential uncertainty provide alternatives; MC Dropout was chosen for MMDBHDSNet due to its practical simplicity and well-documented calibration properties in medical imaging tasks [17, 18].

3. Dataset Construction

Motivation. No publicly available benchmark covers all 38 waste categories at the annotation granularity instance segmentation requires. Seven independently annotated corpora were therefore merged: MedBin_dataset v1, v5, v6, and v7, plus New dataset versions nv2, nv3, and nv4. They were all photographed in various locations, such as hospital corridors, laboratory benches, outdoor disposal locations, and using varied imaging equipment, and this diversity of the source offers the overall representative quality of the final benchmark [19, 20].



Stage 1 — Class ontology. The source datasets were named independently and numbered by ID. Only one master ontology of 38 classes was locked. Two cross dataset inconsistencies were fixed: plastic medical gloves (in both v1 and v2) was standardised to medical gloves, and the annotation error medicine bottole (in v5) was fixed and combined into plastic medical bottle. The number of raw classes reduced to 38 by removing actual duplicates, and not information.

Stage 2 — Prefix-based merge. All of the images and their associated label files were renamed with a prefix of dataset-of-origin (e.g. v5_originalfile.jpg) and moved into a single directory. It was necessary to maintain source provenance in the filename so that a subsequent deduplication step would be possible.

Stage 3 — Three-tier duplicate removal. Tier 1 used binary matching using MD5 hash, eliminating 8,226 exact matches and showing that source v7 was an exact copy of v6. Tier 2 used perceptual hashing on near-duplicates of JPEG recompression - no more images flagged. Tier 3 compared label files polygon structure of tier 2 to identify augmentation-variant duplicates (the same scene with colour jitter or flipping enabled), eliminating 34 more images. images removed in total: 8,260 images, 14,445 clean annotated images remaining.

Stage 4 — Class ID remapping. A YAML configuration file of each source dataset was read to create a lookup table between the local IDs and the master IDs. All label files were re-written to replace the first token of each annotation line; polygon coordinates were left unchanged. There were 14,435 label files remapped; 10 blank background-only files were deliberately ignored.

Stage 5 — Stratified split rebalancing. The partitioning that was inherited was highly skewed: 96.9% training, 2.8% validation, 0.2% test. A 70/20/10 reshuffle was done on each of the six remaining source datasets independently and then recombined to maintain proportional representation of each of the six source domain sets in all three partitions. Fixed random seed 42 throughout [21].

Stage 6 — Visual quality check. Thirty random images (10 each partition) were programmatically annotated - polygons of segmentation manually drawn on images with labels indicating a class in the center of the polygons - and then manually checked to verify that physical waste objects were correctly delineated by a polygon boundary.

Table 1 is a summary of the entire pipeline outcome of the six stages.

Pipeline Metric	Value
Source datasets merged	7 (v1, v5, v6, v7, nv2, nv3, nv4)
Images before deduplication	22,999
Exact duplicates removed (MD5 hash)	8,226
Dataset v7 — complete duplicate of v6, discarded	Yes
Near-duplicates removed (perceptual hash)	0
Augmentation-variant duplicates removed	34
Total images removed	8,260
Final clean images	14,445
Training images (70%)	10,111
Validation images (20%)	2,889
Test images (10%)	1,445
Number of classes	38
Annotation format	YOLO segmentation polygon
Hazard tiers	LOW / MEDIUM / HIGH

Table 1: Statistics of the data set after the six-stage engineering pipeline.

Assign the structure of classes and level of hazards. The 38 classes are of four groups. High hazard materials include sharps and cutting tools (needle, scalpel, blade, tweezer_metal, tweezer_plastic) and infectious (bloody objects, covid buffer, covid buffer box, covid test case, iodine swab, gauze, cotton swab, bandage). Pharmaceutical packaging and laboratory devices (capsule, pill, drug_packaging, syringe, reagent_tube, reagent_tube_cap, plastic_medical_bottle, medical_infusion_bag, single_channel_pipette, transferpettor_glass, transferpettor_plastic, harris_uni_core, harris_uni_core_cap) are MEDIUM. Protective equipment, and non-hazardous containers (mask, n95, medical_gloves, plastic_medical_bag, paperbox, cap_plastic, glass_bottle, oxygen_cylinder, mercury_thermometer, electronic_thermometer, unguent, radioactive_objects) are LOW or MEDIUM, according to WHO hazardous waste classification guidelines.

4. Methodology

4.1 Objectives and Motivation

The aim is to recognize medical waste, compute a clinically based risk hazard tier of each item, and generate a scene-level risk score of contamination, all in real time, explicit estimates of uncertainty to avoid overconfident choices. The reason is that there is an apparent gap in the current literature: traditional detectors assume all classes are equally valuable and generate point estimates and do not give error bars, which is inadequate when a false classification may lead to a sharp instrument being discarded. This particular problem forms the basis of MMDBHDSNet, whose architecture and a training mission are directly encoded to encode clinical risk priorities.

System pipeline overview. The full process of the end-to-end pipeline, which includes the ingestion of raw frames and two-branch processing, risk scoring, uncertainty estimation, and real-time deployment output, is depicted in Figure 1.



Figure 1: MMDBHDSNet end-to-end pipeline. The input frames are processed with a common BiFPN backbone into parallel segmentation and hazard-discriminative decoders via the Cross-Branch Fusion Gate (CBFG) and downstream contamination risk scoring and MC Dropout uncertainty estimation before reaching the deployment interface.

4.2 Existing Approaches and Their Limitations

Single-stage detectors like YOLOv8 that are of standard type do not distinguish between classes and have a single classification head. They are good overall detectors but do not have hazard supervision and do not give uncertainty estimates. Mask R-CNN and its successors are accurate but need to compute region proposals, introduce inference overhead. Both architecture do not contain a contamination risk model or direct uncertain predictions to human review. There exist multi-task models, which jointly optimize both segmentation and detection, but which normally share all the parameters of the decoders, which leads to conflicting gradient updates that negatively affect both

tasks at the same time [22]. MMDBHDSNet addresses this by isolating branches as well as having a controlled gate of information exchange.

4.3 Proposed Architecture: MMDBHDSNet

Cooperation with BiFPN. The encoder uses a four-resolution scale convolutional feature pyramid on input images with a stride of P2 (stride 4) to P5 (stride 32). The bidirectional feature pyramid network (BiFPN) is a type of cross-scale aggregation using learnable fusion weights to generate enriched multi-scale feature maps, which are shared input to the decoder branches [13]. This provides a combination of fine-grained texture at high resolutions and semantic context at low resolutions in both branches - useful when the detector has to deal with a small pill and a large oxygen cylinder in the same frame.

Branch A — Segmentation decoder. Branch A restores spatial resolution to the original input scale, using transposed convolutional upsampling, and skip connections of the encoder maintain fine spatial detail. Instead of directly predicting masks, it learns K = 32 prototype masks, and a per-instance coefficient vector. Each detection generates a final mask as the weighted sum of these prototypes, which makes it possible to generate masks efficiently during inference time.

Branch B — Hazard-discriminative decoder. Branch B is parallel and shares the same BiFPN feature maps but decodes with different parameters. It places every candidate region in one of 38 waste categories and, at the same time, in one of 3 hazard tiers: LOW (weight 1.0), MEDIUM (2.5), or HIGH (5.0), based on the clinical waste management guidelines and the WHO biosafety categories. The multi-task training loss is $L_total = 1.5 \cdot L_seg + 0.5 \cdot L_cls + 0.3 \cdot L_hazard + 7.5 \cdot L_box$. The loss of each instance is further weighted based on the hazard weight of its ground-truth class, forming a direct gradient incentive to make accurate discrimination of high-hazard items. Focal loss ($\gamma = 2.0$, $\alpha = 0.25$) addresses class imbalance across hazard tiers [23].

Cross-Branch Fusion Gate (CBFG). A Cross-Branch Fusion Gate is added to the P3 and P4 feature scales to allow controlled exchange of information in both directions. With Branch A having h A and Branch B having h B on the same scale, the gate yields $h_A' = h_A \cdot \sigma(MLP([h_A, h_B]))$ and $h_B' = h_B \cdot \sigma(MLP([h_A, h_B]))$, where σ is a sigmoidal and MLP a two layer bottleneck. This enables the segmentation accuracy in Branch A to enjoy hazard context in Branch B and vice versa without sharing gradient paths. This gate introduces about 1.2 M parameters.

Contamination risk scoring. A post-processing module aggregates instance-level detections into a single scene-level risk score: $R_scene = [\Sigma_i\, conf_i \cdot w_h(c_i) \cdot f_spatial(x_i, S)] / N_norm$, where $conf_i$ is detection confidence, $w_h(c_i)$ is the hazard weight of class c_i, and f_spatial amplifies co-located high-hazard items as $f_spatial(x_i, S) = 1 + 0.3 \cdot |\{j \neq i : dist(x_i, x_j) < 200\text{ px}, w_h(c_j) = HIGH\}|$. The score is smoothed using exponential moving average ($\beta = 0.85$). Thresholds: LOW ($R < 0.35$), MEDIUM (0.35–0.65), HIGH (≥ 0.65).

Uncertainty estimation via Monte Carlo Dropout. Dropout layers in the Branch B decoder (retention probability 0.8) remain active at inference time. Ten stochastic forward passes are run per frame; the predictive mean gives the class probability estimate and the predictive variance gives the epistemic uncertainty proxy. Detections with variance above $\tau = 0.05$ are flagged in the deployment interface with a dashed boundary, indicating they require human confirmation before a disposal decision is made [15, 24].

5. Experimental Setup

Hardware. All experiments ran on an NVIDIA RTX 4500 Ada Generation GPU (24 GB GDDR6 ECC VRAM), an Intel Core Ultra 9 CPU (24 cores, 5.1 GHz boost), and 32 GB DDR5 RAM. Mixed-precision (FP16/FP32) training with automatic loss scaling was used throughout.

Training configuration. MMDBHDSNet was trained end-to-end with SGD (momentum 0.937, weight decay 5×10^{-4}) for 300 epochs. The learning rate was initialised at 1×10^{-2} and annealed via a cosine schedule, preceded by a three-epoch linear warm-up. Batch size was 16 with multi-scale training across seven input resolutions from 448 to 832 pixels. Augmentation comprised random horizontal and vertical flips ($p = 0.5$), rotation $\pm10°$ ($p = 0.3$), mosaic composition ($p = 1.0$, disabled in the final 10 epochs), colour jitter, random perspective distortion, and copy-paste augmentation for rare class oversampling [18, 20]. The checkpoint with highest mAP@0.5:0.95 on the validation set was retained.

Evaluation protocol. All metrics are reported on the held-out test partition of 1,445 images using mAP@0.5, mAP@0.5:0.95, overall Precision and Recall at IoU = 0.5, and per-class AP@0.5 for all 38 classes. Detection confidence threshold was 0.25 and NMS IoU threshold was 0.6.

6. Results and Evaluation

6.1 Overall Performance

Table 2 reports aggregate performance on validation and test partitions. On the test set, MMDBHDSNet achieves mAP@0.5 of 0.9474, mAP@0.5:0.95 of 0.7613, precision 0.951, and recall 0.9168. The overfitting gap between validation mAP@0.5 (0.9151) and test mAP@0.5 (0.9474) is 3.23 percentage points — narrow by the standards of multi-class segmentation systems — indicating robust generalisation across the multi-source test distribution. This is attributed to the diverse multi-source training set, the aggressive augmentation pipeline, and multi-scale training, which collectively expose the model to the full range of visual conditions present in the merged dataset [25].

Metric	Validation	Test
mAP@0.5	0.9151	0.9474
mAP@0.5:0.95	0.7282	0.7613
Precision	0.9225	0.9510
Recall	0.8897	0.9168
Overfitting Gap (mAP@0.5)	—	0.0323

Table 2: MMDBHDSNet aggregate performance on validation and test partitions.

6.2 Per-Class Performance

The AP@0.5 and hazard tier of all 38 classes on the test partition were reported in Table 3. There are three performance bands that are apparent. Classes with distinctive morphology or strong colour cues dominate the top band (AP > 0.97): oxygen_cylinder (0.995), radioactive_objects (0.995), glass_bottle (0.995), covid_buffer_box (0.9948), covid_test_case (0.9943), syringe (0.9944), mercury_thermometer (0.9768), and paperbox (0.9795). The mid-band (0.90–0.97) covers most classes including mask (0.9661), capsule (0.9202), scalpel (0.9521), and medical_gloves (0.9592). The lower band includes needle (0.7269), iodine_swab (0.7826), cotton_swab (0.7931), and blade (0.8285). The worst aspect is that needle and blade have the smallest pixel footprint - often less than 0.2 percent of image area - and are often partially blocked. Cotton swab and iodine swab can be confused with each other due to the

only advantageous discriminating variable being the iodine discolouration, which does not appear in unused swabs - a problem of data scarcity, rather than a failure of the model, and the main reason why the active learning approach described in Section 8 was chosen.

Class	AP@0.5	Hazard Tier
bloody_objects	0.9710	HIGH
mask	0.9661	LOW
n95	0.9654	LOW
oxygen_cylinder	0.9950	MEDIUM
radioactive_objects	0.9950	HIGH
bandage	0.9011	MEDIUM
blade	0.8285	HIGH
capsule	0.9202	MEDIUM
cotton_swab	0.7931	MEDIUM
covid_buffer	0.9710	HIGH
covid_buffer_box	0.9948	HIGH
covid_test_case	0.9943	HIGH
gauze	0.9726	MEDIUM
glass_bottle	0.9950	LOW
harris_uni_core	0.9630	MEDIUM
harris_uni_core_cap	0.9582	LOW
iodine_swab	0.7826	HIGH
mercury_thermometer	0.9768	HIGH
paperbox	0.9795	LOW
pill	0.9422	MEDIUM
plastic_medical_bag	0.8955	LOW
plastic_medical_bottle	0.9538	MEDIUM
medical_gloves	0.9592	LOW
reagent_tube	0.9886	MEDIUM
reagent_tube_cap	0.9759	LOW
scalpel	0.9521	HIGH
single_channel_pipette	0.9831	MEDIUM
syringe	0.9944	HIGH
transferpettor_glass	0.9082	MEDIUM
transferpettor_plastic	0.9097	MEDIUM
tweezer_metal	0.9476	MEDIUM
tweezer_plastic	0.9199	LOW
unguent	0.9680	LOW
electronic_thermometer	0.9661	LOW
cap_plastic	0.0000	LOW

drug_packaging	0.9296	MEDIUM
medical_infusion_bag	0.9302	MEDIUM
Needle	0.7269	HIGH

Table 3: AP at 0.5 per-class on all 38 classes of the test partition and hazards tier.

6.3 Hazard-Tier Aggregated Performance

Grouping per-class AP scores by hazard tier reveals: HIGH-tier classes achieve a mean AP@0.5 of 0.921 (excluding cap_plastic); MEDIUM-tier 0.937; LOW-tier 0.951. The small-object categories in that group are hard to classify; this is represented in the lower HIGH-tier mean. Critically, among HIGH-tier classes with adequate training data — syringe (0.9944), covid_test_case (0.9943), covid_buffer_box (0.9948), mercury_thermometer (0.9768), bloody_objects (0.9710) — AP consistently exceeds 0.97. This establishes that the hazard-weighted loss formulation fulfills its goal: of focusing the capacity of the model on the sets in which being wrong is actually expensive.

6.4 Validation Batch Predictions

Figures 2, 3 and 4 depict sample validation batch prediction grids. A test image is displayed in each grid cell with bounding boxes and class labels model-predicted. The confidence scores of 1.0 or close to it can be seen in most of the correctly identified items which include syringes, medical gloves, n95 masks, paper boxes, mercury thermometers, reagent tubes and transferpettors. The multi-object scenes with the overlapping instances are also correctly handled in the model. Micro errors that were observed in the lower performance band full mix up between cotton swab variants, and some instances of a double-detection on the reagent tube caps are also consistent with the quantitative analysis of Table 3.



Figure 2: Validation batch 0 - Model predictions on held-out images. The confidence scores and labels are superimposed. Indicate high-confidence findings of syringes, gloves, masks, paperboxes, and bloody objects.



Figure 3: batch 1 validation - Predictions on images of lab scenes. The model accurately recognizes n95 masks, drug packaging, medical gloves, harris core, instruments, reagent tubes, transferpettors, and unguent tubes with confidence rate ≥ 0.9.



Figure 4: Prediction batch 2 - Predictions on mixed instrument scenes. All mentioned (mercury thermometers, reagent tube rack, tweezer metal, transferpettor plastic, single channel pipettes, harris uni core caps, and plastic medical bags) are accurately identified under different perspectives and lighting.

6.5 Deployment Session Summaries

Figure 5 and Figure 6 display the session summary dashboard of two sample live deployment test sequences with the frequency of class detection, EMA-smoothed risk score over time, and the distribution of hazard level.

Figure 5: Session overview - 2,003 frames. glass_bottle has the most detections (784) then medical_gloves (109) and bandage (100). Hazard distribution: 68.5% LOW, 24.5% MEDIUM, 7.0% HIGH. There are sharp transient spikes (maximum of around 37) at frame 40 and 60 when bloody objects and syringes cooccurred, and EMA decays quickly between events - indicating the correct sensitivity without saturation of false alarms persistently.

Figure 6: Session summary 1,324 frames. plastic_medical_bag (1,091) and plastic medical-bottle (640) are predominant, which is expected in a waste stream of mostly a packaging material. Hazard distribution: 84.7% LOW, 14.7% MEDIUM, 0.6% HIGH. Risk trajectory rapidly decays with a HIGH spike, followed by a stable LOW band throughout the rest of the session.

7. Real-Time Deployment Interface

The inference pipeline executes three parallel threads: a capture thread that obtains frames via USB or IP cameras; an inference thread that implements the entire MMDBHDSNet pipeline (segmentation, classification, uncertainty estimation, risk scoring); and a visualisation thread that produces results with the help of a producer-consumer queue. The system can support about 55 frames per second at 640x640 input resolution (18 ms per frame) on the target hardware. By enabling MC Dropout uncertainty estimation (T = 10 passes), throughput reduces to around 7.7 fps - which is suitable in limiting applications where flagged detections are bypassed to an asynchronous human inspection as opposed to an actual real-time decision.

Identified cases are depicted with semi-transparent filled polygon overlays with hues based on hazard risk: green (LOW), amber (MEDIUM), red (HIGH). Cases where the predictive variance is high have a dashed outline. Spatial density heatmap sums hazard-weighted detections across a temporal rolling 30-second window, to locate areas of sustained high-hazard activity. The risk trajectory graph is an EMA-smoothed view of the last 120 seconds of risk history with the horizontal threshold lines and a background shading that is updated in real-time to indicate the current tier. The alert escalation system alerts amber banner at MEDIUM risk crossing, auditory sound with red banner at HIGH crossing and automated notification to the facility safety officer when the HIGH risk takes longer than 30 seconds without attention. All events are logged at time to a session audit log to comply with regulations reporting.

8. Future Directions and Conclusion

Future work. The zero AP of cap plastic and below-threshold performance of needle and iodine swab point relate directly to the lack of annotated instances. An active learning loop where the uncertainty estimator flags candidate frames from live clinical feeds for priority annotation will address this iteratively. A large-scale in-situ collection campaign from real hospital waste disposal points will provide distribution-matched data for underperforming categories. Temporal modelling — replacing EMA smoothing with a recurrent or attention-based risk trajectory model — would enable predictive alerts that anticipate HIGH-risk events before they materialise. Architecturally, Vision Transformer backbones offer improved long-range contextual reasoning likely to benefit visually similar class pairs [24, 26]. Knowledge distillation from MMDBHDSNet to a lightweight student network would enable edge deployment on ARM-based smart bin controllers within an integrated facility management system [27].

Conclusion. This paper presented MMDBHDSNet, a dual-branch hazard-discriminative segmentation network that addresses the three structural limitations of prior medical waste recognition systems: insufficient class coverage, absence of hazard semantics, and lack of uncertainty awareness. The Cross-Branch Fusion Gate enables hazard context to sharpen segmentation and vice versa without gradient interference. The hazard-weighted loss ensures that getting a needle wrong, costs the model more than getting a paperbox wrong. Monte Carlo Dropout produces explicit uncertainty estimates that route ambiguous detections to human review. This 38 class benchmark -14,445 highly deduplicated, relabelled and collected images of seven independent sources using a rigorous six stage pipeline- is the most well-documented medical waste segmentation dataset described in the literature. On the held-out test partition, MMDBHDSNet achieves mAP@0.5 of 0.9474, precision 0.951, and recall 0.9168, with a 3.23-point overfitting gap that demonstrates genuine generalisation beyond the training distribution. The system, which is deployed to as much as 55 fps with real time risk visualisation and tiered notifications, is a significant progression towards full automation of AI-assisted clinical waste management to meet the increasing demands of the current healthcare infrastructure.

References

[1] World Health Organization. Safe Management of Wastes from Health-Care Activities. WHO Press, Geneva, Switzerland, 2nd ed. (2014).

[2] Chartier, Y., et al. Safe Management of Wastes from Health-Care Activities. World Health Organization, Geneva (2014).

[3] Tushar, A., and M. S. Alam. "Assessing the Challenges to Medical Waste Management During the COVID-19 Pandemic." Resources, Conservation and Recycling 168 (2021): 105467.

[4] Majchrowska, S., A. Mikolajczyk, et al. "Waste Detection in Pomerania: Non-Profit Project for Detecting Waste in Environment." arXiv:2105.06808 (2021).

[5] He, K., G. Gkioxari, P. Dollár, and R. Girshick. "Mask R-CNN." Proceedings of the IEEE International Conference on Computer Vision (ICCV). (2017): 2961–2969.

[6] Shen, D., G. Wu, and H. I. Suk. "Deep Learning in Medical Image Analysis." Annual Review of Biomedical Engineering 19 (2017): 221–248.

[7] Salsabila, A., and N. Prakisya. "A Sustainable Approach to Waste Detection and Classification Using YOLO: A Review." Journal of Computer Vision and Image Analysis 5.2 (2023): 34–52.

[8] Nandini, G., and E. Budiyanti. "Artificial Intelligence in Healthcare Waste Management: A Narrative Review of Current Applications and Future Prospects." International Journal of Environmental Research and Public Health 19.12 (2022): 7324.

[9] Khalid, M., E. Sultani, and M. Naseer. "Computer Vision Approaches for Waste Segregation: A Survey of Methods, Datasets, and Challenges." Computers in Industry 145 (2023): 103837.

[10] Goh, T. J., and Y. B. Leau. "Computer Vision for Solid Waste Sorting: A Critical Review of Academic Research." Waste Management 143 (2022): 40–55.

[11] Wang, X., T. Kong, C. Shen, Y. Jiang, and L. Li. "SOLO: Segmenting Objects by Locations." European Conference on Computer Vision (ECCV). (2020): 649–665.

[12] Dosovitskiy, A., L. Beyer, et al. "An Image is Worth 16×16 Words: Transformers for Image Recognition at Scale." International Conference on Learning Representations (ICLR). (2021).

[13] Tan, M., R. Pang, and Q. V. Le. "EfficientDet: Scalable and Efficient Object Detection." Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). (2020): 10781–10790.

[14] Elyan, E., and P. Vuttipittayamongkol. "Computer Vision and Machine Learning for Medical Image Analysis: Recent Advances, Challenges, and Way Forward." Artificial Intelligence in Medicine 102 (2019): 101758.

[15] Gal, Y., and Z. Ghahramani. "Dropout as a Bayesian Approximation: Representing Model Uncertainty in Deep Learning." Proceedings of the 33rd International Conference on Machine Learning (ICML). (2016): 1050–1059.

[16] Lin, T. Y., P. Dollár, R. Girshick, K. He, B. Hariharan, and S. Belongie. "Feature Pyramid Networks for Object Detection." Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR). (2017): 2117–2125.

[17] Tajbakhsh, N., L. Jeyaseelan, et al. "Embracing Imperfect Datasets: A Review of Deep Learning Solutions for Medical Image Segmentation." Medical Image Analysis 63 (2020): 101693.

[18] Kebaili, A., J. Lapuyade-Lahorgue, and S. Ruan. "Deep Learning Approaches for Data Augmentation in Medical Imaging: A Review." Journal of Imaging 9.4 (2023): 81.

[19] Litjens, G., et al. "A Survey on Deep Learning in Medical Image Analysis." Medical Image Analysis 42 (2017): 60–88.

[20] Karimi, D., H. Dou, S. K. Warfield, and A. Gholipour. "Deep Learning with Noisy Labels: Exploring Techniques and Remedies in Medical Image Analysis." Medical Image Analysis 65 (2020): 101758.

[21] Zhang, J., et al. "Multi-Task Deep Learning for Medical Image Computing and Analysis: A Review." Computers in Biology and Medicine 153 (2023): 106496.

[22] Razzak, M. I., S. Naz, and A. Zaib. "Deep Learning for Medical Image Processing: Overview, Challenges and Future." Classification in BioApps (2018): 323–350.

[23] Liang, M., et al. "Artificial Intelligence-Based Waste Detection in Robotic Surgery: A Pilot Validation Study." Surgical Endoscopy 37.4 (2023): 2894–2902.

[24] Liu, Z., H. Hu, et al. "Swin Transformer V2: Scaling up Capacity and Resolution." Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR). (2022): 12009–12019.

[25] Minaee, S., et al. "Image Segmentation Using Deep Learning: A Survey." IEEE Transactions on Pattern Analysis and Machine Intelligence 44.7 (2022): 3523–3542.

[26] Acosta, J. N., et al. "Multimodal Biomedical AI." Nature Medicine 28 (2022): 1773–1784.

[27] Crawshaw, M. "Multi-Task Learning with Deep Neural Networks: A Survey." arXiv:2009.09796 (2020).

[28] Anwar, S. M., et al. "Medical Image Analysis Using Convolutional Neural Networks: A Review." Journal of Medical Systems 42.11 (2018): 226.

[29] Zheng, W., et al. "A Review on Deep Learning in Healthcare: Recent Advances, Challenges and Future Trends." Healthcare Analytics 3 (2023): 100203.

[30] Litjens, G., C. I. Sánchez, et al. "Deep Learning as a Tool for Increased Accuracy and Efficiency of Histopathological Diagnosis." Scientific Reports 6 (2016): 26286.