Lab Sheet 6: MongoDB Basic commands

Branch/ Class: B.Tech Date:11-03-2026

Faculty Name: Prof. S.Gopikrishnan School: SCOPE

Student name: Dakshita Mathur Reg. no.: 23BCE8367

1. Use MongoDB to implement the following DB operations

1. Create a database called ‘vehicles’ and write a MongoDB query to select database as “vehicles”.

```
>_MONGOSH
> use local
< switched to db local
> use vehicles
< switched to db vehicles
```

2. Write a MongoDB query to display all the databases.

```
> show dbs
< admin     40.00 KiB
  config   108.00 KiB
  local     40.00 KiB
  vehicle    8.00 KiB
```

3. Create a collection called ‘two_wheelers’. (use capping) and Create a collection called ‘four_wheelers’.

```
> db.createCollection("two_wheelers", { capped: true, size: 1048576 })
< { ok: 1 }
> db.createCollection("four_wheelers")
< { ok: 1 }
```

4. Add 5 two-wheeler details to the collection named ‘two_wheelers’. Each document consists of following fields as bike_name, model (gear or gearless), category (100cc, 125cc, 150cc, 200cc), colors_available (red, black, blue, sport red etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
>_MONGOSH
> db.two_wheelers.insertMany([
    {
      bike_name: "Yamaha RX",
      model: "gear",
      category: "125cc",
      colors_available: ["red", "black", "blue"],
      manufacturer: "Yamaha",
      performance: 8,
      timestamp: new Date("2020-05-10"),
      price: 150000
    },
    {
      bike_name: "Honda Shine",
      model: "gearless",
      category: "100cc",
      colors_available: ["red", "black"],
      manufacturer: "Honda",
      performance: 7,
      timestamp: new Date("2019-03-15"),
      price: 65000
    },
    {
      bike_name: "Suzuki Gixxer",
      model: "gear",
      category: "150cc",
      colors_available: ["blue", "black"],
      manufacturer: "Suzuki",
      performance: 8,
      timestamp: new Date("2021-07-20"),
      price: 125000
    },
    {
      bike_name: "Bajaj Pulsar",
      model: "gear",
      category: "150cc",
      colors_available: ["red", "black"],
      manufacturer: "Bajaj",
```

```
>_MONGOSH
      manufacturer: "Bajaj",
      performance: 7,
      timestamp: new Date("2018-11-11"),
      price: 120000
    },
    {
      bike_name: "Royal Enfield Bullet",
      model: "gear",
      category: "200cc",
      colors_available: ["black"],
      manufacturer: "Royal Enfield",
      performance: 9,
      timestamp: new Date("2017-06-30"),
      price: 180000
    }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b1353001749becd10f1fb2'),
      '1': ObjectId('69b1353001749becd10f1fb3'),
      '2': ObjectId('69b1353001749becd10f1fb4'),
      '3': ObjectId('69b1353001749becd10f1fb5'),
      '4': ObjectId('69b1353001749becd10f1fb6')
    }
  }
```

5. Add 5 four-wheeler details to the collection named ‘four_wheelers’. Each document consists of following fields as vehicle_name, model (commercial or own), category (car, lorry, bus, mini truck, heavy truck, containers), variants (vxi, zxi, petrol, diesel etc) as array, manufacturer, performance (out of 10), timestamp (date and year release) and price.

```
>_MONGOSH

> db.four_wheelers.insertMany([
    {
      vehicle_name: "Honda City",
      model: "own",
      category: "car",
      variants: ["petrol", "diesel"],
      manufacturer: "Honda",
      performance: 8,
      timestamp: new Date("2020-08-15"),
      price: 1200000
    },
    {
      vehicle_name: "Maruti Alto",
      model: "own",
      category: "car",
      variants: ["petrol"],
      manufacturer: "Maruti",
      performance: 6,
      timestamp: new Date("2019-05-20"),
      price: 400000
    },
    {
      vehicle_name: "Lorry Volvo",
      model: "commercial",
      category: "lorry",
      variants: ["diesel"],
      manufacturer: "Volvo",
      performance: 7,
      timestamp: new Date("2018-03-10"),
      price: 2500000
    },
    {
      vehicle_name: "Bus Tata",
      model: "commercial",
      category: "bus",
      variants: ["petrol", "diesel"],
      manufacturer: "Tata",
```

```
>_MONGOSH
      manufacturer: "Tata",
      performance: 7,
      timestamp: new Date("2021-01-05"),
      price: 1500000
    },
    {
      vehicle_name: "Mini Truck Mahindra",
      model: "own",
      category: "mini truck",
      variants: ["diesel"],
      manufacturer: "Mahindra",
      performance: 6,
      timestamp: new Date("2019-09-25"),
      price: 800000
    }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b1353a01749becd10f1fb7'),
      '1': ObjectId('69b1353a01749becd10f1fb8'),
      '2': ObjectId('69b1353a01749becd10f1fb9'),
      '3': ObjectId('69b1353a01749becd10f1fba'),
      '4': ObjectId('69b1353a01749becd10f1fbb')
    }
  }
```

6. Write a MongoDB query to display all documents available in two_wheelers and four_wheelers.

```
>_MONGOSH
> db.two_wheelers.find()
< {
    _id: ObjectId('69b1353001749becd10f1fb2'),
    bike_name: 'Yamaha RX',
    model: 'gear',
    category: '125cc',
    colors_available: [
      'red',
      'black',
      'blue'
    ],
    manufacturer: 'Yamaha',
    performance: 8,
    timestamp: 2020-05-10T00:00:00.000Z,
    price: 150000
  }
  {
    _id: ObjectId('69b1353001749becd10f1fb3'),
    bike_name: 'Honda Shine',
    model: 'gearless',
    category: '100cc',
    colors_available: [
      'red',
      'black'
    ],
    manufacturer: 'Honda',
    performance: 7,
    timestamp: 2019-03-15T00:00:00.000Z,
    price: 65000
  }
  {
    _id: ObjectId('69b1353001749becd10f1fb4'),
    bike_name: 'Suzuki Gixxer',
    model: 'gear',
    category: '150cc',
    colors_available: [
      'blue',
```

```
>_MONGOSH
      'blue',
      'black'
    ],
    manufacturer: 'Suzuki',
    performance: 8,
    timestamp: 2021-07-20T00:00:00.000Z,
    price: 125000
  }
  {
    _id: ObjectId('69b1353001749becd10f1fb5'),
    bike_name: 'Bajaj Pulsar',
    model: 'gear',
    category: '150cc',
    colors_available: [
      'red',
      'black'
    ],
    manufacturer: 'Bajaj',
    performance: 7,
    timestamp: 2018-11-11T00:00:00.000Z,
    price: 120000
  }
  {
    _id: ObjectId('69b1353001749becd10f1fb6'),
    bike_name: 'Royal Enfield Bullet',
    model: 'gear',
    category: '200cc',
    colors_available: [
      'black'
    ],
    manufacturer: 'Royal Enfield',
    performance: 9,
    timestamp: 2017-06-30T00:00:00.000Z,
    price: 180000
  }
```

```
>_MONGOSH
> db.four_wheelers.find()
< {
    _id: ObjectId('69b1353a01749becd10f1fb7'),
    vehicle_name: 'Honda City',
    model: 'own',
    category: 'car',
    variants: [
      'petrol',
      'diesel'
    ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: 2020-08-15T00:00:00.000Z,
    price: 1200000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fb8'),
    vehicle_name: 'Maruti Alto',
    model: 'own',
    category: 'car',
    variants: [
      'petrol'
    ],
    manufacturer: 'Maruti',
    performance: 6,
    timestamp: 2019-05-20T00:00:00.000Z,
    price: 400000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fb9'),
    vehicle_name: 'Lorry Volvo',
    model: 'commercial',
    category: 'lorry',
    variants: [
      'diesel'
    ],
    manufacturer: 'Volvo',
```

```
>_MONGOSH
    manufacturer: 'Volvo',
    performance: 7,
    timestamp: 2018-03-10T00:00:00.000Z,
    price: 2500000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fba'),
    vehicle_name: 'Bus Tata',
    model: 'commercial',
    category: 'bus',
    variants: [
      'petrol',
      'diesel'
    ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: 2021-01-05T00:00:00.000Z,
    price: 1500000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fbb'),
    vehicle_name: 'Mini Truck Mahindra',
    model: 'own',
    category: 'mini truck',
    variants: [
      'diesel'
    ],
    manufacturer: 'Mahindra',
    performance: 6,
    timestamp: 2019-09-25T00:00:00.000Z,
    price: 800000
  }
```

7. Write a MongoDB query to display only vehicle name and price in all the collection of the database.

```
> db.two_wheelers.find({}, { bike_name: 1, price: 1, _id: 0 })
< {
    bike_name: 'Yamaha RX',
    price: 150000
  }
  {
    bike_name: 'Honda Shine',
    price: 65000
  }
  {
    bike_name: 'Suzuki Gixxer',
    price: 125000
  }
  {
    bike_name: 'Bajaj Pulsar',
    price: 120000
  }
  {
    bike_name: 'Royal Enfield Bullet',
    price: 180000
  }
```

```
> db.four_wheelers.find({}, { vehicle_name: 1, price: 1, _id: 0 })
< {
    vehicle_name: 'Honda City',
    price: 1200000
  }
  {
    vehicle_name: 'Maruti Alto',
    price: 400000
  }
  {
    vehicle_name: 'Lorry Volvo',
    price: 2500000
  }
  {
    vehicle_name: 'Bus Tata',
    price: 1500000
  }
  {
    vehicle_name: 'Mini Truck Mahindra',
    price: 800000
  }
```

8. Write a MongoDB query to display two_wheelers from a particular company

```
> db.two_wheelers.find({ manufacturer: "Honda" })
< {
    _id: ObjectId('69b1353001749becd10f1fb3'),
    bike_name: 'Honda Shine',
    model: 'gearless',
    category: '100cc',
    colors_available: [
      'red',
      'black'
    ],
    manufacturer: 'Honda',
    performance: 7,
    timestamp: 2019-03-15T00:00:00.000Z,
    price: 65000
  }
```

9. Write a MongoDB query to display four_wheelers available in diesel variants

```
> db.four_wheelers.find({ variants: "diesel" })
< {
    _id: ObjectId('69b1353a01749becd10f1fb7'),
    vehicle_name: 'Honda City',
    model: 'own',
    category: 'car',
    variants: [
      'petrol',
      'diesel'
    ],
    manufacturer: 'Honda',
    performance: 8,
    timestamp: 2020-08-15T00:00:00.000Z,
    price: 1200000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fb9'),
    vehicle_name: 'Lorry Volvo',
    model: 'commercial',
```

```
    model: 'commercial',
    category: 'lorry',
    variants: [
      'diesel'
    ],
    manufacturer: 'Volvo',
    performance: 7,
    timestamp: 2018-03-10T00:00:00.000Z,
    price: 2500000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fba'),
    vehicle_name: 'Bus Tata',
    model: 'commercial',
    category: 'bus',
    variants: [
      'petrol',
      'diesel'
    ],
    manufacturer: 'Tata',
    performance: 7,
    timestamp: 2021-01-05T00:00:00.000Z,
    price: 1500000
  }
  {
    _id: ObjectId('69b1353a01749becd10f1fbb'),
    vehicle_name: 'Mini Truck Mahindra',
    model: 'own',
    category: 'mini truck',
    variants: [
      'diesel'
    ],
    manufacturer: 'Mahindra',
    performance: 6,
    timestamp: 2019-09-25T00:00:00.000Z,
    price: 800000
  }
```

10. Write a MongoDB query to display vehicles name, category and manufacturer details whose rating is more than 5.

```
>_MONGOSH
> db.four_wheelers.find({ performance: { $gt: 5 } }, { vehicle_name: 1, category: 1, manufacturer: 1, _id: 0 })
< {
    vehicle_name: 'Honda City',
    category: 'car',
    manufacturer: 'Honda'
  }
  {
    vehicle_name: 'Maruti Alto',
    category: 'car',
    manufacturer: 'Maruti'
  }
  {
    vehicle_name: 'Lorry Volvo',
    category: 'lorry',
    manufacturer: 'Volvo'
  }
  {
    vehicle_name: 'Bus Tata',
    category: 'bus',
    manufacturer: 'Tata'
  }
  {
    vehicle_name: 'Mini Truck Mahindra',
    category: 'mini truck',
    manufacturer: 'Mahindra'
  }
```

```
> db.two_wheelers.find({ performance: { $gt: 5 } }, { bike_name: 1, category: 1, manufacturer: 1, _id: 0 })
< {
    bike_name: 'Yamaha RX',
    category: '125cc',
    manufacturer: 'Yamaha'
  }
  {
    bike_name: 'Honda Shine',
    category: '100cc',
    manufacturer: 'Honda'
  }
  {
    bike_name: 'Suzuki Gixxer',
    category: '150cc',
    manufacturer: 'Suzuki'
  }
  {
    bike_name: 'Bajaj Pulsar',
    category: '150cc',
    manufacturer: 'Bajaj'
  }
  {
    bike_name: 'Royal Enfield Bullet',
    category: '200cc',
    manufacturer: 'Royal Enfield'
  }
```

2. Use MongoDB to implement the following DB operations for a Zoo

1. Create a database called ‘animal’ and write a MongoDB query to select database as ‘animal’.

```
>_MONGOSH
> use local
< switched to db local
> use animal
< switched to db animal
```

2. Write a MongoDB query to display all the databases.

```
> show dbs
< admin    40.00 KiB
  config  108.00 KiB
  local    40.00 KiB
```

3. Create a collection called ‘wild_animals’.(use capping) and Create a collection called ‘domestic_animals’.

```
> db.createCollection("wild_animals", { capped: true, size: 1048576 })
< { ok: 1 }
> db.createCollection("domestic_animals")
< { ok: 1 }
```

4. Add 5 wild_animal details to the collection named ‘wild_animals’. Each document consists of following fields as animal_name, nature (harm or harmless), favorite_foods (meat, rabbits, deer etc) as array, care_taker_name, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
>_MONGOSH
> db.wild_animals.insertMany([
    {
      animal_name: "Lion",
      nature: "harm",
      favorite_foods: ["meat"],
      care_taker_name: "John Doe",
      life_span: 14,
      timestamp: new Date("2021-05-10"),
      expenses: 5000
    },
```

```
  },
  {
    animal_name: "Elephant",
    nature: "harmless",
    favorite_foods: ["rabbits", "deer"],
    care_taker_name: "Alice Smith",
    life_span: 60,
    timestamp: new Date("2020-08-15"),
    expenses: 15000
  },
  {
    animal_name: "Tiger",
    nature: "harm",
    favorite_foods: ["meat"],
    care_taker_name: "Bob Brown",
    life_span: 20,
    timestamp: new Date("2019-07-20"),
    expenses: 7000
  },
  {
    animal_name: "Giraffe",
    nature: "harmless",
    favorite_foods: ["leaves"],
    care_taker_name: "Eve White",
    life_span: 25,
    timestamp: new Date("2018-04-10"),
    expenses: 6000
  },
  {
    animal_name: "Zebra",
    nature: "harmless",
    favorite_foods: ["grass"],
    care_taker_name: "Mike Green",
    life_span: 20,
    timestamp: new Date("2022-01-12"),
    expenses: 4000
  }
```

```
    }
  ])
< {
    acknowledged: true,
    insertedIds: {
      '0': ObjectId('69b13b025db2dd42ae93a678'),
      '1': ObjectId('69b13b025db2dd42ae93a679'),
      '2': ObjectId('69b13b025db2dd42ae93a67a'),
      '3': ObjectId('69b13b025db2dd42ae93a67b'),
      '4': ObjectId('69b13b025db2dd42ae93a67c')
    }
  }
```

5. Add 5 domestic-animal details to the collection named ‘domestic_animals’. Each document consists of following fields as animal_name, gender (male or female), favorite_foods (meat, rabbits, deer etc) as array, animal_petname, life span (in years), timestamp (when the animal registered at the Zoo) and expenses.

```
>_MONGOSH
> db.domestic_animals.insertMany([
    {
      animal_name: "Dog",
      gender: "male",
      favorite_foods: ["meat", "bones"],
      animal_petname: "Buddy",
      life_span: 15,
      timestamp: new Date("2020-02-14"),
      expenses: 2000
    },
    {
      animal_name: "Cat",
      gender: "female",
      favorite_foods: ["fish", "milk"],
      animal_petname: "Whiskers",
      life_span: 12,
      timestamp: new Date("2019-11-05"),
      expenses: 1000
    },
    {
```

```
    animal_name: "Cow",
    gender: "female",
    favorite_foods: ["grass"],
    animal_petname: "Bessie",
    life_span: 20,
    timestamp: new Date("2018-09-10"),
    expenses: 3000
  },
  {
    animal_name: "Sheep",
    gender: "male",
    favorite_foods: ["grass"],
    animal_petname: "Billy",
    life_span: 10,
    timestamp: new Date("2021-03-22"),
    expenses: 1500
  },
  {
    animal_name: "Hamster",
    gender: "female",
    favorite_foods: ["seeds"],
    animal_petname: "Nibbles",
    life_span: 3,
    timestamp: new Date("2022-06-01"),
    expenses: 500
  }
])
< {
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('69b13b095db2dd42ae93a67d'),
    '1': ObjectId('69b13b095db2dd42ae93a67e'),
    '2': ObjectId('69b13b095db2dd42ae93a67f'),
    '3': ObjectId('69b13b095db2dd42ae93a680'),
    '4': ObjectId('69b13b095db2dd42ae93a681')
  }
}
```

6. Write a MongoDB query to display all documents available in wild_animals and domastic_animals.

```
> db.wild_animals.find()
< {
    _id: ObjectId('69b13b025db2dd42ae93a678'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [
      'meat'
    ],
    care_taker_name: 'John Doe',
    life_span: 14,
    timestamp: 2021-05-10T00:00:00.000Z,
    expenses: 5000
  }
  {
    _id: ObjectId('69b13b025db2dd42ae93a679'),
    animal_name: 'Elephant',
    nature: 'harmless',
    favorite_foods: [
      'rabbits',
      'deer'
    ],
    care_taker_name: 'Alice Smith',
    life_span: 60,
    timestamp: 2020-08-15T00:00:00.000Z,
    expenses: 15000
  }
  {
    _id: ObjectId('69b13b025db2dd42ae93a67a'),
    animal_name: 'Tiger',
    nature: 'harm',
    favorite_foods: [
      'meat'
    ],
    care_taker_name: 'Bob Brown',
    life_span: 20,
    timestamp: 2019-07-20T00:00:00.000Z,
    expenses: 7000
```

```
    expenses: 7000
  }
  {
    _id: ObjectId('69b13b025db2dd42ae93a67b'),
    animal_name: 'Giraffe',
    nature: 'harmless',
    favorite_foods: [
      'leaves'
    ],
    care_taker_name: 'Eve White',
    life_span: 25,
    timestamp: 2018-04-10T00:00:00.000Z,
    expenses: 6000
  }
  {
    _id: ObjectId('69b13b025db2dd42ae93a67c'),
    animal_name: 'Zebra',
    nature: 'harmless',
    favorite_foods: [
      'grass'
    ],
    care_taker_name: 'Mike Green',
    life_span: 20,
    timestamp: 2022-01-12T00:00:00.000Z,
    expenses: 4000
  }
> db.domestic_animals.find()
< {
    _id: ObjectId('69b13b095db2dd42ae93a67d'),
    animal_name: 'Dog',
    gender: 'male',
    favorite_foods: [
      'meat',
      'bones'
    ],
    animal_petname: 'Buddy',
    life_span: 15,
```

```
    life_span: 15,
    timestamp: 2020-02-14T00:00:00.000Z,
    expenses: 2000
  }
  {
    _id: ObjectId('69b13b095db2dd42ae93a67e'),
    animal_name: 'Cat',
    gender: 'female',
    favorite_foods: [
      'fish',
      'milk'
    ],
    animal_petname: 'Whiskers',
    life_span: 12,
    timestamp: 2019-11-05T00:00:00.000Z,
    expenses: 1000
  }
  {
    _id: ObjectId('69b13b095db2dd42ae93a67f'),
    animal_name: 'Cow',
    gender: 'female',
    favorite_foods: [
      'grass'
    ],
    animal_petname: 'Bessie',
    life_span: 20,
    timestamp: 2018-09-10T00:00:00.000Z,
    expenses: 3000
  }
  {
    _id: ObjectId('69b13b095db2dd42ae93a680'),
    animal_name: 'Sheep',
    gender: 'male',
    favorite_foods: [
      'grass'
    ],
    animal_petname: 'Billy',
```

```
    animal_petname: 'Billy',
    life_span: 10,
    timestamp: 2021-03-22T00:00:00.000Z,
    expenses: 1500
  }
  {
    _id: ObjectId('69b13b095db2dd42ae93a681'),
    animal_name: 'Hamster',
    gender: 'female',
    favorite_foods: [
      'seeds'
    ],
    animal_petname: 'Nibbles',
    life_span: 3,
    timestamp: 2022-06-01T00:00:00.000Z,
    expenses: 500
  }
```

7. Write a MongoDB query to display only animal name and expenses in all the collection of the database

```
> db.wild_animals.find({}, { animal_name: 1, expenses: 1, _id: 0 })
< {
    animal_name: 'Lion',
    expenses: 5000
  }
  {
    animal_name: 'Elephant',
    expenses: 15000
  }
  {
    animal_name: 'Tiger',
    expenses: 7000
  }
  {
    animal_name: 'Giraffe',
    expenses: 6000
  }
  {
    animal_name: 'Zebra',
    expenses: 4000
  }
```

```
> db.domestic_animals.find({}, { animal_name: 1, expenses: 1, _id: 0 })
< {
    animal_name: 'Dog',
    expenses: 2000
  }
  {
    animal_name: 'Cat',
    expenses: 1000
  }
  {
    animal_name: 'Cow',
    expenses: 3000
  }
  {
    animal_name: 'Sheep',
    expenses: 1500
  }
  {
    animal_name: 'Hamster',
    expenses: 500
  }
```

8. Write a MongoDB query to display domestic_animals whose life is a particular year

```
> db.domestic_animals.find({ life_span: 12 })
< {
    _id: ObjectId('69b13b095db2dd42ae93a67e'),
    animal_name: 'Cat',
    gender: 'female',
    favorite_foods: [
      'fish',
      'milk'
    ],
    animal_petname: 'Whiskers',
    life_span: 12,
    timestamp: 2019-11-05T00:00:00.000Z,
    expenses: 1000
  }
```

9. Write a MongoDB query to display wild_animals available under a particular care_taker.

```
> db.wild_animals.find({ care_taker_name: "John Doe" })
< {
    _id: ObjectId('69b13b025db2dd42ae93a678'),
    animal_name: 'Lion',
    nature: 'harm',
    favorite_foods: [
      'meat'
    ],
    care_taker_name: 'John Doe',
    life_span: 14,
    timestamp: 2021-05-10T00:00:00.000Z,
    expenses: 5000
  }
```

10. Write a MongoDB query to display animal name, favorite_foods and expenses details whose lifespan is more than 5 years.

```
> db.wild_animals.find({ life_span: { $gt: 5 } }, { animal_name: 1, favorite_foods: 1, expenses: 1, _id: 0 })
< {
    animal_name: 'Lion',
    favorite_foods: [
      'meat'
    ],
    expenses: 5000
  }
  {
    animal_name: 'Elephant',
    favorite_foods: [
      'rabbits',
      'deer'
    ],
    expenses: 15000
  }
  {
    animal_name: 'Tiger',
    favorite_foods: [
      'meat'
    ],
    expenses: 7000
  }
  {
    animal_name: 'Giraffe',
    favorite_foods: [
      'leaves'
    ],
```

```
    ],
    expenses: 6000
  }
  {
    animal_name: 'Zebra',
    favorite_foods: [
      'grass'
    ],
    expenses: 4000
  }
> db.domestic_animals.find({ life_span: { $gt: 5 } }, { animal_name: 1, favorite_foods: 1, expenses: 1, _id: 0 })
< {
    animal_name: 'Dog',
    favorite_foods: [
      'meat',
      'bones'
    ],
    expenses: 2000
  }
  {
    animal_name: 'Cat',
    favorite_foods: [
      'fish',
      'milk'
    ],
    expenses: 1000
  }
  {
    animal_name: 'Cow',
    favorite_foods: [
      'grass'
    ],
    expenses: 3000
  }
  {
    animal_name: 'Sheep',
    favorite_foods: [
      'grass'
```

```
    ],
    expenses: 1500
  }
```