Revision A | 3.3 V signals | Separate 3.3 V display supply | <=100 mm Type-A 80-way FFC

display

Datei: display.kicad_sch

ribbon

Datei: ribbon.kicad_sch

power

Datei: power.kicad_sch

Supply present

Supply present


ProtoMate

Sheet: /
File: display-adapter.kicad_sch

Title: display-adapter / Smartwin display interface

Size: A3	Date: 2026-10-15	**Rev: B**
KiCad E.D.A. 10.0.6		Id: 1/4

Bottom-mounted DF23 plug. Pin orientation follows Smartwin mechanical drawing Detail A. All supply/GND pins used.




ProtoMate

Sheet: /display/
File: display.kicad_sch

Title: display-adapter / display

Size: A3	Date: 2026-10-15	**Rev: B**
KiCad E.D.A. 10.0.6		Id: 2/4

80-way Type-A (same-side contacts), 0.5mm pitch, 0.30mm mating thickness. GIGA pin n <-> display socket pin 81-n.





ProtoMate		
Sheet: /ribbon/		
File: ribbon.kicad_sch		
Title: display-adapter / ribbon		
Size: A3	Date: 2026-10-15	**Rev: B**
KiCad E.D.A. 10.0.6		Id: 3/4

3.30V +/−1% regulated input, >=2A continuous. Q1 D=input / S=output. Backlight power does not pass through FFC.































































ProtoMate

Sheet: /power/
File: power.kicad_sch

Title: display-adapter / power

Size: A3	Date: 2026-10-15	**Rev: B**
KiCad E.D.A. 10.0.6		Id: 4/4