

# The Adaptive Method of Lines

## CDEs Group Presentation

Shian Su, Ria Szeregi and Kenneth Young

University of Melbourne

23<sup>rd</sup> of May, 2016



# Motivation

## Method of lines

- Discretise in space (ie using finite difference) to generate a system of ODEs.
- Solve the system using some solver such as ode15s.
- Temporal accuracy guaranteed by the ODE solver, however spatial accuracy results from the discretisation used.


# Motivation

## Mesh adaptation

- Method of lines discretises the space uniformly.
- Using a high density uniform mesh to achieve high spatial accuracy wastes nodes in regions of low activity.
- Want to adapt the spatial mesh such that nodes are efficiently placed.

# Method of Lines - Burgers' Equation

- content



# Equidistribution Principle

## Tracking the action

- We want to assign nodes to areas with high activity.
- Use some monitor function  $m(x)$  to measure the activity in a region.
- Choose the  $x_i$  such that for all  $i$ ,  $\int_{x_{i-1}}^{x^i} = \int_{x_i}^{x^{i+1}}$

# Choice of Monitor Function

- content
- content
- content

# Moving Mesh

- content
- content
- content

# Moving Mesh - KDV Equation Example 1

- Time step = 10

# Moving Mesh - KDV Equation Example 2

- Time step = 2

# Moving Mesh - Burgers' Equation Example 1

- Time step = 0.1

# Moving Mesh - Burgers' Equation Example 2

- Time step = 0.01

# Mesh Refinement

- content
- content
- content

# Mesh Refinement - Burgers' Equation Example 1

- Time step = 0.1

# Mesh Refinement - Burgers' Equation Example 2

- Time step = 0.01

# Dynamic Method

- content
- content
- content

# Dynamic Method - Burgers' Equation Example

- Number of mesh points = 51

This is the last slide.

Any questions?