

Лабораторная работа №3 Дисциплина: Моделирование сетей передачи данных

Леснухин Даниил Дмитриевич Российский университет
дружбы народов Москва

Цель работы

Основной целью работы является:

- Ознакомление с NETEM
- Проведение интерактивных и воспроизводимых экспериментов
- Измерение задержки и дрожания (jitter) в Mininet

Задание

- Создать простейшую топологию с 2 хостами и 1 коммутатором
- Добавить/изменить задержку, джиттер, корреляцию и распределение времени задержки
- Реализовать воспроизводимые эксперименты и построить графики

Теоретическое введение

- Mininet — эмулятор компьютерной сети
- Поддержка хостов, коммутаторов и OpenFlow-контроллеров
- Настройка сетевых интерфейсов, проверка ping
- NETEM — инструмент для тестирования задержки и дрожания

Запуск лабораторной топологии

- Подключаемся к виртуальной машине
- Исправляем права запуска X-соединения
- Копируем MIT magic cookie для пользователя root

```
root@mininet-vm: ~  
login as: mininet  
mininet@192.168.56.3's password:  
Welcome to Ubuntu 20.04.1 LTS (GNU/Linux 5.4.0-42-generic x86_64)  
  
* Documentation:  https://help.ubuntu.com  
* Management:    https://landscape.canonical.com  
* Support:        https://ubuntu.com/advantage  
  
Failed to connect to https://changelogs.ubuntu.com/meta-release-lts. Check your  
Internet connection or proxy settings  
  
Last login: Thu Feb  5 03:06:47 2026 from 192.168.56.1  
mininet@mininet-vm:~$ xauth list $DISPLAY  
mininet-vm/unix:10  MIT-MAGIC-COOKIE-1  8bc7d48dfdf8fd34d1f62dff277b12d  
mininet@mininet-vm:~$ sudo -i  
root@mininet-vm:~# xauth list add^C  
root@mininet-vm:~# xauth list $DISPLAY  
mininet-vm/unix:10  MIT-MAGIC-COOKIE-1  fc04f721fac8ad00af30da488e9b15bd  
root@mininet-vm:~# xauth remove $DISPLAY  
root@mininet-vm:~# xauth list $DISPLAY  
root@mininet-vm:~# xauth add mininet-vm/unix:10  MIT-MAGIC-COOKIE-1  8bc7d48dfdf8fd34d1f62dff277b12d  
root@mininet-vm:~# xauth list $DISPLAY  
mininet-vm/unix:10  MIT-MAGIC-COOKIE-1  8bc7d48dfdf8fd34d1f62dff277b12d  
root@mininet-vm:~# █
```

Простейшая топология

- 2 хоста и 1 коммутатор
- Интерфейсы h1-eth0 и h2-eth0

```
root@mininet-vm:/home/mininet# ifconfig
h2-eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.0.2 netmask 255.0.0.0 broadcast 10.255.255.255
    ether aa:51:el:44:c3:6b txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 1170 bytes 254296 (254.2 KB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 1170 bytes 254296 (254.2 KB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@mininet-vm:/home/mininet#

root@mininet-vm:/home/mininet# ifconfig
h1-eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.0.0.1 netmask 255.0.0.0 broadcast 10.255.255.255
    ether 86:10:be:4d:89:f4 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
```

Проверка соединения

- Команда ping -c 6 между h1 и h2

```
host: h2"@mininet-vm
TX packets 0 bytes 0 (0.0 B)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
inet 127.0.0.1 netmask 255.0.0.0
loop txqueuelen 1000 (Local Loopback)
RX packets 1170 bytes 254296 (254.2 KB)
RX errors 0 dropped 0 overruns 0 frame 0
TX packets 1170 bytes 254296 (254.2 KB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

root@mininet-vm:/home/mininet# ping -c 6 10.0.0.1
PING 10.0.0.1 (10.0.0.1) 56(84) bytes of data.
64 bytes from 10.0.0.1: icmp_seq=1 ttl=64 time=1.84 ms
64 bytes from 10.0.0.1: icmp_seq=2 ttl=64 time=0.042 ms
64 bytes from 10.0.0.1: icmp_seq=3 ttl=64 time=0.042 ms
64 bytes from 10.0.0.1: icmp_seq=4 ttl=64 time=0.044 ms
64 bytes from 10.0.0.1: icmp_seq=5 ttl=64 time=0.134 ms
64 bytes from 10.0.0.1: icmp_seq=6 ttl=64 time=0.046 ms

--- 10.0.0.1 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5105ms
rtt min/avg/max/mdev = 0.042/0.357/1.835/0.661 ms
root@mininet-vm:/home/mininet#
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=0.118 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=0.042 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=0.033 ms

--- 10.0.0.2 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5094ms
rtt min/avg/max/mdev = 0.033/0.422/2.097/0.750 ms
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data.
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=0.084 ms
```

Добавление задержки 100 мс на h1

- `sudo tc qdisc add dev h1-eth0 root netem delay 100ms`
- Проверка `ping -c 6`

```
root@mininet-vm:/home/mininet# sudo tc qdisc add dev h1-eth0 root netem delay 100ms
root@mininet-vm:/home/mininet#
```

```
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data:
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=101 ms
64 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=100 ms
64 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=100 ms
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=101 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=100 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=100 ms

--- 10.0.0.2 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5009ms
rtt min/avg/max/mdev = 100.124/100.422/100.743/0.232 ms
root@mininet-vm:/home/mininet#
```


Добавление двунаправленной задержки 100 мс

- $h1 \rightarrow h2$ и $h2 \rightarrow h1$

```
root@mininet-vm:/home/mininet# sudo tc qdisc add dev h2-eth0 root netem delay 100ms
root@mininet-vm:/home/mininet# 
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=101 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=100 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=100 ms

--- 10.0.0.2 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5009ms
rtt min/avg/max/mdev = 100.124/100.422/100.743/0.232 ms
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data:
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=202 ms
64 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=201 ms
64 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=200 ms
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=201 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=200 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=201 ms

--- 10.0.0.2 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5011ms
rtt min/avg/max/mdev = 200.489/200.830/201.697/0.408 ms
root@mininet-vm:/home/mininet#
```

Изменение задержки до 50 мс на каждом хосте

- RTT проверка ping -c 6

```
root@mininet-vm:/home/mininet# sudo tc qdisc change dev h2-eth0 root netem delay 50ms
```

```
root@mininet-vm:/home/mininet#
```

```
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=201 ms
```

```
--- 10.0.0.2 ping statistics ---
```

```
6 packets transmitted, 6 received, 0% packet loss, time 5011ms
```

```
rtt min/avg/max/mdev = 200.489/200.830/201.697/0.408 ms
```

```
root@mininet-vm:/home/mininet# sudo tc qdisc change dev h1-eth0 root netem delay 50ms
```

```
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
```

```
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data:
```

```
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=101 ms
```

```
64 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=101 ms
```

```
64 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=101 ms
```

```
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=101 ms
```

```
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=101 ms
```

```
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=100 ms
```

```
--- 10.0.0.2 ping statistics ---
```

```
6 packets transmitted, 6 received, 0% packet loss, time 5009ms
```

```
rtt min/avg/max/mdev = 100.184/100.728/101.197/0.361 ms
```

```
root@mininet-vm:/home/mininet#
```

Восстановление исходных значений

- `sudo tc qdisc del dev h1-eth0 root netem`
- `sudo tc qdisc del dev h2-eth0 root netem`

```
root@mininet-vm:/home/mininet# sudo tc qdisc del dev h2-eth0 root netem
root@mininet-vm:/home/mininet# █
tt min/avg/max/mdev = 100.184/100.728/101.197/0.361 ms
root@mininet-vm:/home/mininet#
root@mininet-vm:/home/mininet#
root@mininet-vm:/home/mininet#
root@mininet-vm:/home/mininet#
root@mininet-vm:/home/mininet#
root@mininet-vm:/home/mininet# sudo tc qdisc del dev h1-eth0 root netem
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data.
 4 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=1.83 ms
 4 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=0.481 ms
 4 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=0.161 ms
 4 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=0.048 ms
 4 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=0.053 ms
 4 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=0.040 ms

-- 10.0.0.2 ping statistics --
 6 packets transmitted, 6 received, 0% packet loss, time 5077ms
tt min/avg/max/mdev = 0.040/0.435/1.828/0.641 ms
root@mininet-vm:/home/mininet# █
```

Добавление дрожания ± 10 мс

- RTT проверка ping -c 6

```
root@mininet-vm:/home/mininet# sudo tc qdisc add dev h1-eth0 root netem delay 100ms 10ms
root@mininet-vm:/home/mininet# ping -c 6 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data:
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=103 ms
64 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=96.3 ms
64 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=104 ms
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=91.6 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=93.1 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=92.9 ms

--- 10.0.0.2 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5010ms
rtt min/avg/max/mdev = 91.591/96.824/103.618/4.927 ms
root@mininet-vm:/home/mininet#
```

Добавление корреляции 25% для джиттера

- Задержка $100\text{ ms} \pm 10\text{ ms}$
- Проверка ping -c 20

```
"host: h1"@mininet-vm
54 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=98.4 ms
54 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=104 ms
54 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=110 ms
54 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=99.1 ms
54 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=92.7 ms
54 bytes from 10.0.0.2: icmp_seq=7 ttl=64 time=90.4 ms
54 bytes from 10.0.0.2: icmp_seq=8 ttl=64 time=102 ms
54 bytes from 10.0.0.2: icmp_seq=9 ttl=64 time=99.9 ms
54 bytes from 10.0.0.2: icmp_seq=10 ttl=64 time=103 ms
54 bytes from 10.0.0.2: icmp_seq=11 ttl=64 time=95.5 ms
54 bytes from 10.0.0.2: icmp_seq=12 ttl=64 time=103 ms
54 bytes from 10.0.0.2: icmp_seq=13 ttl=64 time=110 ms
54 bytes from 10.0.0.2: icmp_seq=14 ttl=64 time=90.2 ms
54 bytes from 10.0.0.2: icmp_seq=15 ttl=64 time=109 ms
54 bytes from 10.0.0.2: icmp_seq=16 ttl=64 time=91.2 ms
54 bytes from 10.0.0.2: icmp_seq=17 ttl=64 time=108 ms
54 bytes from 10.0.0.2: icmp_seq=18 ttl=64 time=96.7 ms
54 bytes from 10.0.0.2: icmp_seq=19 ttl=64 time=95.5 ms
54 bytes from 10.0.0.2: icmp_seq=20 ttl=64 time=93.6 ms

--- 10.0.0.2 ping statistics ---
20 packets transmitted, 20 received, 0% packet loss, time 19033ms
```

Нормальное распределение задержки ± 20 мс


- Проверка ping -c 10
- Завершение работы Mininet

```
root@mininet-vm:/home/mininet# sudo tc qdisc add dev h1-eth0 root netem delay 1
90ms 20ms distribution normal
root@mininet-vm:/home/mininet# ping -c 10 10.0.0.2
PING 10.0.0.2 (10.0.0.2) 56(84) bytes of data.
64 bytes from 10.0.0.2: icmp_seq=1 ttl=64 time=125 ms
64 bytes from 10.0.0.2: icmp_seq=2 ttl=64 time=113 ms
64 bytes from 10.0.0.2: icmp_seq=3 ttl=64 time=82.5 ms
64 bytes from 10.0.0.2: icmp_seq=4 ttl=64 time=115 ms
64 bytes from 10.0.0.2: icmp_seq=5 ttl=64 time=103 ms
64 bytes from 10.0.0.2: icmp_seq=6 ttl=64 time=98.8 ms
64 bytes from 10.0.0.2: icmp_seq=7 ttl=64 time=96.8 ms
64 bytes from 10.0.0.2: icmp_seq=8 ttl=64 time=95.1 ms
64 bytes from 10.0.0.2: icmp_seq=9 ttl=64 time=78.0 ms
64 bytes from 10.0.0.2: icmp_seq=10 ttl=64 time=116 ms

--- 10.0.0.2 ping statistics ---
10 packets transmitted, 10 received, 0% packet loss, time 9015ms
rtt min/avg/max/mdev = 77.957/102.259/124.701/14.327 ms
root@mininet-vm:/home/mininet#
```

Воспроизводимые эксперименты

- Создание каталогов simple-delay, change-delay и т.п.
- Скрипты lab_netem_i.py для экспериментов
- Скрипты ping_plot для визуализации



```
mininet@mininet-vm: ~/work/lab_netem_i/simple-delay
GNU nano 4.8 lab_netem_i.py Modified
#!/usr/bin/env python

"""
Simple experiment.
Output: ping.dat
"""

from mininet.net import Mininet
from mininet.node import Controller
from mininet.cli import CLI

from mininet.log import setLogLevel, info
import time

def emptyNet():
    "Create an empty network and add nodes to it."
    net = Mininet( controller=Controller, waitConnected=True )

    info( '*** Adding controller\n' )
    net.addController( 'c0' )

    info( '*** Adding hosts\n' )
    h1 = net.addHost( 'h1', ip='10.0.0.1' )
    h2 = net.addHost( 'h2', ip='10.0.0.2' )


    info( '*** Adding switch\n' )
    s1 = net.addSwitch( 's1' )

    info( '*** Creating links\n' )
    net.addLink( h1, s1 )
    net.addLink( h2, s1 )

    info( '*** Starting network\n' )
```

Визуализация результатов

- Скрипт `ping_plot` строит график по данным эксперимента

 mininet@mininet-vm: ~/work/lab_netem_i/simple-delay

GNU nano 4.8

```
all: ping.dat ping.png
```

```
ping.dat:
```

```
    sudo python lab_netem_i.py
```

```
    sudo chown mininet:mininet ping.dat
```

```
ping.png: ping.dat
```

```
    ./ping_plot
```

```
clean:
```

```
    rm -f *.dat *.png
```



Настройка прав на скрипт

- `chmod +x ping_plot`

```
mininet@mininet-vm:~/work/lab_netem_i/simple-delaymake
sudo python lab_netem_i.py
*** Adding controller
*** Adding hosts
*** Adding switch
*** Creating links
*** Starting network
*** Configuring hosts
h1 h2
*** Starting controller
c0
*** Starting 1 switches
s1 ...
*** Waiting for switches to connect
s1
*** Set delay
*** h1 : ('tc qdisc add dev h1-eth0 root netem delay 100ms',)
*** h2 : ('tc qdisc add dev h2-eth0 root netem delay 100ms',)
*** Ping
*** h1 : ('ping -c 100', '10.0.0.2', '| grep "time=" | awk \'{print $5, $7}\''
sed -e \'/s/time=//g\' -e \'/s/icmp_seq=//g\' > ping.dat')
*** Stopping network*** Stopping 1 controllers
c0
*** Stopping 2 links
..
*** Stopping 1 switches
```

Результаты экспериментов

- Графики RTT



Скрипт анализа RTT

- Расчет минимального, среднего, максимального и стандартного отклонения

mininet@mininet-vm: ~/work/lab_netem_i/simple-delay

```
GNU nano 4.8
with open('ping.dat', 'r') as f:
    s = []
    for line in f.readlines():
        if '\n' in line:
            line.replace('\n', "")
            s.append([int(j) for j in (line.split(" "))])
    s = [j[1] for j in s]
    std = (sum([(i - (sum(s)/len(s)))**2 for i in s])/(len(s)-1))**0.5
    print(f"min: {{min(s)}} \max: {mas(s)} \n avg: {sum(s)/len(s)} \n std: {std}")
```

Выводы

- Ознакомился с NETEM для тестирования задержки
- Провел интерактивные и воспроизводимые эксперименты
- Измерил jitter и распределение задержки
- Построил графики и проверил корректность экспериментов