

# Experts and Adversarial Bandits

## Algorithms and Analysis

<sup>1</sup>ECE  
Technical University of Crete

March 31, 2023

## So Far: assumed arm rewards are IID (“stochastic”)

- Q: Let reward for arm  $i$  take value 1 with probability  $p_i$  or 0 with probability  $1 - p_i$ . Does this satisfy the stochastic MAB environment assumptions?

## So Far: assumed arm rewards are IID (“stochastic”)

- Q: Let reward for arm  $i$  take value 1 with probability  $p_i$  or 0 with probability  $1 - p_i$ . Does this satisfy the stochastic MAB environment assumptions?
- A: Yes! This was the typical example we considered in our code.

## So Far: assumed arm rewards are IID (“stochastic”)

- Q: Let reward for arm  $i$  take value 1 with probability  $p_i$  or 0 with probability  $1 - p_i$ . Does this satisfy the stochastic MAB environment assumptions?
- A: Yes! This was the typical example we considered in our code.
- Q: What if reward for  $i$  is uniformly chosen in the interval  $[0.2, 0.7]$  at every round?

## So Far: assumed arm rewards are IID (“stochastic”)

- Q: Let reward for arm  $i$  take value 1 with probability  $p_i$  or 0 with probability  $1 - p_i$ . Does this satisfy the stochastic MAB environment assumptions?
- A: Yes! This was the typical example we considered in our code.
- Q: What if reward for  $i$  is uniformly chosen in the interval  $[0.2, 0.7]$  at every round?
- A: Yes! This is also part of our framework so far (and is what is asked in your 1st assignment).

- Q: Assume arm  $i$  is a simple 2-state Markov chain: Its reward is either 0 or 1 again, but consecutive rewards work as follows:

- Q: Assume arm  $i$  is a simple 2-state Markov chain: Its reward is either 0 or 1 again, but consecutive rewards work as follows:
  - When previous reward was 0, next reward is 1 with probability  $p$ , or 0 with probability  $1 - p$ .
  - When previous reward was 1, next reward is 0 with probability  $q$ , or 1 with probability  $1 - q$ .
  - The first reward (at time 0) is 0.

- Q: Assume arm  $i$  is a simple 2-state Markov chain: Its reward is either 0 or 1 again, but consecutive rewards work as follows:
  - When previous reward was 0, next reward is 1 with probability  $p$ , or 0 with probability  $1 - p$ .
  - When previous reward was 1, next reward is 0 with probability  $q$ , or 1 with probability  $1 - q$ .
  - The first reward (at time 0) is 0.

Is *this* a “stochastic” MAB?



- Q: Assume arm  $i$  is a simple 2-state Markov chain: Its reward is either 0 or 1 again, but consecutive rewards work as follows:
  - When previous reward was 0, next reward is 1 with probability  $p$ , or 0 with probability  $1 - p$ .
  - When previous reward was 1, next reward is 0 with probability  $q$ , or 1 with probability  $1 - q$ .
  - The first reward (at time 0) is 0.

Is *this* a “stochastic” MAB?

- A: Not really...(food for thought: where does the proof break?)

# Non-IID rewards (cnt'd)

- Q: How about if arm  $i$  has reward 1 for the first  $T/2$  rounds, then reward 0 for the rest  $T/2$ .

# Non-IID rewards (cnt'd)

- Q: How about if arm  $i$  has reward 1 for the first  $T/2$  rounds, then reward 0 for the rest  $T/2$ .
- A: No! unfortunately reward process is not stationary.

# Non-IID rewards (cnt'd)

- Q: How about if arm  $i$  has reward 1 for the first  $T/2$  rounds, then reward 0 for the rest  $T/2$ .
- A: No! unfortunately reward process is not stationary.
- Q: What if an adversary knows our algorithm and thus which arm we will play in the next round, then sets all other rewards to 1 and the chosen arm only to 0??

# Non-IID rewards (cnt'd)

- Q: How about if arm  $i$  has reward 1 for the first  $T/2$  rounds, then reward 0 for the rest  $T/2$ .
- A: No! unfortunately reward process is not stationary.
- Q: What if an adversary knows our algorithm and thus which arm we will play in the next round, then sets all other rewards to 1 and the chosen arm only to 0??
- A: This is an “adversarial” bandit  $\rightarrow$  seems like a more difficult (hopeless?) environment

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.



# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.
- It sets reward for chosen arm to 0, and other arm to 1.

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.
- It sets reward for chosen arm to 0, and other arm to 1.
- Quiz: What is the best regret we can hope for?

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.
- It sets reward for chosen arm to 0, and other arm to 1.
- Quiz: What is the best regret we can hope for?
- Reward  $R(T) = 0$  for the algorithm

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.
- It sets reward for chosen arm to 0, and other arm to 1.
- Quiz: What is the best regret we can hope for?
- Reward  $R(T) = 0$  for the algorithm
- Reward for other arm (which is optimal)  $R^*(T) \geq T/2$

# Stochastic MAB algorithms for Adversarial Bandits

- We would like algorithms that have *sublinear regret* even for adversarial bandits.
- Q: Would deterministic algorithms (e.g., Explore-then-Exploit, UCB) work in such environments?

## Example

- Assume 2 arms only
- Adversary knows our algorithm. Since it's deterministic, it also knows the arm it will pick next.
- It sets reward for chosen arm to 0, and other arm to 1.
- Quiz: What is the best regret we can hope for?
- Reward  $R(T) = 0$  for the algorithm
- Reward for other arm (which is optimal)  $R^*(T) \geq T/2$

## Theorem

Any deterministic algorithm fails: it achieves  $\Omega(T)$  (i.e. linear) regret!

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$



# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played)

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k$

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$



# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$  (always gets 1 when not chosen)

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$  (always gets 1 when not chosen)
  - $\text{Regret}^T = R_*^T - R_{\text{algo}}^T$

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$  (always gets 1 when not chosen)
  - $\text{Regret}^T = R_*^T - R_{\text{algo}}^T \geq T - T/k - 0$

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$  (always gets 1 when not chosen)
  - $\text{Regret}^T = R_*^T - R_{\text{algo}}^T \geq T - T/k - 0 = O(T)$

# Adversarial Bandits: A Negative Result

## Proof of linear regret

- Assume the previous adversarial environment.
- Let  $Q_i$  denote again the number of times arm  $i$  was played by the algorithm
- (1) Optimal arm  $i^* = \operatorname{argmin}_i \{Q_1, Q_2, \dots, Q_k\}$  (arm gets reward 1, unless it is played  $\Rightarrow$  best arm is the one least chosen by our algorithm).
- Claim:  $Q_{i^*} \leq T/k$ .
  - Proof by contradiction: Assume  $Q_{i^*} > T/k$ .
  - $Q_j \geq Q_{i^*} > T/k, \forall j$  (because of (1))
  - Hence  $\sum_{i=1}^k Q_i > \sum_{i=1}^k T/k > T$  (not possible)
  - Optimal reward  $R_*^T \geq T - T/k$  (always gets 1 when not chosen)
  - $\text{Regret}^T = R_*^T - R_{\text{algo}}^T \geq T - T/k - 0 = O(T)$

- In other words *even UCB would not give sublinear regret in this setup*

# Experts Framework

Adversarial Bandit problem have two difficulties:

# Experts Framework

Adversarial Bandit problem have two difficulties:

- 1 **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits

# Experts Framework

Adversarial Bandit problem have two difficulties:

- 1 **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- 2 **Partially Observable:** Only learn reward for played arm.



# Experts Framework

Adversarial Bandit problem have two difficulties:

- ① **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- ② **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

# Experts Framework

Adversarial Bandit problem have two difficulties:

- ① **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- ② **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)

# Experts Framework

Adversarial Bandit problem have two difficulties:

- ① **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- ② **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)
- Their goal is to predict the true label at time  $t$ ,  $y(t) \in \{0, 1\}$

# Experts Framework

Adversarial Bandit problem have two difficulties:

- ① **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- ② **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)
- Their goal is to predict the true label at time  $t$ ,  $y(t) \in \{0, 1\}$
- Algorithm chooses
$$\hat{y}(t) = f(x_1(0 \dots t), x_2(0 \dots t), \dots, x_k(0 \dots t), y(0 \dots t - 1))$$

# Experts Framework

Adversarial Bandit problem have two difficulties:

- 1 **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- 2 **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)
- Their goal is to predict the true label at time  $t$ ,  $y(t) \in \{0, 1\}$
- Algorithm chooses  $\hat{y}(t) = f(x_1(0 \dots t), x_2(0 \dots t), \dots, x_k(0 \dots t), y(0 \dots t - 1))$  (i.e., as some function of **current and past** expert predictions)

# Experts Framework

Adversarial Bandit problem have two difficulties:

- 1 **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- 2 **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)
- Their goal is to predict the true label at time  $t$ ,  $y(t) \in \{0, 1\}$
- Algorithm chooses  $\hat{y}(t) = f(x_1(0 \dots t), x_2(0 \dots t), \dots, x_k(0 \dots t), y(0 \dots t - 1))$  (i.e., as some function of **current and past** expert predictions **and past outcomes**.)

# Experts Framework

Adversarial Bandit problem have two difficulties:

- 1 **Hard to predict:** Rewards per arm harder to “predict” than stochastic bandits
- 2 **Partially Observable:** Only learn reward for played arm.

*Experts* framework: address 1st difficulty, and relax the 2nd (for now).

## Experts: simple classification setup

- $k$  experts: expert  $i$  predicts  $x_i(t) \in \{0, 1\}$  (these are binary classifiers predicting e.g., spam, elections, image class, football score)
- Their goal is to predict the true label at time  $t$ ,  $y(t) \in \{0, 1\}$
- Algorithm chooses  $\hat{y}(t) = f(x_1(0 \dots t), x_2(0 \dots t), \dots, x_k(0 \dots t), y(0 \dots t - 1))$  (i.e., as some function of **current and past** expert predictions **and past** outcomes.)
- True label  $y(t)$  is revealed after  $\hat{y}(t)$  is chosen, and a **loss** is incurred (e.g.,  $-1$ ) for every misclassification

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes



# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)
  - Let  $N_1^t = \{i \in K^t : x_i(t) = 1\}$  (experts predicting 1)

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)
  - Let  $N_1^t = \{i \in K^t : x_i(t) = 1\}$  (experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $\|N_0^t\| \geq \|N_1^t\|$

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)
  - Let  $N_1^t = \{i \in K^t : x_i(t) = 1\}$  (experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $\|N_0^t\| \geq \|N_1^t\|$
    - $\hat{y}(t) = 1$ , if  $\|N_0^t\| < \|N_1^t\|$

# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)
  - Let  $N_1^t = \{i \in K^t : x_i(t) = 1\}$  (experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $\|N_0^t\| \geq \|N_1^t\|$
    - $\hat{y}(t) = 1$ , if  $\|N_0^t\| < \|N_1^t\|$
  - $K^{t+1} = K^t \setminus \{i : x_i(t) \neq y(t)\}$



# Algorithm 1: Majority rule

**Assume first:** there exists an expert  $i^*$  that never makes mistakes

## Majority Rule (MR) Algorithm

- Start with set  $K^0 = \{1, 2, \dots, k\}$  (experts with no mistakes yet)
- At round  $t$ :
  - Let  $N_0^t = \{i \in K^t : x_i(t) = 0\}$  (experts predicting 0)
  - Let  $N_1^t = \{i \in K^t : x_i(t) = 1\}$  (experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $\|N_0^t\| \geq \|N_1^t\|$
    - $\hat{y}(t) = 1$ , if  $\|N_0^t\| < \|N_1^t\|$
  - $K^{t+1} = K^t \setminus \{i : x_i(t) \neq y(t)\}$  (remove experts that made a mistake)

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ .

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ . (1)  $\Rightarrow \|K^{t+1}\| \leq \frac{k}{2^N}$

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ . (1)  $\Rightarrow \|K^{t+1}\| \leq \frac{k}{2^N}$  (every mistake cuts set  $K$  by at least  $1/2$ ).



# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ . (1)  $\Rightarrow \|K^{t+1}\| \leq \frac{k}{2^N}$  (every mistakes cuts set  $K$  by at least  $1/2$ ).
- 3 But  $\|K^t\| \geq 1, \forall t$  (since there is a perfect expert)

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ . (1)  $\Rightarrow \|K^{t+1}\| \leq \frac{k}{2^N}$  (every mistake cuts set  $K$  by at least 1/2).
- 3 But  $\|K^t\| \geq 1, \forall t$  (since there is a perfect expert)  
(2)  $\Rightarrow \frac{k}{2^N} \geq 1$

# Majority Rule (MR) Performance

- Quiz: how many mistakes does MR make?

## Theorem

Majority rule algorithm makes  $\log_2 k$  mistakes (if a perfect expert exists)

## Proof:

- 1 If  $\hat{y}(t) \neq y(t)$  (mistake), then  $\|K^{t+1}\| \leq \frac{\|K^t\|}{2}$  (majority - i.e., more than half of experts - made a mistake)
- 2 Assume the  $N^{\text{th}}$  mistake took place at round  $t$ .  $(1) \Rightarrow \|K^{t+1}\| \leq \frac{k}{2^N}$  (every mistake cuts set  $K$  by at least  $1/2$ ).
- 3 But  $\|K^t\| \geq 1, \forall t$  (since there is a perfect expert)  
 $(2) \Rightarrow \frac{k}{2^N} \geq 1 \Rightarrow N \leq \log_2 k$

# Non-perfect Experts

- Assume now that every expert can make mistakes.

# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?

# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?
- Answer: Normally, MR will eliminate all experts at some point.

# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?
- Answer: Normally, MR will eliminate all experts at some point. Even if we assume it stops when  $\|K^t\| = 1$ , MR makes  $O(T)$  mistakes if no expert is perfect. Why?

# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?
- Answer: Normally, MR will eliminate all experts at some point. Even if we assume it stops when  $\|K^t\| = 1$ , MR makes  $O(T)$  mistakes if no expert is perfect. Why?
- Finite probability that the best expert will be eliminated prematurely. Then regret will accumulate linearly.



# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?
- Answer: Normally, MR will eliminate all experts at some point. Even if we assume it stops when  $\|K^t\| = 1$ , MR makes  $O(T)$  mistakes if no expert is perfect. Why?
- Finite probability that the best expert will be eliminated prematurely. Then regret will accumulate linearly. (in fact, this probability goes to 1 as  $k \rightarrow \infty$ )

# Non-perfect Experts

- Assume now that every expert can make mistakes.
- Quiz: What is the expected number of mistakes the MR algorithms makes in  $T$  steps?
- Answer: Normally, MR will eliminate all experts at some point. Even if we assume it stops when  $\|K^t\| = 1$ , MR makes  $O(T)$  mistakes if no expert is perfect. Why?
- Finite probability that the best expert will be eliminated prematurely. Then regret will accumulate linearly. (in fact, this probability goes to 1 as  $k \rightarrow \infty$ )
- Solution: Need to keep track of “error-prone” experts, without eliminating!

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

### Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ .

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

### Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

### Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

### Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :



# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)

## Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

### Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$
    - $\hat{y}(t) = 1$ , if  $W_0^{(t)} < W_1^{(t)}$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$
    - $\hat{y}(t) = 1$ , if  $W_0^{(t)} < W_1^{(t)}$
  - $w_i^{(t+1)} = (1 - \eta)w_i^{(t)}$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$
    - $\hat{y}(t) = 1$ , if  $W_0^{(t)} < W_1^{(t)}$
  - $w_i^{(t+1)} = (1 - \eta)w_i^{(t)}, \forall i : x_i(t) \neq y(t)$

# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$
    - $\hat{y}(t) = 1$ , if  $W_0^{(t)} < W_1^{(t)}$
  - $w_i^{(t+1)} = (1 - \eta)w_i^{(t)}, \forall i : x_i(t) \neq y(t)$  (discount weight if wrong)



# Algorithm 2: Weighted Majority Rule (WMR)

**Assume:** every expert makes mistakes (but one makes the fewest)

## Weighted Majority Rule (MR) Algorithm

- Let  $w_i^{(t)}$  denote the weight of expert  $i$  at round  $t$ . Set  $w_i^{(0)} = 1, \forall i$
- Let  $W^{(t)} = \sum_{i=1}^k w_i^{(t)}$
- Let  $\eta \in (0, 1/2]$
- At round  $t$ :
  - Let  $W_0^{(t)} = \sum_{i: x_i(t)=0} w_i^{(t)}$  (total weight of experts predicting 0)
  - Let  $W_1^{(t)} = \sum_{i: x_i(t)=1} w_i^{(t)}$  (total weight of experts predicting 1)
  - Choose:
    - $\hat{y}(t) = 0$ , if  $W_0^{(t)} \geq W_1^{(t)}$
    - $\hat{y}(t) = 1$ , if  $W_0^{(t)} < W_1^{(t)}$
  - $w_i^{(t+1)} = (1 - \eta)w_i^{(t)}, \forall i : x_i(t) \neq y(t)$  (discount weight if wrong)
  - $w_i^{(t+1)} = w_i^{(t)}, \forall i : x_i(t) = y(t)$  (same weight if correct)

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$1 \quad W^{(t+1)} = \sum_i w_i^{(t+1)}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$1 \quad W^{(t+1)} = \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$1 \quad W^{(t+1)} = \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} \end{aligned}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \end{aligned}$$



# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \end{aligned}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \end{aligned}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

$$(5) \Rightarrow W^{(T+1)} \leq (1 - \eta/2)^{M_{\text{ALG}}} \cdot W^{(0)}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

$$(5) \Rightarrow W^{(T+1)} \leq (1 - \eta/2)^{M_{\text{ALG}}} \cdot W^{(0)} = k(1 - \eta/2)^{M_{\text{ALG}}}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

$$(5) \Rightarrow W^{(T+1)} \leq (1 - \eta/2)^{M_{\text{ALG}}} \cdot W^{(0)} = k(1 - \eta/2)^{M_{\text{ALG}}} \quad (\text{Key Ineq.})$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

$$(5) \Rightarrow W^{(T+1)} \leq (1 - \eta/2)^{M_{\text{ALG}}} \cdot W^{(0)} = k(1 - \eta/2)^{M_{\text{ALG}}} \quad (\text{Key Ineq.})$$

$$(6) \text{ Also: } W^{(T+1)} \geq w_{i^*}^{(T+1)}$$

# Performance of Algorithm 2 (WMR)

Quiz: How many more mistakes than best expert does WMR make?

## Theorem

If  $M^*$  is the number of mistakes of the best expert, and  $M_{\text{ALG}}$  the number of mistakes of Weighted Majority Rule, then  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

**Proof:** If a mistake is made at round  $t$ , then:

$$\begin{aligned} 1 \quad W^{(t+1)} &= \sum_i w_i^{(t+1)} = \sum_{i: x_i(t) \neq y(t)} w_i^{(t+1)} + \sum_{i: x_i(t) = y(t)} w_i^{(t+1)} \\ 2 \quad &\stackrel{(\text{def. of } w_i^{(t+1)})}{=} \sum_{i: x_i(t) \neq y(t)} (1 - \eta) w_i^{(t)} + \sum_{i: x_i(t) = y(t)} w_i^{(t)} \\ 3 \quad &\leq (1 - \eta) W^{(t)} / 2 + W^{(t)} / 2 \quad (\text{mistake} \Rightarrow \text{majority weight} \geq W^{(t)} / 2) \\ 4 \quad &\Rightarrow W^{(t+1)} \leq (1 - \eta/2) W^{(t)} \end{aligned}$$

$$(5) \Rightarrow W^{(T+1)} \leq (1 - \eta/2)^{M_{\text{ALG}}} \cdot W^{(0)} = k(1 - \eta/2)^{M_{\text{ALG}}} \quad (\text{Key Ineq.})$$

$$(6) \text{ Also: } W^{(T+1)} \geq w_{i^*}^{(T+1)} = (1 - \eta)^{M^*} \quad (\text{Key Ineq.})$$



# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

$$7 \text{ by (5),(6)} \Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{\text{ALG}}}$$

# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

7 by (5),(6)  $\Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{ALG}}$

8 taking logs  $\Rightarrow M^* \cdot \ln(1 - \eta) \leq \ln k + M_{ALG} \cdot \ln(1 - \eta/2)$


# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

7 by (5),(6)  $\Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{\text{ALG}}}$

8 taking logs  $\Rightarrow M^* \cdot \ln(1 - \eta) \leq \ln k + M_{\text{ALG}} \cdot \ln(1 - \eta/2)$

9 Will use known formula:  $-z - z^2 \leq \ln(1 - z) \leq -z$ .




# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

7 by (5),(6)  $\Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{\text{ALG}}}$

8 taking logs  $\Rightarrow M^* \cdot \ln(1 - \eta) \leq \ln k + M_{\text{ALG}} \cdot \ln(1 - \eta/2)$

9 Will use known formula:  $-z - z^2 \leq \ln(1 - z) \leq -z$ .



10  $\stackrel{(9)}{\Rightarrow} M^* \cdot (-\eta - \eta^2)$


# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

7 by (5),(6)  $\Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{ALG}}$

8 taking logs  $\Rightarrow M^* \cdot \ln(1 - \eta) \leq \ln k + M_{ALG} \cdot \ln(1 - \eta/2)$

9 Will use known formula:  $-z - z^2 \leq \ln(1 - z) \leq -z$ .



10  $\stackrel{(9)}{\Rightarrow} M^* \cdot (-\eta - \eta^2) \leq \ln k - \eta/2 \cdot M_{ALG}$


# Performance of Algorithm 2 (WMR) - cnt'd

## Proof(cnt'd):

7 by (5),(6)  $\Rightarrow (1 - \eta)^{M^*} \leq k(1 - \eta/2)^{M_{\text{ALG}}}$

8 taking logs  $\Rightarrow M^* \cdot \ln(1 - \eta) \leq \ln k + M_{\text{ALG}} \cdot \ln(1 - \eta/2)$

9 Will use known formula:  $-z - z^2 \leq \ln(1 - z) \leq -z$ .



10  $\stackrel{(9)}{\Rightarrow} M^* \cdot (-\eta - \eta^2) \leq \ln k - \eta/2 \cdot M_{\text{ALG}}$

11  $M_{\text{ALG}} \leq (2 + 2\eta) \cdot M^* + 2 \frac{\ln k}{\eta}$

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.



# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

Result Observations:  $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ :

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

## Result Observations: $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ : WMR makes *at least* twice as many errors

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

## Result Observations: $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ : WMR makes *at least* twice as many errors
- large  $\eta (\rightarrow 1/2) \Rightarrow M_{ALG} \leq 3M^* + \ln k$ :

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

## Result Observations: $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ : WMR makes *at least* twice as many errors
- large  $\eta (\rightarrow 1/2) \Rightarrow M_{ALG} \leq 3M^* + \ln k$ : could be better if horizon  $T$  is small and/or number of experts  $k$  is large.

# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

## Result Observations: $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ : WMR makes *at least* twice as many errors
- large  $\eta (\rightarrow 1/2) \Rightarrow M_{ALG} \leq 3M^* + \ln k$ : could be better if horizon  $T$  is small and/or number of experts  $k$  is large.
- optimal  $\eta$ ?  $\Rightarrow \eta_{opt} = \sqrt{\frac{\ln K}{2M^*}}$ :



# Observations about WMR performance & Proof

## Methodology Observations

- Before: how fast  $K^{(t)}$  reduces? Now: how fast  $W^{(t)}$  reduces?
- MR (Algo 1) was setting  $\eta = 1 \Rightarrow w_i(t)$  goes to 0 after 1 mistake.
- Key Inequality (5): captures how fast the weight  $W^{(t)}$  of our WMR can drop, as mistakes are made.
- Key Inequality (6): lower bounds this as a function of best expert's mistakes  $\Rightarrow$  if  $W^{(t)}$  were lower the best expert would be chosen

## Result Observations: $M_{ALG} \leq (2 + 2\eta) \cdot M^* + 2\frac{\ln k}{\eta}$

- small  $\eta (\rightarrow 0) \Rightarrow M_{ALG} \leq 2M^* + 2\frac{\ln k}{\eta}$ : WMR makes *at least* twice as many errors
- large  $\eta (\rightarrow 1/2) \Rightarrow M_{ALG} \leq 3M^* + \ln k$ : could be better if horizon  $T$  is small and/or number of experts  $k$  is large.
- optimal  $\eta$ ?  $\Rightarrow \eta_{opt} = \sqrt{\frac{\ln K}{2M^*}}$ : See any problem?

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others. . .

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others...

## Multiplicative Weights Algorithm

- Let  $w_i^{(0)} = 1$  (as before)

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others. . .

## Multiplicative Weights Algorithm

- Let  $w_i^{(0)} = 1$  (as before)
- At round  $t$ :

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others...

## Multiplicative Weights Algorithm

- Let  $w_i^{(0)} = 1$  (as before)
- At round  $t$ :
  - Pick expert  $i$  with probability  $p_i = \frac{w_i^t}{\sum_i w_i^t} = \frac{w_i^t}{W^t}$

# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others...

## Multiplicative Weights Algorithm

- Let  $w_i^{(0)} = 1$  (as before)
- At round  $t$ :
  - Pick expert  $i$  with probability  $p_i = \frac{w_i^t}{\sum_i w_i^t} = \frac{w_i^t}{W^t}$
  - Algorithm incurs loss  $l_i^t$



# Algorithm 3: Multiplicative Weights or “Hedge”

So far: Assumed  $x_i(t), y(t) \in \{0, 1\}$  (binary classification)

Generalise: At round  $t$ : expert  $i$  incurs a loss  $l_i^t \in [0, 1]$  (will further generalize later)

Applications: (a) any prediction (regression) task, (b) stock price loss, (c) channel selection performance  $l_i^t = -\log(1 + \text{SNR}_i^t)$ , many others. . .

## Multiplicative Weights Algorithm

- Let  $w_i^{(0)} = 1$  (as before)
- At round  $t$ :
  - Pick expert  $i$  with probability  $p_i = \frac{w_i^t}{\sum_i w_i^t} = \frac{w_i^t}{W^t}$
  - Algorithm incurs loss  $l_i^t$
  - $w_i^{(t+1)} = (1 - \eta)^{l_i^t} \cdot w_i^{(t)}, \forall i$

# Multiplicative Weights: Some Observations

- Key difference is that discount factor  $(1 - \eta)^{l_i^t}$  is applied to every expert. Bigger reduction of weight for experts seeing large loss at that round.

# Multiplicative Weights: Some Observations

- Key difference is that discount factor  $(1 - \eta)^{l_i^t}$  is applied to every expert. Bigger reduction of weight for experts seeing large loss at that round.
- **Note:** We are talking about *losses* and not *rewards* (as in bandits). Hence, we want to minimize losses (like we minimized mistakes).

# Multiplicative Weights: Some Observations

- Key difference is that discount factor  $(1 - \eta)^{l_i^t}$  is applied to every expert. Bigger reduction of weight for experts seeing large loss at that round.
- **Note:** We are talking about *losses* and not *rewards* (as in bandits). Hence, we want to minimize losses (like we minimized mistakes).
- Algorithm does *not* make a (weighted) *majority* decision anymore  $\rightarrow$  it is now randomized and picks one expert at a time (common theme later).

# Multiplicative Weights: Some Observations

- Key difference is that discount factor  $(1 - \eta)^{l_i^t}$  is applied to every expert. Bigger reduction of weight for experts seeing large loss at that round.
- **Note:** We are talking about *losses* and not *rewards* (as in bandits). Hence, we want to minimize losses (like we minimized mistakes).
- Algorithm does *not* make a (weighted) *majority* decision anymore  $\rightarrow$  it is now randomized and picks one expert at a time (common theme later).
- Proof follows very similar methodology like WMR proof.

# Performance of Multiplicative Weights

## **Proof:**

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{I_i^t},$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{I_i^t}, \forall i (\text{including } i^*)$$



# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{I_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{I_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{I_i^t}$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{I_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{I_i^t}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^t}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^t)$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^t}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^t)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^t$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^T}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^T)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^T \stackrel{\text{def. of } p_i}{=} W^T - \eta W^T \cdot \sum_i p_i^T \cdot l_i^T$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^T}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^T)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^T \stackrel{\text{def. of } p_i}{=} W^T - \eta W^T \cdot \sum_i p_i^T \cdot l_i^T$$

$$6 \quad W^T (1 - \eta \cdot l_{ALG}^T)$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^T}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^T)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^T \stackrel{\text{def. of } p_i}{=} W^T - \eta W^T \cdot \sum_i p_i^T \cdot l_i^T$$

$$6 \quad W^T (1 - \eta \cdot l_{ALG}^T) \quad (\text{expected loss } l_{ALG}^T = \sum_i p_i^T \cdot l_i^T)$$



# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^t}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^t)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^t \stackrel{\text{def. of } p_i}{=} W^T - \eta W^T \cdot \sum_i p_i^T \cdot l_i^t$$

$$6 \quad W^T (1 - \eta \cdot l_{ALG}^t) \text{ (expected loss } l_{ALG}^t = \sum_i p_i^T \cdot l_i^t)$$

$$7 \quad \Rightarrow W^{T+1} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t)$$

# Performance of Multiplicative Weights

## Proof:

Lower bound on  $W^{T+1}$  (similar to (6) in slide 12):

$$1 \quad W^{T+1} \geq w_i^{T+1} = \prod_{t=1}^T (1 - \eta)^{l_i^t}, \forall i (\text{including } i^*)$$

Upper bound on  $W^{T+1}$  (similar to (5) in slide 12):

$$2 \quad W^{T+1} = \sum_i w_i^T \cdot (1 - \eta)^{l_i^T}$$

$$3 \quad \text{but } (1 - \eta)^x \leq (1 - \eta x) \text{ for } x \in [0, 1]$$

$$4 \quad (2), (3) \Rightarrow W^{T+1} \leq \sum_i w_i^T \cdot (1 - \eta l_i^T)$$

$$5 \quad = W^T - \eta \cdot \sum_i w_i^T \cdot l_i^T \stackrel{\text{def. of } p_i}{=} W^T - \eta W^T \cdot \sum_i p_i^T \cdot l_i^T$$

$$6 \quad W^T (1 - \eta \cdot l_{ALG}^T) \text{ (expected loss } l_{ALG}^T = \sum_i p_i^T \cdot l_i^T)$$

$$7 \quad \Rightarrow W^{T+1} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t) \text{ (since } W^0 = k)$$

## Proof (cnt'd):

- 8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta)^{l_i^t} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t)$$

## Proof (cnt'd):

- 8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta) l_i^t \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t)$$

- 9  $\Rightarrow \ln(1 - \eta) \sum_t l_i^t \leq \ln k + \sum_t \ln(1 - \eta \cdot l_{ALG}^t)$  (logarithms both sides)

# Performance of Multiplicative Weights

## Proof (cnt'd):

8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta)^{l_i^t} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t)$$

9  $\Rightarrow \ln(1 - \eta) \sum_t l_i^t \leq \ln k + \sum_t \ln(1 - \eta \cdot l_{ALG}^t)$  (logarithms both sides)

10  $\Rightarrow \ln(1 - \eta) L_{OPT}^T \leq \ln k + \sum_t \ln(1 - \eta \cdot l_{ALG}^t)$

# Performance of Multiplicative Weights

## Proof (cnt'd):

8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta)^{I_i^t} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot I_{ALG}^t)$$

9  $\Rightarrow \ln(1 - \eta) \sum_t I_i^t \leq \ln k + \sum_t \ln(1 - \eta \cdot I_{ALG}^t)$  (logarithms both sides)

10  $\Rightarrow \ln(1 - \eta) L_{OPT}^T \leq \ln k + \sum_t \ln(1 - \eta \cdot I_{ALG}^t)$

(use again)  $-z - z^2 \leq \ln(1 - z) \leq -z$

## Proof (cnt'd):

8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta)^{I_i^t} \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot I_{ALG}^t)$$

9  $\Rightarrow \ln(1 - \eta) \sum_t I_i^t \leq \ln k + \sum_t \ln(1 - \eta \cdot I_{ALG}^t)$  (logarithms both sides)

10  $\Rightarrow \ln(1 - \eta) L_{OPT}^T \leq \ln k + \sum_t \ln(1 - \eta \cdot I_{ALG}^t)$

(use again)  $-z - z^2 \leq \ln(1 - z) \leq -z$

11  $\Rightarrow (-\eta - \eta^2) L_{OPT}^T \leq \ln k - \sum_t \eta \cdot I_{ALG}^t$

## Proof (cnt'd):

8 Combine lower and upper bound:

$$\prod_{t=1}^T (1 - \eta) l_i^t \leq k \cdot \prod_{t=1}^T (1 - \eta \cdot l_{ALG}^t)$$

9  $\Rightarrow \ln(1 - \eta) \sum_t l_i^t \leq \ln k + \sum_t \ln(1 - \eta \cdot l_{ALG}^t)$  (logarithms both sides)

10  $\Rightarrow \ln(1 - \eta) L_{OPT}^T \leq \ln k + \sum_t \ln(1 - \eta \cdot l_{ALG}^t)$

(use again)  $-z - z^2 \leq \ln(1 - z) \leq -z$

11  $\Rightarrow (-\eta - \eta^2) L_{OPT}^T \leq \ln k - \sum_t \eta \cdot l_{ALG}^t$

12 (rearranging)  $L_{ALG}^T \leq \frac{\ln k}{\eta} + (1 + \eta) L_{OPT}^T$



# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^{\mathbf{T}} \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^{\mathbf{T}}$$

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^{\mathbf{T}} \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^{\mathbf{T}}$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta)\mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta)\mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

- Comparing the first formula with that of Weight Majority Rule, we observe that the factor  $(2 + \eta)$  has been cut to  $(1 + \eta) \Rightarrow$  we can get close to optimal expert.

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta)\mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

- Comparing the first formula with that of Weight Majority Rule, we observe that the factor  $(2 + \eta)$  has been cut to  $(1 + \eta) \Rightarrow$  we can get close to optimal expert.
- “optimal”  $\eta$  can be found by minimizing RHS  $\Rightarrow \eta^* = \sqrt{\frac{\ln k}{L_{\text{OPT}}^T}}$ .

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

- Comparing the first formula with that of Weight Majority Rule, we observe that the factor  $(2 + \eta)$  has been cut to  $(1 + \eta) \Rightarrow$  we can get close to optimal expert.
- “optimal”  $\eta$  can be found by minimizing RHS  $\Rightarrow \eta^* = \sqrt{\frac{\ln k}{L_{\text{OPT}}^T}}$ .
- We do not know  $L_{\text{OPT}}^T$  (as in WMR) but we can assume  $L_{\text{OPT}}^T \sim T$ , hence the choice of  $\eta$

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

- Comparing the first formula with that of Weight Majority Rule, we observe that the factor  $(2 + \eta)$  has been cut to  $(1 + \eta) \Rightarrow$  we can get close to optimal expert.
- “optimal”  $\eta$  can be found by minimizing RHS  $\Rightarrow \eta^* = \sqrt{\frac{\ln k}{L_{\text{OPT}}^T}}$ .
- We do not know  $L_{\text{OPT}}^T$  (as in WMR) but we can assume  $L_{\text{OPT}}^T \sim T$ , hence the choice of  $\eta$  (unfortunately, same trick does not hold for WMR)

# Performance of Multiplicative Weights

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

- Comparing the first formula with that of Weight Majority Rule, we observe that the factor  $(2 + \eta)$  has been cut to  $(1 + \eta) \Rightarrow$  we can get close to optimal expert.
- “optimal”  $\eta$  can be found by minimizing RHS  $\Rightarrow \eta^* = \sqrt{\frac{\ln k}{L_{\text{OPT}}^T}}$ .
- We do not know  $L_{\text{OPT}}^T$  (as in WMR) but we can assume  $L_{\text{OPT}}^T \sim T$ , hence the choice of  $\eta$  (unfortunately, same trick does not hold for WMR)
- **Note:** An alternative but **equivalent** formulation requires  $w_i^{t+1} = w_i^t \cdot e^{-\eta \cdot l_i^t}$ . This is known as **Hedge**.



# Performance of Multiplicative Weights or Hedge

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = O(\sqrt{T})$$

## Key Remarks

- Key Remark 1: Randomization is **necessary** for sublinear regret!

# Performance of Multiplicative Weights or Hedge

## Theorem

- The total loss of the MW algorithm is upper bounded

$$\mathbf{L}_{\text{ALG}}^T \leq \frac{\ln k}{\eta} + (1 + \eta) \mathbf{L}_{\text{OPT}}^T$$

- Choosing  $\eta = \sqrt{\frac{\ln k}{T}}$

$$\Rightarrow \text{Regret}^T = \mathbf{L}_{\text{ALG}}^T - \mathbf{L}_{\text{OPT}}^T \leq 2\sqrt{T \ln k} = \mathcal{O}(\sqrt{T})$$

## Key Remarks

- 1 Key Remark 1: Randomization is **necessary** for sublinear regret!
- 2 Key Remark 2: MW/Hedge algorithm is order optimal! Every expert algorithm is  $\Omega(\sqrt{T})$

- like Experts:  $l_i^t$  can change arbitrarily (not IID)

# Adversarial Bandits

- like Experts:  $I_i^t$  can change arbitrarily (not IID)
- unlike Experts: *only*  $I_i^t$  for played arm  $i$  is revealed

# Adversarial Bandits

- like Experts:  $l_i^t$  can change arbitrarily (not IID)
- unlike Experts: *only*  $l_i^t$  for played arm  $i$  is revealed
- We know that we cannot use previous algorithms (e.g., UCB)

# Adversarial Bandits

- like Experts:  $I_i^t$  can change arbitrarily (not IID)
- unlike Experts: *only*  $I_i^t$  for played arm  $i$  is revealed
- We know that we cannot use previous algorithms (e.g., UCB)
- Hence we need to play arms probabilistically for bandits as well

# Adversarial Bandits

- like Experts:  $l_i^t$  can change arbitrarily (not IID)
- unlike Experts: *only*  $l_i^t$  for played arm  $i$  is revealed
- We know that we cannot use previous algorithms (e.g., UCB)
- Hence we need to play arms probabilistically for bandits as well
- (how) can we use expert-like algorithms without full info?

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly!



# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$  (key difference from experts)

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$  (key difference from experts)
- 3 Set

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$  (key difference from experts)
- 3 Set

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- 4 Use  $\hat{l}_i^t$  to discount *all* weights

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly! → Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$  (key difference from experts)
- 3 Set

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- 4 Use  $\hat{l}_i^t$  to discount *all* weights  $\Rightarrow w_i^{t+1} = (1 - \eta)^{\hat{l}_i^t} \cdot w_i^t$

# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly!  $\rightarrow$  Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

- 1 Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)
- 2 Receive **only** loss  $l_i^t$  (key difference from experts)
- 3 Set

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- 4 Use  $\hat{l}_i^t$  to discount *all* weights  $\Rightarrow w_i^{t+1} = (1 - \eta)^{\hat{l}_i^t} \cdot w_i^t \Rightarrow$

$$w_i^{t+1} = \begin{cases} (1 - \eta)^{\hat{l}_i^t} \cdot w_i^t, & \text{for picked arm } i \\ w_i^t, & \text{for all other } i \end{cases}$$



# How to use an expert algorithm (e.g. MW) for Bandits?

Observation: We cannot apply Multipl. Weights (or Hedge) directly!  $\rightarrow$  Requires knowing all rewards/losses at time  $t$  to discount all weights.

## Applying MW to Bandits: Attempt 1

at round  $t$ :

① Pick arm  $i$  according to  $p_i = \frac{w_i}{\sum_{i=1}^k w_i}$  (same as experts)

② Receive **only** loss  $l_i^t$  (key difference from experts)

③ Set

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

④ Use  $\hat{l}_i^t$  to discount *all* weights  $\Rightarrow w_i^{t+1} = (1 - \eta)^{\hat{l}_i^t} \cdot w_i^t \Rightarrow$

$$w_i^{t+1} = \begin{cases} (1 - \eta)^{\hat{l}_i^t} \cdot w_i^t, & \text{for picked arm } i \\ w_i^t, & \text{for all other } i \end{cases}$$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$   
Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$

- Q: What does this even mean?

- A:  $E[\hat{l}_i^t] = l_i^t$

Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0$



# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$

- Q: What does this even mean?

- A:  $E[\hat{l}_i^t] = l_i^t$

Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0 = l_i^t$

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$   
Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0 = l_i^t$
- A2: The above method is also called **Importance Sampling**

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$   
Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0 = l_i^t$
- A2: The above method is also called **Importance Sampling** (We will encounter again in Deep RL methods)

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$   
Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0 = l_i^t$
- A2: The above method is also called **Importance Sampling** (We will encounter again in Deep RL methods)

**Note:** Signal Processing/Estimation Theory: Having “good” estimates usually means estimates with **no/low bias** and **low variance**

# Multiplicative Weights to Bandits: Attempt 1

- Key step/idea is

$$\hat{l}_i^t = \begin{cases} \frac{l_i^t}{p_i}, & \text{for picked arm } i \\ 0, & \forall j \neq i \end{cases}$$

- Q: Why does this make sense?
- A1:  $\hat{l}_i^t$  is an **unbiased** estimate of  $l_i^t$ 
  - Q: What does this even mean?
  - A:  $E[\hat{l}_i^t] = l_i^t$   
Proof:  $E[\hat{l}_i^t] = \sum_{j=1}^k p_j \cdot \hat{l}_j^t = p_i \cdot \frac{l_i^t}{p_i} + \sum_{j \neq i} p_j \cdot 0 = l_i^t$
- A2: The above method is also called **Importance Sampling** (We will encounter again in Deep RL methods)

**Note:** Signal Processing/Estimation Theory: Having “good” estimates usually means estimates with **no/low bias** and **low variance** (Variance concerns will come back to “haunt” us in Deep RL methods)

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ .

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??).

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).



## Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )

## Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$

## Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ )

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ ) .

## Lemma

- 1 Let an expert algorithm (with  $l_i^t \in [0, 1]$ ) achieve  
$$L_{ALG} = E[\sum_{t=1}^T l_t^t] \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \beta$$

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ ) .

## Lemma

- 1 Let an expert algorithm (with  $l_i^t \in [0, 1]$ ) achieve  
$$L_{ALG} = E[\sum_{t=1}^T l_i^t] \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \beta$$
 (for some constants  $\alpha, \beta$ )

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ ) .

## Lemma

- 1 Let an expert algorithm (with  $l_i^t \in [0, 1]$ ) achieve  $L_{ALG} = E[\sum_{t=1}^T l_i^t] \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \beta$  (for some constants  $\alpha, \beta$ )
- 2 Then the same algorithm with  $l_i^t \in [0, \rho]$  ( $\rho > 1$ ) achieves  $L_{ALG} \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \rho \cdot \beta$

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ ) .

## Lemma

- 1 Let an expert algorithm (with  $l_i^t \in [0, 1]$ ) achieve  $L_{ALG} = E[\sum_{t=1}^T l_i^t] \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \beta$  (for some constants  $\alpha, \beta$ )
- 2 Then the same algorithm with  $l_i^t \in [0, \rho]$  ( $\rho > 1$ ) achieves  $L_{ALG} \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \rho \cdot \beta$
- 3 The Multiplicative Weights algorithm for experts with rewards in  $[0, \rho]$  ( $\rho > 1$ ) achieves regret **Regret**<sup>T</sup> =  $2\rho\sqrt{T \ln k}$

# Multiplicative Weights to Bandits: Attempt 2

**BUT:** MW requires loss to be in  $[0, 1]$ . Unfortunately,  $\hat{l}_i^t$  can be  $> 1$  (why??). In fact it can even go to infinity (if  $p_i \rightarrow 0$  at some round).

“Black Box” Method for Experts with generic reward  $l_i^t \in [0, \rho]$

- Assume  $l_i^t \in [0, \rho], \forall i$  ( $\rho > 1$ )
- Can feed (any) Experts Algorithm with  $\hat{l}_i^t = \frac{l_i^t}{\rho}$  ( $\Rightarrow \hat{l}_i^t \in [0, 1]$ ) .

## Lemma

- 1 Let an expert algorithm (with  $l_i^t \in [0, 1]$ ) achieve  $L_{ALG} = E[\sum_{t=1}^T l_i^t] \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \beta$  (for some constants  $\alpha, \beta$ )
- 2 Then the same algorithm with  $l_i^t \in [0, \rho]$  ( $\rho > 1$ ) achieves  $L_{ALG} \leq \alpha \cdot \min_i \sum_{t=1}^T l_i^t + \rho \cdot \beta$
- 3 The Multiplicative Weights algorithm for experts with rewards in  $[0, \rho]$  ( $\rho > 1$ ) achieves regret  $\mathbf{Regret}^T = 2\rho\sqrt{T \ln k}$  (This is just the regret of slide 20 scaled up by  $\rho$ ).



# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

## MW algorithm adapted to (adversarial) bandits

- Solution: add some **exploration**:

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

## MW algorithm adapted to (adversarial) bandits

- Solution: add some **exploration**: Define  $q_i^t = (1 - \epsilon)p_i^t + \frac{\epsilon}{k}$
- Pick arm based on  $q_i^t$

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

## MW algorithm adapted to (adversarial) bandits

- Solution: add some **exploration**: Define  $q_i^t = (1 - \epsilon)p_i^t + \frac{\epsilon}{k}$
- Pick arm based on  $q_i^t$  (rather than  $p_i^t$ )

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

## MW algorithm adapted to (adversarial) bandits

- Solution: add some **exploration**: Define  $q_i^t = (1 - \epsilon)p_i^t + \frac{\epsilon}{k}$
- Pick arm based on  $q_i^t$  (rather than  $p_i^t$ )
- Feed to algorithm  $\hat{l}_i^t = \frac{l_i^t}{q_i^t}$ , for picked arm  $i$  (0 for all other arms)

# Multiplicative Weights to Bandits: Attempt 3

## Note:

- Good news 1: Expert algorithms generalize to any upper bounded loss functions.
- Good news 2: For bandits, the fact that the (unbiased) estimate  $\hat{l}_i^t$  can be larger than 1 (see slide 24), is **not** a problem!
- Bad news: The fact that it is **not upper bounded** (i.e.,  $\rho = \infty$ ) **IS** a major problem.

## MW algorithm adapted to (adversarial) bandits

- Solution: add some **exploration**: Define  $q_i^t = (1 - \epsilon)p_i^t + \frac{\epsilon}{k}$
- Pick arm based on  $q_i^t$  (rather than  $p_i^t$ )
- Feed to algorithm  $\hat{l}_i^t = \frac{l_i^t}{q_i^t}$ , for picked arm  $i$  (0 for all other arms)
- $\rho = \frac{k}{\epsilon}$  in this case  $\Rightarrow$  we can apply the previous “black box” method (and proof).



## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is

$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T l_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is

$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T l_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$

- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability)

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is

$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T \mathbf{l}_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$

- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{T k \ln k})$ .

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is
$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T \mathbf{l}_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$
- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{Tk \ln k})$ .

## Remarks:

- It is (almost) amazing that we can achieve the same  $\mathbf{O}(\sqrt{T})$  regret in this very *hostile* setting

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is
$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T \mathbf{l}_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$
- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{Tk \ln k})$ .

## Remarks:

- It is (almost) amazing that we can achieve the same  $O(\sqrt{T})$  regret in this *very hostile* setting (**adversary and partial observability**)

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is
$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T \mathbf{l}_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$
- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{Tk \ln k})$ .

## Remarks:

- It is (almost) amazing that we can achieve the same  $O(\sqrt{T})$  regret in this *very hostile* setting (**adversary and partial observability**)
- Observe the extra factor  $K$  in the regret.

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is
$$\mathbf{L}_{\text{ALG}} \leq (\mathbf{1} + \eta) \cdot \min_i \sum_{t=1}^T \mathbf{l}_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$
- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{Tk \ln k})$ .

## Remarks:

- It is (almost) amazing that we can achieve the same  $O(\sqrt{T})$  regret in this *very hostile* setting (**adversary and partial observability**)
- Observe the extra factor  $K$  in the regret. This is the penalty of partial observability!

## Theorem

- The total loss of the Multiplicative Weights algorithm for the adversarial bandits setting is
$$\mathbf{L}_{\text{ALG}} \leq (1 + \eta) \cdot \min_i \sum_{t=1}^T l_i^t + \frac{k \ln k}{\epsilon \eta} + \epsilon T$$
- By properly picking  $\eta$  (the discount parameter) and  $\epsilon$  (the exploration probability) :  $\text{Regret}^T = \mathbf{O}(\sqrt{Tk \ln k})$ .

## Remarks:

- It is (almost) amazing that we can achieve the same  $O(\sqrt{T})$  regret in this *very hostile* setting (**adversary and partial observability**)
- Observe the extra factor  $K$  in the regret. This is the penalty of partial observability! ( $\rightarrow$  We need  $k$  rounds to get the same feedback that the experts get in 1 round)