TCP Header Diagram

Byte Offset / Byte numbers: 0, 1, 2, 3

Byte Offset		
0	Source Port	Destination Port
4	Sequence Number	
8	Acknowledgment Number	
12	Offset / Reserved / TCP Flags (C E U A P R S F)	Window
16	Checksum	Urgent Pointer
20	TCP Options (variable length, optional)	

20 Bytes / Offset

Bit: 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31

Nibble — Byte — Word

TCP Flags

C E U A P R S F

Congestion Window
C 0x80 Reduced (CWR)
E 0x40 ECN Echo (ECE)
U 0x20 Urgent
A 0x10 Ack
P 0x08 Push
R 0x04 Reset
S 0x02 Syn
F 0x01 Fin

Congestion Notification

ECN (Explicit Congestion Notification). See RFC 3168 for full details, valid states below.

Packet State	DSB	ECN bits
Syn	0 0	1 1
Syn-Ack	0 0	0 1
Ack	0 1	0 0
No Congestion	0 1	0 0
No Congestion	1 0	0 0
Congestion	1 1	0 0
Receiver Response	1 1	0 1
Sender Response	1 1	1 1

TCP Options

0 End of Options List
1 No Operation (NOP, Pad)
2 Maximum segment size
3 Window Scale
4 Selective ACK ok
8 Timestamp

Checksum

Checksum of entire TCP segment and pseudo header (parts of IP header)

Offset

Number of 32-bit words in TCP header, minimum value of 5. Multiply by 4 to get byte count.

RFC 793

Please refer to RFC 793 for the complete Transmission Control Protocol (TCP) Specification.