Safety & Prevention

Research & Reports

Education & Events

 Articles in <u>Features</u>

La Paz

lssue

Q2 2020

Sentinels for the Seas

La Paz Photo Gallery

Oil and Particulates

Central California Photo Gallery

ADVERTISEMENT

Front row seats available.

Florida Kevs

Getting Centered

Professional Programs

About DAN

+

Home > Features > Carbon Dioxide Safety

Membership & Insurance

Carbon Dioxide Safety

Health & Medicine

 By Francois Burman, Pr.Eng., M.Sc. ⊞ May 1, 2020




Photo by Stephen Frink

A lot of literature discusses the quality of breathing gases, contaminants we should be concerned about, how to analyze them, and their toxic effects. There are many standards and guidelines for safe limits, including the

What is a safe CO2 level in our breathing air?

results of various occupational health and safety studies on the effects of extended exposure. For diving, the situation is different. Many compressed-gas safety standards are based only on breathing at or around sea level (1 atmosphere absolute, or ATA). Commercial and navy diving experts have based their limits on

contaminant exposure for extended times at depth. So what are safe limits for recreational diving with much shorter exposures than navy divers? Particularly, what is a safe limit for carbon dioxide (CO₂), the most abundant potential contaminant?



in compressed air allowed for recreational diving in the U.S. is double the European recommendation, does that mean the U.S. Navy or Compressed Gas Association (CGA)¹ standards do not apply to recreational diving? Almost

all divers have some knowledge about how CO₂ affects them. A safety-conscious diver should also know how to review a filling station's air-quality analysis certificate with some idea of what to look for and be able to discuss concerns about whether standards are being met or if there is surrounding environmental pollution. Many studies exist about the physiological effects of elevated CO₂ in occupational situations. The results published in health and safety



0 - 0.015

0.015 - 0.023

0.023 - 0.066

0.066 - 0.100

II

III

IV

could, in theory, easily manage significantly higher levels. The NOAA Diving Manual (4th edition) describes the relationship between concentrations, exposure limits and symptoms in terms of zones. Table 1 (based on Figure 1) provides a brief correlation between these zones and the units of measure used. The last column indicates the level of CO₂ in a

standards and codes of practice throughout the world² focus on an eight-

hour working day. Due to much shorter exposures, recreational divers

scuba cylinder that would produce the corresponding maximum surface equivalent value (SEV). A cylinder containing 1,950 parts per million (ppm)³ of CO₂, for example, would achieve an SEV of 15,000 ppm (the upper limit for Zone 1) at a depth of 220 feet of seawater (fsw), 67 meters of seawater (msw), or 7.7 ATA.

ppm at 1 ATA

0-15,000

15,000-23,000

23,000-66,000

66,000-100,000

ppm in the cylinder

1,950

2,990

8,570

13,000

| [| V | ≥ 0.100 | ≥ 10 | ≥100,000 | >13,000 | | | | |
|---|---|--------------------------|------|------------------------------|-----------------------------|--|--|--|--|
| Т | Table 1: NOAA zone values after the initial equalizing phase and for a one-hour exposure | | | | | | | | |
| | O bronce outside and a series of the series | | | | | | | | |
| Although these are not trivial values, they have no real meaning to us unless they are associated with the effect on a diver during a typical dive. Figure 1 depicts the effects of a 60-minute dive based on the SEV levels of CO ₂ | | | | | | | | | |
| | | in a charged scuba cylin | ' | cts of a go minate aive base | a off the SEV levels of eo2 | | | | |

Figure 1 illustrates the resulting physiological conditions by zone based on U.S. Navy research, but they do not correlate well with published data from other sources, perhaps because the U.S. Navy expects their divers to be

% CO₂ at 1 ATA

0 - 1.5


1.5 - 2.3

2.3 - 6.6

6.6 - 10

at a much higher level of fitness than the average occupational worker or recreational diver. The value of Figure 1 is in the trend of resulting conditions with the exposure time.

Zone V UNCONSCIOUSNESS 10 Zone IV Dizziness, stupor unconsciousness



ppm (%) at 1 ATA Effect Resulting conditions 250-350 Low CO2 environment None (0.025% - 0.035%)351-1,000 Typical well-ventilated indoors

conditions: at pressure (submarine and navy dive medicine), in an eight-hour working environment (occupational

health and safety), and during long-term continuous exposure (NASA space capsule environments). The results

Maximum depth and bottom time are also important criteria to consider when determining maximum CO₂

exposure levels. The deeper we dive, the shorter the bottom time, which the decompression time and the gas

used to decompress will determine. A dive to 220 fsw will usually not exceed 15 minutes at this depth unless a

longer decompression obligation is accepted. A shallower dive to 60 fsw with a 50-minute bottom time extends

indicate that divers can tolerate similar levels to what these conditions cause in most cases.

exposure but also allows a higher CO₂ level to remain within the safe SEV.

None

(0.035% - 0.1%)

1,001-2,000

| | 1,001–2,000 (0.1%–0.2%) | Complaints | Poor air, drowsiness after several hours | | |
|-----------------------|--|---|--|--|--|
| | 2,001-5,000 (0.2-0.5%) | Increased Respiration | Increased respiration rate, possible headache commencing after several hours | | |
| | 5,00 | num workplace eight-hour exposure. | | | |
| | 5,001–10,000 (0.5%–1%) | Onset of symptoms | Potentially: fatigue, anxiety, loss of energy, jelly legs, poor concentration, drowsiness | | |
| | 10,001–20,000 (1%–2%) | Commencement of hyperventilation | Lung ventilation up to 50% and headache for some people after 60 minutes; elevated blood pressure | | |
| | 20,001–40,000 (2%–4%) | Serious | Dyspnea (from 30,000 ppm), significant headaches after several minutes | | |
| | 25,000 ppm is the National Research Council (NRC) recommended maximum one-hour exposure | | | | |
| | 40,001–50,000 (4%–5%) | Severe breathing | Violent panting, severe headache, dizziness, commencement of danger-to-life while submerged | | |
| | 50,001-100,000 | Potentially irreversible | Serious disturbances, unconscious or near | | |
| | (5%–10%) | or fatal | unconsciousness commencing from one minute | | |
| | | | | | |
| T | (5%-10%) ≥100,001 (≥10%) | or fatal | Unconsciousness commencing from one minute Spasms from above 150,000 ppm (15%), coma, possible death after one minute | | |
| C d a w h | (5%–10%) ≥100,001 (≥10%) able 2: Expected diver processive, the more CO ₂ we accomplicate and avoid there you may experience | or fatal Unconscious Thysiological effects with in the same and the closer we may a symptoms, the CO ₂ SEV shows a minor symptoms, the CO ₂ Sevenot just those when specific parts of the country of | Unconsciousness commencing from one minute Spasms from above 150,000 ppm (15%), coma, possible death after one minute | | |


exceeding Zone 2, the CO₂ level in the cylinder should not exceed 2,990 ppm (which equates to an SEV of 23,000 ppm). The maximum value to avoid exceeding Zone 1 would be 1,950 ppm (which equates to an SEV of 15,000 ppm). Based on maximum expected depths (regardless of the breathing gas) and bottom times determined by realistic recreational decompression obligations, these limits are extremely conservative.

Building on these considerations, we can conclude that for regular breathing air during conservative open-water and open-circuit diving, a level of 2,000 ppm in a filled scuba cylinder is considered safe and acceptable. This value encompasses the levels of CO₂ currently in the air and local CO₂ production, such as from a restaurant or passing vehicles. It is also important to note that sources of carbon monoxide (Carbon

preferably quarterly but at least annually. CO₂ monitors are not cheap, which means that many dive centers and most recreational scuba divers typically would not own an analyzer. Based on only periodic air sampling, a cautious compressed-gas filling facility should trace the source of excess CO₂ production. A CO₂ value above 400 ppm indicates a level above the standard ambient level. The current CGA limit of 1,000 ppm, even though it is 50 percent higher than the European limit, will most likely not cause adverse effects at depth. This limit is conservative and safe.

Dive shops should continue to regularly collect and analyze air samples —

Monoxide Safety) and CO₂ are not significantly different.



adopted.

- **Notes**
- 1. The current applicable reference in the U.S. is CGA G-7.1-2018 with the commonly referred to Grade E (scuba) air specification of = 1,000 ppmv. 2. Several acronyms are found in occupational health and safety standards and guidelines, some indicating instantaneous levels and others the accumulated exposure during an eight-hour working day throughout the life of a worker. The threshold limit value (TLV) describes the upper exposure limit for work in hazardous environments. The permissible exposure limit (PEL) is the legal limit allowed in specific regions or countries. The eight-hour derivative of PEL is the time weighted average (TWA). The recommended
- 3. The term *ppm* (parts per million) in this article is relative to volume: that is, parts per million by volume (ppmv). 4. This figure is a partial replica of Figure 3.11 in the NOAA Diving Manual (4th ed.), originally extracted from the U.S. Navy Diving-Gas Manual (1971). The original data is attributed to Dr. C.J. Lambertsen in the 1971 paper

"Carbon Dioxide Tolerance and Toxicity" (Environmental Biomedical Stress Data Center, Institute for

exposure limit (REL) is simply a recommended guideline but is intended to supersede the PEL once

- Environmental Medicine, University of Pennsylvania Medical Center, Philadelphia; IFEM Report No. 2-71). 5. The author correlated the values in this table from data published by the National Oceanic and Atmospheric Administration (NOAA), the National Institute for Occupational Safety and Health (NIOSH), the Occupational Safety and Health Administration (OSHA), the Environmental Protection Agency (EPA) and the
- National Research Council (NRC). The effects and conditions vary significantly among divers. 6. The NRC recommended Emergency Exposure Guidance Level (EEGL) for a one-hour exposure is 25,000 ppm (National Research Council. Emergency and Continuous Exposure Guidance Levels for Selected Submarine
- Contaminants: Volume 1. Washington, DC: The National Academies Press, 2007. doi:10.17226/11170. Chapter 3 contains a summary of relevant epidemiologic and toxicologic studies on CO₂. The wide range of studies reviewed shows significant variations in conditions based on specific exposure levels; the EEGL is very conservative, accounting for the level at which dangerous conditions may present.

© Alert Diver — Q2 2020

© DAN, Inc. All rights reserved.

Home Site Map Policies Terms & Conditions Advertise Contact Us