

# Data Model & Calculation Logic

This document explains how raw search analytics events are transformed into meaningful metrics. It covers event sequences, timing calculations, and business rules with clear examples.

## Table of Contents

- 1. Event Types & Sequence
- 2. Processing Pipeline Overview
- 3. Timing Calculations
- 4. Business Rules & Classifications
- 5. Output Files & Column Definitions
- 6. Power BI Calculated Columns
- 7. Power BI Measures

## 1. Event Types & Sequence

### Initialization Events

Events fired when the search interface loads (before any user search):

Event	Description	When Fired
SEARCH_USER_LOGGED_IN_SUCCESS	User authenticated	User successfully authenticated in goto/echo
SEARCH_USER_DETAILS_FETCHED	User profile loaded	User details fetched from User Profile after authentication
SEARCH_USER_DETAILS_FETCHED_FROM_CACHE	User profile from cache	User details fetched from local storage after authentication
SEARCH_USER_PHOTO_FETCHED	Profile picture loaded	User profile pic retrieved from User Profile
SEARCH_DATA_FETCH_STARTED	Suggestions request sent	Request to fetch suggestions and trending searches sent to backend
SEARCH_DATA_FETCH_COMPLETED	Suggestions loaded	Suggestions and trending searches retrieved from backend

### Search Flow Events

Core events in the search execution flow (stored in the `name` column):

Event	Description	When Fired
SEARCH_TRIGGERED	User initiates search	User clicks search button OR presses Enter key
SEARCH_STARTED	Request sent to backend	Search request submitted to search service
SEARCH_COMPLETED	Results returned	Search results returned to user
SEARCH_RESULT_COUNT	Results displayed	Search completed and result count returned to user
SEARCH_FAILED	Search error	Any error occurred during search

### Click Events

Events fired when users interact with search results:


Event	Description	When Fired
SEARCH_TAB_CLICK	Tab clicked	Any tab (All, News, GOTO) is clicked
SEARCH_RESULT_CLICK	Result clicked	Any item from search results is clicked
SEARCH_ALL_TAB_PAGE_CLICK	All tab pagination	User on ALL tab clicks page in pagination
SEARCH_NEWS_TAB_PAGE_CLICK	News tab pagination	User on NEWS tab clicks page in pagination
SEARCH_GOTO_TAB_PAGE_CLICK	GoTo tab pagination	User on GOTO tab clicks page in pagination
SEARCH_PEOPLE_*	People result clicked	User clicks a People tab result
SEARCH_TRENDING_CLICKED	Trending item clicked	User clicks a trending search item
SEARCH_FILTER_CLICK	Filter clicked	Date OR Relevance filter clicked on results page

### Full Event Sequence

[Initialization – happens once per session]  
|  
v



Typical Search Sequence (Simplified)




Example: Complete Session

Session: 2025-01-15_user123_session456			
Event 1:	SEARCH_TRIGGERED	@ 10:30:15.123	(search term: "budget report")
Event 2:	SEARCH_STARTED	@ 10:30:15.150	(request to backend)
Event 3:	SEARCH_COMPLETED	@ 10:30:15.400	(results returned)
Event 4:	SEARCH_RESULT_COUNT	@ 10:30:15.567	(15 results displayed)
Event 5:	SEARCH_TAB_CLICK	@ 10:30:18.890	(user clicked a result)
Event 6:	SEARCH_TRIGGERED	@ 10:30:45.000	(user searches again: "2024 budget")
Event 7:	SEARCH_STARTED	@ 10:30:45.030	
Event 8:	SEARCH_COMPLETED	@ 10:30:45.280	
Event 9:	SEARCH_RESULT_COUNT	@ 10:30:45.400	(8 results displayed)
Event 10:	SEARCH_TAB_CLICK	@ 10:30:52.500	(user clicked another result)

2. Processing Pipeline Overview

Data Flow



Key Transformations

1. Event Name Normalization

Raw event names come in mixed case from App Insights. We normalize to uppercase for consistent matching.

```
Input: "Search_completed"
Output: "SEARCH_COMPLETED"
```

2. Session Key Generation

A unique session is identified by combining date + user + session ID:

```
session_key = session_date || '_' || user_id || '_' || session_id
-- Example: "2025-01-15_user123_abc789"
```

3. CET Timezone Conversion

All time-derived columns use Central European Time (CET/CEST) instead of UTC:

```
-- DuckDB:
timestamp_cet = timezone('Europe/Berlin', timestamp)

-- PostgreSQL:
timestamp_cet = timestamp AT TIME ZONE 'UTC' AT TIME ZONE 'Europe/Berlin'
```

This automatically handles:

- **CET (UTC+1)**: Standard time (late October to late March)
- **CEST (UTC+2)**: Daylight saving time (late March to late October)

#### Columns derived from CET timestamp:

- **session\_date**: Extracted from CET timestamp (affects session boundaries)
- **session\_key**: Uses CET-based session\_date
- **event\_hour**: Hour (0-23) in CET
- **event\_weekday**: Day name in CET
- **event\_weekday\_num**: ISO day of week in CET
- **searches\_morning/afternoon/evening/night**: Based on CET hour

#### Example (Winter - CET):

```
UTC timestamp: 2025-01-15 23:30:00.000 (late evening UTC)
CET timestamp: 2025-01-16 00:30:00.000 (early morning CET - next day!)
session_date: 2025-01-16 (CET date)
event_hour: 0 (midnight hour in CET)
```

#### Example (Summer - CEST):

```
UTC timestamp: 2025-07-15 22:30:00.000 (late evening UTC)
CEST timestamp: 2025-07-16 00:30:00.000 (early morning CEST - next day!)
session_date: 2025-07-16 (CEST date)
event_hour: 0 (midnight hour in CEST)
```

## 4. Search Term Normalization

Search terms are cleaned for consistent aggregation:

```
search_term_normalized = LOWER(TRIM(COALESCE(CP_searchQuery, searchQuery, query)))
-- Input: " Budget Report "
-- Output: "budget report"
```

## 3. Timing Calculations

ms\_search\_to\_result (User-Perceived Latency)

**What it measures:** The time from when a user initiates a search until they see results.

**Event span:** **SEARCH\_TRIGGERED** --> **SEARCH\_RESULT\_COUNT**

**How it's calculated:**

```
-- Step 1: Track the most recent SEARCH_TRIGGERED timestamp
last_search_started_ts = LAST_VALUE(
  CASE WHEN name = 'SEARCH_TRIGGERED' THEN timestamp END
  IGNORE NULLS
) OVER (PARTITION BY session_key ORDER BY timestamp)

-- Step 2: Calculate time difference when SEARCH_RESULT_COUNT occurs
ms_search_to_result = DATEDIFF('millisecond', last_search_started_ts, timestamp)
-- Only when name = 'SEARCH_RESULT_COUNT'
```

**Example:**

```
Event: SEARCH_TRIGGERED @ 10:30:15.123
Event: SEARCH_COMPLETED @ 10:30:15.234
Event: SEARCH_RESULT_COUNT @ 10:30:15.567

ms_search_to_result = 10:30:15.567 - 10:30:15.123 = 444ms
```

ms\_result\_to\_click (Decision Time)

**What it measures:** How long the user takes to click a result after seeing search results.

Event span: SEARCH\_RESULT\_COUNT --> Click Event

How it's calculated:

```
ms_result_to_click = ms_since_prev_event
-- Only when click_category IS NOT NULL AND prev_event = 'SEARCH_RESULT_COUNT'
```

Example:

```
Event: SEARCH_RESULT_COUNT @ 10:30:15.567
Event: SEARCH_TAB_CLICK    @ 10:30:18.890

ms_result_to_click = 10:30:18.890 - 10:30:15.567 = 3,323ms (3.3 seconds)
```

ms\_since\_prev\_event (Inter-Event Timing)

What it measures: Time between any two consecutive events in a session.

```
ms_since_prev_event = DATEDIFF('millisecond',
    LAG(timestamp) OVER (PARTITION BY session_key ORDER BY timestamp),
    timestamp
)
```

Example:

```
Event 1: SEARCH_TRIGGERED    @ 10:30:15.123 --> ms_since_prev = NULL (first event)
Event 2: SEARCH_COMPLETED    @ 10:30:15.234 --> ms_since_prev = 111ms
Event 3: SEARCH_RESULT_COUNT @ 10:30:15.567 --> ms_since_prev = 333ms
Event 4: SEARCH_TAB_CLICK    @ 10:30:18.890 --> ms_since_prev = 3,323ms
```

Time Buckets

Timing values are bucketed for easier visualization:

Metric	Bucket	Range
search_to_result	< 0.5s	0-499ms
	0.5-1s	500-999ms
	1-2s	1000-1999ms
	2-5s	2000-4999ms
	> 5s	5000ms+
	No Result	NULL (no SEARCH_RESULT_COUNT event)
result_to_click	< 2s (quick)	0-1999ms
	2-5s	2000-4999ms
	5-10s	5000-9999ms
	10-30s	10000-29999ms
	30-60s	30000-59999ms
	> 60s (browsing)	60000ms+
	No Click	NULL (user didn't click)

4. Business Rules & Classifications

is\_null\_result

Definition: The search returned zero results.

```
is_null_result = CASE
    WHEN name = 'SEARCH_RESULT_COUNT' AND CP_totalResultCount = 0 THEN true
    WHEN name = 'SEARCH_RESULT_COUNT' AND CP_totalResultCount > 0 THEN false
    ELSE NULL -- Only meaningful for SEARCH_RESULT_COUNT events
END
```

Example:

```
Event: SEARCH_RESULT_COUNT with CP_totalResultCount = 0
--> is_null_result = true (user saw "No results found")

Event: SEARCH_RESULT_COUNT with CP_totalResultCount = 15
--> is_null_result = false (user saw 15 results)
```

click\_category

**Definition:** Categorizes click events by which tab/section was clicked.

```
click_category = CASE
  WHEN name = 'SEARCH_TAB_CLICK' THEN 'General'
  WHEN name = 'SEARCH_ALL_TAB_PAGE_CLICK' THEN 'All'
  WHEN name = 'SEARCH_NEWS_TAB_PAGE_CLICK' THEN 'News'
  WHEN name = 'SEARCH_GOTO_TAB_PAGE_CLICK' THEN 'GoTo'
  WHEN name LIKE '%PEOPLE%' THEN 'People'
  ELSE NULL -- Not a click event
END
```

journey\_outcome (Session-Level)

**Definition:** Classifies how a search session ended.

```
journey_outcome = CASE
  WHEN click_count > 0 THEN 'Success'
  WHEN result_count > 0 AND null_result_count = result_count AND click_count = 0
    THEN 'No Results'
  WHEN result_count > 0 AND click_count = 0 THEN 'Abandoned'
  ELSE 'Unknown'
END
```

Example scenarios:

Scenario	click_count	result_count	null_result_count	Outcome
User searched, clicked a result	1	1	0	Success
User searched, got 0 results	0	1	1	No Results
User searched, saw results but didn't click	0	1	0	Abandoned
Incomplete session data	0	0	0	Unknown

session\_complexity

**Definition:** Categorizes sessions by number of events.

```
session_complexity = CASE
  WHEN total_events = 1 THEN 'Single Event'
  WHEN total_events <= 3 THEN 'Simple'
  WHEN total_events <= 10 THEN 'Medium'
  ELSE 'Complex'
END
```

had\_reformulation

**Definition:** Did the user refine/change their search query within the session?

```
had_reformulation = CASE
  WHEN unique_search_terms > 1 THEN true
  ELSE false
END
```

Example:

```
Session with searches: "budget", "2024 budget", "budget report Q4"
--> unique_search_terms = 3
--> had_reformulation = true (user refined their search)
```

recovered\_from\_null

**Definition:** Did the user eventually find something despite getting zero results initially?

```
recovered_from_null = CASE
  WHEN null_result_count > 0 AND click_count > 0 THEN true
  ELSE false
END
```

**Example:**

```
Session: Search "bugdet" (typo) --> 0 results
         Search "budget" --> 15 results --> Click
--> null_result_count = 1, click_count = 1
--> recovered_from_null = true
```

User Cohort: is\_users\_first\_session

**Definition:** Is this the first time we've seen this user search?

```
user_session_number = ROW_NUMBER() OVER (
  PARTITION BY user_id
  ORDER BY session_start
)
is_users_first_session = CASE WHEN user_session_number = 1 THEN true ELSE false END
```

New vs Returning Users (Daily)

**Definition:** Count of users who are new vs returning on each day.

```
-- First, find when each user first appeared
first_seen_date = MIN(session_date) GROUP BY user_id

-- Then classify on each day
new_users = COUNT(DISTINCT CASE WHEN session_date = first_seen_date THEN user_id END)
returning_users = COUNT(DISTINCT CASE WHEN session_date > first_seen_date THEN user_id END)
```

5. Output Files & Column Definitions

searches\_raw.parquet

**Granularity:** One row per event (click, search, result)

**Use case:** Detailed event-level analysis, debugging

Column	Type	Description	Example
timestamp	Timestamp	Event timestamp in UTC (microsecond precision)	2025-01-15 10:30:15.567123
timestamp_cet	Timestamp	Event timestamp in CET/CEST (microsecond precision)	2025-01-15 11:30:15.567123
timestamp_cet_str	String	CET timestamp as string for Power BI	2025-01-15 11:30:15.567
name	String	Event type (normalized to uppercase)	SEARCH_RESULT_COUNT
user_id	String	Anonymous user identifier	user_abc123
session_id	String	Session identifier	sess_xyz789
session_key	String	Composite key: date_user_session (CET date)	2025-01-15_user_abc123_sess_xyz789
session_date	Date	Date of the event (CET-based)	2025-01-15
event_order	Integer	Sequence number within session	3
prev_event	String	Previous event type in session	SEARCH_COMPLETED

Column	Type	Description	Example
ms_since_prev_event	Integer	Milliseconds since previous event	333
search_term_normalized	String	Cleaned search query	budget report
is_null_result	Boolean	True if zero results returned	false
click_category	String	Click type (General/All/News/GoTo/People)	General
last_search_started_ts	Timestamp	Most recent SEARCH_TRIGGERED timestamp	2025-01-15 10:30:15.123

searches\_journeys.parquet

**Granularity:** One row per search session

**Use case:** Session-level behavior analysis, funnel metrics

Column	Type	Description	Calculation
session_date	Date	Date of session	
session_start	Timestamp	First event timestamp	MIN(timestamp)
session_start_str	String	Session start as string	STRFTIME for Power BI compatibility
total_events	Integer	Events in session	COUNT(*)
search_count_in_session	Integer	SEARCH_TRIGGERED events	COUNT(SEARCH_TRIGGERED)
result_count	Integer	SEARCH_RESULT_COUNT events	COUNT(SEARCH_RESULT_COUNT)
click_count	Integer	Click events	COUNT(click_category IS NOT NULL)
unique_search_terms	Integer	Distinct queries	COUNT(DISTINCT search_term)
null_result_count	Integer	Zero-result events	SUM(is_null_result)
max_total_results	Integer	Max results shown	MAX(CP_totalResultCount)
sec_search_to_result	Float	Seconds: search to results	MIN(ms_search_to_result) / 1000
sec_result_to_click	Float	Seconds: results to click	MIN(ms_result_to_click) / 1000
total_duration_sec	Float	Session length in seconds	(MAX - MIN timestamp) / 1000
first_event_hour	Integer	Hour of first event (0-23 CET)	MIN(event_hour)
last_event_hour	Integer	Hour of last event (0-23 CET)	MAX(event_hour)
general_clicks	Integer	General tab clicks	COUNT(click_category='General')
all_tab_clicks	Integer	All tab clicks	COUNT(click_category='All')
news_clicks	Integer	News tab clicks	COUNT(click_category='News')
goto_clicks	Integer	GoTo tab clicks	COUNT(click_category='GoTo')
people_clicks	Integer	People tab clicks	COUNT(click_category='People')
includes_first_search_of_day	Boolean	Session has day's first search	MAX(is_first_search_of_day)
search_to_result_bucket	String	Latency category	See Time Buckets
result_to_click_bucket	String	Decision time category	See Time Buckets
session_duration_bucket	String	Session length category	< 5s, 5-30s, 30-60s, 1-3 min, etc.
journey_outcome	String	Session result	Success/No Results/Abandoned
had_reformulation	Boolean	User changed query	unique_search_terms > 1
session_complexity	String	Session size category	Based on total_events
search_to_result_sort	Integer	Sort order for latency bucket	1-6 for Power BI sorting
result_to_click_sort	Integer	Sort order for click time bucket	1-7 for Power BI sorting
session_duration_sort	Integer	Sort order for duration bucket	1-6 for Power BI sorting
journey_outcome_sort	Integer	Sort order for outcome	1=Success, 2=Abandoned, 3=No Results
session_complexity_sort	Integer	Sort order for complexity	1-4 for Power BI sorting
had_null_result	Boolean	Had zero-result search	null_result_count > 0
recovered_from_null	Boolean	Success despite null result	null_result > 0 AND click > 0
user_session_number	Integer	User's session sequence	ROW_NUMBER per user



Column	Type	Description	Calculation
is_users_first_session	Boolean	First time user	user_session_number = 1
distinct_click_categories	Integer	Tab types clicked	COUNT(DISTINCT click_category)
had_tab_switch	Boolean	Clicked multiple tabs	distinct_click_categories > 1

searches\_daily.parquet

**Granularity:** One row per day

**Use case:** Daily KPIs, trend analysis

Column	Type	Description	Calculation
date	Date	The day	
total_events	Integer	All events	COUNT(*)
unique_sessions	Integer	Distinct sessions	COUNT(DISTINCT session_key)
unique_users	Integer	Distinct users	COUNT(DISTINCT user_id)
unique_search_terms	Integer	Distinct search queries	COUNT(DISTINCT search_term_normalized)
search_starts	Integer	SEARCH_TRIGGERED events	COUNT(SEARCH_TRIGGERED)
result_events	Integer	SEARCH_RESULT_COUNT events	COUNT(SEARCH_RESULT_COUNT)
click_events	Integer	Click events	COUNT(click_category)
null_results	Integer	Zero-result events	SUM(is_null_result)
result_events_with_results	Integer	Results with >0 hits	SUM(is_clickable_result)
sessions_with_results	Integer	Sessions that got results	From session_stats CTE
sessions_with_clicks	Integer	Sessions with clicks	From session_stats CTE
sessions_abandoned	Integer	Results but no click	sessions_with_results - sessions_with_clicks
click_rate_pct	Float	Click rate	click_events / search_starts * 100
null_rate_pct	Float	Null result rate	null_results / result_events * 100
session_success_rate_pct	Float	Session success	sessions_with_clicks / sessions_with_results * 100
session_abandonment_rate_pct	Float	Session abandonment	sessions_abandoned / sessions_with_results * 100
avg_searches_per_session	Float	Avg searches per session	search_starts / unique_sessions
avg_search_term_length	Float	Avg query char length	AVG(search_term_length)
avg_search_term_words	Float	Avg query word count	AVG(search_term_word_count)
sum_search_term_length	Integer	Sum of query lengths	SUM(search_term_length) - for weighted avg in DAX
sum_search_term_words	Integer	Sum of word counts	SUM(search_term_word_count) - for weighted avg in DAX
search_term_count	Integer	Count of queries	COUNT(search_term_length IS NOT NULL)
first_searches_of_day	Integer	First searches of day	COUNT(is_first_search_of_day)
clicks_general	Integer	General tab clicks	COUNT(click_category='General')
clicks_all	Integer	All tab clicks	COUNT(click_category='All')
clicks_news	Integer	News tab clicks	COUNT(click_category='News')
clicks_goto	Integer	GoTo tab clicks	COUNT(click_category='GoTo')
clicks_people	Integer	People tab clicks	COUNT(click_category='People')
day_of_week	String	Day name	DAYNAME(session_date)
day_of_week_num	Integer	ISO day number (1=Mon)	ISODOW(session_date)
searches_morning	Integer	Searches 6:00-12:00 CET	Hour-based filter (CET)
searches_afternoon	Integer	Searches 12:00-18:00 CET	Hour-based filter (CET)
searches_evening	Integer	Searches 18:00-24:00 CET	Hour-based filter (CET)
searches_night	Integer	Searches 0:00-6:00 CET	Hour-based filter (CET)
new_users	Integer	First-time users today	Users where first_seen = today
returning_users	Integer	Repeat users today	Users where first_seen < today

searches\_terms.parquet

**Granularity:** One row per search term per day

**Use case:** Search term performance analysis, content gap identification

Column	Type	Description	Calculation
session_date	Date	The day	
search_term	String	Normalized search query	LOWER(TRIM(query))
word_count	Integer	Words in query	COUNT of spaces + 1
search_count	Integer	Times searched today	COUNT(SEARCH_TRIGGERED)
unique_users	Integer	Users who searched this	COUNT(DISTINCT user_id)
unique_sessions	Integer	Sessions with this term	COUNT(DISTINCT session_key)
result_events	Integer	Result events for term	COUNT(SEARCH_RESULT_COUNT)
null_result_count	Integer	Zero-result count	SUM(is_null_result)
click_count	Integer	Clicks from this term	COUNT(click_category)
clicks_general	Integer	General tab clicks	COUNT(click_category='General')
clicks_all	Integer	All tab clicks	COUNT(click_category='All')
clicks_news	Integer	News tab clicks	COUNT(click_category='News')
clicks_goto	Integer	GoTo tab clicks	COUNT(click_category='GoTo')
clicks_people	Integer	People tab clicks	COUNT(click_category='People')
avg_sec_to_click	Float	Avg decision time	AVG(ms_result_to_click) / 1000
clicks_with_timing	Integer	Clicks with timing data	COUNT(click after SEARCH_RESULT_COUNT)
sum_sec_to_click	Float	Sum of click times	SUM(ms_result_to_click) / 1000 - for weighted avg in DAX
searches_morning	Integer	Searches 6:00-12:00 CET	Hour-based filter (CET)
searches_afternoon	Integer	Searches 12:00-18:00 CET	Hour-based filter (CET)
searches_evening	Integer	Searches 18:00-24:00 CET	Hour-based filter (CET)
searches_night	Integer	Searches 0:00-6:00 CET	Hour-based filter (CET)
first_seen_date	Date	First day term appeared	MIN(session_date) over all time
is_new_term	Boolean	First appearance today	session_date = first_seen_date

6. Power BI Calculated Columns

These columns are created in Power BI using DAX and are not present in the parquet files.

searches\_terms Table

Query\_Length\_Bucket

Categorizes search queries by word count for visualization.

```
Query_Length_Bucket =
SWITCH(
    TRUE(),
    searches_terms[word_count] = 1, "1 word",
    searches_terms[word_count] = 2, "2 words",
    searches_terms[word_count] = 3, "3 words",
    searches_terms[word_count] = 4, "4 words",
    searches_terms[word_count] >= 5, "5+ words",
    "Unknown"
)
```

Query\_Length\_Sort

Sort order for Query\_Length\_Bucket. Set "Sort by column" in Power BI.

```
Query_Length_Sort =
SWITCH(
    TRUE(),
```

```
searches_terms[word_count] = 1, 1,
searches_terms[word_count] = 2, 2,
searches_terms[word_count] = 3, 3,
searches_terms[word_count] = 4, 4,
searches_terms[word_count] >= 5, 5,
99
)
```

Term\_Outcome

Classifies search term performance into actionable categories.

```
Term_Outcome =
VAR nullRate = DIVIDE([null_result_count], [result_events], 0)
VAR ctr = DIVIDE([click_count], [search_count], 0)
RETURN
SWITCH(
    TRUE(),
    nullRate = 1, "Zero Results",
    nullRate > 0.5, "Mostly No Results",
    ctr = 0, "No Clicks",
    ctr < 0.2, "Low CTR",
    "Success"
)
```

Category	Meaning	Action
Zero Results	100% null rate	Content gap - add content
Mostly No Results	>50% null rate	Partial gap - improve coverage
No Clicks	Has results but 0 clicks	Poor relevance - tune ranking
Low CTR	<20% click rate	Suboptimal - review content
Success	Good performance	Monitor

searches\_journeys Table

Journey\_Type

Combines outcome and behavior flags for segmentation.

```
Journey_Type =
searches_journeys[journey_outcome] &
IF(searches_journeys[had_reformulation], " (Refined)", "") &
IF(searches_journeys[recovered_from_null], " (Recovered)", "")
```

7. Power BI Measures

These measures are created in Power BI for aggregated calculations.

Search Effectiveness Score

Combined metric considering both CTR and null rate. Higher is better.

```
Search Effectiveness Score =
VAR ctr = DIVIDE(SUM(searches_terms[click_count]), SUM(searches_terms[search_count]), 0)
VAR nullRate = DIVIDE(SUM(searches_terms[null_result_count]), SUM(searches_terms[result_events]), 0)
RETURN
(ctr * 100) - (nullRate * 50)
```

Score interpretation:

- Positive scores: Good performance (CTR outweighs null rate penalty)
- Near zero: Balanced but could improve
- Negative scores: High null rates hurting performance

Term CTR %

Click-through rate for search terms.

```
Term CTR % =  
DIVIDE(  
    SUM(searches_terms[click_count]),  
    SUM(searches_terms[search_count]),  
    0  
) * 100
```

Term Null Rate %

Percentage of searches returning zero results.

```
Term Null Rate % =  
DIVIDE(  
    SUM(searches_terms[null_result_count]),  
    SUM(searches_terms[result_events]),  
    0  
) * 100
```

Weighted Avg Search Term Length

Correctly weighted average across days (use instead of AVERAGE on avg\_search\_term\_length).

```
Weighted Avg Search Term Length =  
DIVIDE(  
    SUM(searches_daily[sum_search_term_length]),  
    SUM(searches_daily[search_term_count]),  
    0  
)
```

Weighted Avg Search Term Words

Correctly weighted average across days.

```
Weighted Avg Search Term Words =  
DIVIDE(  
    SUM(searches_daily[sum_search_term_words]),  
    SUM(searches_daily[search_term_count]),  
    0  
)
```

Weighted Avg Sec to Click

Correctly weighted average click time (for terms aggregation).

```
Weighted Avg Sec to Click =  
DIVIDE(  
    SUM(searches_terms[sum_sec_to_click]),  
    SUM(searches_terms[clicks_with_timing]),  
    0  
)
```

Example: Full Data Flow

Raw Input (from App Insights)

```
timestamp,name,user_Id,session_Id,CP_searchQuery,CP_totalResultCount  
2025-01-15 10:30:15.123456,Search_Started,user123,sess456,budget report,  
2025-01-15 10:30:15.234567,Search_Completed,user123,sess456,budget report,  
2025-01-15 10:30:15.567890,Search_Result_Count,user123,sess456,,15  
2025-01-15 10:30:18.890123,Search_Tab_Click,user123,sess456,,
```

After Processing (searches\_raw.parquet)

timestamp	name	session_key	prev_event	ms_since_prev	search_term	is_null_result	click_cate
-----------	------	-------------	------------	---------------	-------------	----------------	------------

timestamp	name	session_key	prev_event	ms_since_prev	search_term	is_null_result	click_category
10:30:15.123	SEARCH_TRIGGERED	2025-01-15_user123_sess456	NULL	NULL	budget report	NULL	NULL
10:30:15.234	SEARCH_COMPLETED	2025-01-15_user123_sess456	SEARCH_TRIGGERED	111	NULL	NULL	NULL
10:30:15.567	SEARCH_RESULT_COUNT	2025-01-15_user123_sess456	SEARCH_COMPLETED	333	NULL	false	NULL
10:30:18.890	SEARCH_TAB_CLICK	2025-01-15_user123_sess456	SEARCH_RESULT_COUNT	3323	NULL	NULL	General

Aggregated (searches\_journeys.parquet)

session_date	total_events	search_count	click_count	sec_search_to_result	sec_result_to_click	journey_outcome
2025-01-15	4	1	1	0.44	3.32	Success

Calculation breakdown:

- **sec\_search\_to\_result**: 10:30:15.567 - 10:30:15.123 = 444ms = 0.44s
- **sec\_result\_to\_click**: 10:30:18.890 - 10:30:15.567 = 3323ms = 3.32s
- **journey\_outcome**: click\_count > 0 --> "Success"

Version History

Version	Date	Changes
1.0	2025-01-15	Initial documentation
1.1	2025-01-16	Added missing parquet columns (click breakdowns, sort columns, timing aggregates), Power BI calculated columns section, Power BI measures section
1.2	2025-01-23	Added CET timezone support: timestamp_cet columns, CET-based session_date/event_hour/event_weekday, updated time distribution documentation
1.3	2025-01-23	Expanded event documentation: added initialization events, SEARCH_STARTED distinction, click event details (SEARCH_RESULT_CLICK, SEARCH_TRENDING_CLICKED, SEARCH_FILTER_CLICK, SEARCH_FAILED)