

Reflex-Policy and Novel Materials for the Energy Transition

Pietro Perlo, IFEVS

Layered and reactive control have important precedents. The contribution developed by Pietro Perlo and IFEVS is a specific system-level formulation in which low-bit physical events, verified permission envelopes, bounded first actions, measured feedback, compact event-action traces, energy proportionality, and slower policy or world-model functions are combined within one electronics-centred architecture.

The purpose is not to replace advanced artificial intelligence, optimization, or materials science. It is to ensure that physical and material innovation can produce an immediate, useful, and verifiable system response.

Many research programmes on batteries, photovoltaics, thermoelectrics, power electronics, and energy harvesting concentrate on improving material properties, electrochemical performance, conversion efficiency, degradation models, or AI-based estimation. These developments are essential. However, the surrounding electrical and control topology often remains substantially fixed.

A better material may store more energy, accept more power, tolerate a wider temperature range, or convert more incident energy. Yet the system may still lose part of that advantage because it cannot locally reroute energy, isolate a limiting element, bypass a mismatched source, selectively assist a weak storage element, or react before a centralized control cycle is completed.

Reflex-Policy addresses this gap.

The Reflex layer receives local physical evidence and executes only a bounded, pre-authorized action. The Policy layer retains responsibility for optimization, learning, planning, coordination, and rule updates. The Reflex layer can be implemented using conventional mixed-signal electronics, comparators, microcontrollers, FPGA or ASIC logic, non-volatile memories, neuromorphic technologies, in-memory devices, or emerging material-based rule fabrics.

The architecture is therefore technology-agnostic. Its value does not depend on one particular semiconductor, magnetic material, memory technology, or sensor. Its purpose is to connect material behaviour to a useful local physical action. In this sense, the material is not treated only as a passive component whose properties are measured by a remote controller, but as part of an adaptive physical system whose local condition can trigger a verified change in routing, topology, or operating state.

The next challenge is not only how efficiently machines infer, predict, or optimize, but how electronics should connect that intelligence to the first useful, bounded, observable, and energy-proportional physical action.

The Pallottoliere/Abacus Paradox

The Pallottoliere/Abacus Paradox captures the essential design principle of Reflex-Policy at a moment when Physical and Spatial AI are becoming central research directions.

For some physical energy-system problems, and under defined operating conditions, a low-bit local rule can outperform a sophisticated AI accelerator in the time and energy required to deliver the first useful action because it solves the smaller problem first.

This does not mean that simple logic is more intelligent than advanced AI. It means that the first useful physical answer may be much lower-dimensional than the complete system model.

A complex AI system may estimate state of health, predict degradation, reconstruct operating conditions, or optimize long-term energy use. At the same time, the urgent local question may be only:

- should this battery element receive bounded assistance;
- should this photovoltaic substring be bypassed;
- should this converter channel be isolated;
- should this source be rerouted;
- should the system enter a safe fallback state?

The local Reflex layer answers that narrow question while advanced inference continues at the Policy level.

Nature provides useful analogies. A fly can initiate a rapid escape response through specialized sensory-motor circuitry before richer neural processing is completed. More complex neural structures then support navigation, learning, and adaptive behaviour. Similarly, Reflex-Policy separates the first bounded physical action from slower optimization and learning without treating them as competing functions.

Batteries

Since 2011, the European Commission has supported a very large number of battery-related projects covering new chemistries, advanced materials, manufacturing, modelling, battery management, artificial intelligence, safety, and recycling.

These efforts are fundamental. However, a large part of battery research improves materials, estimation, or control while retaining a substantially fixed electrical topology.

In a series battery pack, the weakest, highest-resistance, hottest, or most charged locally addressable element can limit the complete pack. This remains true even when advanced AI provides excellent state estimation.

The main system gain may therefore come not only from estimating the limiting element more accurately, but from enabling a bounded physical response:

- selective current injection into an eligible low element;
- local isolation of an anomalous zone;
- dynamic limitation of a converter path;
- fast-charge preparation;
- topology-aware current routing;
- local fault containment.

This is the role of Reflex-Policy.

The benefit becomes more important as cells become larger, packs become more structurally integrated, and repair access becomes more difficult. Large-capacity cells and parallel groups make passive balancing slower and more dissipative. Structural adhesives, cell-to-pack integration, and sealed enclosures increase the value of lower heat, fewer balancing paths, consolidated galvanic isolation, and early detection of limiting elements.

A new chemistry does not only modify voltage, capacity, or temperature limits. It can change the optimum electrical segmentation, balancing strategy, cooling architecture, isolation boundary, fast-charge protocol, and fault-containment topology. These system consequences should be assessed alongside intrinsic material performance.

The architecture does not claim that all chemistries should be controlled in the same way. LFP, high-nickel NCM or NCA, sodium-ion, LTO, and solid-state systems require different voltage models, temperature limits, impedance criteria, charge-acceptance rules, and safety envelopes.

The common principle is architectural: material-specific sensing and models determine eligibility; the Reflex layer executes a bounded local action; the Policy layer performs optimization and learning.

Photovoltaics and Distributed Energy Harvesting

The same system-level issue appears in photovoltaics.

European research has produced major advances in silicon, tandem cells, perovskites, encapsulation, coatings, reliability, power electronics, and AI-based forecasting. Nevertheless, mismatch, partial shading, local degradation, contamination, hot spots, and heterogeneous ageing can still reduce the output of a complete string or array.

More advanced inference can identify these conditions more accurately, but a larger physical gain may require, or may be unlocked by, a local topology change:

- bypassing a mismatched source;
- isolating a faulty element;
- reconfiguring a local network;
- changing converter routing;
- generating a fast wake-up event;
- protecting the system before centralized optimization completes.

Reflex-Policy provides the local electronic contract between material behaviour and these bounded physical actions.

The Reflex layer does not replace maximum power point tracking, plant optimization, or forecasting. It changes the local physical condition presented to those higher-level functions by removing or containing severe mismatch before the global optimization cycle is completed.

This is relevant from moving photovoltaic surfaces to static multi-megawatt plants. The implementation scale changes, but the principle remains: local material or electrical evidence should be able to produce a bounded first action without requiring every event to traverse the most complex inference path.

Why This Matters for Novel-Material Programmes

The full value of new materials for the energy transition may not be realized when system architecture is considered only after the material has been developed.

Material research should increasingly be co-designed with:

- sensing and observability;
- packaging and thermal pathways;
- electrical topology;
- local energy routing;
- galvanic isolation;
- fault containment;
- power electronics;
- repairability and lifetime management;
- energy and computation proportionality.

A material should not be evaluated only through intrinsic laboratory metrics. It should also be evaluated through the value it enables at system level.

For example:

- Does a new battery chemistry allow a different balancing or fast-charge topology?
- Does a more temperature-tolerant material reduce isolation, cooling, or derating requirements?
- Can a new photovoltaic material be segmented and locally reconfigured?
- Can a smart material generate a direct low-bit event without continuous high-resolution conversion?
- Can an emerging memory or spintronic material retain a local safety rule with negligible standby energy?

- Does the material reduce full system cost, or merely shift complexity into packaging, control, or power electronics?

Proposed European Research Direction

A useful European research direction would combine material development with a system-level Reflex-Policy layer from the beginning.

Such programmes could require demonstrators to include:

1. a material or electrochemical innovation;
2. a local sensing or material-event interface;
3. a bounded Reflex action;
4. a Policy-level optimization function;
5. measured physical feedback;
6. structured event-action observability;
7. a complete energy, thermal, wiring, isolation, and lifecycle assessment.

This would help ensure that advanced materials are not evaluated only as isolated components, but as active elements inside adaptive energy systems.

Final Message

The energy transition does not require only better materials, better AI, or better power electronics considered separately.

It requires architectures that connect them.

Reflex-Policy provides a system-level framework in which material behaviour can generate a local, bounded, observable, and energy-proportional physical action, while advanced inference remains responsible for prediction, optimization, and learning.

The value of a novel material is maximized when sensing, electronics, packaging, and power conversion are co-designed so that the system can adapt its effective topology and operating state to the material's local physical condition.

That is the system-level opportunity for batteries, photovoltaics, energy harvesting, storage, and future material-enabled energy infrastructures.